

SAFETY DATA SHEETS

This SDS packet was issued with item:

071030725

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071076009

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

W&H Cleaning Solution MC-1000

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Cleaner for turbines, straight and contra-angle handpieces, air motors etc. with W&H ASSISTINA.

Product categories [PC]

PC35 - Washing and cleaning products (including solvent based products)

Uses advised against

None, if handled according to order.

Remark

The product is intended for professional use.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

orochemie GmbH + Co. KG

Street : Max-Planck-Straße 27

Postal code/city : 70806 Kornwestheim

Telephone : +49 7154 1308-0

Telefax : +49 7154 1308-40

Information contact : W&H DENTALWERK BÜRMOOS G.m.b.H., Ignaz-Glaser-Str. 53, A-5111 Bürmoos Austria

Phone No.: +43 6274/6236-0, Telefax No.: +43 6274 6236-55

1.4 Emergency telephone number

INT: +49 6132 84463 (24 h/7 d)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - Specific target organ toxicity (single exposure) : Category 3 ; May cause drowsiness or dizziness.

Classification procedure

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP] as well as in-house investigations.

Classification according to Directive 67/548/EEC or 1999/45/EC

Flammable. · Vapours may cause drowsiness and dizziness.

R 10 · R 67

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Exclamation mark (GHS07)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

Signal word

Warning

Hazard statements

H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
P280 Wear protective gloves.
P305+P351+P338 IF IN EYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to hazardous or special waste collection point.

Labelling (67/548/EEC or 1999/45/EC)

R-phrases

10 Flammable.
67 Vapours may cause drowsiness and dizziness.

S-phrases

37 Wear suitable gloves.
16 Keep away from sources of ignition - No smoking.

2.3 Other hazards

None

SECTION 3: Composition/ information on ingredients

3.2 Mixtures

Description

W&H Cleaning solution contains alcohols and auxiliary agents in aqueous solution.

Hazardous ingredients

1-PROPANOL ; REACH registration No. : 01-2119486761-29 ; EC No : 200-746-9; CAS No. : 71-23-8
Weight fraction : 30 - 35 %
Classification 67/548/EEC : F ; R11 Xi ; R41 R67
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Dam. 1 ; H318 STOT SE 3 ; H336
ETHANOL ; REACH registration No. : 01-2119457610-43 ; EC No : 200-578-6; CAS No. : 64-17-5
Weight fraction : 25 - 30 %
Classification 67/548/EEC : F ; R11
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225
PROPAN-2-OL ; REACH registration No. : 01-2119457558-25 ; EC No : 200-661-7; CAS No. : 67-63-0
Weight fraction : 1 - 2 %
Classification 67/548/EEC : F ; R11 Xi ; R36 R67
Classification 1272/2008 [CLP] : Flam. Liq. 2 ; H225 Eye Irrit. 2 ; H319 STOT SE 3 ; H336

Additional information

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014
Version (Revision) : 2.0.0 (1.0.0)

Wash with plenty of water. When in doubt or if symptoms are observed, get medical advice.

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water Never give anything by mouth to an unconscious person or a person with cramps. Do not induce vomiting. Call a physician immediately.

4.2 Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Extinguishing powder. Water spray Water mist

Unsuitable extinguishing media

High power water jet.

5.2 Special hazards arising from the substance or mixture

None known.

Hazardous combustion products

Vapours can form explosive mixtures with air.

5.3 Advice for firefighters

Cool endangered containers with water in case of fire.

Special protective equipment for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. When using do not smoke. See protective measures under point 7 and 8.

For non-emergency personnel

Use personal protection equipment. See protective measures under point 7 and 8.

For emergency responders

Personal protection equipment

See protective measures under point 7 and 8.

6.2 Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3 Methods and material for containment and cleaning up

For cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents). Collect in closed and suitable containers for disposal.

Other information

Treat the recovered material as prescribed in the section on waste disposal.

6.4 Reference to other sections

None

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Keep/Store only in original container. Please note safety instructions and directions for use on the drum. Open and handle container with care. Keep away from sources of ignition. - No smoking. Provide adequate ventilation. Do not breathe vapour/aerosol.

Protective measures

Fire prevent measures

Usual measures for fire prevention. Keep away from sources of ignition. - No smoking.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep/Store only in original container. Keep container tightly closed. Keep in a cool, well-ventilated place. Do not store in temperatures below 5 °C.

Hints on joint storage

Do not store together with oxidizing, self-igniting substances and highly flammable solid substances. Store the foodstuffs separately.

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

1-PROPANOL ; CAS No. : 71-23-8

Limit value type (country of origin) : TLV/STEL (GB)
Limit value : 250 ppm / 625 mg/m³

ETHANOL ; CAS No. : 64-17-5

Limit value type (country of origin) : TLV/TWA (GB)
Limit value : 1000 ppm / 1920 mg/m³

PROPAN-2-OL ; CAS No. : 67-63-0

Limit value type (country of origin) : TLV/STEL (GB)
Limit value : 500 ppm / 1250 mg/m³

Limit value type (country of origin) : TLV/TWA (GB)

Limit value : 400 ppm / 999 mg/m³

DNEL/DMEL and PNEC values

There are no data available on the preparation itself.

DNEL/DMEL

Limit value type : DNEL/DMEL (DNEL Consumer, Local) (ETHANOL ; CAS No. : 64-17-5)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 950 mg/m³

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (ETHANOL ; CAS No. : 64-17-5)

Exposure route : Oral

Exposure frequency : Long-term (repeated)

Limit value : 87 mg/kg

Safety factor : 24 h

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)

Exposure route : Inhalation

Exposure frequency : Short-term (acute)

Limit value : 1036 mg/m³

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)

Exposure route : Dermal

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014
Version (Revision) : 2.0.0 (1.0.0)

Exposure frequency : Long-term (repeated)
Limit value : 319 mg/kg
Safety factor : 24 h
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 89 mg/m³
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 81 mg/kg
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 206 mg/kg
Safety factor : 24 h
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 114 mg/m³
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 80 mg/m³
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : 26 mg/kg
Safety factor : 24 h
Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Oral
Exposure frequency : Long-term (repeated)
Limit value : 61 mg/kg
Limit value type : DNEL/DMEL (Worker, Local) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 1900 mg/m³
Limit value type : DNEL/DMEL (Worker, Systemic) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 343 mg/kg
Safety factor : 24 h
Limit value type : DNEL/DMEL (Worker, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Inhalation
Exposure frequency : Short-term (acute)
Limit value : 1723 mg/m³
Limit value type : DNEL/DMEL (Worker, Systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 888 mg/kg
Safety factor : 24 h
Limit value type : DNEL/DMEL (Worker, Systemic) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 500 mg/m³
Limit value type : DNEL/DMEL (Worker, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014
Version (Revision) : 2.0.0 (1.0.0)

Exposure route : Dermal
Exposure frequency : Long-term (repeated)
Limit value : 136 mg/kg
Limit value type : DNEL/DMEL (Worker, Systemic) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 950 mg/m³
Limit value type : DNEL/DMEL (Worker, Systemic) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Inhalation
Exposure frequency : Long-term (repeated)
Limit value : 268 mg/m³

PNEC

Limit value type : PNEC aquatic, freshwater (ETHANOL ; CAS No. : 64-17-5)
Limit value : 960 µg/l
Limit value type : PNEC aquatic, freshwater (1-PROPANOL ; CAS No. : 71-23-8)
Limit value : 10 mg/l
Limit value type : PNEC aquatic, freshwater (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 140,9 mg/l
Limit value type : PNEC aquatic, marine water (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 140,9 mg/l
Limit value type : PNEC aquatic, marine water (1-PROPANOL ; CAS No. : 71-23-8)
Limit value : 1 mg/l
Limit value type : PNEC aquatic, marine water (ETHANOL ; CAS No. : 64-17-5)
Limit value : 790 µg/l
Limit value type : PNEC (Industrial) (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Soil
Limit value : 0,63 mg/kg
Limit value type : PNEC (Industrial) (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Soil
Limit value : 2,2 mg/kg
Limit value type : PNEC (Industrial) (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Soil
Limit value : 28 mg/kg
Limit value type : PNEC sediment, freshwater (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 552 mg/kg
Limit value type : PNEC sediment, freshwater (1-PROPANOL ; CAS No. : 71-23-8)
Limit value : 22,8 mg/kg
Limit value type : PNEC sediment, freshwater (ETHANOL ; CAS No. : 64-17-5)
Limit value : 3,6 mg/kg
Limit value type : PNEC sediment, marine water (1-PROPANOL ; CAS No. : 71-23-8)
Limit value : 2,28 mg/kg
Limit value type : PNEC Secondary Poisoning (ETHANOL ; CAS No. : 64-17-5)
Limit value : 0,72 mg/kg
Limit value type : PNEC Secondary Poisoning (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 160 mg/kg
Limit value type : PNEC sewage treatment plant (STP) (PROPAN-2-OL ; CAS No. : 67-63-0)
Limit value : 2251 mg/l

8.2 Exposure controls

Personal protection equipment

Eye / face protection

Eye glasses with side protection DIN EN 166

Skin protection

Hand protection

Short-term exposure (Level 2: < 30 min): disposable gloves to EN374 category III, e.g. nitrile rubber, material

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

thickness 0.1 mm.
Long-term exposure (Level 6: < 480 min): protective gloves to EN374 category III, e.g. nitrile rubber, material thickness 0.7 mm.
When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits.

Body protection

Body protection: not applicable.

Respiratory protection

Usually no personal respiratory protection necessary.

General health and safety measures

Keep away from food, drink and animal feeding stuffs. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing. Wash hands before breaks and after work. Separate storage of work clothes. When using do not eat, drink, smoke, sniff.

Occupational exposure controls

Technical measures to prevent exposure

Provide adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : Alcohol

Safety relevant basis data

Melting point / melting range :	(1013 hPa)		No data available
Boiling temperature / boiling range :	(1013 hPa)		No data available
Decomposition temperature :	(1013 hPa)		No data available
Flash point :			25 °C
Ignition temperature :			360 °C
Lower explosion limit :			2,1 Vol-%
Upper explosion limit :			15 Vol-%
Vapour pressure :	(50 °C)	ca.	150 hPa
Density :	(20 °C)		0,87 - 0,91 g/cm ³
Solvent separation test :	(20 °C)	<	3 %
Water solubility :	(20 °C)		100 Wt %
pH value :			5 - 8,5
log P O/W :			No data available
Flow time :	(20 °C)	<	20 s
Odour threshold :			No data available
Oxidising liquids :			Not applicable.
Explosive properties :			Not applicable.
Corrosive to metals :			Not corrosive to metals.

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

None, if handled according to order.

10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

10.3 Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Oxidising agent.

10.6 Hazardous decomposition products

None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50
Exposure route : Oral
Species : Rat
Effective dose : > 2000 mg/kg
Methode : OECD 401.

Practical experience/human evidence

The product does not have any skin irritating or sensitizing properties. There is no inhalation risk under normal application conditions.

Acute dermal toxicity

Parameter : LD50
Exposure route : Dermal
Species : Rat
Effective dose : > 2000 mg/kg
Methode : OECD 402.

Acute inhalation toxicity

Parameter : LC50 (1-PROPANOL ; CAS No. : 71-23-8)
Exposure route : Inhalation
Species : Rat
Effective dose : > 33,8 mg/l
Exposure time : 4 h
Parameter : LC50 (ETHANOL ; CAS No. : 64-17-5)
Exposure route : Inhalation
Species : Rat
Effective dose : > 51 mg/l
Exposure time : 4 h
Parameter : LD50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Exposure route : Inhalation
Species : Rat
Effective dose : 47,5 mg/l

Irritant and corrosive effects

Rabbit's eye: no irritation. Methode : OECD 405.

Sensitisation

There are no data available on the mixture itself.

11.4 Additional information

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP] as well as in-house investigations.

SECTION 12: Ecological information

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

12.1 Toxicity

Aquatic toxicity

There are no data available on the preparation itself.

Acute (short-term) fish toxicity

Parameter : LC50 (ETHANOL ; CAS No. : 64-17-5)
Species : Oncorhynchus mykiss (Rainbow trout)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 11200 mg/l
Parameter : LC50 (1-PROPANOL ; CAS No. : 71-23-8)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 4480 mg/l
Exposure time : 96 h
Parameter : LC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Pimephales promelas (fathead minnow)
Evaluation parameter : Acute (short-term) fish toxicity
Effective dose : 9640 mg/l
Exposure time : 96 h

Acute (short-term) daphnia toxicity

Parameter : EC50 (1-PROPANOL ; CAS No. : 71-23-8)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 3644 mg/l
Exposure time : 48 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 13299 mg/l
Exposure time : 48 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Daphnia magna (Big water flea)
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 9714 mg/l
Exposure time : 24 h
Parameter : EC50 (ETHANOL ; CAS No. : 64-17-5)
Species : Ceriodaphnia spec
Evaluation parameter : Acute (short-term) daphnia toxicity
Effective dose : 1806 mg/l

Acute (short-term) algae toxicity

Parameter : EC50 (1-PROPANOL ; CAS No. : 71-23-8)
Species : Scenedesmus subspicatus
Evaluation parameter : Inhibition of growth rate
Effective dose : 3100 mg/l
Exposure time : 168 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Pseudokirchneriella subcapitata
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 1000 mg/l
Exposure time : 72 h
Parameter : EC50 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l
Exposure time : 72 h

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

Parameter : EC50 (ETHANOL ; CAS No. : 64-17-5)
Species : Chlorella vulgaris
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 275 mg/l
Parameter : EC50 (ETHANOL ; CAS No. : 64-17-5)
Species : Selenastrum capricornutum
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : 440 mg/l
Parameter : IC50 (ETHANOL ; CAS No. : 64-17-5)
Species : Scenedesmus subspicatus
Evaluation parameter : Acute (short-term) algae toxicity
Effective dose : > 100 mg/l

Bacteria toxicity

Parameter : EC50 (1-PROPANOL ; CAS No. : 71-23-8)
Species : Pseudomonas putida
Evaluation parameter : Bacteria toxicity
Effective dose : 2700 mg/l
Exposure time : 16 h
Parameter : EC10 (PROPAN-2-OL ; CAS No. : 67-63-0)
Species : Pseudomonas putida
Evaluation parameter : Bacteria toxicity
Effective dose : 5175 mg/l
Exposure time : 18 h

12.2 Persistence and degradability

Abiotic degradation

No data available.

Biodegradation

The product is easily biodegradable according to OECD criteria. Methode : OECD 301 D.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

Known or predicted distribution to environmental compartments

There are no data available on the preparation itself.

12.5 Results of PBT and vPvB assessment

No information available.

12.6 Other adverse effects

No information available.

12.7 Further ecological information

Prevent from flowing into surface water/ground water.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product/Packaging disposal

Waste codes / waste designations according to EWC

Waste code product

Concentrate/larger quantities: 18 01 06* (disinfectant).

Waste treatment options

Appropriate disposal / Product

Dispose according to legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

UN 1987

14.2 UN proper shipping name

Land transport (ADR/RID)

ALCOHOLS, N.O.S. (N-PROPANOL · ETHANOL)

Sea transport (IMDG)

ALCOHOLS, N.O.S. (N-PROPANOL · ETHANOL)

Air transport (ICAO-TI / IATA-DGR)

ALCOHOLS, N.O.S. (N-PROPANOL · ETHANOL)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : LQ 5 I · LQ 7 · E 1
Hazard label(s) : 3

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-D
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : No
Sea transport (IMDG) : No
Air transport (ICAO-TI / IATA-DGR) : No

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Restrictions of occupation

According to directive 94/33/EC, juveniles are only allowed to handle this product as long as all effects of dangerous substances are prevented.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000

Revision date : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

Date of print : 12.01.2014

15.2 Chemical Safety Assessment

For this mixture a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 03. Hazardous ingredients · 08. Occupational exposure limit values

16.2 Abbreviations and acronyms

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE = Acute Toxicity Estimates
CAS = Chemical Abstracts Service
CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
CMR = Carcinogen, Mutagen or Reproductive toxicant
CO₂ = Carbon dioxide
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level
EC = European Commission
EC50 = Half maximal effective concentration
EN = European Standard (Norm)
EU = European Union
EUH statement = CLP-specific Hazard statement
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
H statement = GHS Hazard statement
IATA = International Air Transport Association ICAO-TI = International Civil Aviation Organization-Technical Instructions
IMDG = International Maritime Dangerous Goods
LC50 = Median lethal concentration
LD50 = Median lethal dose
LogPow = Logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
NOEC/NOEL = No observed effect concentration/level
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation [Regulation (EC) No. 1907/2006]
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RMM = Risk Management Measure
RRN = REACH Registration Number
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
SVHC = Substances of Very High Concern
TLV/STEL = Threshold limit value/short-term exposure limit
TLV/TWA = Threshold limit value/time weighted average
UN = United Nations
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The classification was carried out according to the calculation method of Regulation No. (EC) 1272/2008 [CLP] as well as in-house investigations.

16.4 Relevant R-, H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

Trade name : W&H Cleaning Solution MC-1000
Revision date : 12.01.2014
Date of print : 12.01.2014

Version (Revision) : 2.0.0 (1.0.0)

H226	Flammable liquid and vapour.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
10	Flammable.
11	Highly flammable.
36	Irritating to eyes.
41	Risk of serious damage to eyes.
67	Vapours may cause drowsiness and dizziness.

16.5 Training advice

None

16.6 Additional information

Notice the directions for use on the label.
Dr. Klaus-Michael Wolf Tel. No.: +49 7154 1308-27 · Fax. No.: +49 7154 1308-40 · info@orochemie.de
Dipl. Ing. Elisabeth Gehring Tel. No.: +49 7154 1308-37

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

1. Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : W & H Service Oil F1 MD 500
Article-No. : 028073

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricating oil

1.3 Details of the supplier of the safety data sheet

KLÜBER LUBRICATION MÜNCHEN
Geisenhausenerstrasse 7
D-81379 München
Deutschland
Tel: +49 (0) 897876-0
Fax: +49 (0) 897876-333

E-mail address : mcm@klueber.com
Responsible/issuing person : Material Compliance Management

National contact : Klüber Lubrication Great Britain Ltd.
Hough Mills, Northowram
Halifax, HX3 7BN
Great Britain
Tel: +44-1422-205115
Fax: +44-1422-206073
sales@uk.klueber.com

1.4 Emergency telephone number

0049 (0) 897876-700 (24hrs)

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

|| Not a hazardous substance or mixture.

Classification (67/548/EEC, 1999/45/EC)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB

//
KLUBER
LUBRICATION

W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

Additional Labelling:

EUH210 Safety data sheet available on request.

2.3 Other hazards

3. Composition/information on ingredients

3.2 Mixtures

Chemical nature : Synthetic hydrocarbon oil
ester oil

Hazardous components

Chemical Name	CAS-No. EC-No. Index-No. Registration number	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [%]
Dec-1-ene, dimers, hydrogenated	68649-11-6	Xn; R20 Xn; R65	Acute Tox. 4; H332 Asp. Tox. 1; H304	>= 1 - < 10

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : If eye irritation persists, consult a specialist.
Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
- If swallowed : If unconscious place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give anything to drink.
Never give anything by mouth to an unconscious person.
Get medical attention if symptoms occur.

W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

: Move the victim to fresh air.

4.2 Most important symptoms and effects, both acute and delayed

4.3 Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : none

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Fire may cause evolution of:
Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
In the case of respirable dust and/or fumes, use self-contained breathing apparatus.
Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Do not breathe vapours or spray mist.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

6.4 Reference to other sections

7. Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling :
- Do not breathe vapours or spray mist.
 - Avoid contact with skin and eyes.
 - For personal protection see section 8.
 - Smoking, eating and drinking should be prohibited in the application area.
 - Wash hands and face before breaks and immediately after handling the product.
 - Do not get in eyes or mouth or on skin.
 - Do not get on skin or clothing.
 - Do not ingest.
 - Do not repack.
 - Do not re-use empty containers.
 - These safety instructions also apply to empty packaging which may still contain product residues.
 - Keep container closed when not in use.
 - Avoid inhalation of vapour or mist.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers :
- Store in original container.
 - Keep container closed when not in use.
 - Keep in a dry, cool and well-ventilated place.
 - To maintain product quality, do not store in heat or direct sunlight.
 - Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 - Store in accordance with the particular national regulations.
 - Keep in properly labelled containers.

7.3 Specific end use(s)

8. Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

- DNEL
Dec-1-ene, dimers,
hydrogenated :
- End Use: Industrial use
 - Exposure routes: Inhalation
 - Potential health effects: Acute systemic effects
 - Value: 60 mg/m³

8.2 Exposure controls

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

Engineering measures

Maintain air concentrations below occupational exposure standards.

It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen deficient environment.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection : For prolonged or repeated contact use protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
- Eye protection : Safety glasses with side-shields conforming to EN166
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Environmental exposure controls

- General advice : Try to prevent the material from entering drains or water courses. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

9. Physical and chemical properties

The data/values refer to the main component.

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : yellow
- Odour : characteristic

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB

KLÜBER
LUBRICATION

W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

Odour Threshold	: No data available
pH	: No data available
Melting point/range	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 200 °C, Test Method: open cup, ISO 2592
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Lower explosion limit	: No data available
Upper explosion limit	: No data available
Vapour pressure	: < 0.17 hPa, 20 °C
Relative vapour density	: No data available
Density	: 0.84 g/cm ³ , 20 °C
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Ignition temperature	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: 22 mm ² /s, 40 °C
Oxidizing properties	: No data available

9.2 Other information

Sublimation point	: No data available
Bulk density	: No data available

10. Stability and reactivity

10.1 Reactivity

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : No conditions to be specially mentioned.

10.5 Incompatible materials

Materials to avoid : No materials to be especially mentioned.

10.6 Hazardous decomposition products

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

11. Toxicological information

11.1 Information on toxicological effects

Product

Acute oral toxicity	: This information is not available.
Acute inhalation toxicity	: Acute toxicity estimate: > 5 mg/l, 4 h, dust/mist, Calculation method
Skin corrosion/irritation	: This information is not available.
Serious eye damage/eye irritation	: This information is not available.
Respiratory or skin sensitisation	: This information is not available.
Carcinogenicity	: No data available
Reproductive toxicity	: No data available
Teratogenicity	: No data available
Repeated dose toxicity	: This information is not available.
Aspiration toxicity	: This information is not available.
Further information	: Information given is based on data on the components and the toxicology of similar products.

Components:

Dec-1-ene, dimers, hydrogenated :

Acute oral toxicity	: LD50: > 5,000 mg/kg, rat, OECD Test Guideline 401, GLP: yes
Acute inhalation toxicity	: LC50: 1.17 mg/l, 4 h, rat, dust/mist, OECD Test Guideline 403, GLP: yes
Acute dermal toxicity	: LD50: > 3,000 mg/kg, rabbit, OECD Test Guideline 402
Skin corrosion/irritation	: rabbit, Result: No skin irritation, Classification: No skin irritation, OECD Test Guideline 404
Serious eye damage/eye irritation	: rabbit, Result: No eye irritation, Classification: No eye irritation, OECD Test Guideline 405
Respiratory or skin sensitisation	: Maximisation Test (GPMT), guinea pig, Result: Does not cause skin sensitisation., Classification: Does not cause skin sensitisation., OECD Test Guideline 406, GLP: yes
Aspiration toxicity	: May be fatal if swallowed and enters airways.

12. Ecological information

12.1 Toxicity

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB

//
KLÜBER
LUBRICATION

W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

Toxicity to fish	:	No data available
Toxicity to daphnia and other aquatic invertebrates	:	No data available
Toxicity to algae	:	No data available
Toxicity to bacteria	:	No data available

Components:

Dec-1-ene, dimers, hydrogenated :

Toxicity to fish	:	LC50: > 1,000 mg/l, 96 h, Oncorhynchus mykiss (rainbow trout), semi-static test, OECD Test Guideline 203, GLP: yes
Toxicity to daphnia and other aquatic invertebrates	:	EC50: > 1,000 mg/l, 48 h, Daphnia magna (Water flea), Immobilization, OECD Test Guideline 202, GLP: yes
Toxicity to algae	:	EC50: > 1,000 mg/l, 72 h, Scenedesmus capricornutum (fresh water algae), static test, OECD Test Guideline 201, GLP: yes
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 125 mg/l, 21 d, Daphnia magna (Water flea), OECD Test Guideline 211, GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability	:	No data available
Physico-chemical removability	:	No data available

Components:

Dec-1-ene, dimers, hydrogenated :

Biodegradability	:	Result: not rapidly biodegradable
------------------	---	-----------------------------------

12.3 Bioaccumulative potential

Product:

Bioaccumulation	:	This mixture contains no substance considered to be persistent, bioaccumulating nor toxic (PBT)., This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).
-----------------	---	--

12.4 Mobility in soil

Product:

Mobility	:	No data available
Distribution among environmental compartments	:	No data available

12.5 Results of PBT and vPvB assessment

Product:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

Dec-1-ene, dimers, hydrogenated :

Assessment : This substance is not considered to be persistent, bioaccumulating nor toxic (PBT)., This substance is not considered to be very persistent nor very bioaccumulating (vPvB).

12.6 Other adverse effects

13. Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
: Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Empty containers can be landfilled, when in accordance with the local regulations.

14. Transport information

14.1 UN number

ADR
Not dangerous goods
IMDG
Not dangerous goods
IATA
Not dangerous goods

14.2 Proper shipping name

ADR
Not dangerous goods
IMDG
Not dangerous goods
IATA
Not dangerous goods

14.3 Transport hazard class

ADR
Not dangerous goods
IMDG
Not dangerous goods
IATA
Not dangerous goods

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.5 Environmental hazards

ADR

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not available

15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Major Accident Hazard Legislation : 96/82/EC Update: not applicable

15.2 Chemical Safety Assessment

This information is not available.

16. Other information

Full text of R-phrases referred to under sections 2 and 3

R20 Harmful by inhalation.
R65 Harmful: may cause lung damage if swallowed.

Full text of H-Statements referred to under sections 2 and 3.

H304 May be fatal if swallowed and enters airways.
H332 Harmful if inhaled.

This safety datasheet applies only to products originally packaged and labelled by KLÜBER LUBRICATION. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of KLÜBER LUBRICATION. This document may be passed on only to the extent required by law. Any dissemination of our

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



W & H Service Oil F1 MD 500

Version 2.0

Revision Date 20.03.2014

Print Date 21.03.2014

safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. KLÜBER LUBRICATION provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. KLÜBER LUBRICATION provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.