

SAFETY DATA SHEETS

This SDS packet was issued with item:

075908199

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075908157 075908165 075908181 075908207

IDENTITY

Trade Name:

Seal-Rite Pit and Fissure Sealant
~~Seal-Rite Low Viscosity Pit and Fissure Sealant~~

Code:

SEAL, SEAL-3, RITE,
SEAL-LV, SEAL-LV3, RITE-LV

Chemical Description: Glass filler materials in methacrylate resins.

Product Use: Visible light-cure pit and fissure dental sealant.

SECTION I

Pulpdent Corporation

80 Oakland Street
Watertown, MA 02472 USA

Phone Numbers

24 Hour Emergency: 1-800-535-5053
Customer Service: 1-800-343-4342/1-617-926-6666

Date prepared: September 1, 2008

SECTION II - HAZARDOUS INGREDIENTS

Ingredients	CAS Number	Percent	PEL / TLV
Uncured Methacrylate resins	-----	66.0	Not established
Amorphous silica	112945-52-5	5.0	6 mg/m ³ / 10 mg/m ³
Sodium fluoride	7981-49-4	2.0	2.5 mg/m ³ (as F)

DOT HAZARD CLASSIFICATION: Not regulated
WHMIS CLASSIFICATION: D-2, Possible Irritation, Possible Sensitization
NFPA HMIS RATING: HEALTH: 1 FLAMMABILITY: 0 REACTIVITY: 1

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

Specific Gravity: SEAL 1.550, SEAL-LV 1.290
Vapor Pressure: <1 mm Hg Vapor Density: 1
Solubility in water: Nil Odor Threshold: Not available
Appearance and Odor: Off-white, thickened liquid with faint characteristic odor.

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Flash Point: Not established Flammable limits: Not established
Extinguishing Media: Carbon dioxide, dry chemical, alcohol foam, or water fog; water spray to keep fire-exposed containers cool.
Special Fire Fighting Procedures: A self-contained breathing apparatus should be worn by fire fighting personnel. Cool exposed containers with water spray to prevent polymerization under fire conditions.
Hazardous Combustion Products: Hazardous polymerization with heat build up and release of carbon monoxide, carbon dioxide and oxides of nitrogen may occur under fire conditions.

SECTION V - REACTIVITY DATA

Stability: Stable
Conditions to avoid: Temperature > 27°C / 80°F; intense light.
Incompatibility: Reducing and oxidizing agents.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen.
Hazardous Polymerization: None under normal conditions of use.
Conditions to avoid: Temperature > 27°C / 80°F; intense light.

SECTION VI - HEALTH HAZARD DATA

Summary of Acute Hazards: Minimal health hazard under normal conditions of use.

<i>Route of Exposure</i>	<i>Signs & Symptoms</i>
Inhalation	May be irritating to mucous membranes
Eye Contact	May be irritating
Skin Absorption	Not applicable
Skin Contact	Primary route of exposure, may cause irritation.
Ingestion	May be irritating to mucous membranes.

Summary of Chronic Hazards: Sensitization with prolonged or repeated contact.

Carcinogenicity None known

Teratogenicity, Mutagenicity, Reproductive Toxicity: None known.

Emergency First Aid Procedures:

Inhalation	Move to fresh air. Administer artificial respiration, if required, and seek medical attention.
Eye contact	Flush eyes with running water for 15+ minutes. Seek medical attention.
Ingestion	Consult physician immediately.
Skin contact	Wash skin with soap and running water.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING & USE

Handling / Storage Precautions: Store tightly capped in original container at cool room temperature. Avoid temperature extremes (>27°C/80°F, <15°C/60°F), intense light, moisture and contaminants. Remove applicator tip and recap immediately after use.

Release or Spill: Wipe up material with paper or cloth towels and collect for disposal.

Waste Disposal Method: Follow all government regulations.

Other Precautions: Wash hands after use.

SECTION VIII - CONTROL MEASURES

Respiratory Protection: None required under anticipated conditions of normal use.

Ventilation: No special ventilation required under anticipated conditions of normal use.

Protective Gloves: Recommended.


Eye Protection: Safety glasses are recommended.

Other Protective Clothing or Equipment: Emergency eye wash fountain should be close by and maintained.

Work/Hygienic Practices: Avoid prolonged contact with skin. Wash hands after use.

The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.

Safety Data SheetTrade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

1.0 Commercial Product Name and Supplier																
1.1	Commercial product name / designation <i>Seal-Rite Pit and Fissure Sealant</i> <i>Seal-Rite Low Viscosity Pit and Fissure Sealant</i>															
1.2	Application / Use Dental material for use by dental professional only.															
1.2.2	SIC 851 Human health activity															
1.2.3	Use Category 55															
1.3	Manufacturer Pulpdent Corporation 80 Oakland Street, P.O. Box 780 Watertown, MA 02472 USA Telephone: 1 617 926-6666 / Fax: 1 617 926-6262 Email: Pulpdent@pulpdent.com															
1.4	Emergency Telephone Number 1-800-535-5053 (24 Hour / USA)															
1.5	Authorized European Representative Advena Ltd. Pure Offices, Plato Close Warwick, CV34 6WE United Kingdom															
2.0 Hazards Identification																
2.1	Classification Irritant.															
2.1.1	Classification according to Regulation (EC) No 1272/2008 [CLP]															
	<table border="1"> <thead> <tr> <th><u>Hazard Class</u></th> <th><u>Hazard Category</u></th> <th><u>Hazard Statement</u></th> </tr> </thead> <tbody> <tr> <td>Eye irritation</td> <td>2</td> <td>H319</td> </tr> <tr> <td>STOT SE</td> <td>3</td> <td>H335</td> </tr> <tr> <td>Skin irritation</td> <td>2</td> <td>H315</td> </tr> <tr> <td>Skin sensitization</td> <td>1</td> <td>H317</td> </tr> </tbody> </table>	<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Hazard Statement</u>	Eye irritation	2	H319	STOT SE	3	H335	Skin irritation	2	H315	Skin sensitization	1	H317
<u>Hazard Class</u>	<u>Hazard Category</u>	<u>Hazard Statement</u>														
Eye irritation	2	H319														
STOT SE	3	H335														
Skin irritation	2	H315														
Skin sensitization	1	H317														
2.1.2	Classification according to Directive 67/548/EEC Irritant; Xi; R 36/37/38 – 43 (See SECTION 16 for full text of risk phrases)															
2.2	GHS Label Elements Hazard Pictograms  Signal Word: WARNING Restricted to use by dental professional only.															
Hazard Statements H319: Eye irritation. 2. May cause eye irritation. H335: STOT SE. 3. May cause respiratory irritation. H315: Skin irritation. 2. May cause skin irritation. H317: Sensitization. 1. May cause an allergic skin reaction.																
Precautionary Statements P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305+P351: If in eyes, rinse cautiously with water for several minutes. P337+P313: If eye irritation persists, get medical advice/attention. P302+P352: If on skin, wash with plenty of soap and water. P333+P313: If irritation or rash occurs, get medical advice/attention. P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.																

Safety Data SheetTrade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

3.0 Composition																
3.1	Chemical characterization of the preparation: Methacrylate ester monomers in a light-cured, glass-filled paste.															
3.2	Hazardous ingredients															
	<table border="1"> <thead> <tr> <th>CAS Number</th> <th>Name of the Ingredient</th> <th>Concentration</th> <th>Classification per 67/548/EEC</th> <th>Classification per Regulation (EC) No.1272/2008 (CLP)</th> </tr> </thead> <tbody> <tr> <td>Proprietary</td> <td>Uncured methacrylate ester monomers</td> <td>55-65%</td> <td>Xi (Irritant), R36/37/38, R43</td> <td>Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317</td> </tr> <tr> <td>112945-52-5</td> <td>Amorphous silica</td> <td>5 %</td> <td>Xi (Irritant), R36/37/38</td> <td>Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315</td> </tr> </tbody> </table>	CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP)	Proprietary	Uncured methacrylate ester monomers	55-65%	Xi (Irritant), R36/37/38, R43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317	112945-52-5	Amorphous silica	5 %	Xi (Irritant), R36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315
CAS Number	Name of the Ingredient	Concentration	Classification per 67/548/EEC	Classification per Regulation (EC) No.1272/2008 (CLP)												
Proprietary	Uncured methacrylate ester monomers	55-65%	Xi (Irritant), R36/37/38, R43	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315 Skin sensitization, 1, H317												
112945-52-5	Amorphous silica	5 %	Xi (Irritant), R36/37/38	Eye irritation, 2, H319 STOT SE 3, H335 Skin irritation, 2, H315												
4.0 First Aid Measures																
4.1	General Information May be irritating to eyes, respiratory system and skin. Prolonged or repeated contact with methacrylate may cause sensitization. Show this safety data sheet to medical personnel. Get medical attention in case of uncertainty.															
4.2	Inhalation Move to fresh air. If necessary, administer oxygen and/or artificial respiration and seek medical attention.															
4.3	Skin Contact Take off contaminated clothing. Wash skin thoroughly with soap and water.															
4.4	Eye Contact Keep eyelids apart and flush with running water for 15+ minutes. Get medical attention.															
4.5	Ingestion Rinse mouth with water. Do not induce vomiting. Get immediate medical attention. May be irritating to mucous membranes. Never give anything by mouth to an unconscious person.															
4.6	Precautions for first responders Ventilate the area. Wear eye and skin protection.															
4.7	Information for physicians Symptoms Irritation or redness in eyes, throat or on skin. Hazards May be irritating to eyes, respiratory system and skin. May cause sensitization by skin contact. Treatment As above under First Aid.															
5.0 Fire Fighting Measures																
5.1	Suitable extinguishing media Carbon dioxide, dry chemical, alcohol foam, or water fog. Water spray may be used to keep fire exposed containers cool.															
5.2	Extinguishing media to avoid Do not use direct water stream															
5.3	Special exposure hazards in a fire Heat may cause polymerization with rapid release of energy.															
5.4	Special protective equipment for fire-fighters Self-contained breathing apparatus.															
6.0 Accidental Release Measures																
6.1	Personal precautions. Ventilate area. Wear safety glasses, gloves and lab coat.															
6.2	Environmental precautions Contain spilled material. Follow all government regulations.															

Safety Data SheetTrade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

6.3 Method for clean up Absorb/wipe up spill with paper towels or cloths. Collect for disposal in a covered container. Wash area of spill with alcohol or soap and water.

7.0 Handling and Storage

7.1 Handling For use only by dental professionals trained in its use. Follow good hygiene practices. Remove applicator tip from syringe and cap container immediately after use. Keep light-cured materials shaded from intense light sources.

7.2 Storage Store product tightly capped in original container at cool room temperature (<25°C). Avoid direct, strong light, ignition sources, temperature extremes (>27°C/80°F, <5°C/40°F). Shelf life for unopened product is two years from date of manufacture, provided that the material has been stored properly.

7.3 Specific uses Dental material

8.0 Exposure Controls / Personal Protection

8.1 Exposure limit values PEL: Not established. TLV: Not established.

8.2 Exposure controls

8.2.1 Occupational exposure controls No special equipment required under normal conditions of use.

8.2.1.1 Respiratory protection Good general ventilation is sufficient to control any airborne vapors.

8.2.1.2 Hand protection No special requirements other than the usual surgical gloves.

8.2.1.3 Eye protection No special requirements other than the usual safety glasses..

8.2.1.4 Skin protection Good personal hygiene and safety practices; wearing a lab coat.

8.2.1.5 Other controls Emergency eye wash fountain. Wash hands after use.

8.2.2 Environmental exposure controls Cure material before disposing. To the best of our knowledge, cured material is inert. Follow all government regulations.

9.0 Physical and Chemical Properties

9.1 Appearance / Color .

9.1.1 Color / Physical state Off-white paste

9.1.2 Odor Faint, characteristic

9.2 Important health, safety and environmental information

9.2.1 pH Not determined

9.2.2 Boiling point Not determined

9.2.3 Flash point Not determined

9.2.4 Flammability (solid, gas) Not applicable

9.2.5 Explosive properties Not applicable

9.2.6 Oxidizing properties Not determined

9.2.7 Vapor pressure < 1 mm Hg / 133 Pa / Id: B

9.2.8 Specific gravity Seal-Rite: 1.550; Seal-Rite LV: 1.290

9.2.9 Solubility in water Nil

9.2.10 Partition coefficient Not determined

Safety Data SheetTrade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

9.2.11	Viscosity	Not determined
9.2.12	Vapor density	> 1
9.2.13	Evaporation rate	Not determined
10.0	Stability and reactivity	
10.1	Conditions to avoid	Temperature extremes (>27°C/80°F, <5°C/40°F), light.
10.2	Materials to avoid	Reducing and oxidizing agents, peroxides, amines.
10.3	Hazardous decomposition products	Under fire conditions and with amounts far greater than that supplied in this product, hazardous polymerization may occur with heat buildup and release of carbon monoxide, carbon dioxide, oxides of nitrogen.
10.4	Further information	Direct light will polymerize light-cured material.
11.0	Toxicological information	
11.1	Acute toxicity	Not toxic. Minimal health hazard in the quantities present in this product and under normal conditions of use.
11.2	Irritation and corrosiveness	May be irritating to eyes, mucous membranes or skin on contact or with prolonged exposure.
11.3	Sensitization	May be sensitizing. Prolonged or frequent skin contact may cause allergic skin reactions in some susceptible individuals.
11.4	Sub-acute, sub-chronic and prolonged toxicity	Prolonged/frequent skin contact may cause allergic skin reactions in susceptible individuals. Prolonged exposure to large amounts of this material may cause eye and respiratory irritation.
11.5	Carcinogenicity, Mutagenicity, Reproductive Toxicity	None known.
11.6	Empirical data	None available.
11.7	Clinical experience	Seal-Rite and Seal-Rite-LV have been used safely and effectively by dentists in the US and internationally for more than 15 years with no reports of adverse events.
12.0	Ecological Information	
12.1	Ecotoxicity	To the best of our knowledge, polymerized material is inert. No other information is available.
13.0	Disposal Considerations	
13.1	Regulations	Polymerize before disposal. Follow all local and national government regulations in disposing material or contaminated packaging.
14.0	Transport Information	
14.1	Restrictions	None. Not regulated.
15.0	Regulatory Information	
15.1	EU	Class IIa medical devices under MDD 93/42/EEC.
15.2	US FDA	Class II medical devices
15.3	Health Canada	Class III medical devices

Safety Data SheetTrade Name: **SEAL-RITE™ PIT AND FISSURE SEALANT**

16.0 Other information		
16.1	List of relevant R phrases	R36/37/38: Irritating to eyes, respiratory system and skin. R43: Sensitizing by skin contact
16.2	Hazard Statements	H319: Eye irritation. Hazard category 2. H335: Specific Target Organ Toxicity - Single exposure; hazard category. 3. Respiratory tract irritation. H315: Skin irritation. Hazard category 2. H317: Skin Sensitization. Hazard category 1.
16.3	Precautionary Statements	P261: Avoid breathing vapor. P280: Wear protective gloves and eye protection P305+P351: If in eyes, rinse cautiously with water for several minutes. P337+P313: If eye irritation persists, get medical advice/attention. P302+P352: If on skin, wash with plenty of soap and water. P333+P313: If irritation or rash occurs, get medical advice/attention. P410+P411: Protect from sunlight. Store at temperature not exceeding 27°C / 80°F.
16.4	Restrictions on use	Pulpdent products are to be sold to and used by dental professionals only.
16.5	Further information	The information presented herein is believed to be factual as it has been derived from the works of persons believed to be qualified experts. However, nothing contained in this information is to be taken as a warranty or representation for which Pulpdent Corporation bears legal responsibility. The user should review any recommendations in the specific context of the intended use to determine whether they are appropriate.
16.6	Sources of key data	National Institute for Occupational Safety (NIOSH) US Occupational Safety and Health Administration (OSHA) Eur-Lex European Union Law: Regulation (EC) No. 1272/2008 (CLP) and Regulation (EC) No. 1907/2006 (REACH). Guidance on the compilation of safety data sheets. Version 1.1; December 2011. European Chemicals Agency
16.7	Information which has been added, deleted or revised.	This Safety Data Sheet has been revised to meet the requirements of GHS SDS format and Regulations (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH). Specifically Sections 2.1, 2.2, 3.2, 16.2, 16.3 have been modified.