# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

075769526

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

075769534



# **Material Safety Data Sheet**

Copyright, 2011, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** 30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA)

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center

St. Paul. MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 03/02/11 **Supercedes Date:** 04/09/10

**Document Group:** 16-4015-0

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals. Specific Use: Used in impressioning systems.

# **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	C.A.S. No.	% by Wt
ETHYL ACETATE	141-78-6	25 - 50
HEPTANE	142-82-5	25 - 35
ACETONE	67-64-1	5 - 15
METHYLCYCLOHEXANE	108-87-2	5 - 10
FORMALDEHYDE, POLYMER WITH 1,3-BENZENEDIOL AND 4-(1,1-	59633-97-5	0 - 5
DIMETHYLETHYL)PHENOL		
POLYCHLOROPRENE	9010-98-4	0 - 5

# **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

General Physical Form: Liquid

**Immediate health, physical, and environmental hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eve Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Skin Contact:**

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

## **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

# **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature** No Data Available

Flash Point 30 °F [Test Method: Closed Cup]

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

## **6.2. Environmental precautions**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

#### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water. Seal the container.

Page 3 of 8

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid skin contact.

### 7.2 STORAGE

Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use in an enclosed process area is recommended. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

# 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid skin contact.

## 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

### 8.2.4 Prevention of Swallowing

Not applicable. Do not ingest.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
ETHYL ACETATE	ACGIH	TWA	400 ppm	
ETHYL ACETATE	OSHA	TWA	1400 mg/m3	
HEPTANE	OSHA	TWA	2000 mg/m3	
Heptane, all isomers	ACGIH	TWA	400 ppm	
Heptane, all isomers	ACGIH	STEL	500 ppm	
METHYLCYCLOHEXANE	ACGIH	TWA	400 ppm	

Page 4 of 8

METHYLCYCLOHEXANE OSHA TWA 2000 mg/m3

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

General Physical Form: Liquid

**Autoignition temperature** No Data Available

Flash Point 30 °F [Test Method: Closed Cup]

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

**Boiling Point** 133 °F

**Density**No Data Available **Vapor Density**2 - 4 [Ref Std: AIR=1]

Vapor Pressure 180 mmHg

**Specific Gravity** 0.8 - 0.9 [*Ref Std:* WATER=1]

pH No Data Available
Melting point No Data Available

Solubility in Water Moderate

**Evaporation rate** Approximately 1 [*Ref Std:* BUOAC=1]

Volatile Organic CompoundsNo Data AvailableKow - Oct/Water partition coefNo Data AvailablePercent volatileNo Data AvailableVOC Less H2O & Exempt SolventsNo Data AvailableViscosity40000 centipoise

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

<u>Substance</u> <u>Condition</u>

Carbon monoxide During Combustion
Carbon dioxide During Combustion
Irritant Vapors or Gases During Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

## ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

# SECTION 14:TRANSPORT INFORMATION

## **ID Number(s):**

70-2011-0648-4, 70-2011-0895-1, 70-2011-0997-5

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: REGULATORY INFORMATION**

# US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

This material contains a chemical which requires export notification under TSCA Section 12[b]:

<b>Ingredient (Category if applicable)</b>	C.A.S. No	Regulation	<b>Status</b>
HEPTANE (Heptane)	142-82-5	Toxic Substances Control Act (TSCA) 4 Test	Applicable
		Rule Chemicals	
HEPTANE	142-82-5	Toxic Substances Control Act (TSCA) 4 Test	Applicable
		Rule Chemicals	

## STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

Health: 1 Flammability: 3 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Page 7 of 8

#### **Revision Changes:**

Copyright was modified.

Section 3: Potential effects from inhalation information was modified.

Section 3: Potential effects from ingestion information was modified.

Section 14: Transportation legal text was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 15: TSCA section 12[b] information was modified.

Section 6: Methods for cleaning up information was modified.

Section 3: Immediate other hazard(s) was added.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

Section 6: Clean-up methods heading was added.

Section 6: Release measures heading was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Page 8 of 8



# Safety Data Sheet

Copyright.2016.3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:

16-5566-1

Version Number:

6.00

Issue Date:

02/25/16

Supercedes Date:

12/16/14

## **SECTION 1: Identification**

#### 1.1. Product identifier

IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST

#### **Product Identification Numbers**

LE-FSFD-6306-1

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression

#### Restrictions on use

For use only by dental professionals

### 1.3. Supplier's details

MANUFACTURER:

3M

DIVISION:

Oral Care Solutions Division

ADDRESS:

3M Center, St. Paul, MN 55144-1000, USA

Telephone:

1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

### 2.2. Label elements

Signal word

Warning

### Symbols

Not applicable

#### IMPREGUM GARANT L DUOSOFT/IMPREGUM GARANT SOFT LB CATALYST 02/25/16

#### **Pictograms**

Not applicable

### **Hazard Statements**

Causes eye irritation.

### **Precautionary Statements**

#### Prevention:

Wash thoroughly after handling.

### Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do,

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

### 2.3. Hazards not otherwise classified

None.

# SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
POLYMERIC ACETATE	91825-26-2	25 - 35 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	20 - 30 Trade Secret *
CITRIC ESTER	77-90-7	10 - 20 Trade Secret *
SULFONIUM SALT	72140-65-9	10 - 20 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
SILANE TREATEAD SILICA	68909-20-6	I - 10 Trade Secret *
FATTY ACIDS TRIGLYCERIDES	67701-27-3	I - 5 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### Inhalation:

No need for first aid is anticipated.

#### Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

No need for first aid is anticipated.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

## **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### Hazardous Decomposition or By-Products

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

#### Condition

During Combustion
During Combustion
During Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong hases. Store away from oxidizing agents. Store away from amines.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

## IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST 02/25/16

#### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

#### 8.2.2. Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### Respiratory protection

Respiratory protection is not required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

General Physical Form: Solid Specific Physical Form: Paste

Odor, Color, Grade: slightly characteristic odor, red colored pastes

Odor threshold No Data Available
pH Not Applicable
Melting point No Data Available

Melting point No Data Available
Boiling Point Not Applicable

Flash Point Flash point  $> 93 \,^{\circ}\text{C} (200 \,^{\circ}\text{F})$ 

Evaporation rate

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

Vapor Density

Density

Not Applicable
Not Applicable
Not Applicable
Not Applicable
No Data Available
No Data Available
1,1 g/cm3 - 1,2 g/cm3

Specific Gravity 1.1 - 1.2 [Ref Std: WATER=1]

Solubility in Water Negligible

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available Autoignition temperature Not Applicable No Data Available Decomposition temperature Viscosity No Data Available Molecular weight No Data Available Volatile Organic Compounds Not Applicable Not Applicable Percent volatile

VOC Less H2O & Exempt Solvents Not Applicable

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

### IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST 92/25/16

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Amines
Strong acids
Strong bases
Strong oxidizing agents

#### 10.6. Hazardous decomposition products

Substance

Condition

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### Eve Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or bazy vision.

## Ingestion:

No known health effects.

# Carcinogenicity:

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYS AIRRESP	68855-54-9	Grp. 1 Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYS AIRRESP	68855-54-9	Known human caremogen	National Toxicology Program Carcinogens

## Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg kg
Overall product	Ingestion	1	No data available: calculated ATE > 5,000 mg kg
POLYMERIC ACETATE	Dermal	Professio nal judgeme nt	LD50 estimated to be + 5,000 mg kg
POLYMERIC ACETATE	Ingestion	Rat	LD50 + 2,000 mg/kg
DIATOMACEOUS EARTH	Dermai	Professio nal judgeme nt	1.D50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation- Dust Mist (4 hours)	Rat	LC50 + 2.7 mg l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 + 2,000 mg kg
CITRIC ESTER	Dermal	Professional judgement	1.D50 estimated to be > 5,000 mg/kg
CITRIC ESTER	Ingestion	Rat	1.D50 - 25,000 mg kg
SULFONIUM SALT	Dermal	Professio nal judgeme nt	1.D50 estimated to be 2.000 - 5.000 mg kg
SULFONIUM SALT	Ingestion	Rat	1.D50 + 2.000 mg kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 + 2,000 mg kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
SILANE TREATEAD SILICA	Dermal	Rabbit	LD50 ~ 5,000 mg/kg
SILANE TREATEAD SILICA	Inhalation- Dust Mist (4 hours)	Rat	LC50 × 0.691 mg/l
SILANE TREATEAD SILICA	Ingestion	Rat	1.D50 + 5,110 mg kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professio nal judgeme nt	1.D50 estimated to be + 5,000 mg kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50_5,700 mg/kg
FATTY ACIDS TRIGLYCERIDES	Dermal	Rabbit	LD50 - 2,000 mg/kg
FATTY ACIDS TRIGLYCERIDES	Ingestion	Rat	1.D50 + 2,000 mg kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
DIATOMACEOUS EARTH	In vuro data	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
SILANE TREATEAD SILICA	Rabbit	No significant irritation

Serious Ev	e Damag	e/Irritation
------------	---------	--------------

Name	Species	Value	

# IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST 02/25/16

DIATOMACEOUS EARTH	Rabbit	Mild irritant
SULFONIUM SALT	similar	Moderate irritant
	health	
	hazards	
SILANE TREATEAD SILICA	Rabbit	No significant irritation

### **Skin Sensitization**

Name	Species	Value
DIATOMACEOUS EARTH	Mouse	Not sensitizing
SILANE TREATEAD SILICA	Human	Not sensitizing
	and	·
	animal	

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
POLYMERIC ACETATE	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification
SULFONIUM SALT	In Vitro	Not mutagenic
SILANE TREATITAD SILICA	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIATOMACEOUS EARTH	Inhalation	Human	Carcinogenic
		and	
		animal	
SILANE TREATEAD SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

## Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATEAD SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg kg dav	I generation
SILANE TREATEAD SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg kg day	1 generation
SILANE TREATEAD SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg kg day	during organogenesi s

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SULFONIUM SALT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 2,000 mg kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
DIATOMACEOUS EARTH	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Ingestion	hematopoietic system   eyes .	All data are negative	Rat	NOAEL 3,738	90 days

## IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST 02/25/16

		kidney and or bladder			mg kg day	
SILANE TREATFAD SILICA	Inhalation	respiratory system silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

#### Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

#### Ecotoxicological information

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

## **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinto or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

#### 15.1. US Federal Regulations

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information

## California Proposition 65

Ingredient	
SILICA, CRYSTALLINE (AIRBORNE	
PARTICLES OF RESPIRABLE SIZE)	

C.A.S. No.	Classification
None	Carcinogen

#### IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST 92/25/16

WARNING: This product contains a chemical known to the State of California to cause cancer.

#### 15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: I Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 16-5566-1
 Version Number:
 6.00

 Issue Date:
 02/25/16
 Supercedes Date:
 12/16/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



# **Safety Data Sheet**

Copyright, 2016, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-5818-7
 Version Number:
 3.00

 Issue Date:
 02/25/16
 Supercedes Date:
 01/29/15

## **SECTION 1: Identification**

#### 1.1. Product identifier

IMPREGUM™ SOFT CATALYST

#### **Product Identification Numbers**

LE-F100-0608-0

### 1.2. Recommended use and restrictions on use

## Recommended use

Dental Product, Impression Material

## Restrictions on use

For use only by dental professionals.

## 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** Oral Care Solutions Division

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

## 2.2. Label elements

Signal word

Warning

# **Symbols**

Not applicable

Page 1 of 9

### **Pictograms**

Not applicable

#### **Hazard Statements**

Causes eye irritation.

## **Precautionary Statements**

#### **Prevention:**

Wash thoroughly after handling.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
CITRIC ESTER	77-90-7	35 - 45 Trade Secret *
SILANE TREATED SILICA	68909-20-6	20 - 30 Trade Secret *
SULFONIUM SALT	72140-65-9	< 25 Trade Secret *
CRISTOBALITE	14464-46-1	5 - 10 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	1 - 10 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

## **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

# 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

Page 2 of 9

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

## 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

## Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable	A2: Suspected human
			fraction):0.025 mg/m3	carcin.
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(as total	
			dust):0.15 mg/m3;TWA	

	concentration(respirable):0.05	
	mg/m3(1.2 millions of	
	particles/cu. ft.)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

## 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

Respiratory protection is not required.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

General Physical Form:
Specific Physical Form:
Paste

Odor, Color, Grade: White paste with characteristic odor

**Odor threshold** No Data Available Not Applicable pН **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** No Data Available Flammability (solid, gas) Not Classified Flammable Limits(LEL) Not Applicable Not Applicable Flammable Limits(UEL) Not Applicable **Vapor Pressure Vapor Density** Not Applicable **Density** 1.2 - 1.4 g/cm3

**Specific Gravity** 1.2 - 1.4 [*Ref Std:* WATER=1]

Solubility in Water Negligible

Solubility - non-water

Solubility - non-water

Partition coefficient: n-octanol/ water

Autoignition temperature

Decomposition temperature

No Data Available

No Data Available

No Data Available

No Data Available

Page 4 of 9

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

## 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents

## 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

## **Eye Contact:**

Page 5 of 9

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Additional Health Effects:**

## Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	CAS No.	Class Description	Regulation
SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
SILICA, CRYS AIRRESP	68855-54-9	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYS AIRRESP	68855-54-9	Known human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
CITRIC ESTER	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
SULFONIUM SALT	Dermal	Professio nal judgeme nt	LD50 estimated to be 2,000 - 5,000 mg/kg
SULFONIUM SALT	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Dermal	Professio nal judgeme nt	LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation- Dust/Mist (4 hours)	Rat	LC50 > 2.7 mg/l
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
CRISTOBALITE	Professio	No significant irritation
	nal	
	judgeme	
	nt	

DIATOMACEOUS EARTH	In vitro	No significant irritation
	data	

**Serious Eye Damage/Irritation** 

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	similar	Moderate irritant
	health	
	hazards	
DIATOMACEOUS EARTH	Rabbit	Mild irritant

## **Skin Sensitization**

Name	Species	Value
SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	
DIATOMACEOUS EARTH	Mouse	Not sensitizing

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
SILANE TREATED SILICA	In Vitro	Not mutagenic
SULFONIUM SALT	In Vitro	Not mutagenic
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not sufficient for classification
CRISTOBALITE	In vivo	Some positive data exist, but the data are not sufficient for classification
DIATOMACEOUS EARTH	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
CRISTOBALITE	Inhalation	Human	Carcinogenic
		and	
		animal	
DIATOMACEOUS EARTH	Inhalation	Human	Carcinogenic
		and	
		animal	

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure

						Duration
SULFONIUM SALT	Ingestion	central nervous	May cause drowsiness or	Rat	LOAEL	
		system depression	dizziness		2,000 mg/kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
SILANE TREATED	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
SILICA		silicosis			available	exposure
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through	Human	NOAEL Not	occupational
			prolonged or repeated exposure		available	exposure
DIATOMACEOUS	Inhalation	silicosis	Causes damage to organs through	Human	NOAEL Not	occupational
EARTH			prolonged or repeated exposure		available	exposure
DIATOMACEOUS	Ingestion	hematopoietic	All data are negative	Rat	NOAEL	90 days
EARTH		system   eyes	_		3,738	
		kidney and/or			mg/kg/day	
		bladder				

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# SECTION 15: Regulatory information

## 15.1. US Federal Regulations

Contact 3M for more information.

**Page** 8 **of** 9

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 25-5818-7
 Version Number:
 3.00

 Issue Date:
 02/25/16
 Supercedes Date:
 01/29/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9



# **Material Safety Data Sheet**

Copyright, 2011, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**PRODUCT NAME:** 3M<sup>TM</sup> ESPE<sup>TM</sup> IMPREGUM<sup>TM</sup> SOFT INTRO KIT

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

## EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 08/23/11 **Supercedes Date:** 10/27/08

**Document Group:** 25-6736-0

## **ID** Number(s):

70-2011-3463-5, 70-2011-3784-4

This product is a kit or a multipart product which consists of multiple, independently packaged components. An MSDS for each of these components is included. Please do not separate the component MSDSs from this cover page. The document numbers of the MSDSs for components of this product are:

25-5898-9, 25-5818-7, 16-5565-3, 16-5566-1, 16-4015-0

**Revision Changes:** 

Kit: Component document group number(s) was modified.

Page Heading: Product name was modified.

Kit: Product name was modified. Kit: ID Number(s) was modified.

Section 1: Manufacturer name was added.

Section 16: Disclaimer (first paragraph) was added.

Section 16: Disclaimer (second paragraph) was added.

Section 16: Web address was added.

Section 1: Address was added.

Copyright was added.

Company logo was added.

### MATERIAL SAFETY DATA SHEET 3MTM ESPETM IMPREGUMTM SOFT INTRO KIT 08/23/11

Telephone header was added.

Company Telephone was added.

Section 1: Emergency phone information was added.

Company Logo was deleted.

Copyright was deleted.

Kit: Manufacturer's name was deleted.

Kit: Emergency phone information was deleted.

Kit: Disclaimer (first paragraph) was deleted.

Kit: Disclaimer (second paragraph) was deleted.

Kit: Address line 1 was deleted.

Kit: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



# **Material Safety Data Sheet**

Copyright, 2011, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

# **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** 30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA)

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center

St. Paul. MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 03/02/11 **Supercedes Date:** 04/09/10

**Document Group:** 16-4015-0

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals. Specific Use: Used in impressioning systems.

# **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	C.A.S. No.	% by Wt
ETHYL ACETATE	141-78-6	25 - 50
HEPTANE	142-82-5	25 - 35
ACETONE	67-64-1	5 - 15
METHYLCYCLOHEXANE	108-87-2	5 - 10
FORMALDEHYDE, POLYMER WITH 1,3-BENZENEDIOL AND 4-(1,1-	59633-97-5	0 - 5
DIMETHYLETHYL)PHENOL		
POLYCHLOROPRENE	9010-98-4	0 - 5

# **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

General Physical Form: Liquid

**Immediate health, physical, and environmental hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. May cause target organ effects. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eve Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Skin Contact:**

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

## **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

# **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature** No Data Available

Flash Point 30 °F [Test Method: Closed Cup]

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** Flammable liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

# SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Remove all ignition sources such as flames, smoking materials, and electrical spark sources. Use only non-sparking tools. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard.

## **6.2. Environmental precautions**

For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Collect the resulting residue containing solution. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

#### Clean-up methods

Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Cover spill area with a fire-extinguishing foam designed for use on solvents, such as alcohols and acetone, that can dissolve in water. An AR - AFFF type foam is recommended. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water. Seal the container.

Page 3 of 8

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

# **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Contents may be under pressure, open carefully. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid skin contact.

## 7.2 STORAGE

Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Keep container tightly closed.

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1 ENGINEERING CONTROLS

Use in an enclosed process area is recommended. Use in a well-ventilated area. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits and/or control mist, vapor, or spray. If ventilation is not adequate, use respiratory protection equipment.

# 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid skin contact.

## 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

### 8.2.4 Prevention of Swallowing

Not applicable. Do not ingest.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
ACETONE	ACGIH	TWA	500 ppm	
ACETONE	ACGIH	STEL	750 ppm	
ACETONE	OSHA	TWA	2400 mg/m3	
ETHYL ACETATE	ACGIH	TWA	400 ppm	
ETHYL ACETATE	OSHA	TWA	1400 mg/m3	
HEPTANE	OSHA	TWA	2000 mg/m3	
Heptane, all isomers	ACGIH	TWA	400 ppm	
Heptane, all isomers	ACGIH	STEL	500 ppm	
METHYLCYCLOHEXANE	ACGIH	TWA	400 ppm	

Page 4 of 8

METHYLCYCLOHEXANE OSHA TWA 2000 mg/m3

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

General Physical Form: Liquid

 ${\bf Autoignition \ temperature} \qquad \qquad No \ Data \ Available$ 

Flash Point 30 °F [Test Method: Closed Cup]

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

**Boiling Point** 133 °F

**Density**No Data Available **Vapor Density**2 - 4 [Ref Std: AIR=1]

Vapor Pressure 180 mmHg

**Specific Gravity** 0.8 - 0.9 [*Ref Std:* WATER=1]

pH No Data Available
Melting point No Data Available

Solubility in Water Moderate

**Evaporation rate** Approximately 1 [*Ref Std:* BUOAC=1]

Volatile Organic CompoundsNo Data AvailableKow - Oct/Water partition coefNo Data AvailablePercent volatileNo Data AvailableVOC Less H2O & Exempt SolventsNo Data AvailableViscosity40000 centipoise

# **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

Sparks and/or flames

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

<u>Substance</u> <u>Condition</u>

Carbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

# **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

# **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator. As a disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

Since regulations vary, consult applicable regulations or authorities before disposal.

# SECTION 14:TRANSPORT INFORMATION

## **ID Number(s):**

70-2011-0648-4, 70-2011-0895-1, 70-2011-0997-5

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: REGULATORY INFORMATION**

# US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	C.A.S. No	Regulation	Status
HEPTANE (Heptane)	142-82-5	Toxic Substances Control Act (TSCA) 4 Test	Applicable
		Rule Chemicals	
HEPTANE	142-82-5	Toxic Substances Control Act (TSCA) 4 Test	Applicable
		Rule Chemicals	

## STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

Health: 1 Flammability: 3 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Page 7 of 8

### MATERIAL SAFETY DATA SHEET 30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA) 03/02/11

#### **Revision Changes:**

Copyright was modified.

Section 3: Potential effects from inhalation information was modified.

Section 3: Potential effects from ingestion information was modified.

Section 14: Transportation legal text was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 2: Ingredient table was modified.

Section 8: Exposure guidelines ingredient information was modified.

Section 15: TSCA section 12[b] information was modified.

Section 6: Methods for cleaning up information was modified.

Section 3: Immediate other hazard(s) was added.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

Section 6: Clean-up methods heading was added.

Section 6: Release measures heading was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com

Page 8 of 8



## **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB BASE

**MANUFACTURER: 3**3

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

#### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 12/10/12 **Supercedes Date:** 02/07/12

**Document Group:** 16-5565-3

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals

Specific Use: Impression

## **SECTION 2: INGREDIENTS**

Ingredient	<b>C.A.S. No.</b>	% by Wt
POLYETHER	110531-92-5	75 - 85
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 10
DIATOMACEOUS EARTH	68855-54-9	1 - 10
DIBENZYL TOLUENE	26898-17-9	1 - 10
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5
C.I. PIGMENT WHITE 5	1345-05-7	1 - 5
1-DODECYLIMIDAZOLE	4303-67-7	< 1

## **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Orange colored pastes, characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: No immediate health, physical, or environmental hazards are anticipated.

#### 3.2 POTENTIAL HEALTH EFFECTS

### **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **SECTION 4: FIRST AID MEASURES**

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. **Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** During a fire irritating gases may develop.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air.

#### 6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Clean up residue with detergent and water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid prolonged or repeated skin contact.

### 7.2 STORAGE

Store away from heat.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Not applicable.

## **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

#### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

#### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<b>Authority</b>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
BARIUM, SOLUBLE COMPOUNDS	ACGIH	TWA, as Ba	0.5 mg/m3	
BARIUM, SOLUBLE COMPOUNDS	OSHA	TWA, as Ba	0.5 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of	

particles/cu. ft.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Paste

Odor, Color, Grade: Orange colored pastes, characteristic odor

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableBoiling PointNot ApplicableDensity1 g/cm3 - 1.2 g/cm3Vapor DensityNot Applicable

Vapor Pressure No Data Available

Specific Gravity 1 - 1.2 [Ref Std: WATER=1]

**pH Melting point**Not Applicable
Not Applicable

Solubility in WaterNegligibleEvaporation rateNot ApplicableVolatile Organic CompoundsNo Data AvailableKow - Oct/Water partition coefNo Data AvailablePercent volatileNo Data AvailableVOC Less H2O & Exempt SolventsNo Data AvailableViscosity40 Pa-s - 150 Pa-s

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

**Materials and Conditions to Avoid:** 

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

#### CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions.

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

LE-FSFD-3061-2

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: REGULATORY INFORMATION**

#### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
C.I. PIGMENT WHITE 5 (Barium compounds,	1345-05-7	1 - 5
except barium sulfate)		
C.I. PIGMENT WHITE 5 (ZINC COMPOUNDS)	1345-05-7	1 - 5

### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision Changes:**

Section 2: Ingredient table was modified.

Section 15: EPCRA 313 information was added.

Section 15: EPCRA 313 text was added.

Section 8: Exposure guidelines ingredient information was added.

Section 8: Exposure guidelines information - none - was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



## **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB CATALYST

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

#### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 02/07/12 **Supercedes Date:** 02/10/10

**Document Group:** 16-5566-1

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals

Specific Use: Impression

## **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYMERIC ACETATE	91825-26-2	25 - 35
DIATOMACEOUS EARTH	68855-54-9	20 - 30
CITRIC ESTER	77-90-7	10 - 20
SULFONIUM SALT	72140-65-9	10 - 20
DIBENZYL TOLUENE	26898-17-9	1 - 10
SILANE TREATEAD SILICA	68909-20-6	1 - 10
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 5
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5

## **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Red colored pastes, slightly acrid odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: May cause target organ effects.

#### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### **Target Organ Effects:**

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **SECTION 4: FIRST AID MEASURES**

#### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Page 2 of 7

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air.

#### 6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

#### Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid prolonged or repeated skin contact.

### 7.2 STORAGE

Store away from heat.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable.

## **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

### 8.3 EXPOSURE GUIDELINES

None Established

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Specific Physical Form:** Paste

Odor, Color, Grade: Red colored pastes, slightly acrid odor

**General Physical Form:** 

**Autoignition temperature** Not Applicable **Flash Point** No flash point Not Applicable Flammable Limits(LEL) Flammable Limits(UEL) Not Applicable Not Applicable **Boiling Point** 1.1 g/cm3 - 1.2 g/cm3 **Density** Vapor Density No Data Available

**Vapor Pressure** No Data Available

1.1 - 1.2 [*Ref Std:* WATER=1] **Specific Gravity** 

Not Applicable **Melting point** No Data Available

Negligible Solubility in Water **Evaporation rate** Not Applicable Not Applicable **Volatile Organic Compounds Kow - Oct/Water partition coef** No Data Available Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

Viscosity No Data Available

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid:

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

**Substance Condition** Carbon monoxide **During Combustion** Carbon dioxide **During Combustion** 

Page 4 of 7

Irritant Vapors or Gases

**During Combustion** 

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

#### CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions.

Dispose of completely absorbed waste product in a sanitary landfill. As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

Combustion products will include HF. Facility must be capable of handling halogenated materials.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

LE-FSFD-6306-1

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: REGULATORY INFORMATION**

## US FEDERAL REGULATIONS

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

#### STATE REGULATIONS

Contact 3M for more information.

### **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the

FDA.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision Changes:**

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 8: Eye/face protection information was modified.

Section 14: Transportation legal text was modified.

Section 9: Vapor density value was modified.

Section 9: Vapor pressure value was modified.

Section 9: Boiling point information was modified.

Section 5: Flammable limits (UE) information was modified.

Section 5: Flammable limits (LEL) information was modified.

Section 5: Autoignition temperature information was modified.

Section 5: Flash point information was modified.

Section 9: Property description for optional properties was modified.

Section 9: Specific gravity information was modified.

Section 9: pH information was modified.

Section 9: Melting point information was modified.

Section 9: Solubility in water text was modified.

Section 9: Flash point information was modified.

Section 9: Flammable limits (LEL) information was modified.

Section 9: Flammable limits (UEL) information was modified.

Section 9: Autoignition temperature information was modified.

Section 2: Ingredient table was modified.

Section 10: Materials to avoid physical property was modified.

Section 10: Conditions to avoid physical property was modified.

Section 9: Density information was added.

Section 6: 6.2. Environmental precautions heading was added.

Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.

Section 16: Web address was added.

Section 1: Address was added.

Copyright was added.

Company logo was added.

Section 6: Clean-up methods heading was added.

Telephone header was added.

Page 6 of 7

Company Telephone was added.

Section 1: Emergency phone information was added.

Section 1: Emergency phone information was deleted.

Company Logo was deleted.

Copyright was deleted.

Section 16: Web address heading was deleted.

Section 6: Release measures heading was deleted.

Section 1: Address line 1 was deleted.

Section 1: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com

Page 7 of 7



## **Material Safety Data Sheet**

Copyright, 2009, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** IMPREGUM(TM) SOFT CATALYST

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center

St. Paul. MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 02/27/2009 **Supercedes Date:** 09/29/2008

**Document Group:** 25-5818-7

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals.

Specific Use: Impression Material

## **SECTION 2: INGREDIENTS**

<u>Ingredient</u>	<u>C.A.S. No.</u>	% by Wt
CITRIC ESTER	77-90-7	35 - 45
SILANE TREATED SILICA	68909-20-6	20 - 30
SULFONIUM SALT	72140-65-9	< 25
CRISTOBALITE	14464-46-1	5 - 10
DIATOMACEOUS EARTH	68855-54-9	1 - 10

## **SECTION 3: HAZARDS IDENTIFICATION**

## 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: White paste with characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards:

Contains a chemical or chemicals which can cause

cancer.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this

document may vary depending on the potential for exposure.

See Section 3.2 for other hazards that can be associated with the ingredients in this product in a non-emergency situation.

### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### **Inhalation:**

No health effects are expected.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u> <u>C.A.S. No.</u> <u>Class Description</u> <u>Regulation</u>

CRISTOBALITE 14464-46-1 Known human carcinogen National Toxicology Program Carcinogens

## **SECTION 4: FIRST AID MEASURES**

## 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

#### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature** Not Applicable

Flash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot Applicable

### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Ventilate the area with fresh air. Contain spill. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

#### 7.1 HANDLING

Avoid eye contact. Avoid skin contact. Wash hands after handling and before eating. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

### 7.2 STORAGE

Store away from heat. Store out of direct sunlight.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

## 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields.

## 8.2.2 Skin Protection

Gloves not normally required. Avoid skin contact.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not ingest. Wash hands after handling and before eating.

#### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	Additional Information
CRISTOBALITE	ACGIH	TWA, respirable	0.025  mg/m	_
CRISTOBALITE	OSHA	TWA, as respirable	0.05  mg/m3	Table Z-1A
		quartz		
DIATOMACEOUS EARTH	OSHA	TWA, as total dust	6 mg/m3	Table Z-1A

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Paste

Odor, Color, Grade: White paste with characteristic odor

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNot ApplicableFlammable Limits - LELNot ApplicableFlammable Limits - UELNot ApplicableBoiling pointNot ApplicableDensity1.2 - 1.4 g/cm3Vapor DensityNot Applicable

Vapor Pressure

Not Applicable

**Specific Gravity** 1.2 - 1.4 [*Ref Std:* WATER=1]

pH Not ApplicableMelting point No Data Available

Solubility in Water Negligible

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Materials and Conditions to Avoid: Heat

**Hazardous Polymerization:** Hazardous polymerization will not occur.

### **Hazardous Decomposition or By-Products**

<u>Substance</u> <u>Condition</u>

Carbon monoxide During Combustion
Carbon dioxide During Combustion

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **ECOTOXICOLOGICAL INFORMATION**

Not determined.

## CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

LE-F100-0608-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## **SECTION 15: REGULATORY INFORMATION**

### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

### STATE REGULATIONS

Contact 3M for more information.

#### CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:** 

Copyright was modified.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely

within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com



## **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

**PRODUCT NAME:** 3M<sup>TM</sup> ESPE<sup>TM</sup> IMPREGUM<sup>TM</sup> SOFT BASE

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

#### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 01/02/12 **Supercedes Date:** 09/29/08

**Document Group:** 25-5898-9

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals.

Specific Use: Impression Material

## **SECTION 2: INGREDIENTS**

Ingredient	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYETHER	110531-92-5	60 - 70
CRISTOBALITE	14464-46-1	5 - 15
FLUX CALCINED DIATOMACEOUS EARTH	68855-54-9	< 10
POLY GLYCOL MONOBUTYLETHER	9038-95-3	5 - 10
TRIGLYCERIDES	67701-27-3	5 - 10
MAGNESIUM OXIDE	1309-48-4	1 - 5
1-DODECYLIMIDAZOLE	4303-67-7	< 1.0

## **SECTION 3: HAZARDS IDENTIFICATION**

### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Lilac paste, characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: Contains a chemical or chemicals which can cause cancer. .

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

See Section 3.2 for other hazards that can be associated with the ingredients in this product in a non-emergency situation.

### 3.2 POTENTIAL HEALTH EFFECTS

#### **Eve Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### **Target Organ Effects:**

Prolonged or repeated exposure may cause:

Liver Effects: Signs/symptoms may include loss of appetite, weight loss, fatigue, weakness, abdominal tenderness and jaundice.

Kidney/Bladder Effects: Signs/symptoms may include changes in urine production, abdominal or lower back pain, increased protein in urine, increased blood urea nitrogen (BUN), blood in urine, and painful urination.

#### Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

IngredientC.A.S. No.Class DescriptionRegulationCRISTOBALITE14464-46-1Known human carcinogenNational Toxicology Program Carcinogens

## **SECTION 4: FIRST AID MEASURES**

#### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** If signs/symptoms develop, remove person to fresh air. If signs/symptoms persist, get medical attention. No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

## 5.1 FLAMMABLE PROPERTIES

Page 2 of 8

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Not applicable.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

### 6.1. Personal precautions, protective equipment and emergency procedures

## 6.2. Environmental precautions

#### Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Avoid skin contact. Wash hands after handling and before eating. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

### 7.2 STORAGE

Store away from heat. Store out of direct sunlight.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 ENGINEERING CONTROLS

Not applicable.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

#### 8.2.2 Skin Protection

Avoid skin contact. Gloves not normally required.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

### 8.2.4 Prevention of Swallowing

Do not ingest. Wash hands after handling and before eating.

## 8.3 EXPOSURE GUIDELINES

Ingredient	<b>Authority</b>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
CRISTOBALITE	ACGIH	TWA, respirable	$\overline{0.025}$ mg/m3	
		fraction		
CRISTOBALITE	OSHA	TWA concentration,	0.05  mg/m3	
		respirable		
CRISTOBALITE	OSHA	TWA concentration,	0.15  mg/m3	
		as total dust		
MAGNESIUM OXIDE	ACGIH	TWA, inhalable	10 mg/m3	
		fraction		
MAGNESIUM OXIDE	OSHA	TWA, as total	15 mg/m3	
		particulates		

## SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**Specific Physical Form:** Paste

Odor, Color, Grade: Lilac paste, characteristic odor

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableBoiling PointNot ApplicableDensity1 - 1.2 g/cm3Vapor DensityNot Applicable

Vapor Pressure No Data Available

**Specific Gravity** 1 - 1.2 [*Ref Std:* WATER=1]

pH Not Applicable
Melting point Not Applicable

Solubility in Water Evaporation rate Kow - Oct/Water partition coef Negligible No Data Available No Data Available No Data Available

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

Viscosity

Materials and Conditions to Avoid: 10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

**Substance** Condition

Carbon monoxide During Combustion
Carbon dioxide During Combustion

## **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### ECOTOXICOLOGICAL INFORMATION

Not determined.

## CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in an industrial or commercial facility in the presence of a combustible material. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

LE-F100-0608-7

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: REGULATORY INFORMATION**

#### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

#### STATE REGULATIONS

Contact 3M for more information.

#### CHEMICAL INVENTORIES

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: OTHER INFORMATION**

### **NFPA Hazard Classification**

**Health:** 1 Flammability: 0 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:** 

Section 1: Product name was modified.

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 8: Skin protection phrase was modified.

Section 10: Hazardous decomposition or by-products table was modified.

Section 8: Eye/face protection information was modified.

Section 14: Transportation legal text was modified.

Page Heading: Product name was modified.

Section 9: Density information was modified.

Section 9: Vapor density value was modified.

Section 9: Vapor pressure value was modified.

Page 6 of 8

- Section 9: Boiling point information was modified.
- Section 5: Flammable limits (UE) information was modified.
- Section 5: Flammable limits (LEL) information was modified.
- Section 5: Autoignition temperature information was modified.
- Section 5: Flash point information was modified.
- Section 9: Specific gravity information was modified.
- Section 9: pH information was modified.
- Section 9: Melting point information was modified.
- Section 9: Solubility in water text was modified.
- Section 9: Flash point information was modified.
- Section 9: Flammable limits (LEL) information was modified.
- Section 9: Flammable limits (UEL) information was modified.
- Section 9: Autoignition temperature information was modified.
- Section 2: Ingredient table was modified.
- Section 8: Exposure guidelines ingredient information was modified.
- Section 3: Carcinogenicity table was modified.
- Section 9: Property description for optional properties was added.
- Section 6: 6.2. Environmental precautions heading was added.
- Section 6: 6.1. Personal precautions, protective equipment and emergency procedures heading was added.
- Section 10.1 Conditions to avoid heading was added.
- Section 10.2 Materials to avoid heading was added.
- Section 16: Web address was added.
- Section 6: Methods for cleaning up information was added.
- Section 10: Materials to avoid physical property was added.
- Section 10: Conditions to avoid physical property was added.
- Section 8: Hand protection information was added.
- Section 1: Address was added.
- Copyright was added.
- Company logo was added.
- Section 6: Clean-up methods heading was added.
- Telephone header was added.
- Company Telephone was added.
- Section 1: Emergency phone information was added.
- Section 1: Emergency phone information was deleted.
- Company Logo was deleted.
- Copyright was deleted.
- Section 16: Web address heading was deleted.
- Section 6: Release measures information was deleted.
- Section 6: Release measures heading was deleted.
- Section 10: Materials and conditions to avoid physical property was deleted.
- Section 1: Address line 1 was deleted.
- Section 1: Address line 2 was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

Page 7 of 8

ERIAL SAFETY DATA	SHEET 3MTM ESPETM	IMPREGUM <sup>TM</sup> SOF	T BASE 01/02/12	 
3M USA MSDSs are	available at www.3M.c	om		
	avanable at www.51vi.e	OIII		



## **Material Safety Data Sheet**

Copyright, 2012, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

## **SECTION 1: PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME: IMPREGUM GARANT L DUOSOFT/ IMPREGUM GARANT SOFT LB BASE

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

ADDRESS: 3M Center, St. Paul, MN 55144-1000

#### EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 12/10/12 **Supercedes Date:** 02/07/12

**Document Group:** 16-5565-3

**Product Use:** 

Intended Use: Dental Product

Limitations on Use: For use only by dental professionals

Specific Use: Impression

## **SECTION 2: INGREDIENTS**

Ingredient	<u>C.A.S. No.</u>	<u>% by Wt</u>
POLYETHER	110531-92-5	75 - 85
FATTY ACIDS TRIGLYCERIDES	67701-27-3	1 - 10
DIATOMACEOUS EARTH	68855-54-9	1 - 10
DIBENZYL TOLUENE	26898-17-9	1 - 10
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5
C.I. PIGMENT WHITE 5	1345-05-7	1 - 5
1-DODECYLIMIDAZOLE	4303-67-7	< 1

## **SECTION 3: HAZARDS IDENTIFICATION**

### 3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: Orange colored pastes, characteristic odor

General Physical Form: Solid

Immediate health, physical, and environmental hazards: No immediate health, physical, or environmental hazards are anticipated.

#### 3.2 POTENTIAL HEALTH EFFECTS

### **Eye Contact:**

Mechanical eye irritation: Signs/symptoms may include pain, redness, tearing and corneal abrasion.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **SECTION 4: FIRST AID MEASURES**

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention. **Skin Contact:** Wash affected area with soap and water. If signs/symptoms develop, get medical attention.

**Inhalation:** No need for first aid is anticipated.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## **SECTION 5: FIRE FIGHTING MEASURES**

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not Applicable

### 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

#### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** During a fire irritating gases may develop.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air.

#### 6.2. Environmental precautions

Collect the resulting residue containing solution. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Contain spill. Collect as much of the spilled material as possible. Clean up residue with detergent and water.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

## **SECTION 7: HANDLING AND STORAGE**

### 7.1 HANDLING

Avoid eye contact. Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid prolonged or repeated skin contact.

#### 7.2 STORAGE

Store away from heat.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

#### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Not applicable.

## **8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)**

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid prolonged or repeated skin contact. Gloves not normally required.

#### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

#### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Do not ingest.

#### 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<b>Authority</b>	<b>Type</b>	<u>Limit</u>	<b>Additional Information</b>
BARIUM, SOLUBLE COMPOUNDS	ACGIH	TWA, as Ba	0.5  mg/m3	
BARIUM, SOLUBLE COMPOUNDS	OSHA	TWA, as Ba	0.5 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA concentration	0.8 mg/m3	
SILICA, AMORPHOUS	OSHA	TWA	20 millions of	

particles/cu. ft.

## **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Specific Physical Form: Paste

Odor, Color, Grade: Orange colored pastes, characteristic odor

General Physical Form: Solid

Autoignition temperatureNot ApplicableFlash PointNo flash pointFlammable Limits(LEL)Not ApplicableFlammable Limits(UEL)Not ApplicableBoiling PointNot ApplicableDensity1 g/cm3 - 1.2 g/cm3Vapor DensityNot Applicable

Vapor Pressure No Data Available

Specific Gravity 1 - 1.2 [Ref Std: WATER=1]

**pH Melting point**Not Applicable
Not Applicable

Solubility in WaterNegligibleEvaporation rateNot ApplicableVolatile Organic CompoundsNo Data AvailableKow - Oct/Water partition coefNo Data AvailablePercent volatileNo Data AvailableVOC Less H2O & Exempt SolventsNo Data AvailableViscosity40 Pa-s - 150 Pa-s

## **SECTION 10: STABILITY AND REACTIVITY**

Stability: Stable.

**Materials and Conditions to Avoid:** 

10.1 Conditions to avoid

Heat

10.2 Materials to avoid

None known

Hazardous Polymerization: Hazardous polymerization will not occur.

## **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

# **SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## **SECTION 12: ECOLOGICAL INFORMATION**

### **ECOTOXICOLOGICAL INFORMATION**

Not determined.

#### CHEMICAL FATE INFORMATION

Not determined.

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Waste Disposal Method: Cure (harden, set, or react) the product according to product instructions.

Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## **SECTION 14:TRANSPORT INFORMATION**

LE-FSFD-3061-2

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: REGULATORY INFORMATION**

#### US FEDERAL REGULATIONS

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	C.A.S. No	% by Wt
C.I. PIGMENT WHITE 5 (Barium compounds,	1345-05-7	1 - 5
except barium sulfate)		
C.I. PIGMENT WHITE 5 (ZINC COMPOUNDS)	1345-05-7	1 - 5

### STATE REGULATIONS

Contact 3M for more information.

## **CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: OTHER INFORMATION**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

#### **Revision Changes:**

Section 2: Ingredient table was modified.

Section 15: EPCRA 313 information was added.

Section 15: EPCRA 313 text was added.

Section 8: Exposure guidelines ingredient information was added.

Section 8: Exposure guidelines information - none - was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

3M USA MSDSs are available at www.3M.com



## **Safety Data Sheet**

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-5898-9
 Version Number:
 2.00

 Issue Date:
 04/30/14
 Supercedes Date:
 01/02/12

## **SECTION 1: Identification**

#### 1.1. Product identifier

3M<sup>TM</sup> ESPE<sup>TM</sup> IMPREGUM<sup>TM</sup> SOFT BASE

#### **Product Identification Numbers**

LE-F100-0608-7

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression Material

#### Restrictions on use

For use only by dental professionals.

## 1.3. Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

#### 2.2. Label elements

Signal word

Warning

**Symbols** 

Exclamation mark |

#### **Pictograms**



#### **Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

## **Precautionary Statements**

#### **Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### 2.3. Hazards not otherwise classified

None.

68% of the mixture consists of ingredients of unknown acute dermal toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYETHER	110531-92-5	60 - 70 Trade Secret *
CRISTOBALITE	14464-46-1	5 - 15 Trade Secret *
POLY GLYCOL MONOBUTYLETHER	9038-95-3	5 - 10 Trade Secret *
FLUX CALCINED DIATOMACEOUS EARTH	68855-54-9	< 10 Trade Secret *
TRIGLYCERIDES	67701-27-3	5 - 10 Trade Secret *
MAGNESIUM OXIDE	1309-48-4	1 - 5 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1.0 Trade Secret *
MENTHA ARVENSIS, ext.	90063-97-1	< 0.5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

## Condition

During Combustion
During Combustion
During Combustion

## 5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

# **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Observe precautions from other sections.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
MAGNESIUM OXIDE	1309-48-4	Amer Conf of	TWA(inhalable fraction):10	
		Gov. Indust.	mg/m3	
		Hyg.		
MAGNESIUM OXIDE	1309-48-4	US Dept of	TWA(as total particulates):15	
		Labor - OSHA	mg/m3	
CRISTOBALITE	14464-46-1	Amer Conf of	TWA(respirable	
		Gov. Indust.	fraction):0.025 mg/m3	
		Hyg.		
CRISTOBALITE	14464-46-1	US Dept of	TWA concentration(as total	
		Labor - OSHA	dust):0.15 mg/m3;TWA	
			concentration(respirable):0.05	
			mg/m3(1.2 millions of	
			particles/cu. ft.)	

Amer Conf of Gov. Indust. Hyg.: American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid: Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

# 8.2.2. Personal protective equipment (PPE)

## Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

**General Physical Form:**Specific Physical Form:

Paste

Odor, Color, Grade: characteristic odor, lilac colored paste

No Data Available

**Odor threshold** No Data Available pН Not Applicable **Melting point** Not Applicable **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** No Data Available Not Classified Flammability (solid, gas) Not Applicable Flammable Limits(LEL) Flammable Limits(UEL) Not Applicable

Vapor Density Not Applicable

**Density** 1 - 1.2 g/cm3

Specific Gravity 1 - 1.2 [Ref Std: WATER=1]

Solubility in Water Negligible

**Solubility- non-water** No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosityNo Data Available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

# 10.2. Chemical stability

Vapor Pressure

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

## 10.5. Incompatible materials

Strong acids Strong bases

Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with individual components of the uncured product. Once properly mixed and cured, the product is safe for its intended use.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

## **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Carcinogenicity:**

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

Ingredient	C.A.S. No.	Class Description	Regulation
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

#### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000
			mg/kg
POLYETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg

TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
POLY GLYCOL MONOBUTYLETHER	Dermal	Rabbit	LD50 > 16,960 mg/kg
POLY GLYCOL MONOBUTYLETHER	Inhalation-	Rat	LC50 > 5 mg/l
	Dust/Mist		
	(4 hours)		
POLY GLYCOL MONOBUTYLETHER	Ingestion	Rat	LD50 4,240 mg/kg
FLUX CALCINED DIATOMACEOUS EARTH	Dermal	Rabbit	LD50 > 5,000 mg/kg
FLUX CALCINED DIATOMACEOUS EARTH	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 5,110 mg/kg
MAGNESIUM OXIDE	Ingestion	Rat	LD50 3,870 mg/kg
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
MENTHA ARVENSIS, ext.	Dermal	Rabbit	LD50 > 5,000 mg/kg
MENTHA ARVENSIS, ext.	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
POLYETHER	Rabbit	No significant irritation
POLY GLYCOL MONOBUTYLETHER	Rabbit	Minimal irritation
FLUX CALCINED DIATOMACEOUS EARTH	Rabbit	No significant irritation
MAGNESIUM OXIDE		No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
MENTHA ARVENSIS, ext.	Rabbit	Mild irritant

**Serious Eye Damage/Irritation** 

Name	Species	Value
POLYETHER	Rabbit	Moderate irritant
POLY GLYCOL MONOBUTYLETHER	Rabbit	No significant irritation
FLUX CALCINED DIATOMACEOUS EARTH	Rabbit	No significant irritation
1-DODECYLIMIDAZOLE	similar	Moderate irritant
	health	
	hazards	
MENTHA ARVENSIS, ext.	In vitro	Severe irritant
	data	

# **Skin Sensitization**

Name	Species	Value
POLYETHER	Guinea	Not sensitizing
	pig	
FLUX CALCINED DIATOMACEOUS EARTH	Human	Not sensitizing
	and	
	animal	
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
MENTHA ARVENSIS, ext.	Guinea	Sensitizing
	pig	

**Respiratory Sensitization** 

Name	Species	Value

**Germ Cell Mutagenicity** 

Name	Route	Value
POLYETHER	In Vitro	Not mutagenic
FLUX CALCINED DIATOMACEOUS EARTH	In Vitro	Not mutagenic
MAGNESIUM OXIDE	In Vitro	Not mutagenic
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic

Carcinogenicity

caremogementy			
Name	Route	Species	Value
POLY GLYCOL MONOBUTYLETHER	Ingestion	Rat	Not carcinogenic
FLUX CALCINED DIATOMACEOUS EARTH	Not	Mouse	Some positive data exist, but the data are not

	Specified		sufficient for classification
MAGNESIUM OXIDE	Not	Human	Some positive data exist, but the data are not
	Specified	and	sufficient for classification
		animal	

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
POLY GLYCOL MONOBUTYLETHER	Ingestion	Not toxic to female reproduction	Rat	NOAEL 3,770 mg/kg/day	90 days
POLY GLYCOL MONOBUTYLETHER	Ingestion	Not toxic to male reproduction	Rat	NOAEL 3,770 mg/kg/day	90 days
POLY GLYCOL MONOBUTYLETHER	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1 mg/l	2 weeks
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POLY GLYCOL MONOBUTYLETHER	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
MAGNESIUM OXIDE	Inhalation	respiratory system	All data are negative	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POLY GLYCOL MONOBUTYLETHER	Inhalation	endocrine system   hematopoietic system   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1 mg/l	2 weeks
POLY GLYCOL MONOBUTYLETHER	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL .005 mg/l	2 weeks
POLY GLYCOL MONOBUTYLETHER	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL .001 mg/l	2 weeks
POLY GLYCOL MONOBUTYLETHER	Inhalation	heart	All data are negative	Rat	NOAEL .5 mg/l	2 weeks
POLY GLYCOL MONOBUTYLETHER	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
POLY GLYCOL MONOBUTYLETHER	Ingestion	hematopoietic system	All data are negative	Rat	NOAEL 500 mg/kg/day	2 years
POLY GLYCOL MONOBUTYLETHER	Ingestion	heart   endocrine system   respiratory system	All data are negative	Rat	NOAEL 3,770 mg/kg/day	90 days
FLUX CALCINED DIATOMACEOUS EARTH	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

#### **Aspiration Hazard**

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

## **SECTION 14: Transport Information**

For Transport Information, please visit <u>http://3M.com/Transportinfo</u> or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

#### 15.2. State Regulations

Contact 3M for more information.

#### **15.3.** Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### **NFPA Hazard Classification**

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 25-5898-9
 Version Number:
 2.00

 Issue Date:
 04/30/14
 Supercedes Date:
 01/02/12

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

#### 3MTM ESPETM IMPREGUMTM SOFT QUICK STEP INTRODUCTORY KIT 04/15/15



# Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-6840-0
 Version Number:
 1.03

 Issue Date:
 04/15/15
 Supercedes Date:
 08/23/11

#### **Product identifier**

3MTM ESPETM IMPREGUMTM SOFT QUICK STEP INTRODUCTORY KIT

**ID** Number(s):

70-2011-3785-1

#### Recommended use

Dental Product, Impression Material **Restrictions on use**For use only by dental professionals

For use only by dental professionals.

# Supplier's details

**MANUFACTURER:** 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

#### **Emergency telephone number**

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

16-4015-0, 18-7383-5, 25-5821-1, 25-5901-1, 18-7382-7

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

3M <sup>TM</sup> ESPE <sup>TM</sup> IMPREGUM <sup>TM</sup> SOFT QUICK STEP INTRODUCTORY KIT 04/15/15					
In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M					
3M USA SDSs are available at www.3M.com					



# **Safety Data Sheet**

Copyright,2015,3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 18-7382-7
 Version Number:
 7.01

 Issue Date:
 06/09/15
 Supercedes Date:
 05/29/15

# **SECTION 1: Identification**

#### 1.1. Product identifier

3MTM ESPETM IMPREGUMTM SOFT QUICK STEP LIGHT BODY BASE

#### **Product Identification Numbers**

LE-FSFD-7382-7

#### 1.2. Recommended use and restrictions on use

## Recommended use

Dental Product, Impression material

#### Restrictions on use

For use only by dental professionals

#### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

#### 2.2. Label elements

## Signal word

Warning

#### **Symbols**

Exclamation mark |

Page 1 of 9

#### **Pictograms**



#### **Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

### **Precautionary Statements**

#### **Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

## Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYETHER	110531-92-5	75 - 85 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
TRIALKYL GLYCERIDES	67701-27-3	1 - 10 Trade Secret *
SULFONAMIDE	80-39-7	1 - 5 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	1 - 5 Trade Secret *
C.I. PIGMENT WHITE 5	1345-05-7	1 - 5 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1.0 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

#### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

#### Substance Carbon monoxide

Carbon dioxide Irritant Vapors or Gases

#### Condition

During Combustion
During Combustion
During Combustion

#### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment.

Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

#### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

#### **Respiratory protection**

Respiratory protection is not required.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**General Physical Form:** Solid **Specific Physical Form:** Paste

Odor, Color, Grade: characteristic odor, orange colored paste

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNot ApplicableBoiling PointNot Applicable

**Flash Point** Flash point > 93 °C (200 °F)

**Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Not Applicable Flammable Limits(LEL) Flammable Limits(UEL) Not Applicable **Vapor Pressure** Not Applicable **Vapor Density** Not Applicable No Data Available **Density Specific Gravity** > 1 [Ref Std: WATER=1]

Page 4 of 9

Solubility in Water Negligible

Solubility- non-water No Data Available No Data Available Partition coefficient: n-octanol/ water **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available No Data Available Viscosity **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

#### 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Page 5 of 9

## 3M<sup>TM</sup> ESPE<sup>TM</sup> IMPREGUM<sup>TM</sup> SOFT QUICK STEP LIGHT BODY BASE 06/09/15

#### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

## **Skin Contact:**

May be harmful in contact with skin.

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### **Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE 2,000 - 5,000
			mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000
			mg/kg
POLYETHER	Dermal	Professio	LD50 Not applicable
		nal	
		judgeme	
		nt	
POLYETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
TRIALKYL GLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
TRIALKYL GLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
SULFONAMIDE	Dermal	Rabbit	LD50 > 5,000 mg/kg
SULFONAMIDE	Ingestion	similar	LD50 estimated to be 300 - 2,000 mg/kg
		compoun	
		ds	
DIATOMACEOUS EARTH	Dermal	Rabbit	LD50 > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
C.I. PIGMENT WHITE 5	Ingestion	Rat	LD50 > 15,000 mg/kg
C.I. PIGMENT WHITE 5	Dermal	similar	LD50 > 1,000 mg/kg
		compoun	
		ds	
C.I. PIGMENT WHITE 5	Inhalation-	similar	LC50 > 2.52 mg/l
	Dust/Mist	compoun	
	(4 hours)	ds	
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg

ATE = acute toxicity estimate

#### Skin Corrosion/Irritation

Name Species Value
--------------------

POLYETHER	Rabbit	No significant irritation
DIATOMACEOUS EARTH	Rabbit	No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant

Serious Eve Damage/Irritation

Name	Species	Value
POLYETHER	Rabbit	Moderate irritant
DIATOMACEOUS EARTH	Rabbit	No significant irritation
1-DODECYLIMIDAZOLE	In vitro	Severe irritant
	data	

## **Skin Sensitization**

Name	Species	Value
POLYETHER	Guinea	Not sensitizing
	pig	
DIATOMACEOUS EARTH	Human	Not sensitizing
	and	
	animal	
1-DODECYLIMIDAZOLE	Mouse	Sensitizing

#### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
POLYETHER	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Not mutagenic
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIATOMACEOUS EARTH	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

#### Reproductive Toxicity

Reproductive and/or Developmental Effects

Reproductive and/or Developmental Effects								
Name	Route	Value	Species	Test Result	Exposure			
					Duration			
DIATOMACEOUS EARTH	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509	1 generation			
		_		mg/kg/day				
DIATOMACEOUS EARTH	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497	1 generation			
		_		mg/kg/day				
DIATOMACEOUS EARTH	Ingestion	Not toxic to development	Rat	NOAEL	during			
		_		1,350	organogenesi			
				mg/kg/day	S			

## Target Organ(s)

## **Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Specific ranger organ	pecific Turget Organ Toxicity Tepetatea exposure								
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure			
						Duration			
DIATOMACEOUS	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational			
EARTH		silicosis			available	exposure			

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

## 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

## 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 18-7382-7
 Version Number:
 7.01

 Issue Date:
 06/09/15
 Supercedes Date:
 05/29/15

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9



# Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 18-7383-5
 Version Number:
 5.00

 Issue Date:
 12/16/14
 Supercedes Date:
 10/27/08

## **SECTION 1: Identification**

#### 1.1. Product identifier

3MTM ESPETM IMPREGUMTM SOFT QUICK STEP LIGHT BODY CATALYST

#### **Product Identification Numbers**

LE-FSFD-7383-5

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression

#### Restrictions on use

For use only by dental professionals

## 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

# **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

#### 2.2. Label elements

# Signal word

Warning

#### **Symbols**

Not applicable

Page 1 of 9

#### **Pictograms**

Not applicable

#### **Hazard Statements**

Causes eye irritation.

## **Precautionary Statements**

#### **Prevention:**

Wash thoroughly after handling.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

#### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYMERIC ACETATE	91825-26-2	25 - 35 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	20 - 30 Trade Secret *
SULFONIUM SALT	72140-65-9	10 - 20 Trade Secret *
CITRIC ESTER	77-90-7	10 - 20 Trade Secret *
DIBENZYL TOLUENE	26898-17-9	1 - 10 Trade Secret *
SILANE TREATEAD SILICA	68909-20-6	1 - 10 Trade Secret *
FATTY ACIDS TRIGLYCERIDES	87701-27-3	1 - 5 Trade Secret *
POLYETHYLENE-POLYPROPYLENE GLYCOL	9003-11-6	1 - 5 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

# **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

## 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

Page 2 of 9

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

## 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

#### **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

# Condition

During Combustion During Combustion During Combustion

## 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

# **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

## 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

#### Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

#### 8.2. Exposure controls

Page 3 of 9

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

#### **8.2.2.** Personal protective equipment (PPE)

#### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

**General Physical Form:** Solid **Specific Physical Form:** Paste

Odor, Color, Grade: slightly acrid odor, dark red paste

Odor thresholdNo Data AvailablepHNot ApplicableMelting pointNo Data AvailableBoiling PointNot Applicable

Flash Point Flash point > 93 °C (200 °F)

**Evaporation rate** Not Applicable Not Classified Flammability (solid, gas) Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Not Applicable Not Applicable **Vapor Pressure** Not Applicable **Vapor Density Density** No Data Available **Specific Gravity** > 1 [*Ref Std:* WATER=1]

Solubility in Water Negligible

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** No Data Available No Data Available Viscosity **Volatile Organic Compounds** Not Applicable Percent volatile Not Applicable **VOC Less H2O & Exempt Solvents** Not Applicable

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

#### 10.2. Chemical stability

Stable.

Page 4 of 9

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

## 10.5. Incompatible materials

Strong acids Strong bases Strong oxidizing agents

#### 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure. The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

## 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

#### **Eve Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestions

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Page 5 of 9

## **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
POLYMERIC ACETATE	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
POLYMERIC ACETATE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIATOMACEOUS EARTH	Dermal	Rabbit	LD50 > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 5,110 mg/kg
CITRIC ESTER	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SULFONIUM SALT	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
		nal	
		judgeme	
		nt	
SULFONIUM SALT	Ingestion	Rat	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Dermal	Rabbit	LD50 > 2,000 mg/kg
DIBENZYL TOLUENE	Ingestion	Rat	LD50 > 10,360 mg/kg
SILANE TREATEAD SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATEAD SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATEAD SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYETHYLENE-POLYPROPYLENE GLYCOL	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
POLYETHYLENE-POLYPROPYLENE GLYCOL	Ingestion	Rat	LD50 5,700 mg/kg
FATTY ACIDS TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg
FATTY ACIDS TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg

ATE = acute toxicity estimate

## **Skin Corrosion/Irritation**

Name	Species	Value
DIATOMACEOUS EARTH	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
SILANE TREATEAD SILICA	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Serious Lye Daniage III tation						
Name	Species	Value				
DIATOMACEOUS EARTH	Rabbit	No significant irritation				
SULFONIUM SALT	similar	Moderate irritant				
	health					
	hazards					
SILANE TREATEAD SILICA	Rabbit	No significant irritation				

# **Skin Sensitization**

Name	Species	Value
DIATOMACEOUS EARTH	Human	Not sensitizing
	and	
	animal	
SILANE TREATEAD SILICA	Human	Not sensitizing
	and	
	animal	

#### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
POLYMERIC ACETATE	In Vitro	Not mutagenic
DIATOMACEOUS EARTH	In Vitro	Not mutagenic
SULFONIUM SALT	In Vitro	Not mutagenic
SILANE TREATEAD SILICA	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
DIATOMACEOUS EARTH	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
SILANE TREATEAD SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
DIATOMACEOUS EARTH	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
DIATOMACEOUS EARTH	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
DIATOMACEOUS EARTH	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
SILANE TREATEAD SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATEAD SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATEAD SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

# Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SULFONIUM SALT	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 2,000 mg/kg	not applicable

Specific Target Organ Toxicity - repeated exposure

Specific Turget Organ	1 Omiciej	epeated exposure				
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure
						Duration
DIATOMACEOUS	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
EARTH		silicosis	_		available	exposure
SILANE TREATEAD	Inhalation	respiratory system	All data are negative	Human	NOAEL Not	occupational
SILICA		silicosis	_		available	exposure

## **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

# **SECTION 14: Transport Information**

For Transport Information, please visit <a href="http://3M.com/Transportinfo">http://3M.com/Transportinfo</a> or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

## 15.1. US Federal Regulations

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

#### 15.2. State Regulations

Contact 3M for more information.

#### 15.3. Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

#### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### **NFPA Hazard Classification**

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 18-7383-5
 Version Number:
 5.00

 Issue Date:
 12/16/14
 Supercedes Date:
 10/27/08

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com

Page 9 of 9



# Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-5901-1
 Version Number:
 2.00

 Issue Date:
 04/30/14
 Supercedes Date:
 09/29/08

# **SECTION 1: Identification**

#### 1.1. Product identifier

 $3M^{TM}$  ESPE $^{TM}$  IMPREGUM $^{TM}$  SOFT QUICK STEP BASE

#### 1.2. Recommended use and restrictions on use

## Recommended use

Dental Product, Impression Material

#### Restrictions on use

For use only by dental professionals.

#### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

## 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

## 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

Skin Sensitizer: Category 1A.

#### 2.2. Label elements

#### Signal word

Warning

#### **Symbols**

Exclamation mark |

**Pictograms** 

Page 1 of 10



## **Hazard Statements**

Causes eye irritation.

May cause an allergic skin reaction.

#### **Precautionary Statements**

#### **Prevention:**

Wear protective gloves.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

#### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

#### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

## 2.3. Hazards not otherwise classified

None.

3% of the mixture consists of ingredients of unknown acute oral toxicity. 68% of the mixture consists of ingredients of unknown acute dermal toxicity.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
POLYETHER	110531-92-5	60 - 70 Trade Secret *
CRISTOBALITE	14464-46-1	5 - 15 Trade Secret *
POLYGLYCOLS, MONOBUTYL ETHER	9038-95-3	5 - 10 Trade Secret *
FLUX CALCINED DIATOMACEOUS EARTH	68855-54-9	< 10 Trade Secret *
TRIGLYCERIDES	67701-27-3	5 - 10 Trade Secret *
MAGNESIUM OXIDE	1309-48-4	1 - 5 Trade Secret *
ETHYL-TOLUENESULFONAMIDE	80-39-7	1 - 5 Trade Secret *
1-DODECYLIMIDAZOLE	4303-67-7	< 1.0 Trade Secret *
Mentha arvensis, ext.	90063-97-1	<= 0.5

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

## 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

## 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

## **Hazardous Decomposition or By-Products**

Substance
Carbon monoxide
Carbon dioxide
Irritant Vapors or Gases

#### **Condition**

During Combustion
During Combustion
During Combustion

## 5.3. Special protective actions for fire-fighters

No unusual fire or explosion hazards are anticipated.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

# 7.1. Precautions for safe handling

Page 3 of 10

Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

#### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
MAGNESIUM OXIDE	1309-48-4	Amer Conf of	TWA(inhalable fraction):10	
		Gov. Indust.	mg/m3	
		Hyg.		
MAGNESIUM OXIDE	1309-48-4	US Dept of	TWA(as total particulates):15	
		Labor - OSHA	mg/m3	
CRISTOBALITE	14464-46-1	Amer Conf of	TWA(respirable	
		Gov. Indust.	fraction):0.025 mg/m3	
		Hyg.		
CRISTOBALITE	14464-46-1	US Dept of	TWA concentration(as total	
		Labor - OSHA	dust):0.15 mg/m3;TWA	
			concentration(respirable):0.05	
			mg/m3(1.2 millions of	
			particles/cu. ft.)	

Amer Conf of Gov. Indust. Hyg. : American Conference of Governmental Industrial Hygienists

American Indust. Hygiene Assoc : American Industrial Hygiene Association

Chemical Manufacturer Rec Guid: Chemical Manufacturer's Recommended Guidelines

US Dept of Labor - OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

#### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

# 8.2.2. Personal protective equipment (PPE)

# Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

## Skin/hand protection

See Section 7.1 for additional information on skin protection.

## **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

Page 4 of 10

## 9.1. Information on basic physical and chemical properties

General Physical Form: Solid Specific Physical Form: Paste

Odor, Color, Grade: characteristic odor, lilac colored paste

**Odor threshold** No Data Available pН Not Applicable **Melting point** Not Applicable **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** No Data Available Not Classified Flammability (solid, gas) Not Applicable Flammable Limits(LEL) Not Applicable Flammable Limits(UEL) Vapor Pressure No Data Available

Vapor Density Not Applicable

**Density** 1 - 1.2 g/cm<sup>3</sup>

Specific Gravity 1 - 1.2 [Ref Std: WATER=1]

Solubility in Water Negligible

**Solubility- non-water** No Data Available

Partition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosityNo Data Available

# **SECTION 10: Stability and reactivity**

## 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

## 10.2. Chemical stability

Stable.

## 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

#### 10.5. Incompatible materials

Strong acids Strong bases

Strong oxidizing agents

## 10.6. Hazardous decomposition products

<u>Substance</u> <u>Condition</u>

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with individual components of the uncured

# 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

This product may have a characteristic odor; however, no adverse health effects are anticipated.

product. Once properly mixed and cured, the product is safe for its intended use.

#### **Skin Contact:**

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

## **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

#### Ingestions

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use:

Contains a chemical or chemicals which can cause cancer.

<u>Ingredient</u>	C.A.S. No.	Class Description	<b>Regulation</b>
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer
SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

# **Acute Toxicity**

1100100 10111010			
Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000
			mg/kg
POLYETHER	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
TRIGLYCERIDES	Dermal	Rabbit	LD50 > 2,000 mg/kg

TRIGLYCERIDES	Ingestion	Rat	LD50 > 2,000 mg/kg
FLUX CALCINED DIATOMACEOUS EARTH	Dermal	Rabbit	LD50 > 5,000 mg/kg
FLUX CALCINED DIATOMACEOUS EARTH	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 5,110 mg/kg
POLYGLYCOLS, MONOBUTYL ETHER	Dermal	Rabbit	LD50 > 16,960 mg/kg
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation-	Rat	LC50 > 5 mg/l
	Dust/Mist		
	(4 hours)		
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	Rat	LD50 4,240 mg/kg
MAGNESIUM OXIDE	Ingestion	Rat	LD50 3,870 mg/kg
1-DODECYLIMIDAZOLE	Ingestion	Rat	LD50 641 mg/kg
Mentha arvensis, ext.	Dermal	Rabbit	LD50 > 5,000 mg/kg
Mentha arvensis, ext.	Ingestion	Rat	LD50 1,240 mg/kg

ATE = acute toxicity estimate

# **Skin Corrosion/Irritation**

Name	Species	Value
POLYETHER	Rabbit	No significant irritation
FLUX CALCINED DIATOMACEOUS EARTH	Rabbit	No significant irritation
POLYGLYCOLS, MONOBUTYL ETHER	Rabbit	Minimal irritation
MAGNESIUM OXIDE		No significant irritation
1-DODECYLIMIDAZOLE	Rabbit	Mild irritant
Mentha arvensis, ext.	Rabbit	Mild irritant

**Serious Eye Damage/Irritation** 

Name	Species	Value
POLYETHER	Rabbit	Moderate irritant
FLUX CALCINED DIATOMACEOUS EARTH	Rabbit	No significant irritation
POLYGLYCOLS, MONOBUTYL ETHER	Rabbit	No significant irritation
1-DODECYLIMIDAZOLE	similar	Moderate irritant
	health	
	hazards	
Mentha arvensis, ext.	In vitro	Severe irritant
	data	

# **Skin Sensitization**

Name	Species	Value
POLYETHER	Guinea	Not sensitizing
	pig	
FLUX CALCINED DIATOMACEOUS EARTH	Human	Not sensitizing
	and	
	animal	
1-DODECYLIMIDAZOLE	Mouse	Sensitizing
Mentha arvensis, ext.	Guinea	Sensitizing
	pig	

**Respiratory Sensitization** 

Name	Species	Value

**Germ Cell Mutagenicity** 

our viatagement				
Name	Route	Value		
POLYETHER	In Vitro	Not mutagenic		
FLUX CALCINED DIATOMACEOUS EARTH	In Vitro	Not mutagenic		
MAGNESIUM OXIDE	In Vitro	Not mutagenic		
1-DODECYLIMIDAZOLE	In Vitro	Not mutagenic		

Carcinogenicity

Name	Route	Species	Value
FLUX CALCINED DIATOMACEOUS EARTH	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	Rat	Not carcinogenic

## 3M<sup>TM</sup> ESPE<sup>TM</sup> IMPREGUM<sup>TM</sup> SOFT QUICK STEP BASE 04/30/14

MAGNESIUM OXIDE	Not Specified	Human and	Some positive data exist, but the data are not sufficient for classification
		animal	

# **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
FLUX CALCINED DIATOMACEOUS EARTH	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	Not toxic to female reproduction	Rat	NOAEL 3,770 mg/kg/day	90 days
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	Not toxic to male reproduction	Rat	NOAEL 3,770 mg/kg/day	90 days
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1 mg/l	2 weeks

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL Not available	
MAGNESIUM OXIDE	Inhalation	respiratory system	All data are negative	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
FLUX CALCINED DIATOMACEOUS EARTH	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation	endocrine system   hematopoietic system   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1 mg/l	2 weeks
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL .005 mg/l	2 weeks
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL .001 mg/l	2 weeks
POLYGLYCOLS, MONOBUTYL ETHER	Inhalation	heart	All data are negative	Rat	NOAEL .5 mg/l	2 weeks
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 145 mg/kg/day	90 days
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	hematopoietic system	All data are negative	Rat	NOAEL 500 mg/kg/day	2 years
POLYGLYCOLS, MONOBUTYL ETHER	Ingestion	heart   endocrine system   respiratory system	All data are negative	Rat	NOAEL 3,770 mg/kg/day	90 days

## **Aspiration Hazard**

### 3MTM ESPETM IMPREGUMTM SOFT QUICK STEP BASE 04/30/14

Name	Value

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

## **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate uncured product in a permitted waste incineration facility. Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

## **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

#### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### **15.3.** Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

Page 9 of 10

### 3MTM ESPETM IMPREGUMTM SOFT QUICK STEP BASE 04/30/14

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

**NFPA Hazard Classification** 

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 25-5901-1
 Version Number:
 2.00

 Issue Date:
 04/30/14
 Supercedes Date:
 09/29/08

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



# Safety Data Sheet

Copyright, 2015, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 25-5821-1
 Version Number:
 2.01

 Issue Date:
 01/29/15
 Supercedes Date:
 10/08/14

## **SECTION 1: Identification**

### 1.1. Product identifier

IMPREGUM™ SOFT QUICK STEP CATALYST

### **Product Identification Numbers**

LE-F100-0608-1

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Impression Material

#### Restrictions on use

For use only by dental professionals.

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2B.

### 2.2. Label elements

### Signal word

Warning

### **Symbols**

Not applicable

Page 1 of 9

#### **Pictograms**

Not applicable

#### **Hazard Statements**

Causes eye irritation.

### **Precautionary Statements**

### **Prevention:**

Wash thoroughly after handling.

### **Response:**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

If eye irritation persists: Get medical advice/attention.

#### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
CITRIC ESTER	77-90-7	35 - 45 Trade Secret *
SILANE TREATED SILICA	68909-20-6	20 - 30 Trade Secret *
SULFONIUM SALT	72140-65-9	< 25 Trade Secret *
CRISTOBALITE	14464-46-1	5 - 10 Trade Secret *
DIATOMACEOUS EARTH	68855-54-9	1 - 10 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### **Skin Contact:**

Wash with soap and water. If signs/symptoms develop, get medical attention.

#### Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

Page 2 of 9

# **SECTION 5: Fire-fighting measures**

#### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

### 5.2. Special hazards arising from the substance or mixture

None inherent in this product.

### **Hazardous Decomposition or By-Products**

SubstanceConditionCarbon monoxideDuring CombustionCarbon dioxideDuring CombustionIrritant Vapors or GasesDuring Combustion

### 5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

#### 6.2. Environmental precautions

Avoid release to the environment.

## 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid eye contact. Avoid prolonged or repeated skin contact. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

## 7.2. Conditions for safe storage including any incompatibilities

Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
CRISTOBALITE	14464-46-1	ACGIH	TWA(respirable	A2: Suspected human
			fraction):0.025 mg/m3	carcin.
CRISTOBALITE	14464-46-1	OSHA	TWA concentration(as total	
			dust):0.15 mg/m3;TWA	
			concentration(respirable):0.05	

	mg/m3(1.2 millions of	
	particles/cu. ft.)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

#### Skin/hand protection

See Section 7.1 for additional information on skin protection.

### **Respiratory protection**

Respiratory protection is not required.

# **SECTION 9: Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

General Physical Form: Solid Specific Physical Form: Paste

Odor, Color, Grade: White paste with characteristic odor

Odor threshold No Data Available Not Applicable pH **Melting point** No Data Available **Boiling Point** Not Applicable **Flash Point** No flash point **Evaporation rate** No Data Available Not Classified Flammability (solid, gas) Not Applicable Flammable Limits(LEL) Flammable Limits(UEL) Not Applicable **Vapor Pressure** Not Applicable **Vapor Density** Not Applicable **Density** 1.2 - 1.4 g/cm<sup>3</sup>

**Specific Gravity** 1.2 - 1.4 [*Ref Std:* WATER=1]

Solubility in Water Negligible

Solubility- non-waterNo Data AvailablePartition coefficient: n-octanol/ waterNo Data AvailableAutoignition temperatureNot ApplicableDecomposition temperatureNo Data AvailableViscosityNo Data Available

Page 4 of 9

# **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong acids
Strong bases
Strong oxidizing agents

### 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

### Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

#### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### **Eye Contact:**

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## **Additional Health Effects:**

## Carcinogenicity:

Exposures needed to cause the following health effect(s) are not expected during normal, intended use: Contains a chemical or chemicals which can cause cancer.

Ingredient	CAS No.	Class Description	Regulation
SILICA, CRYS AIRRESP	14464-46-1	Known human carcinogen	National Toxicology Program Carcinogens
CRISTOBALITE	14464-46-1	Grp. 1: Carcinogenic to humans	International Agency for Research on Cancer

### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
CITRIC ESTER	Dermal	Professio	LD50 estimated to be > 5,000 mg/kg
		nal	
		judgeme	
		nt	
CITRIC ESTER	Ingestion	Rat	LD50 > 25,000 mg/kg
SILANE TREATED SILICA	Dermal	Rabbit	LD50 > 5,000 mg/kg
SILANE TREATED SILICA	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
SILANE TREATED SILICA	Ingestion	Rat	LD50 > 5,110 mg/kg
SULFONIUM SALT	Dermal	Professio	LD50 estimated to be 2,000 - 5,000 mg/kg
		nal	
		judgeme	
		nt	
SULFONIUM SALT	Ingestion	Rat	LD50 > 2,000 mg/kg
CRISTOBALITE	Dermal		LD50 estimated to be > 5,000 mg/kg
CRISTOBALITE	Ingestion		LD50 estimated to be > 5,000 mg/kg
DIATOMACEOUS EARTH	Dermal	Rabbit	LD50 > 5,000 mg/kg
DIATOMACEOUS EARTH	Inhalation-	Rat	LC50 > 0.691 mg/l
	Dust/Mist		
	(4 hours)		
DIATOMACEOUS EARTH	Ingestion	Rat	LD50 > 5,110 mg/kg
ATE - coute toxicity estimate	ingestion		2200 7 5,110 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	Rabbit	Mild irritant
CRISTOBALITE		No significant irritation
DIATOMACEOUS EARTH	Rabbit	No significant irritation

**Serious Eye Damage/Irritation** 

Name	Species	Value
SILANE TREATED SILICA	Rabbit	No significant irritation
SULFONIUM SALT	similar	Moderate irritant
	health	
	hazards	

## IMPREGUM<sup>TM</sup> SOFT QUICK STEP CATALYST 01/29/15

DIATOMACEOUS EARTH	Rabbit	No significant irritation

## **Skin Sensitization**

Name	Species	Value
SILANE TREATED SILICA	Human	Not sensitizing
	and	
	animal	
DIATOMACEOUS EARTH	Human	Not sensitizing
	and	
	animal	

## **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Germ Cell Mutagenicity** 

Name	Route	Value
SILANE TREATED SILICA	In Vitro	Not mutagenic
SULFONIUM SALT	In Vitro	Not mutagenic
CRISTOBALITE	In Vitro	Some positive data exist, but the data are not sufficient for classification
CRISTOBALITE	In vivo	Some positive data exist, but the data are not sufficient for classification
DIATOMACEOUS EARTH	In Vitro	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
SILANE TREATED SILICA	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification
CRISTOBALITE	Inhalation	Human	Carcinogenic
		and	
		animal	
DIATOMACEOUS EARTH	Not	Mouse	Some positive data exist, but the data are not
	Specified		sufficient for classification

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
SILANE TREATED SILICA	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s
DIATOMACEOUS EARTH	Ingestion	Not toxic to female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
DIATOMACEOUS EARTH	Ingestion	Not toxic to male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
DIATOMACEOUS EARTH	Ingestion	Not toxic to development	Rat	NOAEL 1,350 mg/kg/day	during organogenesi s

## Target Organ(s)

Specific Target Organ Toxicity - single exposure

Specific Target Organ Toxicity - single exposure						
Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SULFONIUM SALT	Ingestion	central nervous	May cause drowsiness or	Rat	LOAEL 2.000 mg/kg	not applicable
		system depression	dizziness		2,000 IIIg/Kg	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED SILICA	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure
CRISTOBALITE	Inhalation	silicosis	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	occupational exposure
DIATOMACEOUS EARTH	Inhalation	respiratory system   silicosis	All data are negative	Human	NOAEL Not available	occupational exposure

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

#### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

EPA Hazardous Waste Number (RCRA): Not regulated

## **SECTION 14: Transport Information**

For Transport Information, please visit <a href="http://3M.com/Transportinfo">http://3M.com/Transportinfo</a> or call 1-800-364-3577 or 651-737-6501.

## **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

### 311/312 Hazard Categories:

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

Page 8 of 9

#### 15.3. Chemical Inventories

The components of this product are in compliance with the new substance notification requirements of CEPA.

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

## 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

# **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 25-5821-1
 Version Number:
 2.01

 Issue Date:
 01/29/15
 Supercedes Date:
 10/08/14

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com



# Safety Data Sheet

Copyright, 2014, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

 Document Group:
 16-4015-0
 Version Number:
 15.00

 Issue Date:
 10/09/14
 Supercedes Date:
 03/02/11

## **SECTION 1: Identification**

### 1.1. Product identifier

30601 POLYETHER ADHESIVE - 17 ML BOTTLE (NA)

### **Product Identification Numbers**

70-2011-0895-1, 70-2011-0997-5

#### 1.2. Recommended use and restrictions on use

#### Recommended use

Dental Product, Used in impressioning systems.

#### Restrictions on use

For use only by dental professionals.

### 1.3. Supplier's details

MANUFACTURER: 3M

**DIVISION:** 3M ESPE Dental Products

**ADDRESS:** 3M Center, St. Paul, MN 55144-1000, USA **Telephone:** 1-888-3M HELPS (1-888-364-3577)

### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

## **SECTION 2: Hazard identification**

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 2.1. Hazard classification

Flammable Liquid: Category 2.

Serious Eye Damage/Irritation: Category 2A.

Specific Target Organ Toxicity (central nervous system): Category 3.

### 2.2. Label elements

Signal word

Danger

**Symbols** 

Page 1 of 12

Flame | Exclamation mark |

## **Pictograms**



### **Hazard Statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

### **Precautionary Statements**

### **Prevention:**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Avoid breathing dust/fume/gas/mist/vapors/spray.

Use only in a well-ventilated area.

Wear protective gloves and eye/face protection.

Wash thoroughly after handling.

#### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Call a POISON CENTER or doctor/physician if you feel unwell.

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### Storage:

Store in a well-ventilated place. Keep cool.

Keep container tightly closed.

#### Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

### 2.3. Hazards not otherwise classified

None.

# **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
ETHYL ACETATE	141-78-6	25 - 50 Trade Secret *
HEPTANE	142-82-5	25 - 35 Trade Secret *
ACETONE	67-64-1	5 - 15 Trade Secret *
METHYLCYCLOHEXANE	108-87-2	5 - 10 Trade Secret *
FORMALDEHYDE, POLYMER WITH 1,3-	59633-97-5	0 - 5 Trade Secret *
BENZENEDIOL AND 4-(1,1-		
DIMETHYLETHYL)PHENOL		

POLYCHLOROPRENE	9010-98-4	0 - 5 Trade Secret *
CYCLOHEXANE	110-82-7	0 - 0.5 Trade Secret *
ZINC OXIDE	1314-13-2	0 - 0.2 Trade Secret *

<sup>\*</sup>The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

## **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

### **Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

### **Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

### **Eye Contact:**

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

# **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for flammable liquids such as dry chemical or carbon dioxide to extinguish.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### **Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	During Combustion
Carbon dioxide	During Combustion
Irritant Vapors or Gases	During Combustion

## 5.3. Special protective actions for fire-fighters

Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture.

## **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use only non-sparking tools.

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Contain spill. Collect as much of the spilled material as possible using non-sparking tools. Place in a metal container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

# **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store away from heat. Store away from acids. Store away from oxidizing agents.

# **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
METHYLCYCLOHEXANE	108-87-2	ACGIH	TWA:400 ppm	
METHYLCYCLOHEXANE	108-87-2	OSHA	TWA:2000 mg/m3(500 ppm)	
CYCLOHEXANE	110-82-7	ACGIH	TWA:100 ppm	
CYCLOHEXANE	110-82-7	OSHA	TWA:1050 mg/m3(300 ppm)	
ZINC OXIDE	1314-13-2	ACGIH	TWA(respirable fraction):2	
			mg/m3;STEL(respirable	
			fraction):10 mg/m3	
ZINC OXIDE	1314-13-2	OSHA	TWA(as fume):5	
			mg/m3;TWA(as total dust):15	
			mg/m3;TWA(respirable	
			fraction):5 mg/m3	
ETHYL ACETATE	141-78-6	ACGIH	TWA:400 ppm	
ETHYL ACETATE	141-78-6	OSHA	TWA:1400 mg/m3(400 ppm)	
HEPTANE	142-82-5	OSHA	TWA:2000 mg/m3(500 ppm)	
HEPTANE	142-82-5	ACGIH	TWA:400 ppm;STEL:500 ppm	
ACETONE	67-64-1	ACGIH	TWA:500 ppm;STEL:750 ppm	A4: Not class. as human
				carcin
ACETONE	67-64-1	OSHA	TWA:2400 mg/m3(1000 ppm)	

ACGIH: American Conference of Governmental Industrial Hygienists

AIHA: American Industrial Hygiene Association

CMRG: Chemical Manufacturer's Recommended Guidelines

OSHA: United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use in a well-ventilated area.

### 8.2.2. Personal protective equipment (PPE)

### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
Safety Glasses with side shields

### Skin/hand protection

See Section 7.1 for additional information on skin protection.

### **Respiratory protection**

None required.

# **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

General Physical Form:

Specific Physical Form:

Liquid
Liquid

Odor, Color, Grade: Blue in color, characteristic solvent odor.

Odor thresholdNo Data AvailablepHNo Data AvailableMelting pointNo Data Available

**Boiling Point** 133 °F

Flash Point 30 °F [Test Method: Closed Cup]
Evaporation rate Approximately 1 [Ref Std: BUOAC=1]

Flammability (solid, gas)

Flammable Limits(LEL)

Flammable Limits(UEL)

Vapor Pressure

No Data Available
No Data Available
180 mmHg

**Vapor Density** 2 - 4 [Ref Std: AIR=1] **Density** No Data Available

Specific Gravity 0.8 - 0.9 [Ref Std: WATER=1]

Solubility in Water Moderate

Solubility- non-water No Data Available Partition coefficient: n-octanol/ water No Data Available No Data Available **Autoignition temperature** No Data Available **Decomposition temperature** 40,000 centipoise Viscosity **Volatile Organic Compounds** No Data Available Percent volatile No Data Available **VOC Less H2O & Exempt Solvents** No Data Available

# **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Page 5 of 12

Stable.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

#### 10.4. Conditions to avoid

Heat

Sparks and/or flames

### 10.5. Incompatible materials

Strong acids

Strong oxidizing agents

### 10.6. Hazardous decomposition products

**Substance** 

**Condition** 

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

# **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### **Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause target organ effects after inhalation.

### **Skin Contact:**

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

### **Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause target organ effects after ingestion.

## **Target Organ Effects:**

## Single exposure may cause:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity** 

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE > 5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE > 5,000 mg/kg
HEPTANE	Dermal	Rabbit	LD50 3,000 mg/kg
HEPTANE	Inhalation-	Rat	LC50 103 mg/l
	Vapor (4		
	hours)		
HEPTANE	Ingestion	Rat	LD50 > 15,000 mg/kg
ETHYL ACETATE	Dermal	Rabbit	LD50 > 18,000 mg/kg
ETHYL ACETATE	Inhalation-	Rat	LC50 70.5 mg/l
	Vapor (4		
	hours)		
ETHYL ACETATE	Ingestion	Rat	LD50 5,620 mg/kg
ACETONE	Dermal	Rabbit	LD50 > 15,688 mg/kg
ACETONE	Inhalation-	Rat	LC50 76 mg/l
	Vapor (4		
	hours)		
ACETONE	Ingestion	Rat	LD50 5,800 mg/kg
METHYLCYCLOHEXANE	Inhalation-	Mouse	LC50 26 mg/l
	Vapor (4		
	hours)		
METHYLCYCLOHEXANE	Dermal	Rabbit	LD50 > 86,700 mg/kg
METHYLCYCLOHEXANE	Ingestion	Rat	LD50 > 3,200 mg/kg
POLYCHLOROPRENE	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYCHLOROPRENE	Ingestion	Rat	LD50 > 20,000 mg/kg
CYCLOHEXANE	Dermal	Rat	LD50 > 2,000 mg/kg
CYCLOHEXANE	Inhalation-	Rat	LC50 > 32.9 mg/l
	Vapor (4		
	hours)		
CYCLOHEXANE	Ingestion	Rat	LD50 6,200 mg/kg
ZINC OXIDE	Dermal		LD50 estimated to be > 5,000 mg/kg
ZINC OXIDE	Inhalation-	Rat	LC50 > 5.7 mg/l
	Dust/Mist		
	(4 hours)		
ZINC OXIDE	Ingestion	Rat	LD50 > 5,000 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
HEPTANE	Human	Mild irritant
ETHYL ACETATE	Rabbit	Minimal irritation
ACETONE	Mouse	Minimal irritation
METHYLCYCLOHEXANE	Rabbit	Minimal irritation
POLYCHLOROPRENE	Human	No significant irritation
CYCLOHEXANE	Rabbit	Mild irritant
ZINC OXIDE	Human	No significant irritation
	and	
	animal	

## **Serious Eye Damage/Irritation**

Name	Species	Value
HEPTANE		Moderate irritant
ETHYL ACETATE	Rabbit	Mild irritant
ACETONE	Rabbit	Severe irritant
METHYLCYCLOHEXANE	Rabbit	Mild irritant
POLYCHLOROPRENE		No significant irritation
CYCLOHEXANE	Rabbit	Mild irritant
ZINC OXIDE	Rabbit	Mild irritant

## **Skin Sensitization**

Name	Species	Value
ETHYL ACETATE	Guinea	Not sensitizing
	pig	
ZINC OXIDE	Guinea	Some positive data exist, but the data are not
	pig	sufficient for classification

**Respiratory Sensitization** 

Name Species Value	/alue
--------------------	-------

**Germ Cell Mutagenicity** 

Name	Route	Value
HEPTANE	In Vitro	Not mutagenic
ETHYL ACETATE	In Vitro	Not mutagenic
ETHYL ACETATE	In vivo	Not mutagenic
ACETONE	In vivo	Not mutagenic
ACETONE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
CYCLOHEXANE	In Vitro	Not mutagenic
CYCLOHEXANE	In vivo	Some positive data exist, but the data are not
		sufficient for classification
ZINC OXIDE	In Vitro	Some positive data exist, but the data are not
		sufficient for classification
ZINC OXIDE	In vivo	Some positive data exist, but the data are not
		sufficient for classification

Carcinogenicity

Name	Route	Species	Value
ACETONE	Not	Multiple	Not carcinogenic
	Specified	animal	
	1	species	
METHYLCYCLOHEXANE	Inhalation	Multiple	Not carcinogenic
		animal	
		species	

## **Reproductive Toxicity**

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
ACETONE	Ingestion	Not toxic to female reproduction	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
ACETONE	Ingestion	Some positive male reproductive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,700 mg/kg/day	13 weeks
ACETONE	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 5.2 mg/l	during organogenesi s
CYCLOHEXANE	Inhalation	Not toxic to female reproduction	Rat	NOAEL 24 mg/l	2 generation
CYCLOHEXANE	Inhalation	Not toxic to male reproduction	Rat	NOAEL 24 mg/l	2 generation
CYCLOHEXANE	Inhalation	Some positive developmental data exist, but the data are not sufficient for classification	Rat	NOAEL 6.9 mg/l	2 generation

ZINC OXIDE	Ingestion	Some positive	Multiple	NOAEL 125	premating &
		reproductive/developmental data exist,	animal	mg/kg/day	during
		but the data are not sufficient for	species		gestation
		classification			

# Target Organ(s)

**Specific Target Organ Toxicity - single exposure** 

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HEPTANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
HEPTANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
HEPTANE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ETHYL ACETATE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ETHYL ACETATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ETHYL ACETATE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ACETONE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
ACETONE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
ACETONE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 hours
ACETONE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	
ACETONE	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse
METHYLCYCLOHEXAN E	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Multiple animal species	NOAEL Not available	
METHYLCYCLOHEXAN E	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
CYCLOHEXANE	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
CYCLOHEXANE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human and animal	NOAEL Not available	

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
HEPTANE	Inhalation	liver   nervous system   kidney and/or bladder	All data are negative	Rat	NOAEL 12 mg/l	26 weeks
ETHYL ACETATE	Inhalation	endocrine system   liver   nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.043 mg/l	90 days
ETHYL ACETATE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rabbit	LOAEL 16 mg/l	40 days
ETHYL ACETATE	Ingestion	hematopoietic system   liver   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3,600 mg/kg/day	90 days

ACETONE	Dermal	eyes	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL Not available	3 weeks
ACETONE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 3 mg/l	6 weeks
ACETONE	Inhalation	immune system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL 1.19 mg/l	6 days
ACETONE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Guinea pig	NOAEL 119 mg/l	not available
ACETONE	Inhalation	heart   liver	All data are negative	Rat	NOAEL 45 mg/l	8 weeks
ACETONE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 900 mg/kg/day	13 weeks
ACETONE	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 200 mg/kg/day	13 weeks
ACETONE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 3,896 mg/kg/day	14 days
ACETONE	Ingestion	eyes	All data are negative	Rat	NOAEL 3,400 mg/kg/day	13 weeks
ACETONE	Ingestion	respiratory system	All data are negative	Rat	NOAEL 2,500 mg/kg/day	13 weeks
ACETONE	Ingestion	muscles	All data are negative	Rat	NOAEL 2,500 mg/kg	13 weeks
ACETONE	Ingestion	skin   bone, teeth, nails, and/or hair	All data are negative	Mouse	NOAEL 11,298 mg/kg/day	13 weeks
METHYLCYCLOHEXA NE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.6 mg/l	12 months
METHYLCYCLOHEXA NE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 12 mg/l	10 weeks
CYCLOHEXANE	Inhalation	liver	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 24 mg/l	90 days
CYCLOHEXANE	Inhalation	auditory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.7 mg/l	90 days
CYCLOHEXANE	Inhalation	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rabbit	NOAEL 2.7 mg/l	10 weeks
CYCLOHEXANE	Inhalation	hematopoietic system	Some positive data exist, but the data are not sufficient for classification	Mouse	NOAEL 24 mg/l	14 weeks
CYCLOHEXANE	Inhalation	peripheral nervous system	All data are negative	Rat	NOAEL 8.6 mg/l	30 weeks
ZINC OXIDE	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 600 mg/kg/day	10 days
ZINC OXIDE	Ingestion	endocrine system   hematopoietic system   kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Other	NOAEL 500 mg/kg/day	6 months

# **Aspiration Hazard**

Name	Value
------	-------

HEPTANE	Aspiration hazard
METHYLCYCLOHEXANE	Aspiration hazard
CYCLOHEXANE	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

# **SECTION 12: Ecological information**

### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### **Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

# **SECTION 13: Disposal considerations**

#### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Incinerate in a permitted waste incineration facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D001 (Ignitable)

# **SECTION 14: Transport Information**

For Transport Information, please visit <a href="http://3M.com/Transportinfo">http://3M.com/Transportinfo</a> or call 1-800-364-3577 or 651-737-6501.

# **SECTION 15: Regulatory information**

### 15.1. US Federal Regulations

Contact 3M for more information.

## 311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### 15.2. State Regulations

Contact 3M for more information.

### **15.3.** Chemical Inventories

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

### 15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## **SECTION 16: Other information**

#### NFPA Hazard Classification

Health: 2 Flammability: 3 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

 Document Group:
 16-4015-0
 Version Number:
 15.00

 Issue Date:
 10/09/14
 Supercedes Date:
 03/02/11

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M

3M USA SDSs are available at www.3M.com