

## SAFETY DATA SHEETS

**This SDS packet was issued with item:**

076208300

N/A



### 1. Substance / Preparation and Company name

Product Name: riva luting capsules

Recommended use: For cementing dental restoratives.

#### **Manufacturer / Supplier**

SDI Limited  
3-13 Brunsdon Street, Bayswater  
Victoria, 3153, Australia

SDI Inc.  
729 N.Route 83, Suite 315  
Bensenville 60106 IL, USA

#### **Telephone:**

+61 3 8727 7111 (Business hours)

#### **Telephone:**

630 238 8300 (Business hours)

Southern Dental Industries Ltd  
Block 8, St Johns Court  
Swords Road  
Santry, Dublin 9, Ireland

SDI Brasil Indústria e Comércio Ltda  
Rua Dr. Virgílio de Carvalho Pinto, 612  
Pinheiros, São Paulo, 05415-020  
Brasil

#### **Telephone:**

+353 1 886 9577 (Business Hours)

#### **Telephone:**

(55 11 3092 7100 (Business Hours)

**Emergency contact number:** +61 3 8727 7111

### 2. Composition / Information on ingredients

| <u>Composition:</u>                 | <u>CAS No.</u> | <u>Wt. %</u> |
|-------------------------------------|----------------|--------------|
| <b>Compartment 1 (powder)</b>       |                |              |
| Fluoro Aluminosilicate Glass        | -              | 80.0         |
| Polyacrylic Acid                    | 9003-01-4      | 20.0         |
| <b>Compartment 2 (liquid)</b>       |                |              |
| Polyacrylic acid                    | 9003-01-4      | 15.0         |
| Tartaric Acid                       | 87-69-4        | 10.0         |
| Balanced ingredient (non-hazardous) | -              | 75.0         |

### 3. Hazard Identification

Under normal conditions of use, product does not pose any danger to the user. However, the liquid and powder are irritating to skin, eyes and respiratory system.

Risk phrases: **36/37/38** Irritating to eyes, respiratory system and skin.

Safety phrases: **2** Keep out of reach of children  
**24/25** Avoid contact with skin and eyes.



---

#### 4. First Aid Measures

Eye (contact): Flush opened eye with running water for at least 5 minutes. Seek medical attention.

Skin (contact): Remove contaminated clothing. Wash skin with plenty of water. If irritation occurs seek medical attention.

Ingestion: Drink plenty of water. Seek medical attention if discomfort continues.

---

#### 5. Fire Fighting Measures

Suitable extinguishing media: None required.

Unusual Fire and Explosion Hazards: None.

Special protective equipment: No special protective equipment required.

---

#### 6. Accidental Release Measures

Personal precautions: Do not get into eyes, on skin or clothing.

Environmental precautions: Clear up spillages. Transfer to a container for disposal.

Methods for cleaning up: Wash the spillage area clean with water.

---

#### 7. Handling and storage

##### Handling

Store sealed containers away from heat and light.

##### Storage

Storage by the end user (Dental Clinic) is recommended to be at temperatures between 4° - 20°C (39° - 68°F) and should be kept away from direct sunlight.

##### Distribution

During distribution, to our customers, this product can be transported in non-refrigerated conditions between 15° to 25° C. This product can also withstand temperatures up to 40° C for short periods (2 to 3 days) and intermittent peaks up to 50° C.

---

#### 8. Exposure controls and personal protection

Respiratory protection: None required.

Hand protection: Rubber gloves.

Eye protection: Safety glasses, goggles or face shield.

General safety and hygiene measures: None.

---



---

## 9. Physical and chemical properties

|                           |                                      |
|---------------------------|--------------------------------------|
| Appearance:               | Smooth, pale-coloured paste          |
| Odour:                    | Slightly characteristic odour        |
| Boiling point:            | Approx. 100°C (212°F)                |
| Melting point:            | Not applicable                       |
| Specific gravity:         | 2.0 g/cm <sup>3</sup>                |
| Flash point:              | Not applicable                       |
| Flammable:                | Not flammable                        |
| Autoflammability:         | Not applicable                       |
| Explosive properties:     | Does not present an explosion hazard |
| Oxidizing properties:     | Not applicable                       |
| Vapour pressure (@ 20°C): | Approx. 23 kPa                       |
| Relative density:         | <1.0                                 |
| Solubility:               | Miscible                             |

---

## 10. Stability and Reactivity

|  |                                 |
|--|---------------------------------|
| Stability:                             | Stable under normal conditions. |
| Conditions to avoid:                   | Avoid excessive heat            |
| Materials to avoid:                    | None.                           |
| Hazardous decomposition products:      | None when used as directed.     |
| Hazardous reactivity (polymerization): | No hazardous reactions known.   |

---

## 11. Toxicological information

|                      |  |
|----------------------|--|
| Acute toxicity:      | Contact with skin and eyes may cause irritation. |
| Eye (contact):       | Irritating to eyes                               |
| Skin (contact):      | Possible skin irritant                           |
| Inhalation (powder): | Irritating to respiratory system.                |
| Ingestion:           | Irritant not likely in small amounts             |

---

## 12. Ecological information

|                  |   |
|------------------|---|
| Self assessment: | Not readily biodegradable. Avoid large quantities entering drains, surface water or ground water. |
|------------------|---|

---



---

**13. Disposal considerations**

Dispose of in accordance with local official regulations.

---

**14. Transport information**

This product is not considered to be a dangerous good within the meaning of transportation regulations.

---

**15. Regulatory information**

This product is regulated by

TGA  
Medical Devices Directive 93/42/EEC  
FDA  
National regulations

---

**16. Other information**

The information contained in the Material Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

**Prepared by:** SDI Limited  
3-13 Brunsdon Street, Bayswater  
Victoria, 3153, Australia

**Phone Number:**  
+61 3 8727 7111

**Department issuing MSDS:** Research and Development  
**Contact:** Operations Director

---



## Riva Luting Capsules

### SDI Limited

Version No: 4.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: **18/03/2016**

Print Date: **23/03/2016**

Initial Date: **Not Available**

L.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |                      |
|-------------------------------|----------------------|
| Product name                  | Riva Luting Capsules |
| Synonyms                      | Not Available        |
| Other means of identification | Not Available        |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | Dental professional use: For cementing dental restoratives. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

|                         |   |  |   |
|-------------------------|---|--|---|
| Registered company name | SDI Limited                                       | SDI Brazil Industria E Comercio Ltda                                   | SDI Germany GmbH                        |
| Address                 | 3-15 Brunsdon Street VIC Bayswater 3153 Australia | Rua Dr. Virgilio de Carvalho Pinto, 612 São Paulo CEP 05415-020 Brazil | Hansestrasse 85 Cologne D-51149 Germany |
| Telephone               | +61 3 8727 7111 (Business Hours)                  | +55 11 3092 7100   | +49 0 2203 9255 0                       |
| Fax                     | +61 3 8727 7222                                   | +55 11 3092 7101   | +49 0 2203 9255 200                     |
| Website                 | www.sdi.com.au                                    | www.sdi.com.au   | www.sdi.com.au                          |
| Email                   | info@sdi.com.au                                   | brasil@sdi.com.au  | germany@sdi.com.au                      |

|                         |   |
|-------------------------|---|
| Registered company name | SDI (North America) Inc.                            |
| Address                 | 1279 Hamilton Parkway IL Itasca 60143 United States |
| Telephone               | +1 630 361 9200 (Business hours)                    |
| Fax                     | Not Available                                       |
| Website                 | Not Available                                       |
| Email                   | USA.Canada@sdi.com.au                               |

### Emergency telephone number

|                                   |                       |               |               |
|-----------------------------------|-----------------------|---------------|---------------|
| Association / Organisation        | SDI Limited           | Not Available | Not Available |
| Emergency telephone numbers       | +61 3 8727 7111       | Not Available | Not Available |
| Other emergency telephone numbers | ray.cahill@sdi.com.au | Not Available | Not Available |

|                                   |                 |
|-----------------------------------|-----------------|
| Association / Organisation        | Not Available   |
| Emergency telephone numbers       | +61 3 8727 7111 |
| Other emergency telephone numbers | Not Available   |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture


**HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

|                               |  |
|-------------------------------|--|
| Poisons Schedule              | Not Applicable   |
| Classification <sup>[1]</sup> | Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation) |
| Legend:                       | 1. Classification by vendor; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI   |

### Label elements

Continued...

## Riva Luting Capsules

|                    |   |
|--------------------|---|
| GHS label elements |  |
|--------------------|---|

|             |                |
|-------------|----------------|
| SIGNAL WORD | <b>WARNING</b> |
|-------------|----------------|

## Hazard statement(s)

|      |                                   |
|------|-----------------------------------|
| H302 | Harmful if swallowed.             |
| H315 | Causes skin irritation.           |
| H319 | Causes serious eye irritation.    |
| H335 | May cause respiratory irritation. |

## Precautionary statement(s) Prevention

|      |  |
|------|--|
| P271 | Use only outdoors or in a well-ventilated area.                            |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.                          |
| P270 | Do not eat, drink or smoke when using this product.                        |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |

## Precautionary statement(s) Response

|                |  |
|----------------|--|
| P362           | Take off contaminated clothing and wash before reuse.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P301+P312      | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P304+P340      | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.                                 |
| P330           | Rinse mouth.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |

## Precautionary statement(s) Storage

|           |  |
|-----------|--|
| P405      | Store locked up.   |
| P403+P233 | Store in a well-ventilated place. Keep container tightly closed. |

## Precautionary statement(s) Disposal

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

## SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

## Substances

See section below for composition of Mixtures

## Mixtures

| CAS No        | %[weight] | Name                            |
|---------------|-----------|---------------------------------|
|               |           | compartment 1 (powder) contains |
| Not Available | 80        | <u>glass powder</u>             |
| 9003-01-4     | 20        | <u>acrylic acid homopolymer</u> |
|               |           | compartment 2 (liquid) contains |
| 9003-01-4     | 15        | <u>acrylic acid homopolymer</u> |
| 87-69-4       | 10        | <u>tartaric acid</u>            |

## SECTION 4 FIRST AID MEASURES

## Description of first aid measures

|              |   |
|--------------|---|
| Eye Contact  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| Inhalation   | <ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Seek medical attention.</li> </ul>   |

## Riva Luting Capsules

|                  |   |
|------------------|---|
| <b>Ingestion</b> | <ul style="list-style-type: none"> <li>▶ Immediately give a glass of water.</li> <li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor. Seek medical attention.</li> </ul> |
|------------------|---|

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5 FIREFIGHTING MEASURES

### Extinguishing media

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

### Special hazards arising from the substrate or mixture

|                             |             |
|-----------------------------|-------------|
| <b>Fire Incompatibility</b> | None known. |
|-----------------------------|-------------|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> <li>▶ Mists containing combustible materials may be explosive.</li> </ul> <p>Combustion products include; carbon monoxide (CO) carbon dioxide (CO<sub>2</sub>) other pyrolysis products typical of burning organic material. May emit poisonous fumes. May emit corrosive fumes.</p>  |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Wear impervious gloves and safety goggles.</li> <li>▶ Trowel up/scrape up.</li> <li>▶ Place spilled material in clean, dry, sealed container.</li> <li>▶ Flush spill area with water.</li> </ul>   |
| <b>Major Spills</b> | <ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li> <li>▶ Collect solid residues and seal in labelled drums for disposal.</li> <li>▶ Wash area and prevent runoff into drains.</li> <li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                      |  |
|----------------------|--|
| <b>Safe handling</b> | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT</b> enter confined spaces until atmosphere has been checked.</li> <li>▶ <b>DO NOT</b> allow material to contact humans, exposed food or food utensils.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT</b> eat, drink or smoke.</li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
|----------------------|--|



## Riva Luting Capsules

|                          |   |
|--------------------------|---|
| <b>Other information</b> | Do not store in direct sunlight.<br>Store in a dry and well ventilated-area, away from heat and sunlight.<br>Store between 5 and 25 deg. C. |
|--------------------------|---|

**Conditions for safe storage, including any incompatibilities**

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ <b>DO NOT repack.</b> Use containers supplied by manufacturer only.</li> <li>▶ Check that containers are clearly labelled and free from leaks</li> </ul> |
| <b>Storage incompatibility</b> | None known  |

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Not Available

**EMERGENCY LIMITS**

| Ingredient               | Material name                                     | TEEL-1                | TEEL-2               | TEEL-3                |
|--------------------------|---|-----------------------|----------------------|-----------------------|
| acrylic acid homopolymer | Acrylic acid polymers; (Acrylic polymer or resin) | 7.5 mg/m <sup>3</sup> | 83 mg/m <sup>3</sup> | 500 mg/m <sup>3</sup> |
| acrylic acid homopolymer | Acrylic acid polymers; (Acrylic polymer or resin) | 7.5 mg/m <sup>3</sup> | 83 mg/m <sup>3</sup> | 500 mg/m <sup>3</sup> |
| tartaric acid            | Tartaric acid                                     | 1.6 mg/m <sup>3</sup> | 17 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup> |

| Ingredient               | Original IDLH | Revised IDLH  |
|--------------------------|---------------|---------------|
| glass powder             | Not Available | Not Available |
| acrylic acid homopolymer | Not Available | Not Available |
| acrylic acid homopolymer | Not Available | Not Available |
| tartaric acid            | Not Available | Not Available |

**MATERIAL DATA****Exposure controls**

| <b>Appropriate engineering controls</b>   | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1" style="width: 100%;"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion) | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|---|--|----------------------|------------|--|-----------------------------|---|----------------------------|--|----------------------------|---|------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
| Type of Contaminant:  | Air Speed:   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min)  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)   | 2.5-10 m/s (500-2000 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |

|                            |   |
|----------------------------|---|
| <b>Personal protection</b> |  |
|----------------------------|---|

## Riva Luting Capsules

|                                |   |
|--------------------------------|---|
| <b>Eye and face protection</b> | <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul> |
| <b>Skin protection</b>         | See Hand protection below   |
| <b>Hands/feet protection</b>   | ▶ Rubber Gloves   |
| <b>Body protection</b>         | See Other protection below  |
| <b>Other protection</b>        | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>   |
| <b>Thermal hazards</b>         | Not Available   |

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

## Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | Smooth, pale-coloured paste with slightly characteristic odour, partially mixes with water. |  |                |
| <b>Physical state</b>                               | Non Slump Paste   | <b>Relative density (Water = 1)</b>            | Not Available  |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Available   | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available   | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Not Available   | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Available   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Available   | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available   | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Partly miscible   | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available   | <b>VOC g/L</b>                                 | Not Available  |

## SECTION 10 STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Reactivity</b>                         | See section 7   |
| <b>Chemical stability</b>                 | Product is considered stable and hazardous polymerisation will not occur. |
| <b>Possibility of hazardous reactions</b> | See section 7   |
| <b>Conditions to avoid</b>                | See section 7   |
| <b>Incompatible materials</b>             | See section 7   |
| <b>Hazardous decomposition products</b>   | See section 5   |

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system. |
| <b>Ingestion</b>    | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual.  |
| <b>Skin Contact</b> | Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to  |

## Riva Luting Capsules

|   |   |
|---|---|
|   | blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.<br>The material may accentuate any pre-existing dermatitis condition<br>Open cuts, abraded or irritated skin should not be exposed to this material<br>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. |
| Eye   | Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.<br>Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.   |
| Chronic   | Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.<br>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.  |
| Riva Luting Capsules  | <b>TOXICITY</b>   |
|   | Not Available   |
| glass powder  | <b>IRRITATION</b>   |
|   | Not Available   |
| acrylic acid homopolymer  | <b>TOXICITY</b>   |
|   | Oral (rat) LD50: 2500 mg/kg <sup>[2]</sup>  |
| acrylic acid homopolymer  | <b>IRRITATION</b>   |
|   | Nil reported  |
| tartaric acid   | <b>TOXICITY</b>   |
|   | Oral (rat) LD50: 2500 mg/kg <sup>[2]</sup>  |
| Legend:   | <b>IRRITATION</b>   |
|   | dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>   |
|   | Oral (rat) LD50: ca.920 mg/kg <sup>[1]</sup>  |
| 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances |   |

|                          |   |
|--------------------------|---|
| TARTARIC ACID            | Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. Convulsions, haemorrhage recorded.   |
| ACRYLIC ACID HOMOPOLYMER | Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production. The substance is classified by IARC as Group 3:<br><b>NOT</b> classifiable as to its carcinogenicity to humans.<br>Evidence of carcinogenicity may be inadequate or limited in animal testing. |

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ✓ | Carcinogenicity          | ⊘ |
| Skin Irritation/Corrosion         | ✓ | Reproductivity           | ⊘ |
| Serious Eye Damage/Irritation     | ✓ | STOT - Single Exposure   | ⊘ |
| Respiratory or Skin sensitisation | ⊘ | STOT - Repeated Exposure | ⊘ |
| Mutagenicity                      | ⊘ | Aspiration Hazard        | ⊘ |

Legend: ✗ – Data available but does not fill the criteria for classification  
✓ – Data required to make classification available  
⊘ – Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| Ingredient               | Endpoint | Test Duration (hr) | Species                       | Value        | Source |
|--------------------------|----------|--------------------|-------------------------------|--------------|--------|
| acrylic acid homopolymer | EC50     | 384                | Crustacea                     | 389.869mg/L  | 3      |
| acrylic acid homopolymer | EC50     | 96                 | Algae or other aquatic plants | 8596.446mg/L | 3      |

Continued...

## Riva Luting Capsules

|                          |      |     |                               |               |   |
|--------------------------|------|-----|-------------------------------|---------------|---|
| acrylic acid homopolymer | LC50 | 96  | Fish                          | 1684.686mg/L  | 3 |
| acrylic acid homopolymer | EC50 | 384 | Crustacea                     | 389.869mg/L   | 3 |
| acrylic acid homopolymer | EC50 | 96  | Algae or other aquatic plants | 8596.446mg/L  | 3 |
| acrylic acid homopolymer | LC50 | 96  | Fish                          | 1684.686mg/L  | 3 |
| tartaric acid            | EC50 | 96  | Algae or other aquatic plants | 434.65983mg/L | 3 |
| tartaric acid            | LC50 | 96  | Fish                          | >100mg/L      | 2 |
| tartaric acid            | EC50 | 48  | Crustacea                     | 93.313mg/L    | 2 |
| tartaric acid            | EC50 | 72  | Algae or other aquatic plants | 51.4043mg/L   | 2 |
| tartaric acid            | NOEC | 72  | Algae or other aquatic plants | 3.125mg/L     | 2 |

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

**Persistence and degradability**

| Ingredient               | Persistence: Water/Soil | Persistence: Air |
|--------------------------|-------------------------|------------------|
| acrylic acid homopolymer | LOW                     | LOW              |
| acrylic acid homopolymer | LOW                     | LOW              |
| tartaric acid            | LOW                     | LOW              |

**Bioaccumulative potential**

| Ingredient               | Bioaccumulation        |
|--------------------------|------------------------|
| acrylic acid homopolymer | LOW (LogKOW = 0.4415)  |
| acrylic acid homopolymer | LOW (LogKOW = 0.4415)  |
| tartaric acid            | LOW (LogKOW = -1.0017) |

**Mobility in soil**

| Ingredient               | Mobility           |
|--------------------------|--------------------|
| acrylic acid homopolymer | HIGH (KOC = 1.201) |
| acrylic acid homopolymer | HIGH (KOC = 1.201) |
| tartaric acid            | HIGH (KOC = 1)     |

**SECTION 13 DISPOSAL CONSIDERATIONS****Waste treatment methods**

| Product / Packaging disposal |  |
|------------------------------|--|
|                              | Consult State Land Waste Management Authority for disposal.<br>Bury residue in an authorised landfill. |

**SECTION 14 TRANSPORT INFORMATION****Labels Required**

| Marine Pollutant |                |
|------------------|----------------|
|                  | NO             |
| HAZCHEM          |                |
|                  | Not Applicable |

**Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS**

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**SECTION 15 REGULATORY INFORMATION**

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

**GLASS POWDER(NOT APPLICABLE) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Not Applicable

**ACRYLIC ACID HOMOPOLYMER(9003-01-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**ACRYLIC ACID HOMOPOLYMER(9003-01-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Continued...

## Riva Luting Capsules

Australia Inventory of Chemical Substances (AICS)

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

**TARTARIC ACID(87-69-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS**

Australia Inventory of Chemical Substances (AICS)

| National Inventory            | Status   |
|-------------------------------|--|
| Australia - AICS              | Y  |
| Canada - DSL                  | Y  |
| Canada - NDSL                 | N (acrylic acid homopolymer; tartaric acid)  |
| China - IECSC                 | Y  |
| Europe - EINEC / ELINCS / NLP | N (acrylic acid homopolymer)   |
| Japan - ENCS                  | Y  |
| Korea - KECI                  | Y  |
| New Zealand - NZIoC           | Y  |
| Philippines - PICCS           | Y  |
| USA - TSCA                    | Y  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

**SECTION 16 OTHER INFORMATION****Other information**

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

**Definitions and abbreviations**

PC – TWA: Permissible Concentration-Time Weighted Average  
 PC – STEL: Permissible Concentration-Short Term Exposure Limit  
 IARC: International Agency for Research on Cancer  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 STEL: Short Term Exposure Limit  
 TEEL: Temporary Emergency Exposure Limit,  
 IDLH: Immediately Dangerous to Life or Health Concentrations  
 OSF: Odour Safety Factor  
 NOAEL :No Observed Adverse Effect Level  
 LOAEL: Lowest Observed Adverse Effect Level  
 TLV: Threshold Limit Value  
 LOD: Limit Of Detection  
 OTV: Odour Threshold Value  
 BCF: BioConcentration Factors  
 BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited  
 3-15 Brunson Street, Bayswater Victoria, 3153, Australia

Phone Number: +61 3 8727 7111

Date of preparation/revision: 23rd September 2015

Department issuing SDS: Research and Development

Contact: Technical Director