

SAFETY DATA SHEETS

This SDS packet was issued with item:

077181258

N/A

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Adhesive

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

for dental use only

1.3. Details of the supplier of the safety data sheet

Company name: COLTENE/Whaledent AG
Street: Feldwiesenstrasse 20
Place: CH-9450 Altstätten
Telephone: +41 (71) 75 75 300
Telefax: +41 (71) 75 75 301
e-mail: info.ch@coltene.com
Internet: www.coltene.com
Responsible Department: Regulatory Affairs
msds@coltene.com

1.4. Emergency telephone number: +41 (0) 44 251 51 51 - Tox Info Suisse (24 h)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazardous to the aquatic environment: Aquatic Acute 1

Hazard Statements:

Highly flammable liquid and vapour.

Very toxic to aquatic life.

2.2. Label elements**Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.
H400 Very toxic to aquatic life.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P391 Collect spillage.

SECTION 3: Composition/information on ingredients

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 2 of 6

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
107-46-0	Hexamethyldisiloxane			<80 %
	203-492-7		01-2119496108-31	
	Flam. Liq. 2, Aquatic Acute 1 (M-Factor = 1); H225 H400			
1330-20-7	xylene			< 1 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Seek medical advice.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray. Foam. Extinguishing powder. Carbon dioxide (CO₂). Sand.

Additional information

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

Wipe up with absorbent material (eg. cloth, fleece). Clear contaminated areas thoroughly.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Avoid contact with skin and eyes.

for professional use only Keep out of the reach of children.

Observe instructions for use.

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 3 of 6

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

Further information on handling

After use replace the closing cap immediately.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

Further information on storage conditions

Recommended storage temperature: 15 - 23 °C

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

8.2. Exposure controls

Protective and hygiene measures

When using do not eat, drink or smoke.

Eye/face protection

Framed glasses.

Hand protection

Single-use gloves.

Skin protection

Lab apron.

Respiratory protection

Provide adequate ventilation.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
 Colour: red
 Odour: characteristic

Test method

Changes in the physical state

Flash point: - 6 °C DIN 51755

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 4 of 6

Density: 0.8 g/cm³

Water solubility: insoluble

Solubility in other solvents

Ethanol, ketone.

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat.

10.5. Incompatible materials

Oxidizing agents.

SECTION 11: Toxicological information

11.1. Information on toxicological effects**Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
107-46-0	Hexamethyldisiloxane				
	dermal	LD50 mg/kg	>2000	Rabbit	
	inhalative (4 h) vapour	LC50	106 mg/l	Rat	
1330-20-7	xylene				
	dermal	ATE mg/kg	1100		
	inhalative vapour	ATE	11 mg/l		
	inhalative aerosol	ATE	1,5 mg/l		

Irritation and corrosivity

Hazards identification: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1. Toxicity

Very toxic to aquatic organisms.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
107-46-0	Hexamethyldisiloxane					
	Acute fish toxicity	LC50 mg/l	0.46	96 h Oncorhynchus mykiss	OECD 203	
	Acute crustacea toxicity	EC50 mg/l	>0.37	48 h Daphnia magna	OECD 202	

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 5 of 6

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
107-46-0	Hexamethyldisiloxane	>= 3.0

Further information

Does not enter into waste water by proper application.

Do not allow uncontrolled leakage of product into the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

SECTION 14: Transport information

Land transport (ADR/RID)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	LQ6
Hazard No:	33

Other applicable information (land transport)

Special provisions: 274

E3

: 1

D/E

Special provisions: 274 601 640C

E2

: 2

Special provisions: 640C

Marine transport (IMDG)

<u>14.1. UN number:</u>	UN 1133
<u>14.2. UN proper shipping name:</u>	Adhesives
<u>14.3. Transport hazard class(es):</u>	3
<u>14.4. Packing group:</u>	II
Hazard label:	3
Marine pollutant:	•
Limited quantity:	5 L
EmS:	F-E, S-D

Other applicable information (marine transport)

Special provisions: 274, 330, 944

Special provisions: 944

Air transport (ICAO-TI/IATA-DGR)

<u>14.1. UN number:</u>	UN 1133
--------------------------------	---------

according to Regulation (EC) No 1907/2006

Adhesive

Revision date: 21.04.2015

Print date: 22.02.2018

Page 6 of 6

14.2. UN proper shipping name:	Adhesives
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3
Limited quantity Passenger:	1 L
IATA-packing instructions - Passenger:	305
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	307
IATA-max. quantity - Cargo:	60 L

Other applicable information (air transport)

E2
: Y305
60 L

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

National regulatory information

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)