# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

074752234

N/A



# SAFETY DATA SHEET

### L&R ADVANCED FORMULA TEMPORARY CEMENT REMOVER PCN: 293

Use: Ultrasonic Cleaning Solution, use as is.

Manufacturer: L&R Manufacturing Company, 577 Elm Street, P.O. Box 607 Kearny, NJ 07032-0607 USA. Publication

Date: 05/04/2018 REV: O

Product information call 201-991-5330 www.lrultrasonics.com

For emergencies involving a spill, leak fire or accident contact CHEMTEL 800-255-3924 within the United States. Or

1-813-248-0585 for International calls.

### 1. HAZARDS IDENTIFICATION



# WARNING! CORROSIVES, IRRITANT. HARMFUL IF SWALLOWED.

### A: Warning Statement:

Good industrial hygiene practices should be used when handling this material.

Acute Eyes: Direct contact will cause severe irritation to the eyes.

Acute Skin: Will cause irritation to skin..

Acute Inhalation: May cause irritation to nose, throat, along with possible respiratory irritation.

Acute Ingestion: Can cause severe irritation to the mucous membranes.

**B: POTENTIAL HEALTH EFFECTS:** 

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogens.

Do not use directly in an ultrasonic tank.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Component   | CAS Number | Percentage |
|---|------------|------------|
| WATER   | 7732-18-5  | 60 - 70    |
| 2-Propoxyethanol  | 2807-30-9  | 10-20      |
| Quaternary Ammonium Chloride Surfactant                                     | 68610-19-5 | 1-10       |
| Sodium Dodecylbenzenesulfonate  | 25155-30-0 | 1- 10      |
| Sodium Hydroxide  | 1310-73-2  | 1 - 10     |
| The exact concentration of composition has been withheld as a trade secret. |            |            |

# 4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: Seek immediate medical attention. DO NOT INDUCE VOMITING.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

## 5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Extinguish surrounding area with dry chemical, CO2 or a BC/ABC extinguisher.

Special Fire Fighting Procedures: None known

**Unusual Fire and Explosion Hazards:** Product will burn under fire conditions. Closed containers may explode due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire conditions) Oxides of nitrogen and carbon.

# 6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Sweep up powder, avoid breathing dust. Dispose of by dilution to a sanitary sewer system as permitted by Federal, State and Local regulations. Environmental and Regulatory Reporting: Not required

#### 7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 40 to 100 o F Protect from moisture.

HANDLING: AVOID CONTACT WITH SKIN, EYES OR CLOTHING

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

**General:** These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

INGREDIENTS LIMITS INGREDIENTS LIMITS

Water None established 2 Propoxy Ethanol 2 mg/m3 ACGIH TWA

Quaternary Aammonium Chloride 400 PPM ASHA TWA Sodium Dodecylbenzene Sulfonate None established

Sodium Hydroxide 2 mg/ m<sub>3</sub> OSHA / PEL

Engineering Controls: Normal room ventilation.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

Melting Point Range: Not available

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Clear Liquid

**pH**: 13

Water Solubility: Soluble

Freezing Point Range: Less than 32 oF

Vapor Pressure: Not established Flash Point: 136 ° F (57.8 ° C) Method: Tag Closed Cup

Flammability limits (vol/vol %):

Lower: No Data

Percent volatile by volume: Approx. 85 % by volume as water

Color: Pale Amber

Specific Gravity: 1.05

Boiling Point: 210 -212 °F.

Vapor Density: Not established

Upper: No Data

Auto Ignition Temperature: Not available

Viscosity: Similar to water

**V.O.C.** (calculated): 1.24 lbs./ gal or 148.3 grams / 1.

**Decomposition Temperature:** Not available

Partition Coefficient; n-octanol / water: Not available

Odor: Characteristic Detergent odor.

Odor Threshold: Not available

Evaporation Rate: Not available

## 10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to be avoided: Heat and open flames

Materials/Chemicals to be avoided: Strong acids, strong oxidizing agens, aluminum

**Decomposition Type: Thermal:** Oxides of carbon and nitrogen. Possibility of Hazardous Reactions: WILL NOT OCCUR

# 11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product. Acute Dermal Toxicity: No test data found for product. Acute Respiratory Irritation: No test data found for product. Acute Inhalation Toxicity: No test data found for product.

Acute Oral Toxicity LD50 (rat): 2 Propoxy Ethanol = 3089 mg/kg Sodium Hydroxide = LD 50 (mouse) 40 mg/kg Sodium Dodecylbenzenesulfonate = 438 mg/kg Quaternary Ammonium Chloride Surfactant = Unknown LD 50 Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR ACGIH to be a probable or suspected human carcinogen. No additional test data was found for this product.

### 12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

#### 13. DISPOSAL CONSIDERATIONS

This product can be disposed of with dilution in sanitary sewer system, where permitted by local, federal and state regulations.

## 14. TRANSPORTATION INFORMATION

DOT HAZARD CLASS: Limited Quantities. For containers over 1 gallon or for export: Flammable liquid, corrosive, n.o.s. (Contains 2-propoxyethanol, sodium hydroxide), 3 UN2924, PG III, EmS F-E, S-C Subsidiary Risk 8. Do not stack cartons more than five high.

## 15. REGULATORY INFORMATION

Inventory Issues: All components of this product are listed on the U.S. TSCA, Canadian DSL, European EINECS/ELINS chemical listings.

## 16. OTHER INFORMATION

### **National Fire Protection Association**

Hazard Rating,NFPA

Health

Flammability

Reactivity

Special

DESCRIPTION OF CHANGE

# SDS CHANGES

REV 0

DATE 05/04/2018

**Emergency Contact Change** 

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made. This Advanced Formula Temporary Cement Remover SDS has been prepared by L&R Manufacturing Company.