SAFETY DATA SHEETS

This SDS packet was issued with item:

074582490

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

074582656

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

074582482 074582508 074582516 074586517 074586525 074586541 074586558



SAFETY DATA SHEET

Issue Date 26-Sept-2014 Revision Date 14-July-2015 Version 3

1. IDENTIFICATION

Product Identifier

Product Name PREMIUM LIQUID / HIGH IMPACT-45 LIQUID

Other means of identification

SDS# 034 UN/ID No UN1993

Product Code 0703, 0704, 0706, 0707, 0708, 0709, 0734, 0745, 0756 /0504, 0505, 0506, 0507, 0508, 0534, 0545, 0556

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of dentures

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

Emergency telephone number

Company Phone Number 847-215-6622

Emergency Telephone (INFOTRAC) 352-323-3500 (International)

800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL

11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 2
Skin Corrosion / Irritation	Category 2
Skin Sensitization	Category 1
Specific Target Organ Toxicity - Single Exposure (Respiratory)	Category 3

Signal word Danger

Hazard statements H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.H335 May cause respiratory irritation.

Premium Liquid / High Impact-45 Liquid 034 v.3



Appearance Clear Physical state Liquid Odor Acrid

Precautionary Statements - Prevention

P210 Keep away from heat/sparks/open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before use.

P370+P378 In case of fire: Use CO2, for extinction.

Precautionary Statements - Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

P501 Dispose of contents/container in accordance with local regulation.

Hazardous component(s)

for labeling

Contains methyl methacrylate

Other Information Harmful to aquatic life

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Methyl Methacrylate	80-62-6	<100	*
Trimethylolpropane	3290-92-4	<10	*
Trimethacrylate			

^{*}Specific chemical weight has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Premium Liquid / High Impact-45 Liquid 034 v.3

Page 2 of 9

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing

for at least 15 minutes. Call a physician immediately.

Ingestion Do NOT induce vomiting. Drink plenty of water or milk immediately. Never give anything by mouth to an

unconscious person. Provide an estimate of the time at which the material was ingested and the amount of

the substance that was swallowed. Call a physician or poison control center immediately.

Skin Contact Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated

clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptoms conventionally, after thorough decontamination.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Chemical foam, carbon dioxide (CO₂), dry chemical

Unsuitable: Water spray

Specific hazards arising from the chemical

For bulk size >1L – High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce or direct vapors. Extremely flammable. Vapors are heavier than air and may spread along the floors. Vapors may travel to source of ignition and flash back. Heat/impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk or burns/injuries.

Hazardous Combustion Products: Carbon oxides

Sensitivity to Mechanical Impact: No Sensitivity to Static Discharge: Yes

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Use

personal protective equipment as required. Ensure adequate ventilation. Remove any

Page 3 of 9

contaminated clothing and wash thoroughly before reuse.

Environmental precautions Prevent product from entering drains. Spillages or uncontrolled discharges into watercourses must

be alerted to the appropriate regulatory body.

Methods and material for containment and clean-up

Premium Liquid / High Impact-45 Liquid 034 v.3

Method for containment

Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal. DO NOT use combustible materials such as sawdust.

Method for clean-up Use only non-sparking tools. Wash all affected areas with plenty of warm water and soap.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Observe precautions found on the label. Keep containers closed when not in use. All equipment used when handling the product must be grounded. Use spark-proof tools and explosion-proof equipment. Avoid contact with skin, eyes and clothing. Use only in well-ventilated areas. Vapors are heavier than air and may travel along the floor and in the bottom of containers. Take precautionary measures against static discharges. Keep away from heat, sparks, open flames, and hot surfaces. NO SMOKING. Use personal protection recommended in Section 8. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not breathe dust, fume, gas, mist, vapor or spray.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat,

sparks, flame and other sources of ignition (i.e. pilot lights, electric motors and static electricity). Protect from direct sunlight. Keep container closed to prevent water absorption and contamination. Methacrylate stored in bulk must be kept in contact with air (oxygen). Keep at a temperature not

exceeding 25°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen

scavengers

Material has strong solvent properties and can soften paint and rubber.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines Consideration should be given to the work procedures involved and the potential extent of

exposure as they may determine whether a higher level of protection is required. The following

information is given as general guidance.

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl Methacrylate	STEL: 100 ppm	TWA:100 ppm	IDLH: 1000 ppm
80-62-6	TWA: 50 ppm	TWA: 410 mg/m ³	TWA: 100 ppm
		TWA:100 ppm (vacated)	TWA: 410 mg/m ³
		TWA: 410 mg/m ³ (vacated)	

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

Eyewash stations

Individual protection measures, such as personal protective equipment

Eye / face protection Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to

US OSHA 29CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure

that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, wear

gloves for routine industrial use. If necessary, refer to US OSHA 29CFR SS1910.138 or the appropriate standards of Canada or the EC member states. Wear suitable protective clothing.

Respiratory protectionWear suitable respiratory equipment if exposure to levels above the occupational exposure limit is

likely. A suitable mask with filter type A may be appropriate. In the event of formation of particularly

high levels of vapor, a self-contained breathing apparatus may be appropriate.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Odor Acrid

Appearance Liquid Odor threshold Not determined

Color Clear

<u>Property</u> <u>Values</u> <u>Remarks / Method</u>

pH Not determined

Melting point / freezing point

Boiling point / boiling range

101°C / 214° F

Flash point

11.5°C / 52.7°F

Evaporation rate 3.1 Butyl acetate = 1 Flammability (solid, gas) n/a (liquid)

Flammability (solid, gas) Flammability limits in air

Upper flammability limit 12.5% Lower flammability limit 2.12% Vapor pressure 28mm Hg

 Vapor pressure
 28mm Hg
 @ 20°C

 Vapor density
 3.5
 @15.5°C (Air = 1)

 Specific gravity
 0.955
 Water = 1

Water solubility 1.6% Solubility in other solvents Not determined Not determined Partition coefficient **Autoignition temperature** 421°C / 790°F **Decomposition temperature** Not determined Kinematic viscosity Not determined Dynamic viscosity Like water **Explosive properties** Not determined **Oxidizing properties** Not determined

Other information 0.955 g/mL

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

Chemical stability Unstable/reactive upon depletion of inhibitor

<u>Possibility of hazardous reactions</u> None under normal processing

Hazardous polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent or

flame arresters, resulting in blockage of vents.

Conditions to avoid Temperatures above 25°C (77°F), localized heat sources (e.g. drum or band heaters), oxidizing conditions,

freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing

Incompatible materials Strong oxidizing agents, strong reducing agents, free-radical generators, inert gases, oxygen scavengers

Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information

Inhalation Harmful if inhaled.

Eye contactCauses severe eye irritation.Skin contactCauses skin irritation.IngestionDo not taste or swallow.

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
Methyl Methacrylate	7872 mg/kg (rat)	>5 g/kg (rabbit)	400 ppm (rat) 1 h
80-62-6			4632 ppm (rat) 4 h
Trimethylolpropane	14000 mg/kg (rat)	-	>0.29 mg/L (rat) 4 h
Trimethacrylate			
3290-92-4			

Information on physical, chemical and toxicological effects

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract.

Irritating to mouth, throat and stomach if ingested.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause allergic skin reaction.

Carcinogenicity Not classifiable as a human carcinogen

Chemical Name	ACGIH	IARC	NTP	OSHA
Methyl Methacrylate 80-62-6	-	Group 3	-	-

IARC (International Agency for Research on Cancer)

Group 3 IARC components are "not classifiable as human carcinogens"

STOT – single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

Not determined

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	8045	mg/kg
ATEmix (dermal)	5269	mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Methyl Methacrylate 80-62-6	170: 96 h Psuedokirchneriella subcapitata mg/L EC50	125.5-190.7: 96 h Pimephales promelas mg/L LC50 static; 153.9-341.8: 96 h Lepomis macrochirus mg/L LC50 static;	-	69: 48 h Daphnia magna mg/L EC50

		170-206: 96 h Lepomis macrochirus mg/L LC50 flow-through; 243-275: 96 h Pimephales promelas mg/L LC50 flow-through; 326.4-426.9 96 h Poecilia reticulata mg/L LC50 static; >79: 96 h Oncorhynchus mykiss mg/L LC50 flow-through; >79: 96 h Oncorhynchus mykiss mg/L LC50 static		
Trimethylolpropane	_	21700: 48 h Cyprinodon mg/L LC50	_	13000: 48 h Daphnia species
Trimethylolphopane Trimethacrylate 3290-92-4	-	21700. 40 II Oypiilidddi Illig/L LC30	-	mg/L EC50 10330-106360: 48 h Daphnia magna mg/L EC50 Static

Persistence and degradability Not readily biodegradable

Bioaccumulation Not determined

Mobility Potential for mobility in soil is very high

Chemical Name	Partition coefficient
Methyl Methacrylate 80-62-6	0.7
Trimethylolpropane Trimethacrylate 3290-92-4	-2.37

Other adverse effects COD = 88% (28 days), DOC removal > 95% (28 days)

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Follow all local and national government regulations in disposing material or contaminated

packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. When discarded, it is considered a hazardous waste by the EPA under RCRA. The reportable quantity for methyl $\,$

methacrylate is 1000 lb. (40 CFR Part 302). Add excess inhibitor before disposing.

Contaminated Packaging Reuse of empty drums or containers is not recommended. Employees should be advised of the

potential hazards due to residual material associated with empty containers.

Dispose of all empty containers in accordance with local and national government regulations.

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
Methyl Methacrylate	U162	Included in waste stream;	-	U162
80-62-6		F039		
Chemic	al Name	California Hazardous Wa	ste Status	
Methyl Me	ethacrylate	Toxic Ignitable		
80-6	62-6			

14. TRANSPORTATION INFORMATION

DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl methacrylate monomer, stabilized /
	Trimethylolpropane Trimethacrylate solution)
Hazard Class	3
Packing Group	
Reportable Quantity (RQ)	1000 lb.

<u>IATA</u>

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (Methyl methacrylate monomer, stabilized / Trimethylolpropane Trimethacrylate solution)
Hazard Class	3
Packing Group	

<u>IMDG</u>

UN / ID No	UN1993	
Proper shipping name	Flammable liquid, n.o.s. (Methyl methacrylate monomer, stabilized / Trimethylolpropane Trimethacrylate solution)	
Hazard Class	3	
Packing Group		

15. REGULATORY INFORMATION

International Inventories

TSCA Listed United States Toxic Substances Control Act, Section 8(b) Inventory

DSL Listed Canadian Domestic Substances List

EINECS Listed European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

Medical Devices Directive 93/42/EEC - Class I Medical Devices

US Federal Regulations

Chemical Name	CAS	Weight %	SARA 313 Threshold Values %
Methyl Methacrylate	80-62-6	<100	1.0

SARA 311 / 312 Hazard Categories

Chemical Name	CWA – Reportable	CWA – Toxic	CWA – Priority	CWA – Hazardous
	Quantities	Pollutants	Pollutants	Substances
Methyl Methacrylate 80-62-6	1000 lb.	-	-	Х

Chemical Name	Hazardous Substances	CERCLA /	Reportable Quantity (RQ)
	RQs	SARA RQ	Final
Methyl Methacrylate 80-62-6	1000 lb.	-	1000 lb. / 454 kg

US State Regulations

US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl Methacrylate	X	X	Χ
80-62-6			

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	2	3	2
HMIS	Health Hazards	Flammability	Physical Hazards
			•

Issue Date 26-Sept-2014 **Revision Date** 14-July-2015

Revision Note Section 2 – revise classification categories, add hazard codes, revise some Hazard Statements and

Precautionary Statements, add hazardous component for labeling information

Information to be updated in due course Hazard pictograms listed in this SDS to be added to product label

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



Effective Date 13-Apr-2020

1. IDENTIFICATION

SAFETY DATA SHEET

Version 3

Product Identifier

Product Name PREMIUM POWDER

Other means of identification

SDS# 019

Product Code 0730, 0734, 0745, 0750, 0756, 0770, 0780

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of dentures

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.

175 Messner Dr. Wheeling, IL 60090

USA

Emergency telephone number

Company Phone Number +1-847-215-6622

Emergency Telephone (INFOTRAC) +1-352-323-3500 (International)

800-535-5053 (North America)

<u>Authorized European Representative</u> Medimark® Europe Sarl

11 rue Emile Zola. BP 2332 38033 Grenoble Cedex 2

France

Tel: +33 4 76 86 43 22 Fax: +33 4 76 17 19 82

Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification This chemical does not meet the hazardous criteria set forth by the 2012 OSHA Hazard Communication Standard (29

CFR 1910.1200); however, this Safety Data Sheet (SDS) contains valuable information critical to the safe handling and

proper use of this product and should be retained for employees and other users of this product.

Signal word Warning

<u>Hazard statements</u> H320 Causes eye irritation



Precautionary Statements - Prevention

P202 Do not handle until all safety precautions have been read and understood.

P264 Wash thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary Statements - Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs, get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Classification of the substance or mixture

Chemical Name	CAS No	Weight - %	Trade Secret
Polymer	9011-14-7	90 - 100	*

^{*}Specific chemical weight has been withheld as a trade secret.

Premium Powder 019 v.3 Page 1 of 4

4. FIRST AID MEASURES

First aid measures

Inhalation Remove victim to fresh air. Keep at rest in a position comfortable for breathing. Seek immediate medical

attention if needed.

Eye contact Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists,

call a physician immediately.

Ingestion If ingested, do not induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer

water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately and provide an estimate of when and how much material was ingested. Seek immediate

medical attention.

Skin Contact Wash with soap and water. If irritation, redness or swelling persists, call a physician immediately. Take off

contaminated clothing and wash before reuse.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Water spray, chemical foam, carbon dioxide (CO₂), dry chemical

Unsuitable: Water may not be effective in extinguishing this fire.

Specific hazards arising from the chemical

For bulk size: Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

Special Fire Fighting Procedures

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

Protective equipment and precautions for firefighters

Polymer dust is combustible. The explosive limits of the polymer particles suspended in air approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bounding procedures. Polymers are not sensitive to mechanical impacts.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions For bulk size: Use personal protective equipment as required. Keep airborne particulates at a

minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any

contaminated clothing and wash thoroughly before reuse.

Methods and material for containment and clean-up

Method for containment Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g.

sand or earth). May contaminate water supply.

Method for clean-up Sweep up to avoid slipping hazard. Place into appropriate closed container(s) for disposal in

accordance with local, state, and federal regulations. Wash all affected areas with plenty of warm

water and soap. Not a RCRA Hazardous waste.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Use in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust. Use

good personal hygiene and housekeeping. Avoid prolonged contact with the product. Use in well-ventilated location. After use, wash hands and exposed skin with soap and water. Do not eat, drink

or smoke when using this product.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed to prevent water absorption and contamination. Store containers in a

cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of

intense heat. Preferable storage temperature not to exceed 35°C.

Packaging materials Keep in original container.

Incompatible materials Strong oxidizers, strong oxidizing agents.

Premium Powder 019 v.3 Page 2 of 4

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines

Appropriate engineering controls Apply technical measures to comply with the occupational exposure limits. When working with

large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

Individual protection measures, such as personal protective equipment

Eye / face protection Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to

US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure

that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and body protection If anticipated that prolonged and repeated skin contact will occur during use of this product, wear

gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the

appropriate standards of Canada or the EC member states.

Respiratory protection No special respiratory protection is required under typical circumstances of use or handling. If

necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its

provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after

handling. An eyewash station is recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before

eating, drinking, or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical statePowderOdorFaint odor in bulkColorWhite to pinkOdor thresholdNot determinedPropertyValuesRemarks / Method

pH Not determined
Melting point / freezing point Not determined
Boiling point / boiling range Not applicable
Flash point 304°C / 579°F
Evaporation rate Not applicable

Flammability (solid, gas) Flammability limits in air

Upper flammability limit
Lower flammability limit
Not applicable
Vapor pressure
Vapor density
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Not applicable
Insoluble in water

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

<u>Chemical stability</u>
Stable under recommended storage conditions
<u>Possibility of hazardous reactions</u>
Hazardous polymerization will not occur.

Incompatible materials Strong oxidizing agents

Hazardous decomposition products Methacrylate monomer and oxides of carbon when burned

Non-flammable

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information This product has not been tested on animals to obtain toxicology data.

Inhalation Not expected to be an inhalation hazard under normal conditions of intended use

Eye contact Avoid contact with eyes. Skin contact Avoid contact with skin. Ingestion Do not taste or swallow.

Premium Powder 019 v.3 Page 3 of 4

Information on physical, chemical and toxicological effects

Symptoms Skin contact may aggravate an existing dermatitis. Direct contact with eyes may cause temporary irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity No data available.

12. ECOLOGICAL INFORMATION

Ecotoxicity No data available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

For bulk only: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with federal, state, local regulations.

14. TRANSPORTATION INFORMATION

DOT
IATANot regulated
Not regulatedIMDGNot regulated

15. REGULATORY INFORMATION

International Inventories

TSCA For use in FDA regulated products only.

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging

Medical Devices Directive 93/42/EEC - Class I Medical Devices

<u>US State Regulations</u> California Proposition 65 – Warning. This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: None

16. OTHER INFORMATION

HMIS	Health Hazards	Flammability	Physical Hazards
	1	1	0

Effective Date 13-Apr-2020

<u>Disclaimer</u> The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Premium Powder 019 v.3 Page 4 of 4