

SAFETY DATA SHEETS

This SDS packet was issued with item:

073241304

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071691005 072557858 072557890 072557908 072557916 072557924 072557932 072557940 072557965 072557973
072558021 072558039 073239100 073239118 073239126 073239134 073239142 073239159 073239167 073239217
073239225 073239233 073239456 073239464 073239472 073239480 073239498 073239506 073239555 073239563
073239571 073239589 073241338 073241346 073241353 073241361 073241379 073241387 073241411 073241429
073241437 073242443 073242476 073242682 078634810 078634813 078634822 078634955

Safety Data Sheet

according to UK REACH Regulation

Luxatemp Ultra Fluorescence AM-Plus SolarRevision date: 15.04.2021 110368, 110400-110404, 110406, 110585-110589, 110710, 110719, 110722, 110723,
110360, 110906-110911, 110901, 110904, 110905Product code: 1300

Page 1 of 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Luxatemp Ultra Fluorescence AM-Plus Solar

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

for dental use only

Uses advised against

pregnant or breastfeeding people should not work with hazardous substances

1.3. Details of the supplier of the safety data sheet

Company name:	DMG America LLC	
Street:	242 South Dean Street	
Place:	Englewood, NJ 07631	
Telephone:	(800) 662-6383	Telefax: (201) 894-0213
e-mail:	info@dmg-america.com	
Internet:	www.dmg-america.com	

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GB CLP Regulation**

Hazard categories:

Skin corrosion/irritation: Skin Irrit. 2

Serious eye damage/eye irritation: Eye Irrit. 2

Respiratory or skin sensitisation: Skin Sens. 1

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

May cause respiratory irritation.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

2.2. Label elements**GB CLP Regulation****Signal word:** Warning**Pictograms:****Hazard statements**

H335 May cause respiratory irritation.

H319 Causes serious eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352 IF ON SKIN: Wash with plenty of water.

2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

Safety Data Sheet

according to UK REACH Regulation

Luxatemp Ultra Fluorescence AM-Plus SolarRevision date: 15.04.2021 110368, 110400-110404, 110406, 110585-110589, 110710, 110719, 110722, 110723,
110360, 110906-110911, 110901, 110904, 110905 Product code: 1300

Page 2 of 5

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Chemical characterization**

chemical characterization (preparation): Acrylate.-resin.

Hazardous components

CAS No	Chemical name	Quantity
	EC No	
	Index No	
	REACH No	
	Classification (GB CLP Regulation)	
41637-38-1	Dimethacrylate Resin	35-45 %
	Skin Irrit. 2, Eye Irrit. 2, Skin Sens. 1, STOT SE 3, Aquatic Chronic 4; H315 H319 H317 H335 H413	

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures**4.1. Description of first aid measures****After inhalation**

Avoid exposure. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Medical treatment necessary.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).**Unsuitable extinguishing media**

High power water jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Provide adequate ventilation.

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up**Other information**

Take up mechanically. Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Safety Data Sheet

according to UK REACH Regulation

Luxatemp Ultra Fluorescence AM-Plus Solar

Revision date: 15.04.2021 110368, 110400-110404, 110406, 110585-110589, 110710, 110719, 110722, 110723,
110360, 110906-110911, 110901, 110904, 110905 Product code: 1300

Page 3 of 5

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

Advice on general occupational hygiene

When using do not eat or drink.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Additional advice on limit values**

To date, no national critical limit values exist.

8.2. Exposure controls**Individual protection measures, such as personal protective equipment****Eye/face protection**

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Paste
Colour:	characteristic
Odour:	ester

Changes in the physical state

Boiling point or initial boiling point and boiling range:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Auto-ignition temperature:	>380 °C
pH-Value (at 20 °C):	ca. 7
Water solubility:	10 g/L
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm ³
Relative vapour density:	1

SECTION 10: Stability and reactivity

Safety Data Sheet

according to UK REACH Regulation

Luxatemp Ultra Fluorescence AM-Plus Solar

Revision date: 15.04.2021 110368, 110400-110404, 110406, 110585-110589, 110710, 110719, 110722, 110723, 110360, 110906-110911, 110901, 110904, 110905 Product code: 1300

Page 4 of 5

10.4. Conditions to avoid

heat. Light.
Decomposition takes place from temperatures above: 200 °C
Decomposition under formation of: Acrylate.

10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

In case of fire may be liberated: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Acute toxicity

LD50: Rat 5000 mg/kg

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.
Irritant effect on the eye:

Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

12.2. Persistence and degradability

Preparation not tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

List of Wastes Code - residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (EXCEPT KITCHEN AND RESTAURANT WASTES NOT ARISING FROM IMMEDIATE HEALTH CARE); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing hazardous substances; hazardous waste

SECTION 14: Transport information

Other applicable information

No dangerous good in sense of these transport regulations.

Safety Data Sheet

according to UK REACH Regulation

Luxatemp Ultra Fluorescence AM-Plus SolarRevision date: 15.04.2021 110368, 110400-110404, 110406, 110585-110589, 110710, 110719, 110722, 110723,
110360, 110906-110911, 110901, 110904, 110905Product code: 1300

Page 5 of 5

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H413	May cause long lasting harmful effects to aquatic life.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)