

SAFETY DATA SHEETS

This SDS packet was issued with item:

071051937

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071051945 071055482 071055490 071055508

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1


Reviewed on 07/13/2018

1 Identification

- **Product identifier**
- **Trade name:** GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)
- **Relevant identified uses of the substance or mixture and uses advised against**
Dental material
The product is intended for professional use.
To avoid risks for humans and environment obtain instructions.
- **Application of the substance / the mixture** Dental filling material
- **Details of the supplier of the safety data sheet**
- **Information department:** Regulatory Affairs
- **Emergency telephone number:**
During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900
Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**

Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Repr. 2	H361	Suspected of damaging fertility or the unborn child.
Aquatic Acute 3	H402	Harmful to aquatic life.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.
- **Additional information:**
The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.
- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**

GHS08
- **Signal word** Danger
- **Hazard-determining components of labeling:**
2-hydroxyethyl methacrylate (HEMA)
dimethacrylate component**
urethane dimethacrylate (UDMA)
initiator**

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 1)

- **Hazard statements**

Causes skin irritation.
 Causes serious eye irritation.
 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 May cause an allergic skin reaction.
 Suspected of damaging fertility or the unborn child.
 Harmful to aquatic life.
 Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Wear protective gloves/protective clothing/eye protection/face protection.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Specific treatment (see on this label).
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Hazard not otherwise classified (HNOC):** None known.

- **Additional information:**

5.9 % of the mixture consists of component(s) of unknown toxicity.

- **Classification system:**

- **NFPA ratings (scale 0 - 4)**



Health = 2
 Fire = 0
 Reactivity = 0

- **HMIS-ratings (scale 0 - 4)**



HEALTH 2 Health = 2
 FIRE 0 Fire = 0
 REACTIVITY 0 Reactivity = 0

- **Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 868-77-9	2-hydroxyethyl methacrylate (HEMA)	10 - < 25%
	dimethacrylate component**	2.5 - < 5%
CAS: 41637-38-1	ethoxylated bisphenol-A dimethacrylate (Bis-EMA)	2.5 - < 5%
CAS: 72869-86-4	urethane dimethacrylate (UDMA)	2.5 - < 5%
	photoinitiator**	0.2 - < 0.5%
	butylated hydroxytoluene (BHT)	0.2 - < 0.5%
	initiator**	0.2 - < 0.5%

(Contd. on page 3)

-US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 2)

- **Additional information:**

If a substance is marked with **, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.
If symptoms persist consult doctor.

- **After inhalation:**

Supply fresh air; consult doctor in case of complaints.
In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.
Seek medical treatment.

- **After eye contact:**

Protect unharmed eye.
Rinse opened eye for several minutes under running water. Then consult a doctor.

- **After swallowing:**

Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.

- **Information for doctor:**

- **Most important symptoms and effects, both acute and delayed** Allergic reactions

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

· **For safety reasons unsuitable extinguishing agents:** Water

- **Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

- **Advice for firefighters**

· **Protective equipment:** Wear self-contained respiratory protective device.

- **Additional information**

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Remove persons from danger area.
Avoid contact with the eyes and skin.
Wear protective clothing.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.
Do not allow to penetrate the ground/soil.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 3)

- **Methods and material for containment and cleaning up:**

Ensure adequate ventilation.
Absorb liquid components with liquid-binding material.
Dispose of the collected material according to regulations.

- **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

- **Protective Action Criteria for Chemicals**

Protective Action Criterion (PAC); Protective Action Criteria (PACs); Lower Explosive Limit (LEL)
* indicates the PAC value is between 10% and up to 50% of the LEL (10% LEL ≤ PAC < 50% LEL).
** indicates the PAC value is between 50% and up to 100% of the LEL (50% LEL ≤ PAC < 100% LEL).
*** indicates the PAC value is at 100% or more of the LEL (PAC ≥ LEL).
excerpt from Introduction to PAC Table 2 – PAC Rev. 29 – May 2016

- **PAC-1:**

CAS: 65997-17-3	glass, oxide, chemicals	15 mg/m ³
CAS: 868-77-9	2-hydroxyethyl methacrylate (HEMA)	1.9 mg/m ³
	dimethacrylate component**	33 mg/m ³
CAS: 72869-86-4	urethane dimethacrylate (UDMA)	120 mg/m ³
	initiator**	0.3 mg/m ³

- **PAC-2:**

CAS: 65997-17-3	glass, oxide, chemicals	170 mg/m ³
CAS: 868-77-9	2-hydroxyethyl methacrylate (HEMA)	21 mg/m ³
	dimethacrylate component**	360 mg/m ³
CAS: 72869-86-4	urethane dimethacrylate (UDMA)	1,300 mg/m ³
	initiator**	26 mg/m ³

- **PAC-3:**

CAS: 65997-17-3	glass, oxide, chemicals	990 mg/m ³
CAS: 868-77-9	2-hydroxyethyl methacrylate (HEMA)	1,000 mg/m ³
	dimethacrylate component**	2,100 mg/m ³
CAS: 72869-86-4	urethane dimethacrylate (UDMA)	7,900 mg/m ³
	initiator**	160 mg/m ³

7 Handling and storage

- **Handling:**

- **Precautions for safe handling**

Observe instructions for use.
Ensure good ventilation/exhaustion at the workplace.
Do not inhale dust / smoke / mist.
Prevent formation of aerosols.
Avoid contact with the eyes and skin.

- **Information about protection against explosions and fires:** Protect against electrostatic charges.

- **Conditions for safe storage, including any incompatibilities**

- **Storage:**

- **Requirements to be met by storerooms and receptacles:**

Store only in unopened original receptacles.

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 4)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Observe instructions for use / storage.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

initiator**

TLV	Long-term value: 0.1 mg/m ³ as persulfate
-----	---

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures for handling chemicals should be followed.
Avoid contact with the eyes and skin.
Immediately remove all soiled and contaminated clothing.
- **Breathing equipment:**



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Safety glasses

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 5)

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Paste

Color: According to product specification

- **Odor:** Odorless
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:** Undetermined.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure:** Not determined.

- **Density at 20 °C (68 °F):** 2.1 g/cm³ (17.5245 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Insoluble.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

- **Solvent content:**

VOC content: 0.00 %

Solids content: 66.0 %

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.

- **Chemical stability** Stable at ambient temperature.

(Contd. on page 7)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 6)

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

butylated hydroxytoluene (BHT)

Oral	LD50	10,700 mg/kg (guinea pig)
		1,040 mg/kg (mouse)
		2,930 mg/kg (rat (f+m))
Dermal	LD50	890 mg/kg (rat (f+m))

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

glass, oxide, chemicals	65997-17-3
butylated hydroxytoluene (BHT)	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Carcinogenic categories' legend:**

IARC Group 1: The agent is carcinogenic to humans.
 IARC Group 2A: The agent is probably carcinogenic to humans.
 IARC Group 2B: The agent is possibly carcinogenic to humans.
 IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.
 IARC Group 4: The agent is probably not carcinogenic to humans.
 NTP K: Known to be human carcinogen.
 NTP R: Reasonably anticipated to be human carcinogen.

- **Repeated dose toxicity.** No further relevant information available.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
No further relevant information available.

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

Repr. 2

(Contd. of page 7)

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:**

butylated hydroxytoluene (BHT)

NOEC-value Ecol. other effects	0.07 mg/l (daphnia magna) 21 day, reproductive effects
--------------------------------	---

- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:** Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:** Smaller quantities can be disposed of with household waste.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---------------------------------------|-----------------|
| · UN-Number | |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · UN proper shipping name | |
| · DOT, ADR, ADN, IMDG, IATA | Void |
| · Transport hazard class(es) | |
| · DOT, ADR, ADN, IMDG, IATA | |
| · Class | Void |
| · Packing group | |
| · DOT, ADR, IMDG, IATA | Void |
| · Environmental hazards: | Not applicable. |
| · Special precautions for user | Not applicable. |

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 8)

- | | |
|--|-----------------|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · UN "Model Regulation": | Void |

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- SARA (Superfund Amendments and Reauthorization Act)

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

glass, oxide, chemicals

2-hydroxyethyl methacrylate (HEMA)

surface-treated silica**

dimethacrylate component**

ethoxylated bisphenol-A dimethacrylate (Bis-EMA)

urethane dimethacrylate (UDMA)

photoinitiator**

photoinitiator**

butylated hydroxytoluene (BHT)

initiator**

· TSCA new (21st Century Act) (Substances not listed)

CAS: 41637-38-1 | ethoxylated bisphenol-A dimethacrylate (Bis-EMA)

· Carcinogenic categories
· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

butylated hydroxytoluene (BHT)

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms


GHS08

· Signal word Danger

(Contd. on page 10)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 9)

- **Hazard-determining components of labeling:**

2-hydroxyethyl methacrylate (HEMA)
dimethacrylate component**
urethane dimethacrylate (UDMA)
initiator**

- **Hazard statements**

Causes skin irritation.
Causes serious eye irritation.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
Suspected of damaging fertility or the unborn child.
Harmful to aquatic life.
Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

Wear protective gloves/protective clothing/eye protection/face protection.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If exposed or concerned: Get medical advice/attention.
Specific treatment (see on this label).
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

- **Department issuing SDS:** Regulatory Affairs

- **Contact:**

Regulatory Affairs
Telephone No. +1 (708) 597-0900
sds@gcamerica.com

- **Date of preparation / last revision** 07/13/2018 / -

- **Abbreviations and acronyms:**

GHS: Globally Harmonized System of Classification and Labelling of Chemicals
HCS: Hazard Communication Standard (USA)
MSDS: Material Safety Data Sheet
SDS: Safety Data Sheet
ADN: Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement Concerning the International Carriage of Dangerous Goods by Inland Waterways)
ECHA: European Chemicals Agency
OSHA: Occupational Safety and Health Administration (USA)
PAC: Protective Action Criterion (USA)
PACs: Protective Action Criteria (USA)
HNOC: Hazard Not Otherwise Classified (USA)
LEL: Lower Explosive Limit
UEL: Upper Explosive Limit
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS 29 CFR 1910.1200

Printing date 07/13/2018

Version US-EN-Rev 1

Reviewed on 07/13/2018

Trade name: GC Fuji Automix LC (Paste A: Shades A1, A2, and A3)

(Contd. of page 10)

LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
 Resp. Sens. 1: Respiratory sensitisation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Repr. 2: Reproductive toxicity – Category 2
 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3
 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

• **Sources**

- Manufacturers' MSDSs/SDSs
- OSHA (<https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html>)
- TOXNET (<http://toxnet.nlm.nih.gov/>)
- ECHA (<http://echa.europa.eu/>)
- EnviChem (www.echemportal.org)

• **Notes:**

CAS Registry Number is a Registered Trademark of the American Chemical Society.
 CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.

- * **Data compared to the previous version altered.** This version replaces all previous versions.

• **Disclaimer:**

The information contained herein is believed to be true and accurate. However, all statements, recommendations or suggestions are made without any guarantee, representation or warranty, express or implied, on our part. Therefore, no warranty is made or to be implied that the information set out in this document is accurate or complete, and we accordingly exclude all liability in connection with the use of this information or the products referred to herein. All such risks are assumed by the purchaser/user. The information contained herein is also subject to change without notice. For the avoidance of doubt, however, nothing in this document excludes or limits our liability for death or personal injury caused by our negligence or for fraudulent misrepresentation.

US