

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

071423482

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

071422997 071423532

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

071422989

### Section 1. Identification

**GHS product identifier** : TAC Tray Adhesive Compound  
**Other means of identification** : Not available.  
**Product code** : 0921881, 0921882  
**Product type** : Liquid.  
**Product use** : Dental Products  
Relevant identified uses of the substance or mixture and uses advised against

Not applicable.

**Supplier's details** : Keystone Industries  
 52 West King Street  
 Myerstown, PA 17067  
 (856) 663-4700

**Emergency telephone number (with hours of operation)** : (800) 535-5053

### Section 2. Hazards identification

**OSHA/HCS status** : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).  
**Classification of the substance or mixture** : FLAMMABLE LIQUIDS - Category 2  
 ACUTE TOXICITY (oral) - Category 4  
 SKIN IRRITATION - Category 2  
 EYE IRRITATION - Category 2A  
 TOXIC TO REPRODUCTION (Unborn child) - Category 2  
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2  
 Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 37.8%

GHS label elements

**Hazard pictograms** : 

**Signal word** : Danger  
**Hazard statements** : Highly flammable liquid and vapor.  
 Harmful if swallowed.  
 Causes serious eye irritation.  
 Causes skin irritation.  
 Suspected of damaging the unborn child.  
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

**Prevention** : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection: Recommended: safety glasses with side-shields. Wear protective clothing. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Do not breathe vapor. Do not eat, drink or smoke when

## Section 2. Hazards identification

- using this product. Wash hands thoroughly after handling.
- Response** : Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF SWALLOWED: Call a POISON CENTER or physician if you feel unwell. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

## Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

### CAS number/other identifiers

- CAS number** : Not applicable.

May contain one or more of the following components in quantities considered hazardous:

Ingredient name	CAS number	EC number	%
Isopropyl alcohol	67-63-0	200-661-7	≥25 - ≤50
toluene	108-88-3	203-625-9	≥10 - <20

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

**There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. If necessary, call a poison center or physician. Never give anything by mouth to an unconscious

## Section 4. First aid measures

person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.
- Skin contact** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.  
redness  
irritation
- Ingestion** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.

### Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Highly flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

- Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide

## Section 5. Fire-fighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.

## Section 7. Handling and storage

### Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

### Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
Isopropyl alcohol	<p><b>ACGIH TLV (United States, 3/2015).</b> TWA: 200 ppm 8 hours. STEL: 400 ppm 15 minutes.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 400 ppm 8 hours. TWA: 980 mg/m<sup>3</sup> 8 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m<sup>3</sup> 15 minutes.</p> <p><b>NIOSH REL (United States, 10/2013).</b> TWA: 400 ppm 10 hours. TWA: 980 mg/m<sup>3</sup> 10 hours. STEL: 500 ppm 15 minutes. STEL: 1225 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 2/2013).</b> TWA: 400 ppm 8 hours. TWA: 980 mg/m<sup>3</sup> 8 hours.</p>
toluene	<p><b>OSHA PEL 1989 (United States, 3/1989).</b> TWA: 100 ppm 8 hours. TWA: 375 mg/m<sup>3</sup> 8 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL Z2 (United States, 2/2013).</b> TWA: 200 ppm 8 hours. CEIL: 300 ppm AMP: 500 ppm 10 minutes.</p> <p><b>NIOSH REL (United States, 10/2013).</b> TWA: 100 ppm 10 hours. TWA: 375 mg/m<sup>3</sup> 10 hours. STEL: 150 ppm 15 minutes. STEL: 560 mg/m<sup>3</sup> 15 minutes.</p> <p><b>ACGIH TLV (United States, 3/2015).</b> TWA: 20 ppm 8 hours.</p>

## Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. Recommended: safety glasses with side-shields
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.
- Personal protective equipment (Pictograms)** :



## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid. [Clear.]
- Color** : Amber.
- Odor** : Characteristic.
- pH** : Not available.
- Melting point** : Not available.
- Boiling point** : >80°C (>176°F)

## Section 9. Physical and chemical properties

<b>Flash point</b>	: Closed cup: 12°C (53.6°F)
<b>Lower and upper explosive (flammable) limits</b>	: Lower: 2% Upper: 12%
<b>Vapor pressure</b>	: 4.4 kPa (33 mm Hg) [room temperature]
<b>Vapor density</b>	: 2.01 [Air = 1]
<b>Relative density</b>	: 0.84
<b>Solubility</b>	: Very slightly soluble in the following materials: cold water and hot water.
<b>Solubility in water</b>	: Not available.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Do not allow vapor to accumulate in low or confined areas.
<b>Incompatible materials</b>	: Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Isopropyl alcohol	LD50 Dermal	Rabbit	12800 mg/kg	-
	LD50 Oral	Rat	5000 mg/kg	-
toluene	LC50 Inhalation Vapor	Rat	49 g/m <sup>3</sup>	4 hours
	LD50 Oral	Rat	636 mg/kg	-

#### Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Isopropyl alcohol	Eyes - Moderate irritant	Rabbit	-	10 milligrams	-
	Eyes - Severe irritant	Rabbit	-	100 milligrams	-
	Skin - Mild irritant	Rabbit	-	500 milligrams	-
	Eyes - Moderate irritant	Rabbit	-	24 hours 100 milligrams	-
toluene	Eyes - Mild irritant	Rabbit	-	0.5 minutes 100	-



## Section 11. Toxicological information

	Eyes - Mild irritant	Rabbit	-	milligrams 870	-
	Eyes - Severe irritant	Rabbit	-	Micrograms 24 hours 2	-
	Skin - Mild irritant	Pig	-	milligrams 24 hours 250	-
	Skin - Mild irritant	Rabbit	-	microliters 435	-
	Skin - Moderate irritant	Rabbit	-	milligrams 24 hours 20	-
	Skin - Moderate irritant	Rabbit	-	milligrams 500	-
				milligrams	

### Classification

Product/ingredient name	OSHA	IARC	NTP
Isopropyl alcohol	-	3	-
toluene	-	3	-

### Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 3	Not applicable.	Narcotic effects

### Specific target organ toxicity (repeated exposure)

Name	Category	Route of exposure	Target organs
toluene	Category 2	Not determined	Not determined

### Aspiration hazard

Name	Result
toluene	ASPIRATION HAZARD - Category 1

**Information on the likely routes of exposure** : Not available.

### Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Causes skin irritation.
- Ingestion** : Harmful if swallowed.

### Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Inhalation** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.
- Skin contact** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.  
redness  
irritation
- Ingestion** : Adverse symptoms may include the following:  
Suspected of damaging the unborn child.

## Section 11. Toxicological information

### Delayed and immediate effects and also chronic effects from short and long term exposure

#### Short term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Long term exposure

**Potential immediate effects** : Not available.

**Potential delayed effects** : Not available.

#### Potential chronic health effects

Not available.

**General** : May cause damage to organs through prolonged or repeated exposure.

**Carcinogenicity** : No known significant effects or critical hazards.

**Mutagenicity** : No known significant effects or critical hazards.

**Teratogenicity** : Suspected of damaging the unborn child.

**Developmental effects** : No known significant effects or critical hazards.

**Fertility effects** : No known significant effects or critical hazards.

### Numerical measures of toxicity

#### Acute toxicity estimates

Route	ATE value
Oral	1587.2 mg/kg

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
Isopropyl alcohol toluene	Acute LC50 1400000 µg/l Marine water	Crustaceans - Crangon crangon	48 hours
	Acute LC50 4200 mg/l Fresh water	Fish - Rasbora heteromorpha	96 hours
	Acute EC50 12500 µg/l Fresh water	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 11600 µg/l Fresh water	Crustaceans - Gammarus pseudolimnaeus - Adult	48 hours
	Acute EC50 6000 µg/l Fresh water	Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling)	48 hours
	Acute LC50 5500 µg/l Fresh water Chronic NOEC 1000 µg/l Fresh water	Fish - Oncorhynchus kisutch - Fry Daphnia - Daphnia magna	96 hours 21 days

### Bioaccumulative potential

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
Isopropyl alcohol	0.05	-	low
toluene	2.73	90	low

### Mobility in soil

**Soil/water partition coefficient (K<sub>oc</sub>)** : Not available.

## Section 12. Ecological information

**Other adverse effects** : No known significant effects or critical hazards.







## Section 13. Disposal considerations

**Disposal methods** : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

### United States - RCRA Toxic hazardous waste "U" List

Ingredient	CAS #	Status	Reference number
Toluene; Benzene, methyl-	108-88-3	Listed	U220

## Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ADR/RID	IMDG	IATA
<b>UN number</b>	UN1993	UN1993	UN1993	UN1993	UN1993	UN1993
<b>UN proper shipping name</b>	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)	FLAMMABLE LIQUID, N.O.S. (Isopropyl alcohol, toluene)
<b>Transport hazard class(es)</b>	3 	3 	3 	3 	3 	3 
<b>Packing group</b>	II	II	II	II	II	II
<b>Environmental hazards</b>	No.	No.	No.	No.	No.	No.
<b>Additional information</b>	<b>Reportable quantity</b> 5068.9 lbs / 2301.3 kg [723.74 gal / 2739.6 L] Package sizes shipped in quantities less than the product reportable	Product classified as per the following sections of the Transportation of Dangerous Goods Regulations: 2.18-2.19 (Class 3).	-	<b>Special provisions</b> 640 (C) <b>Tunnel code</b> (D/E)	-	-

## Section 14. Transport information

	quantity are not subject to the RQ (reportable quantity) transportation requirements.					
--	---	--	--	--	--	--

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

**Transport in bulk according to Annex II of MARPOL and the IBC Code** : Not available.

## Section 15. Regulatory information

**U.S. Federal regulations** : **TSCA 8(a) CDR Exempt/Partial exemption:** Not determined  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Clean Water Act (CWA) 307:** toluene  
**Clean Water Act (CWA) 311:** toluene

**Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs)** : Listed

**Clean Air Act Section 602 Class I Substances** : Not listed

**Clean Air Act Section 602 Class II Substances** : Not listed

**DEA List I Chemicals (Precursor Chemicals)** : Not listed

**DEA List II Chemicals (Essential Chemicals)** : Listed

### SARA 302/304

#### Composition/information on ingredients

No products were found.

**SARA 304 RQ** : Not applicable.

### SARA 311/312

**Classification** : Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

#### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
Isopropyl alcohol	≥25 - ≤50	Yes.	No.	No.	Yes.	No.
toluene	≥10 - <20	Yes.	No.	No.	Yes.	Yes.

### SARA 313

## Section 15. Regulatory information

	Product name	CAS number	%
Form R - Reporting requirements	Isopropyl alcohol	67-63-0	≥25 - ≤50
	toluene	108-88-3	≥10 - <20
Supplier notification	Isopropyl alcohol	67-63-0	≥25 - ≤50
	toluene	108-88-3	≥10 - <20

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: TOLUENE; ISOPROPYL ALCOHOL
- New York** : The following components are listed: Toluene
- New Jersey** : The following components are listed: TOLUENE; BENZENE, METHYL-; ISOPROPYL ALCOHOL; 2-PROPANOL
- Pennsylvania** : The following components are listed: BENZENE, METHYL-; ISOPROPYL ALCOHOL MANUFACTURE (STRONG-ACID PROCESS)

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
toluene	No.	Yes.	No.	7000 µg/day (ingestion)

**Canada inventory** : All components are listed or exempted.

### International regulations

- International lists** :
- Australia inventory (AICS):** All components are listed or exempted.
  - China inventory (IECSC):** All components are listed or exempted.
  - Japan inventory (ENCS):** Not determined.
  - Japan inventory (ISHL):** Not determined.
  - Korea inventory:** All components are listed or exempted.
  - Malaysia Inventory (EHS Register):** Not determined.
  - New Zealand Inventory of Chemicals (NZIoC):** All components are listed or exempted.
  - Philippines inventory (PICCS):** All components are listed or exempted.
  - Taiwan Chemical Substances Inventory (TCSI):** All components are listed or exempted.
  - Turkey inventory:** Not determined.

**Chemical Weapons Convention List Schedule I Chemicals** : Not listed

**Chemical Weapons Convention List Schedule II Chemicals** : Not listed

**Chemical Weapons Convention List Schedule III Chemicals** : Not listed

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	2
Flammability	3
Physical hazards	0
Personal protection	

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

<b>Date of printing</b>	: 3/3/2016
<b>Date of issue/Date of revision</b>	: 3/3/2016
<b>Date of previous issue</b>	: No previous validation
<b>Version</b>	: 1
<b>Key to abbreviations</b>	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

**References** : Not available.

✔ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## Section 16. Other information

Information contained within this SDS is only to be distributed as required by law.