

SAFETY DATA SHEETS

This SDS packet was issued with item:

073092418

N/A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : EZ-Fill Xpress Paste A
 Product code : 1620-00, 1625-00, 1628-00

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Obturation material. This is part of a two-component system. For use with Paste B component.
 Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

Essential Dental Systems
 89 Leuning St, South Hackensack, NJ 07606
 Tel: (201) 487-9090
 Email: info@edsdental.com

1.4. Emergency telephone number

Emergency number : +1-201-487-9090 9:00 a.m. to 5:00 p.m. Eastern Standard Time

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Acute Tox. 4 (Oral) H302
 Acute Tox. 4 (Dermal) H312
 Skin Corr. 1C H314
 Eye Dam. 1 H318
 Carc. 2 H351

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H312 - Harmful if swallowed or in contact with skin
 H314 - Causes severe skin burns and eye damage
 H318 - Causes serious eye damage
 H351 - Suspected of causing cancer (Inhalation)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P260 - Do not breathe dust, fume, mist, spray
 P264 - Wash hands thoroughly after handling
 P270 - Do not eat, drink or smoke when using this product
 P280 - Wear eye protection, protective clothing, protective gloves
 P301+P312 - If swallowed: Call a a POISON CENTER if you feel unwell
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P302+P352 - If on skin: Wash with plenty of water
 P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P310 - Immediately call a a doctor, a POISON CENTER
 P312 - Call a a doctor if you feel unwell
 P321 - Specific treatment (see on this label)
 P330 - Rinse mouth
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P363 - Wash contaminated clothing before reuse

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

P405 - Store locked up
P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS No) 9046-10-0	5 - 25	Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Skin Corr. 1C, H314 Eye Dam. 1, H318
Titanium dioxide	(CAS No) 13463-67-7	1 - 5	Carc. 2, H351

Titanium dioxide used in this material is not believed to have the potential to become of respirable size.

Normal application procedures pose no hazard since the material is encapsulated.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Assure fresh air breathing. Maintain an open airways. Seek immediate medical advice. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Do not rub the skin and eyes after direct contact with the product. Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation	: Inhalation of dust may cause irritation of the respiratory system. May cause cancer by inhalation.
Symptoms/injuries after skin contact	: Harmful in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.
Symptoms/injuries after eye contact	: Causes serious eye damage. Symptoms include stinging, watering, redness, and swelling.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Ingestion may cause immediate pain and severe burns of the mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Cool closed containers exposed to fire with water spray. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection.

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Other information : Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, SiO₂. Titanium dioxide. Metal oxides. Nitrogen oxides (NO_x).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothes. Avoid breathing dust. Use special care to avoid static electric charges. Avoid raising powdered materials into airborne dust. Work in a well-ventilated area. Eliminate all ignition sources if safe to do so.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Avoid raising powdered materials into airborne dust. Minimize generation of dust. Store away from other materials. Ensure all national/local regulations are observed.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, mist or spray. Use only in well-ventilated areas. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : A washing facility/water for eye and skin cleaning purposes should be present. Provide local exhaust or general room ventilation. Provide adequate ventilation to minimize dust concentrations.

Storage conditions : Keep only in the original container in a cool, well ventilated place. Keep container closed when not in use. Keep away from ignition sources (including static discharges). Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep out of reach of children. Keep away from food and drink.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

8.2. Exposure controls

Appropriate engineering controls : A washing facility/water for eye and skin cleaning purposes should be present. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use ventilation to keep exposure to airborne contaminants below the exposure limits. Provide local exhaust or general room ventilation to minimize exposure to dust.

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective goggles. Protective clothing. For certain operations, additional Personal Protection Equipment (PPE) may be required. Personal protective equipment should be selected based upon the conditions under which this product is handled or used.



Hand protection : Wear protective gloves.
Eye protection : Wear safety glasses with side shields, goggles or face shield for protection against dust or flying debris.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour under TLV.
Environmental exposure controls : Avoid release to the environment.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Paste. Gel.
Colour : Peach
odour : Not available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : 3.4 g/cm³ at 23 °C / 73 °F
Solubility : Water: insoluble
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, SiO₂. Fume. Metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed. Harmful in contact with skin.

EZ-Fill Xpress Paste A	
ATE US (oral)	500.00000000 mg/kg bodyweight
ATE US (dermal)	1100.00000000 mg/kg bodyweight

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)	
LD50 oral rat	242 mg/kg
LD50 dermal rabbit	360 mg/kg
ATE US (oral)	242.00000000 mg/kg bodyweight
ATE US (dermal)	360.00000000 mg/kg bodyweight

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : Not classified
(Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)

Carcinogenicity : Suspected of causing cancer (Inhalation).

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (repeated exposure) : Not classified
(Based on available data, the classification criteria are not met)

Aspiration hazard : Not classified
(Based on available data, the classification criteria are not met)

Potential Adverse human health effects and symptoms : Harmful if swallowed.

Symptoms/injuries after inhalation : Inhalation of dust may cause irritation of the respiratory system. May cause cancer by inhalation.

Symptoms/injuries after skin contact : Harmful in contact with skin. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Symptoms/injuries after eye contact : Causes serious eye damage. Symptoms include stinging, watering, redness, and swelling.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Ingestion may cause immediate pain and severe burns of the mucous membranes.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

12.2. Persistence and degradability

EZ-Fill Xpress Paste A

Persistence and degradability	Not established.
-------------------------------	------------------

12.3. Bioaccumulative potential

EZ-Fill Xpress Paste A

Bioaccumulative potential	Not established.
---------------------------	------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with applicable local, national and international regulations.

Additional information : Do not re-use empty containers.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description : UN1760 Corrosive liquids, n.o.s. Propylene glycol diamine, 2-amino-, diether with Propylene, 8, III

UN-No.(DOT) : 1760

DOT NA no. : UN1760

DOT Proper Shipping Name : Corrosive liquids, n.o.s.
Propylene glycol diamine, 2-amino-, diether with Propylene

Department of Transportation (DOT) Hazard Classes : 8 - Class 8 - Corrosive material 49 CFR 173.136

Hazard labels (DOT) : 8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Special Provisions (49 CFR 172.102) : IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).
T7 - 4 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / (1 + a (tr - tf))$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 154

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Additional information

Other information : No supplementary information available.

ADR

Transport document description : No additional information available

Transport by sea

UN-No. (IMDG) : 1760

Proper Shipping Name (IMDG) : CORROSIVE LIQUID, N.O.S.

Class (IMDG) : 8 - Corrosive substances

Packing group (IMDG) : III - substances presenting low danger

Air transport

UN-No.(IATA) : 1760

Proper Shipping Name (IATA) : CORROSIVE LIQUID, N.O.S.

Class (IATA) : 8 - Corrosives

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

Titanium dioxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification : Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC or 1999/45/EC

No additional information available

15.2.2. National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Skin Corr. 1C	Skin corrosion/irritation Category 1C
H301	Toxic if swallowed
H302	Harmful if swallowed

EZ-Fill Xpress Paste A

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

H311	Toxic in contact with skin
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : EZ-Fill Xpress Paste B
 Product code : 1620-00, 1625-00, 1628-00

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Obturation material. This is part of a two-component system. For use with Paste A component.
 Use of the substance/mixture : For professional use only

1.3. Details of the supplier of the safety data sheet

Essential Dental Systems
 89 Leuning St, South Hackensack, NJ 07606
 Tel: (201) 487-9090
 Email: info@edsdental.com

1.4. Emergency telephone number

Emergency number : +1-201-487-9090 9:00 a.m. to 5:00 p.m. Eastern Standard Time

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Skin Irrit. 2 H315
 Eye Irrit. 2A H319
 Skin Sens. 1 H317
 Carc. 2 H351

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H315 - Causes skin irritation
 H317 - May cause an allergic skin reaction
 H319 - Causes serious eye irritation
 H351 - Suspected of causing cancer (Inhalation)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P261 - Avoid breathing dust, fume, mist, spray, vapours
 P264 - Wash hands thoroughly after handling
 P272 - Contaminated work clothing must not be allowed out of the workplace
 P280 - Wear eye protection, protective clothing, protective gloves
 P302+P352 - If on skin: Wash with plenty of water
 P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P308+P313 - If exposed or concerned: Get medical advice/attention
 P321 - Specific treatment (see on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 P337+P313 - If eye irritation persists: get medical advice/attention
 P362 - Take off contaminated clothing and wash before reuse
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P405 - Store locked up
 P501 - Dispose of contents/container to comply with applicable local, national and international regulation.

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Bisphenol A	(CAS No) 80-05-7	1 - 10	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1, H317
Titanium dioxide	(CAS No) 13463-67-7	1 - 5	Carc. 2, H351
Propylene carbonate	(CAS No) 108-32-7	1 - 5	Eye Irrit. 2A, H319

Titanium dioxide used in this material does not have the potential to become of respirable size.

Normal application procedures poses no hazard since the material is bound and encapsulated.

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing. Assure fresh air breathing. Maintain an open airways. Seek immediate medical advice. Immediately call a POISON CENTER or doctor/physician.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
First-aid measures after eye contact	: Do not rub the skin and eyes after direct contact with the product. Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: If swallowed, rinse mouth with water (only if the person is conscious). Do NOT induce vomiting. Obtain emergency medical attention. Immediately call a POISON CENTER or doctor/physician. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Inhalation of dust may cause irritation of the respiratory system. May cause cancer by inhalation.
Symptoms/injuries after skin contact	: May cause an allergic skin reaction. Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation. Effects may include discomfort or pain and redness.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available

5.3. Advice for firefighters

Firefighting instructions	: Cool closed containers exposed to fire with water spray. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protective equipment for firefighters	: Do not enter fire area without proper protective equipment, including respiratory protection.
Other information	: Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, SiO ₂ . Titanium dioxide. Metal oxides. Nitrogen oxides (NO _x).

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothes. Avoid breathing dust. Use special care to avoid static electric charges. Avoid raising powdered materials into airborne dust. Work in a well-ventilated area. Eliminate all ignition sources if safe to do so.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : On land, sweep or shovel into suitable containers. Avoid raising powdered materials into airborne dust. Minimize generation of dust. Store away from other materials. Ensure all national/local regulations are observed.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust, mist or spray. Use only in well-ventilated areas. Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : A washing facility/water for eye and skin cleaning purposes should be present. Provide local exhaust or general room ventilation. Provide adequate ventilation to minimize dust concentrations.

Storage conditions : Keep only in the original container in a cool, well ventilated place. Keep container closed when not in use. Keep away from ignition sources (including static discharges). Keep the packing dry and well sealed to prevent contamination and absorption of humidity. Keep out of reach of children. Keep away from food and drink.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

8.2. Exposure controls

Appropriate engineering controls : A washing facility/water for eye and skin cleaning purposes should be present. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Use ventilation to keep exposure to airborne contaminants below the exposure limits. Provide local exhaust or general room ventilation to minimize exposure to dust.

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Protective goggles. Protective clothing. For certain operations, additional Personal Protection Equipment (PPE) may be required. Personal protective equipment should be selected based upon the conditions under which this product is handled or used.



Hand protection : Wear protective gloves.
Eye protection : Wear safety glasses with side shields, goggles or face shield for protection against dust or flying debris.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear appropriate breathing apparatus if air renewal not sufficient to maintain dust/vapour under TLV.
Environmental exposure controls : Avoid release to the environment.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Paste. Gel.
Colour : Peach
Odour : Not available
Odour threshold : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : No data available
Boiling point : No data available
Flash point : No data available
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapour pressure : No data available
Relative vapour density at 20 °C : No data available
Relative density : No data available
Density : 3.4 g/ml at 23 °C / 73 °F
Solubility : Water: insoluble
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidising properties : No data available
Explosive limits : No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products may be released during prolonged heating like smokes, carbon monoxide and dioxide, SiO₂. Fume. Metal oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Titanium dioxide (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Propylene carbonate (108-32-7)	
LD50 oral rat	29000 mg/kg
LD50 dermal rabbit	> 20 ml/kg
ATE US (oral)	29000.00000000 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Causes serious eye irritation.
Respiratory or skin sensitisation : May cause an allergic skin reaction.
(Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)
Carcinogenicity : Suspected of causing cancer (Inhalation).

Titanium dioxide (13463-67-7)	
IARC group	2B - Possibly carcinogenic to humans

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)
Specific target organ toxicity (single exposure) : Not classified
(Based on available data, the classification criteria are not met)
Specific target organ toxicity (repeated exposure) : Not classified
(Based on available data, the classification criteria are not met)
Aspiration hazard : Not classified
(Based on available data, the classification criteria are not met)
Symptoms/injuries after inhalation : Inhalation of dust may cause irritation of the respiratory system. May cause cancer by inhalation.
Symptoms/injuries after skin contact : May cause an allergic skin reaction. Causes skin irritation.
Symptoms/injuries after eye contact : Causes serious eye irritation. Effects may include discomfort or pain and redness.

SECTION 12: Ecological information

12.1. Toxicity

Propylene carbonate (108-32-7)	
LC50 fishes 1	> 1000 mg/l (Exposure time: 96 h - Species: Cyprinus carpio [semi-static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

EZ-Fill Xpress Paste B	
Persistence and degradability	Not established.

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

12.3. Bioaccumulative potential

EZ-Fill Xpress Paste B	
Bioaccumulative potential	Not established.

Propylene carbonate (108-32-7)	
Log Pow	0.48 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to comply with applicable local, national and international regulations.

Additional information : Do not re-use empty containers.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT
Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

Transport document description : No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

No additional information available

15.2. International regulations

CANADA

Titanium dioxide (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Propylene carbonate (108-32-7)	
Listed on the Canadian DSL (Domestic Substances List)	
WHMIS Classification	Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Classification according to Directive 67/548/EEC or 1999/45/EC

No additional information available

EZ-Fill Xpress Paste B

Safety Data Sheet

according to the federal final rule of hazard communication revised on 2012 (HazCom 2012)

15.2.2. National regulations

No additional information available



WARNING: This product can expose you to Bisphenol A, which is known to the State of California to cause reproductive harm. For more information go to www.P65Warnings.ca.gov.

15.3. US State regulations

Bisphenol A (80-05-7)		
U.S. - California - Proposition 65 – Female List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female

SECTION 16: Other information

Other information : None.

Full text of H-phrases: see section 16:

Carc. 2	Carcinogenicity, Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H351	Suspected of causing cancer

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product