

SAFETY DATA SHEETS

This SDS packet was issued with item:

073243516

N/A

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 1 of 6

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond-TotalEtch-PreBond

CAS No: 64-17-5

Index No: 603-002-00-5

EC No: 200-578-6

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company Name: DMG America LLC
Address: 242 South Dean Street
Englewood, NJ. 07631
Telephone: (800) 662-6383
(800) 535-5053 (INFOTRAC Emergency number number)
Email address: info@dmg-america.com
Website: www.dmg-america.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazard Statements:

Highly flammable liquid and vapour.

2.2. Label elements

Signal word: Danger

Pictograms: GHS02



Hazard statements

H225 Highly flammable liquid and vapour.

Precautionary statements

P233 Keep container tightly closed.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P102 Keep out of reach of children.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Ethanol.

Sum formula: C₂H₆O

Molecular weight: 46,07

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 2 of 6

Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification according to Directive 67/548/EEC	
Index No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	
REACH No		
200-578-6	ethanol, ethyl alcohol	< 100 %
64-17-5	F - Highly flammable R11	
603-002-00-5	Flam. Liq. 2; H225	

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap. Change contaminated clothing. Rub in high-fat content cream.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

If swallowed, immediately drink: Water. Consult physician.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Atomized water. alcohol resistant foam. Carbon dioxide (CO2). Extinguishing powder. Sand.

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Concentrated vapors are heavier than air. Vapours may form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition - No smoking.
The following must be prevented: inhalation. skin contact. Eye contact.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep away from sources of ignition - No smoking. Provide adequate ventilation.

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 3 of 6

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.
Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
64-17-5	Ethanol	1000	1920		TWA (8 h)	WEL
		-	-		STEL (15 min)	WEL

8.2. Exposure controls



Protective and hygiene measures

When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Respiratory protection

The following must be prevented: inhalation. Exceeding critical value: Filter respirator (full mask or mouth-piece) with filter: A

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: colourless-transparent
Odour: characteristic

Test method

pH-Value: neutral

Changes in the physical state

Melting point: ca. -115 °C

Initial boiling point and boiling range: ca. 80 °C

Flash point: 12 °C

Lower explosion limits: 3.5 vol. %

Upper explosion limits: 15 vol. %

Ignition temperature: 425 °C

Vapour pressure: 59 hPa
(at 20 °C)

Density (at 20 °C): ca. 0,8 g/cm³

Water solubility: complete miscible

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 4 of 6

Viscosity / dynamic:
(at 20 °C)

1,3 mPa·s

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

heat.

10.5. Incompatible materials

Oxidizing agents. peroxides. acid. Alkali metals.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Acute toxicity, oral LD50: (species: Rat.): > 6200 mg/kg; Acute toxicity, inhalant 95.6 mg / l / 4 h

CAS No	Chemical name	Exposure routes	Method	Dose	Species	Source
64-17-5	ethanol, ethyl alcohol	oral	LD50	6200 mg/kg	Rat	IUCLID
		inhalative (4 h) vapour	LC50	95,6 mg/l	Rat	RTECS

Irritation and corrosivity

In case of prolonged or frequently repeated skin contact: irritant.; Following eye contact: irritant.

SECTION 12: Ecological information

12.1. Toxicity

Acute fish toxicity (Leuciscus idus): LC50: > 8140 mg / l / 48 h (Ethanol);

Acute Daphnia toxicity (Daphnia magna): EC50: 9268 - 14221 mg / l / 48 h

CAS No	Chemical name	Aquatic toxicity	Method	Dose	[h] [d]	Species	Source
64-17-5	ethanol, ethyl alcohol	Acute crustacea toxicity	EC50	9268 - 14221 mg/l	48 h	Daphnia magna	IUCLID

12.2. Persistence and degradability

Easily biodegradable (concerning to the criteria of the OECD)

12.3. Bioaccumulative potential

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
64-17-5	ethanol, ethyl alcohol	-0,31

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Remove according to the regulations.

Waste disposal number of waste from residues/unused products

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 5 of 6

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Special Provisions: 144 601
Limited quantity: 1 L
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Other applicable information (land transport)

E2

Marine transport (IMDG)

14.1. UN number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Special Provisions: 144
Limited quantity: 3 L
EmS: F-E, S-D

Other applicable information (marine transport)

E2

Air transport (ICAO)

14.1. UN number: UN 1170
14.2. UN proper shipping name: ETHANOL (ETHYL ALCOHOL)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3

Safety Data Sheet

LuxaBond-Total Etch (Pre-Bond)

Product code: 212384 (GHS_6700)

Page 6 of 6



Special Provisions:	A3	
Limited quantity Passenger:	1 L	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

Other applicable information (air transport)

E2
: Y341

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

SECTION 16: Other information

Relevant R-phrases (Number and full text)

11 Highly flammable.

Relevant H- and EUH-phrases (Number and full text)

H225 Highly flammable liquid and vapour.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)

Safety Data Sheet

LuxaBond-Total Etch (Bond A + B)

Product code: 212384 (GHS_2222)

Page 1 of 4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LuxaBond-Total Etch (Bond A + B)

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company Name: DMG America LLC
Address: 242 South Dean Street
Englewood, NJ. 07631
Telephone no: (800) 662-6383
(800) 535-5053 (INFOTRAC Emergency number)
Email address: info@dmg-america.com
Website: ww.dmg-america.com

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant
R phrases:
Irritating to eyes, respiratory system and skin.
May cause sensitisation by skin contact.

GHS classification

Hazard Statements:
May cause respiratory irritation.
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.

2.2. Label elements

Signal word: Warning
Pictograms: GHS07



Hazard statements

H335 May cause respiratory irritation.
H319 Causes serious eye irritation.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

Precautionary statements

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

Safety Data Sheet

LuxaBond-Total Etch (Bond A + B)

Product code: 212384 (GHS_2222)

Page 2 of 4

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Move victim to fresh air. Put victim at rest and keep warm.

After contact with skin

After contact with skin, wash immediately with: Water and soap.

After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After ingestion

Immediately get medical attention.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO₂).

Extinguishing media which must not be used for safety reasons

High power water jet.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear suitable protective clothing. Provide adequate ventilation.

6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

6.3. Methods and material for containment and cleaning up

Collect mechanically.

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

Store only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.2. Exposure controls



Occupational exposure controls

Ensure adequate ventilation of the storage area.

Safety Data Sheet

LuxaBond-Total Etch (Bond A + B)

Product code: 212384 (GHS_2222)

Page 3 of 4

Protective and hygiene measures

When using do not eat or drink.

Respiratory protection

The following must be prevented: inhalation.

Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

Eye protection

Tightly sealed safety glasses.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid
Colour: yellow
Odour: like: ester

Test method

pH-Value (at 20 °C): 4.5 - 7

Changes in the physical state

Boiling point: 100 °C

point of decomposition: > 200 °C

Flash point: > 100 °C

Vapour pressure: 23 hPa
(at 20 °C)

Density: 1,1 g/cm³

Solubility in other solvents

Solubility ca. 50 %

Vapour density: > 1

SECTION 10: Stability and reactivity

10.4. Conditions to avoid

Light. heat.

10.5. Incompatible materials

Keep away from strong acids, leachates, heavy metal salts and reducing materials.

10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent)

Further information

Substances sensitive to light.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

LD50: Rat. 5500mg/kg

Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye: Frequently or prolonged contact with skin may cause dermal irritation.

Sensitising effects

May cause sensitization by skin contact.

Safety Data Sheet

LuxaBond-Total Etch (Bond A + B)

Product code: 212384 (GHS_2222)

Page 4 of 4

Additional information on tests

Contains Methacrylates: May produce an allergic reaction. May cause sensitization by skin contact.

SECTION 12: Ecological information

12.1. Toxicity

Aquaticity LC50: > 360 mg / l / 48h

12.2. Persistence and degradability

Product is partially biodegradable. 50%

Further information

Do not empty into drains or the aquatic environment. Leakage into the environment must be prevented.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Carry out a burning of hazardous waste according to official regulations.

Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances
Classified as hazardous waste.

SECTION 14: Transport information

Other applicable information

Not a hazardous material with respect to these transportation regulations.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulatory information

Water contaminating class (D): - - not water contaminating

SECTION 16: Other information

Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.
43 May cause sensitisation by skin contact.

Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Further Information

-

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)