# **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

075184999

N/A

# SAFETY DATA SHEET SILICONE REMOVER

# 1. Identification

Product identifier

Product name SILICONE REMOVER

Chemical name METHYL METHACRYLATE

CAS number 80-62-6

#### Recommended use of the chemical and restrictions on use

Restriction on use SILICONE REMOVER is an auxiliary agent used to remove the silicone-based materials from

the acrylic resin. This product is classified as non medical device because of the limited application with outside of the patient's mouth even though it is used in a dental clinic or

dental laboratory.

# Details of the supplier of the safety data sheet

**Supplier** Tokuyama Dental America, Inc.

740 Garden View CT., Suite 200 Encinitas, CA 92024 U.S.A.

Tel: +1-760-942-7211 Fax:+1-760-942-7212

Contact person http://www.tokuyama-dental.com/tdc/contact.html

Manufacturer Tokuyama Dental Corporation

38-9, Taitou 1-chome, Taitou-ku, Tokyo

110-0016, Japan TEL: +81-3-3835-2261 FAX: +81-3-3835-2265

# **Emergency telephone number**

Emergency telephone Tokuyama Dental America, Inc. Tel: +1-760-942-7211

Days and hours of operation: 9:00-17:00(PST/PDT), Weekdays, except national holidays in

US.

Language: English only.

# 2. Hazard identification

# Classification of the substance or mixture

WHMIS Regulatory Status This product has been classified according to the hazard criteria of the Hazardous Product

Regulations and the SDS contains all required information.

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit. 2 - H315 Skin Sens. 1 - H317 STOT SE 3 - H335

Environmental hazards Not Classified

Label elements

**Pictogram** 





Signal word

Danger

#### SILICONE REMOVER

Hazard statements H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling. P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTRE/doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

P362+P364 Take off contaminated clothing and wash it before reuse.
P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with local regulations.

# 3. Composition/information on ingredients

#### Substances

METHYL METHACRYLATE 100%

CAS number: 80-62-6

Product name SILICONE REMOVER

Chemical name METHYL METHACRYLATE

CAS number 80-62-6

#### 4. First-aid measures

#### Description of first aid measures

**General information** Move affected person to fresh air at once. Get medical attention if any discomfort continues.

**Inhalation** Move affected person to fresh air at once.

Ingestion Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any

discomfort continues.

Skin contact Wash skin thoroughly with soap and water. Take off contaminated clothing. Wash

contaminated clothing before reuse.

# SILICONE REMOVER

Eye contact Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes

with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get

medical attention if irritation persists after washing.

Most important symptoms and effects, both acute and delayed

Inhalation Irritation of nose, throat and airway.

Skin contact Allergic rash. Skin irritation.

Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations.

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media Extinguish with the following media: Foam. Carbon dioxide or dry powder.

Specific hazards arising from the hazardous product

Specific hazards Irritating gases or vapours.

Hazardous combustion

products

No known hazardous decomposition products.

Advice for firefighters

Protective actions during

firefighting

Avoid breathing fire gases or vapours.

for firefighters

**Special protective equipment** Wear chemical protective suit.

# 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

**Environmental precautions** 

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses.

#### Methods and material for containment and cleaning up

No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate Methods for cleaning up

> ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Ground/bond container and receiving equipment. Use only non-sparking tools. Avoid the spillage or runoff

entering drains, sewers or watercourses.

Reference to other sections

Reference to other sections For waste disposal, see Section 13.

# 7. Handling and storage

#### Precautions for safe handling

Usage precautions All handling should only take place in well-ventilated areas. Ground/bond container and

receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use

only non-sparking tools. Take precautionary measures against static discharge.

#### Conditions for safe storage, including any incompatibilities

# SILICONE REMOVER

Storage precautions Store at temperatures between 0°C/25°F and 32°C/77°F. Keep away from heat, sparks and

open flame. Store in a cool and well-ventilated place. Ground/bond container and receiving

equipment.

Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.

#### 8. Exposure Controls/personal protection

#### Control parameters

#### Occupational exposure limits

#### METHYL METHACRYLATE

Long-term exposure limit (8-hour TWA): ACGIH 50 ppm 205 mg/m<sup>3</sup> Short-term exposure limit (15-minute): ACGIH 100 ppm 410 mg/m<sup>3</sup>

A4, DSens

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

DSens = Dermal sensitizer.

# **Exposure controls**

Appropriate engineering

Provide adequate general and local exhaust ventilation. Use explosion-proof electrical,

ventilating and lighting equipment.

**Eye/face protection** The following protection should be worn: Chemical splash goggles.

Hand protection Wear protective gloves.

Other skin and body

Odour threshold

protection

controls

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures Do not eat, drink or smoke when using this product. Wash at the end of each work shift and

before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Take off

contaminated clothing and wash it before reuse.

**Respiratory protection** Wear a respirator fitted with the following cartridge: Organic vapour filter.

# 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

Appearance Liquid

Colour Clear, Colourless

Not available.

Odour Characteristic

pH Not available.

Melting point Not available.

Initial boiling point and range 100°C

Flash point 14.5°C

**Evaporation rate** Not available.

**Evaporation factor** Not available.

Flammability (solid, gas) Not available.

# SILICONE REMOVER

Upper/lower flammability or

explosive limits

Upper flammable/explosive limit: 12.5% Lower flammable/explosive limit: 1.7%

Other flammability Not available.

Vapour pressure Not available.

Vapour density Not available.

**Relative density** Not available.

Solubility(ies) Not available.

Partition coefficient Not available.

Auto-ignition temperature 421°C

**Decomposition Temperature** Not available.

Viscosity Not available.

**Explosive properties** Not explosive.

Oxidising properties Not available.

Other information Not available.

# 10. Stability and reactivity

**Reactivity** May polymerize. See the other subsections of this section for further details.

**Stability** The product is highly flammable.

Possibility of hazardous

reactions

May polymerize.

Conditions to avoid Keep away from heat, sparks and open flame. Protect against direct sunlight.

Materials to avoid Strong oxidizing agents.

Hazardous decomposition

products

Heating may generate the following products: Toxic gases or vapours.

# 11. Toxicological information

# Information on toxicological effects

Routes of exposure See section 4. Skin , Eyes , Ingestion , Inhalation

Acute toxicity - oral

Notes (oral LD<sub>50</sub>) Not available.

Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) Not available.

Acute toxicity - inhalation

Notes (inhalation LC50) Not available.

Skin corrosion/irritation

**Skin corrosion/irritation** Skin Irrit. 2 - H315 Causes skin irritation.

Animal data Not available.

# SILICONE REMOVER

Serious eye damage/irritation

Serious eye damage/irritation Not available.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Skin Sens. 1 - H317 May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Not available. Genotoxicity - in vivo

Carcinogenicity

Carcinogenicity Not available.

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

NTP carcinogenicity Not listed. **OSHA Carcinogenicity** Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity -

Not available.

development

Specific target organ toxicity - single exposure

STOT - single exposure STOT SE 3 - H335 May cause respiratory irritation.

Specific target organ toxicity - repeated exposure STOT - repeated exposure

Not available.

Aspiration hazard

Aspiration hazard Not available.

# 12. Ecological Information

**Toxicity** Not available.

Persistence and degradability

Persistence and degradability No data available.

Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility No information available.

Other adverse effects

Other adverse effects Not known.

# 13. Disposal considerations

#### Waste treatment methods

# SILICONE REMOVER

**Disposal methods**Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

# 14. Transport information

**UN** number

UN No. (TDG) 1247 UN No. (IMDG) 1247 UN No. (ICAO) 1247 UN No. (DOT) UN1247

UN proper shipping name

Proper shipping name (TDG) METHYL METHACRYLATE MONOMER, STABILIZED

Proper shipping name (IMDG) METHYL METHACRYLATE MONOMER, STABILIZED

Proper shipping name (ICAO) METHYL METHACRYLATE MONOMER, STABILIZED

Proper shipping name (DOT) METHYL METHACRYLATE MONOMER, STABILIZED

# Transport hazard class(es)

DOT class 3
DOT hazard label 3
TDG class 3
TDG label(s) 3
IMDG class 3

ICAO class/division 3

# DOT transport label



#### Transport labels



# Packing group

TDG packing group || IMDG packing group || ICAO packing group || IDOT packing group || II

# **Environmental hazards**

Environmentally hazardous substance/marine pollutant

No.

# Special precautions for user

EmS F-E, S-D

# SILICONE REMOVER

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

# 15. Regulatory information

Regulatory References According to WHMIS 2015, in compliance with the Hazardous Product Act (HPA, as

amended) and the requirements of the Hazardous Product Regulations (HPR) Hazardous Products Regulations - SOR/2015-17. Transportation of Dangerous Goods Regulations -

SOR/2015-100.

16. Other information

**Training advice** Ensure operatives are trained to minimize exposure. Only trained personnel should use this

material.

**Revision comments** This is first issue.

Revision date 20/03/2018

Revision 1

Hazard statements in full H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H335 May cause respiratory irritation.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be replied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.