

SAFETY DATA SHEETS

This SDS packet was issued with item:

071805357

N/A

**DENTSPLY/International
DENTSPLY/Caulk
Safety Data Sheet**

534891

1. Identification

| | |
|---|--|
| Product Name Self Cure Activator | SDS Code Number 534891 |
| Trade Name & Synonyms Self Cure Activator | Date of Last Revision 02/21/14 |
| Manufacturer: DENTSPLY Caulk | Address 38 West Clarke Avenue Milford DE 19963-1805 http://www.caulk.com http://www.dentsply.com |
| Grades or Minor Variant Identities Not Applicable | Information Telephone Number (302) 422-4511 (8:00 AM – 4:30 PM Eastern Time) |
| Product Use (for Canada) Not Applicable | Emergency Telephone Number (302) 422-4511 (8:00 AM – 4:30 PM Eastern Time) |

2. Hazard(s) Identification



DANGER

HIGHLY FLAMMABLE LIQUID AND VAPOR



WARNING

MAY CAUSES AN ALLERGIC SKIN REACTION

Keep away from heat/sparks/open flames / hot surfaces. No smoking.
Keep container tightly closed.
Use only non-sparking tools.
Take precautionary measures against static discharge.
In case of fire: Use dry chemical, alcohol foam, or carbon dioxide for extinction.
Store in a well ventilated place. Keep Cool.
Avoid breathing vapors.
Contaminated work clothing should not be allowed out of the workplace.
Wash thoroughly after handling.
Wear protective gloves.

IF IN EYES: Rinse cautiously for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: Get medical attention.

IF ON SKIN: Remove immediately all contaminated clothing. Rinse with water.
If skin irritation occurs: Get Medical Advice/attention.
Wash contaminated clothing before reuse.
Avoid breathing vapors.
Use only outdoors or in well ventilated area.

IF INHALED: remove victim to fresh air and keep at rest in a position comfortable for breathing.
Call a POISON Center or physician if you feel unwell.
Dispose of contents/container in accordance with local regulations.

3. Composition/Information on Ingredients

| Hazardous Components | C.A.S. Number | Exposure Limits | % |
|-------------------------------|---------------|-----------------|------|
| Acetone | 67-64-1 | 500 ppm | < 70 |
| Urethane dimethacrylate resin | 105883-40-7 | Not Applicable | < 20 |
| 2-Hydroxyethyl methacrylate | 868-77-9 | Not Applicable | < 10 |
| Initiator | Trade Secret | Not Applicable | < 5 |

4. First Aid Measures

| Routes of Exposure | First Aid Instructions | Immediate Medical Attention | Delayed Effects |
|--------------------|---|-----------------------------|-----------------|
| Eye | Rinse opened eye for several minutes under running water. If symptoms persist consult physician | Not Applicable | Not Applicable |
| Skin | Immediately wash with soap and water and rinse thoroughly | Not Applicable | Not Applicable |

| | | | |
|---|--|----------------|----------------|
| Inhalation | Supply fresh air. This may not be of concern when using clinically relevant quantities. | Not Applicable | Not Applicable |
| Ingestion | This may not be of concern when using clinically relevant quantities. | Not Applicable | Not Applicable |
| Other | Not Applicable | Not Applicable | Not Applicable |
| Note to Physicians (Treating, Testing and Monitoring): Treat symptomatically. | | | |

5. Fire Fighting Measures

| | | | |
|--|---|---|-----------------------|
| Flashpoint Method: 2°C (36°F) Pensky-Marten Closed Cup | Flammable (Explosive) Limits in Air LEL: 2.5 vol. % UEL: 12.8 vol. % | Autoignition Temperature: Not Applicable | Other: Not Applicable |
| Flame Propagation or Burning Rate (for Solids): Not Applicable | Properties Contributing to Fire Intensity: Not Applicable | Flammability Classification: 3 | |
| Extinguishing Media: CO ₂ , extinguishing powder or water spray. Fight larger fires with water sprat or alcohol resistant foam. | | Extinguishing Media to Avoid: Water with full jet. | |
| Protection and Procedures for Firefighters: Firefighters should wear self-contained respiratory protective devices. | | | |
| Unusual Fire and Explosion Hazards: Formation of toxic gases is possible during heating or in case of fire. | | | |


6. Accidental Release Measures

| | | |
|--|--------------------------------------|--|
| Containment Techniques: Wear protective clothing and absorb spill with inert material (e.g. vermiculite, sand, earth), then place material in suitable labeled plastic or metal container. | | |
| Spill/Leak Clean-up Procedures and Equipment: Wear protective clothing and absorb spill with inert material (e.g. vermiculite, sand, earth), then place material in suitable labeled plastic or metal container. Avoid gross skin contact to minimize the possibility of contact dermatitis to susceptible persons. Ensure adequate ventilation. | | |
| Evacuation Procedures: Not Applicable | Special Instructions: Not Applicable | Reporting Requirements: Not Applicable |

7. Handling and Storage

| |
|---|
| Handling Practices and Warnings: Handling of this product should be by trained dental healthcare professionals only. Observe normal care for working with chemicals. |
| Storage Practices and Warnings: Store only in the original package. Keep package tightly sealed. Protect from exposure to direct light. Store away from food and beverages. |

8. Exposure Control / Personal Protection



| Ventilation: None required during normal intended use of this product | | |
|---|---|---|
| Engineering Controls: Not Applicable | | |
| Individual Protection Measures | Personal Protective Equipment for Normal Use | Personal Protective Equipment for Emergencies |
| Eye/Face | Safety Glasses | Not Applicable |
| Skin | The glove material has to be impermeable and resistant to the product. | Not Applicable |
| Inhalation | Not required when using clinically relevant quantities used in Dental office. | Not Applicable |
| Body Protection | Protective work clothing | Not Applicable |

9. Physical and Chemical Characteristics

| | | |
|---|--|--|
| Appearance: Light yellow liquid. | Odor: Acetone like with characteristic sweet acrylic ester odor. | |
| Normal Physical State: Low viscosity liquid | Melting Point: Not Determined | Boiling Point: 56.2°C (133°F) |
| Specific Gravity: ~0.9 g/cm ³ | Solubility in Water: Partially | pH: 6-8 |
| Vapor Pressure (mm Hg): 233 mbar @ 20°C | Vapor Density (AIR=1): Not Applicable | Evaporation Rate (Butyl Acetate=1): Not Applicable |
| Other: Not Applicable | | |

10. Stability and Reactivity Data

| | |
|--|---|
| Incompatibility (Materials to Avoid): Visible light, high temperatures, strong acids, strong oxidizing agents. | |
| Hazardous Products Produced During Decomposition: Methacrylates, acrylates, carbon dioxide, carbon monoxide, peroxides and irritating gases. | |
| Hazardous Polymerization: <input type="checkbox"/> May Occur <input checked="" type="checkbox"/> May Not Occur | Conditions to Avoid: High Temperatures, ignition sources. |
| Stability? <input checked="" type="checkbox"/> Stable <input type="checkbox"/> Unstable | Conditions to Avoid: High Temperatures, ignition sources. |

11. Toxicological Information

| |
|--|
| <p>Toxicity Data, Epidemiology Studies, Carcinogenicity, Neurological Effects, Genetic Effects, Reproductive Effects, or Structure Activity Data:</p> <p>Product is an irritant to the skin and mucous membranes. The unpolymerized product may be an irritant to the skin in susceptible persons. On the eye the product has an irritating effect. Sensitization: Repeated or prolonged contact with the unpolymerized material may cause sensitization for persons allergic to acrylates and methacrylates. This product shows the following dangers according to internally approved calculation methods for composite materials: Irritant.</p> |
|--|

| ACGIH: A4- Not classifiable as a Human Carcinogen. | | | | | |
|--|--|--|-----------------------------------|---|-----------------|
| Emergency Overview: Material is irritating to eyes, respiratory system and skin. Breathing vapors may cause drowsiness and dizziness. | | | | | |
| Routes of Exposure | Signs and Symptoms | Single, Repeated, or Lifetime Exposure | Severity (Mild, Moderate, Severe) | Acute and Chronic Health Effect(s) | Target Organ(s) |
| Eye | Material can cause irritation. | Single | Moderate | Irritation and possible corneal damage | Yes |
| Skin | Material may be an irritant and may be absorbed through the skin. | Single & Repeated | Moderate | Irritation or possible allergic response. Severe allergic response may result in breathing difficulties. | Yes |
| Inhalation | Inhalation of high concentrations may cause central nervous system effects characterized by nausea, headache, dizziness, unconsciousness and coma. This may not be of concern when using clinically relevant quantities. | Repeated | Moderate | Chronic inhalation may cause effects similar to those of acute inhalation. Causes respiratory tract irritation. May cause motor in coordination and speech abnormalities. | Yes |
| Ingestion | May cause irritation of the digestive tract. This may not be of concern when using clinically relevant quantities. | Single & Repeated | Mild | Not Applicable | No |
| Other Central nervous system | Not Applicable | Not Applicable | Not Applicable | Not Applicable | Not Applicable |
| Medical Conditions Aggravated by Exposure Open sores and wounds of the skin. Individuals with known sensitivity to methacrylates, acrylates, or urethane dimethacrylate resin used in Dental restorative products. | | | | | |
| Carcinogenicity NTP?: Not listed IARC monographs?: Not listed OSHA regulated?: No. All components of this product are in compliance with the inventory listing Requirements of the U. S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory. | | | | | |
| Potential Environmental Effects Do not allow to enter sewers/ surface or ground water. | | | | | |
| NFPA Hazard Classification Ratings (Scale 0-4) Health =2, Fire =3, Reactivity=0 Specific Hazard = None | | | | | |

12. Ecological Information

| |
|---|
| Toxicity Data, Environmental Fate, Physical/Chemical Data, or other Data Supporting Environmental Hazard Statements: Water Hazard class1 (Self-assessment): The acetone in the product will volatilizes, leech and biodegrade when released to the soil. Terrestrial Fate: If release on soil, acetone will both volatilize and leach into the ground. Acetone readily biodegrades and there is evidence suggesting that it biodegrades fairly rapidly in soils. Aquatic Fate: If released into water acetone will probable biodegrade. It is readily biodegradable in screening tests, although data from natural water are lacking. It will also be lost due to volatilization. Adsorption to sediment should not be significant. |
|---|

13. Disposal Considerations

| |
|---|
| Regulations: Must not be disposed of together with household garbage. Do not allow product to reach sewage system. Dispose of material as solid waste in a closed container. Dispose of in accordance with Federal, State and Local regulations |
| Properties (Physical/Chemical) Affecting Disposal: Dispose of material as solid waste in a closed container. |
| RCRA P-Series: None Listed, RCRA U-Series CAS#67-64-1: Waste Number U002 (Ignitable Waste) |

14. Transport Information



Flammable Liquid

| | | |
|---|--|--------------------------------|
| Regulated for Shipping: Yes | Proper Shipping Name: Acetone Solution | Packing Group: II |
| Do Changes in Quantities, packaging, or shipment method change product classification? No | Hazard Class: 3 | UN Identification Number: 1090 |

15. Regulatory Information

| |
|---|
| This product has been classified in accordance with the hazard criteria of the Globally Harmonized System of Classification and Labeling of Chemicals and the SDS contains all of the information required by the Canadian Controlled Products Regulations. |
| U.S. Federal Regulations: CERCLA 103 Reportable Quantity: RQ is 5,000 pounds (2268Kg) for CAS# 67-64-1 Acetone. Report spills required under federal, state and local regulations. Many states have more stringent release reporting requirements. |
| RCRA U-Series Hazardous Waste Code for CAS# 67-64-1 Acetone: U002 |
| Section 313 Toxic Chemicals: This product does not contain any chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372). |
| Section 302 Extremely Hazardous Substances (TPQ): None |
| EPA Toxic Substances Control Act (TSCA) Status: All of the components of this product are listed on the TSCA inventory. |
| U.S. State Regulations California Proposition 65: This product does not contain any chemicals, which are on the California Proposition 65 list. |
| Federal Regulations: The product has been classified and marked in accordance with directives on hazardous materials. Hazard Symbol: Flammable Water Hazard class1 (Self-assessment): slightly hazardous for water. SARA Codes: CAS # 67-64-1 Acute, chronic, flammable. |
| International Regulations: Hazard Symbol: Flammable XI F Risk Phrases: R11 Highly Flammable, R36/37/38 Irritating to Eyes, respiratory system and skin. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R67 Vapors may cause drowsiness and dizziness. Safety Phrases: S9 Keep container in well-ventilated place. S16 Keep away from sources of ignition – No Smoking, S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice, S28 After contact with skin wash immediately with plenty of water, S61 Avoid release to the environment. |

Other: Canada WHMIS for the acetone, classification of B2, D2B. Acetone CAS#67-64-1 is on the Canadian Ingredient Disclosure List.

16. Other Information

To the best of our knowledge this product does not contain gluten, wheat grains, flaxseed, natural rubber, or natural latex.

All components are synthetically produced; none are derived from animal products.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific products features and shall not establish a legally valid contractual relationship.

The attached safety data sheet covers the dangers and measures to be taken when large quantities of material are released, for example due to accidents during transport or storage by the dealer. For quantities of material typically used in clinical practice, information necessary for safe use and storage of the product is given in the DFU.