

## SAFETY DATA SHEETS

**This SDS packet was issued with item:**

073239563

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

071691005 072557858 072557890 072557908 072557916 072557924 072557932 072557940 072557965 072557973  
072558021 072558039 073239100 073239118 073239126 073239134 073239142 073239159 073239167 073239217  
073239225 073239233 073239456 073239464 073239472 073239480 073239498 073239506 073239555 073239571  
073239589 073241304 073241338 073241346 073241353 073241361 073241379 073241387 073241411 073241429  
073241437 073242443 073242476 073242682 078634810 078634813 078634822 078634955



# Safety Data Sheet

according to Regulation (EC) No 1907/2006

## Luxatemp Ultra

Print date: 03.07.2014

Product code: 1300\_GHS

Page 2 of 4

### Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).

#### Extinguishing media which must not be used for safety reasons

High power water jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.  
Store only in original container.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

### 8.2. Exposure controls



**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Ultra**

Print date: 03.07.2014

Product code: 1300\_GHS

Page 3 of 4

**Protective and hygiene measures**

When using do not eat or drink.

**Respiratory protection**

The following must be prevented: inhalation.

**Hand protection**

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

**Eye protection**

Tightly sealed safety glasses.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state:	Paste
Colour:	characteristic
Odour:	ester

pH-Value (at 20 °C):	ca. 7	<b>Test method</b>
----------------------	-------	--------------------

**Changes in the physical state**

Boiling point:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm <sup>3</sup>
Water solubility:	10 g/L
Vapour density:	1

**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

heat. Light.  
Decomposition takes place from temperatures above: 200 °C  
Decomposition under formation of: Acrylate.

**10.5. Incompatible materials**

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

**10.6. Hazardous decomposition products**

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NOx).

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

LD50: Rat. 5000 mg/kg

**Irritation and corrosivity**

Frequently or prolonged contact with skin may cause dermal irritation.  
Irritant effect on the eye:

**Additional information on tests**

Contains Methacrylic esters.: May produce an allergic reaction.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Luxatemp Ultra**

Print date: 03.07.2014

Product code: 1300\_GHS

Page 4 of 4

**SECTION 12: Ecological information****12.1. Toxicity**

Acute fish toxicity LC50: &gt;360 mg/l/48h

**12.2. Persistence and degradability**

Preparation not tested.

**Further information**

Do not empty into drains or the aquatic environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

**Waste disposal number of waste from residues/unused products**

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

**SECTION 14: Transport information****Other applicable information**

Not a hazardous material with respect to these transportation regulations.

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information****Full text of R phrases referred to under Sections 2 and 3**

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

**Full text of H statements referred to under Sections 2 and 3**

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*