

# SAFETY DATA SHEETS

**This SDS packet was issued with item:**

077181258

N/A

according to Regulation (EC) No 1907/2006

**Adhesive**

Revision date: 21.04.2015

Print date: 17.05.2016

Page 1 of 6

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Adhesive

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Use of the substance/mixture**

for dental use only

**1.3. Details of the supplier of the safety data sheet**

Company name:	Coltène/Whaledent AG
Street:	Feldwiesenstrasse 20
Place:	CH-9450 Altstätten
Telephone:	+41 (71) 75 75 300
Telefax:	+41 (71) 75 75 301
e-mail:	info.ch@coltene.com
Internet:	www.coltene.com
Responsible Department:	Regulatory Affairs msds@coltene.com

**1.4. Emergency telephone number:** +41 (0) 44 251 51 51 - Tox Info Suisse (24 h)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Flammable liquid: Flam. Liq. 2

Hazardous to the aquatic environment: Aquatic Acute 1

Hazard Statements:

Highly flammable liquid and vapour.

Very toxic to aquatic life.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Signal word:** Danger**Pictograms:****Hazard statements**

H225 Highly flammable liquid and vapour.

H400 Very toxic to aquatic life.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P391 Collect spillage.

**SECTION 3: Composition/information on ingredients**

according to Regulation (EC) No 1907/2006

**Adhesive**

Revision date: 21.04.2015

Print date: 17.05.2016

Page 2 of 6

**3.2. Mixtures****Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
107-46-0	Hexamethyldisiloxane			<80 %
	203-492-7		01-2119496108-31	
	Flam. Liq. 2, Aquatic Acute 1 (M-Factor = 1); H225 H400			
1330-20-7	xylene			< 1 %
	215-535-7	601-022-00-9		
	Flam. Liq. 3, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2; H226 H332 H312 H315			

Full text of H and EUH statements: see section 16.

**SECTION 4: First aid measures****4.1. Description of first aid measures****After inhalation**

Provide fresh air.

**After contact with skin**

After contact with skin, wash immediately with: Water and soap.

**After contact with eyes**

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**After ingestion**

Seek medical advice.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Water spray. Foam. Extinguishing powder. Carbon dioxide (CO<sub>2</sub>). Sand.**Additional information**

Co-ordinate fire-fighting measures to the fire surroundings.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains.

**6.3. Methods and material for containment and cleaning up**

Wipe up with absorbent material (eg. cloth, fleece). Clear contaminated areas thoroughly.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Avoid contact with skin and eyes.

for professional use only Keep out of the reach of children.

Observe instructions for use.

according to Regulation (EC) No 1907/2006

### Adhesive

Revision date: 21.04.2015

Print date: 17.05.2016

Page 3 of 6

#### Advice on protection against fire and explosion

Keep away from sources of ignition. - No smoking.

#### Further information on handling

After use replace the closing cap immediately.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Keep container tightly closed and in a well-ventilated place.

##### Further information on storage conditions

Recommended storage temperature: 15 - 23 °C

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
1330-20-7	Xylene: mixed isomers	50	220		TWA (8 h)	WEL
		100	441		STEL (15 min)	WEL

##### Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
1330-20-7	Xylene, o-, m-, p- or mixed isomers	methyl hippuric acid	650 mmol/mol	urine	Post shift

#### 8.2. Exposure controls

##### Protective and hygiene measures

When using do not eat, drink or smoke.

##### Eye/face protection

Framed glasses.

##### Hand protection

Single-use gloves.

##### Skin protection

Lab apron.

##### Respiratory protection

Provide adequate ventilation.

##### Environmental exposure controls

Do not allow to enter into surface water or drains.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	liquid
Colour:	red
Odour:	characteristic

#### Test method

##### Changes in the physical state

Flash point: - 6 °C DIN 51755

Density: 0.8 g/cm<sup>3</sup>

according to Regulation (EC) No 1907/2006

**Adhesive**

Revision date: 21.04.2015

Print date: 17.05.2016

Page 4 of 6

Water solubility: insoluble

**Solubility in other solvents**

Ethanol, ketone.

**SECTION 10: Stability and reactivity****10.4. Conditions to avoid**

heat.

**10.5. Incompatible materials**

Oxidizing agents.

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

Based on available data, the classification criteria are not met.

CAS No	Chemical name			
	Exposure route	Dose	Species	Source
107-46-0	Hexamethyldisiloxane			
	dermal	LD50 >2000 mg/kg	Rabbit	
	inhalative (4 h) vapour	LC50 106 mg/l	Rat	
1330-20-7	xylene			
	dermal	ATE 1100 mg/kg		
	inhalative vapour	ATE 11 mg/l		
	inhalative aerosol	ATE 1,5 mg/l		

**Irritation and corrosivity**

Hazards identification: Frequently or prolonged contact with skin may cause dermal irritation.

**Sensitising effects**

Based on available data, the classification criteria are not met.

**STOT-single exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**SECTION 12: Ecological information****12.1. Toxicity**

Very toxic to aquatic organisms.

CAS No	Chemical name				
	Aquatic toxicity	Dose	[h]   [d]	Species	Source
107-46-0	Hexamethyldisiloxane				
	Acute fish toxicity	LC50 0.46 mg/l	96 h	Oncorhynchus mykiss	OECD 203
	Acute crustacea toxicity	EC50 >0.37 mg/l	48 h	Daphnia magna	OECD 202

**12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
107-46-0	Hexamethyldisiloxane	>= 3.0

according to Regulation (EC) No 1907/2006

**Adhesive**

Revision date: 21.04.2015

Print date: 17.05.2016

Page 5 of 6

**Further information**

Does not enter into waste water by proper application.  
Do not allow uncontrolled leakage of product into the environment.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

**SECTION 14: Transport information****Land transport (ADR/RID)**

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Classification code:	F1
Limited quantity:	LQ6
Hazard No:	33

**Other applicable information (land transport)**

Special provisions: 274  
E3  
: 1  
D/E  
Special provisions: 274 601 640C  
E2  
: 2  
Special provisions: 640C

**Marine transport (IMDG)**

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Marine pollutant:	•
Limited quantity:	5 L
EmS:	F-E, S-D

**Other applicable information (marine transport)**

Special provisions: 274, 330, 944  
Special provisions: 944

**Air transport (ICAO)**

<b>14.1. UN number:</b>	UN 1133
<b>14.2. UN proper shipping name:</b>	Adhesives
<b>14.3. Transport hazard class(es):</b>	3
<b>14.4. Packing group:</b>	II
Hazard label:	3
Limited quantity Passenger:	1 L

according to Regulation (EC) No 1907/2006

**Adhesive**

Revision date: 21.04.2015

Print date: 17.05.2016

Page 6 of 6

IATA-packing instructions - Passenger:	305
IATA-max. quantity - Passenger:	5 L
IATA-packing instructions - Cargo:	307
IATA-max. quantity - Cargo:	60 L

**Other applicable information (air transport)**

E2  
: Y305  
60 L

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****National regulatory information****SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.

**Further Information**

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*