

SAFETY DATA SHEETS

This SDS packet was issued with item:

074586319

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071365568 074585097 074585121 074586301 074586376

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

074585105 074585113 074585220 074585253 074586384 074586392 074586400 074586418 074586426 074592663



SAFETY DATA SHEET

Issue Date 26-Sept-2014

Revision Date 14-July-2015

Version 3

1. IDENTIFICATION

Product Identifier

Product Name FLEXACRYL HARD LIQUID

Other means of identification

SDS# 037
UN/ID No UN1993
Product Code 0903, 0904, 0906, 0907, 0908, 0923, 0934, 0956

Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of denture relines

Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc.
175 Messner Dr.
Wheeling, IL 60090
USA

Emergency telephone number

Company Phone Number 847-215-6622
Emergency Telephone (INFOTRAC) 352-323-3500 (International)
800-535-5053 (North America)

Authorized European Representative

MediMark® Europe SARL
11, rue Emile Zola – BP 2332
38033 Grenoble Cedex 2
France
Tel: +33 476 86 43 22
Fax: +33 476 17 19 82
Email: info@medimark-europe.com

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.



Appearance Colorless to slightly yellow **Physical state** Liquid **Odor** Acrid

Precautionary Statements – Prevention

- P271 Use only outdoors or in a well-ventilated area.
- P264 Wash face, hands and any exposed skin thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P261 Avoid breathing dust.
- P210 Keep away from heat/sparks/open flames/hot surface. – No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.

Precautionary Statements – Response

- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P312 Call a POISON CENTER or doctor/physician if you feel unwell.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P362 Take off contaminated clothing and wash it before reuse.
- P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P370+P378 In case of fire: Use CO₂, dry chemical or foam for extinction.

- Precautionary Statements – Storage** P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements – Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) May be harmful if swallowed.

Other Information Harmful to aquatic life.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
N-Butyl Methacrylate	97-88-1	<94	*
Trimethylolpropane Trimethacrylate	3290-92-4	<10	*
N, N-Dimethyl-p-Toluidine	99-97-8	<2	*

*Specific chemical weight has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician immediately.
Ingestion	Do NOT induce vomiting. Wash out mouth with water and give 200-300 mL (half pint) of water to drink. Get medical attention. Never give anything by mouth to an unconscious person.
Skin Contact	Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms	May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. Irritating to mouth, throat and stomach if ingested.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable: Chemical foam, carbon dioxide (CO₂), dry chemical

Unsuitable: Not determined.

Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Fine mist or sprays may be flammable at temperatures below the flash point. Sealed containers may rupture explosively if hot. Cool containers exposed to flames with water until well after the fire is out.

Hazardous Combustion Products:	Carbon oxides
Sensitivity to Static Discharge:	Yes

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Refer to protective measures listed in Sections 7 and 8. Review Fire Fighting Measures and Handling (Personnel) sections before proceeding with clean-up. Ventilate affected area. Wear self-contained breathing apparatus (SCBA). Evacuate personnel to safe area.
Environmental precautions	Do not allow into any sewer, on the ground or any body of water.
Methods and material for containment and clean-up	
Method for containment	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Dike far ahead of liquid spill for later disposal.

Method for clean-up Take up with sand, earth or other non-combustible absorbent material. Clean-up material as a RCRA Hazardous Waste. Use non-sparking hand tools and explosion-proof electrical equipment.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe dust, fume, gas, mist, vapor or spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Keep containers closed when not in use. Ground container and transfer equipment to eliminate static electric sparks. Keep away from heat, spark, open flame and hot surfaces. NO SMOKING. Use only in well-ventilated areas. Use personal protection recommended in Section 8. Contaminated work clothing should not be allowed out of the workplace. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharge.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Store in accordance with National Fire Protection Association recommendations. Maintain air space inside storage containers. Inhibitor requires air (oxygen) contact to function.

Incompatible materials Oxidizers, reducing agent
Material has strong solvent properties and can soften paint and rubber.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines The following information is given as general guidance.

Appropriate engineering controls

Engineering controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye / face protection Wear approved safety goggles.

Skin and body protection Wear impervious protective clothing, including: booths, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Nitrile rubber is better than PVC.

Respiratory protection Use NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure is not known or any other circumstances where air purifying respirators may not provide adequate protections.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid	Odor	Acrid
Appearance	Liquid	Odor threshold	Not determined
Color	Clear to slightly yellow		

<u>Property</u>	<u>Values</u>	<u>Remarks / Method</u>
pH	Not determined	
Melting point / freezing point	Not determined	
Boiling point / boiling range	163-164°C / 325-327° F	
Flash point	51°C / 124°F	
Evaporation rate	Not determined	
Flammability (solid, gas)	n/a (liquid)	
Flammability limits in air		
Upper flammability limit	8.0%	
Lower flammability limit	2.0%	
Vapor pressure	28mm Hg	@ 20°C
Vapor density	4.9	@15.5°C (Air = 1)
Specific gravity	0.910	
Water solubility	0.36%	
Solubility in other solvents	Not determined	
Partition coefficient	Not determined	
Autoignition temperature	296°C / 564.8°F	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic viscosity	Not determined	
Explosive properties	Not determined	
Oxidizing properties	Not determined	

Other information

10. STABILITY AND REACTIVITY

Reactivity Not reactive under normal conditions

Chemical stability Stable under recommended storage conditions

Possibility of hazardous reactions None under normal processing

Hazardous polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent or flame arresters, resulting in blockage of vents. Conditions to avoid for hazardous polymerization: excessive heat, storage in absence of inhibitor, inadvertent addition of catalyst.

Conditions to avoid Heat
All possible sources of ignition
Contamination

Incompatible materials Oxidizers
Reducing agent
Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products Carbon oxides

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposures

Product information

Inhalation	Harmful if inhaled.
Eye contact	Causes severe eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be harmful if swallowed.

Component information

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
N-Butyl Methacrylate 97-88-1	16 g/kg (rat)	10181 mg/kg (rabbit)	4910 ppm (rat) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	=5660 /kg (rat)	= 16 mL/kg (rabbit)	-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	-	1400 mg/m ³ (rat) 4 h

Information on physical, chemical and toxicological effects

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. Irritating to mouth, throat and stomach if ingested.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization May cause allergic skin reaction.

Carcinogenicity Not classifiable as a human carcinogen

STOT – single exposure May cause respiratory irritation. May cause drowsiness or dizziness.

STOT – repeated exposure May cause damage to organs through prolonged or repeated exposure.

Numerical measures of toxicity – Product Not determined

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	3864	mg/kg
ATEmix (dermal)	10834	mg/kg
ATEmix (inhalation-dust/mist)	5225	mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
N-Butyl Methacrylate 97-88-1	57: 96 h Pseudokirchneriella subcapitata mg/L EC50	11: 96 h Pimephales promelas mg/L LC50 flow-through;	EC50 = 37 mg/L 5 min EC50 = 49 mg/L 15 min EC50 = 55 mg/L 30 min EC50 > 253.6 mg/L 18 h	32: 48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	144: 96 h Oncorhynchus mykiss LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-	-
N,N-Dimethyl-p- Toluidine 99-97-8	-	42-50.5: 96 h Pimephales promelas mg/L LC50 flow-through	-	-

Persistence and degradability Material is readily biodegradable. 88% in 28 days

Bioaccumulation This product has moderate potential for bioaccumulation.

Mobility The product is predicted to have moderate mobility in soil.

Chemical Name	Partition coefficient
N-Butyl Methacrylate	2.26

Other adverse effects This product is substantially removed in biological treatment processes BOD 28 day/DOC=32.8%

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Follow all local and national government regulations in disposing material or contaminated packaging.

For U.S. - Dispose of in accordance with federal, state and local regulations. Do not flush to surface or sanitary sewer system Dispose of by incineration or in accordance with local regulations. Do not incinerate closed containers.

Contaminated Packaging Dispose of all empty containers in accordance with local and national government regulations.

14. TRANSPORTATION INFORMATION

Note Based on package size, product may be eligible for limited quantity exception

DOT

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	III

IATA

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	III

IMDG

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	III

15. REGULATORY INFORMATION

International Inventories

DSL Listed Canadian Domestic Substances List
EINECS Listed European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging
Medical Devices Directive 93/42/EEC - Class I Medical Devices

US Federal Regulations

SARA 311 / 312 Hazard Categories

US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butyl methacrylate 97-88-1	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Issue Date 26-Sept-2014
Revision Date 14-July-2015
Revision Note Section 2 – revise classification categories, revise some Hazard Statements and Precautionary Statements, remove pictogram

Information to be updated in due course Hazard pictograms listed in this SDS to be added to product label.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet