# **SAFETY DATA SHEETS**

# This SDS packet was issued with item: 074586426

# The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071365550 071365568 071365576 071365618 074585097 074585121 074586301 074586319 074586327 074586376 71365618

# The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071386531 071386549 071386556 071390400 074585006 074585014 074585022 074585105 074585113 074585220 074585253 074585287 074585311 074585345 074585378 074585402 074585899 074585915 074585923 074585931 074585949 074586384 074586392 074586400 074586418 074586434 074586467 074586475 074592663

LANG

# SAFETY DATA SHEET

Issue Date

26-Sept-2014

**Revision Date** 

14-July-2015

Version 3

# 1. IDENTIFICATION

<u>Product Identifier</u> Product Name	FLEXACR	YL SOFT LIQUID	
Other means of identification SDS# UN/ID No Product Code	038 UN1993 1103, 1104, 1106, 1107, 1108, 1109, 1123, 1134, 1156		
Recommended use of the che	mical and	restrictions on use	
Recommended Use		n of denture relines	
<u>Details of the supplier of the s</u> Supplier Address	-	al Mfg. Co., Inc.	
	Wheeling,	IL 60090	
	USA		
Emergency telephone number	<u>:</u>	847-215-6622	
Emergency Telephone (INFOT	RAC)	352-323-3500 (International)	
Emergency relephone (in Or	11.10)	800-535-5053 (North America)	
Authorized European Represe	entative	MediMark® Europe SARL 11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2 France Tel: +33 476 86 43 22 Fax: +33 476 17 19 82 Email: info@medimark-europe.com	

# 2. HAZARDS IDENTIFICATION

#### **Classification**

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.



Colorless to slight yellow liquid

Physical state Liquid

Odor Acrid

#### **Precautionary Statements – Prevention**

P271 Use only outdoors or in a well-ventilated area.

P264 Wash face, hands and any exposed skin thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P272 Contaminated work clothing should not be allowed out of the workplace.

P261 Avoid breathing dust.

P210 Keep away from heat/sparks/open flames/hot surface. - No smoking.

- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P273 Avoid release to the environment.

#### **Precautionary Statements – Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P362 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use CO<sub>2</sub>, dry chemical or foam for extinction.

Precautionary Statements – Storage	P403+P233	Store in a well-ventilated place. Keep container tightly closed	
	P403+P235	Store in a well-ventilated place. Keep cool.	

Precautionary Statements – Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) May be harmful if swallowed

Other Information

Harmful to aquatic life.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Citric Plasticizer	Proprietary	<50	*
N-Butyl Methacrylate	97-88-1	<50	*
Trimethylolpropane Trimethacrylate	3290-92-4	<5	*
N. N-Dimethyl-p-Toluidine	99-97-8	<5	*

\*Specific chemical weight has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures

General advice	If exposed or concerned, get medical advice or attention.	
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.	
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician immediately.	
Ingestion	Do NOT induce vomiting. Wash out mouth with water and give 200-300 mL (half pint) of water to drink. Get medical attention. Never give anything by mouth to an unconscious person.	
Skin Contact	Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.	
Most important symptoms and effects, both acute and delayed		
Symptoms	May cause skin and eye irritation. Irritating to mouth, throat, and stomach if ingested. May cause irritation to the mucous membranes and upper respiratory tract	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	

#### 5. FIRE-FIGHTING MEASURES

#### **Extinguishing Media**

**Suitable:** Chemical foam, carbon dioxide (CO<sub>2</sub>), dry chemical **Unsuitable:** Not determined

#### Specific hazards arising from the chemical

Flammable. Vapors may travel to source of ignition and flash back. Fine mist or sprays may be flammable at temperatures below the flash point. May polymerize on heating. Sealed containers may rupture explosively if hot. Cool containers exposed to flames with water until well after the fire is out.

Hazardous Combustion Products:	Carbon oxides
Sensitivity to Static Discharge:	Yes

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

# 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

 
 Personal precautions
 Review Section 5 Fire-Fighting Measures and Section 7 Handling and Storage before proceeding with clean up. Refer to protective measures listed in sections 7 and 8. Evacuate personnel to safe areas. Ventilate affected area. Wear self-contained breathing apparatus (SCBA).

Environmental precautions Prevent entry into waterways, sewers, basements or confined areas.

#### Methods and material for containment and clean-up

Method for containment	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Dike the spilled material, where this is possible.
Method for clean-up	Take up with sand or other non-combustible absorbent material and place into containers for later disposal. Clean up material as RCRA Hazardous Waste. Use non-sparking hand tools and explosion-proof electrical equipment.

# 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Do not breathe dust, fume, gas, mist, vapors, or spray. Avoid contact with skin, eyes, or clothing. Wash thoroughly after handling. Keep containers closed when not in use. Ground container and transfer equipment to eliminate static electric sparks. Keep away from heat, sparks, open flame, and hot surfaces. NO SMOKING. Use non-sparking hand tools and explosion proof electrical equipment. Take precautionary measures against static discharges. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protection recommended in Section 8. Contaminated clothing should not be allowed out of the workplace.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Store in accordance with National Fire Protection Association recommendations. Maintain air space inside storage containers. Inhibitor requires air (oxygen) contact to function.
Incompatible materials	Oxidizers and reducing agents Material has strong solvent properties and can soften paint and rubber.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

```
Exposure guidelines
```

Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required. The following information is given as general guidance.

vapor respirator with a dust/mite pre-filter. Use positive pressure air supplied respirator if there is

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Citric Plasticizer	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	IDLH: 4000 mg/m <sup>3</sup>
	C C	TWA: 5 mg/m <sup>3</sup> (vacated)	TWA: 5 mg/m <sup>3</sup>

#### Appropriate engineering controls

 Engineering controls
 Apply technical measures to comply with the occupational exposure limits.

 Individual protection measures, such as personal protective equipment
 Individual protection measures, such as personal protective equipment

Eye / face protection	Wear approved safety goggles. Wear coverall chemical splash goggles and face shield when possibility exists for eye and face contact due to splashing or spraying material.
Skin and body protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls as appropriate to prevent skin contact. Nitrile rubber is better than PVC.
Respiratory protection	None needed under normal use conditions. If the TLV is exceeded, use NIOSH approved organic

any potential for an uncontrolled release, exposure is not known, or any other circumstances where air purifying respirators may not provide adequate protections.

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state Appearance Color	Liquid Colorless to slightly yellow liquid Clear to slightly yellow	Odor Odor threshold	Acrid Not determined
<u>Property</u> pH Melting point / freezing point Boiling point / boiling range	<u>Values</u> Not determined -25°C / -13°F 163-164°C / 325- 327°F	<u>Remarks / Method</u>	
Flash point	59°C / 139°F		
Evaporation rate	Not determined		
Flammability (solid, gas)	n/a (liquid)		
Flammability limits in air			
Upper flammability limit	Not established		
Lower flammability limit	Not established		
Vapor pressure	2 mm Hg	@ 20°C	
Vapor density	4.9	@15.5°C (Air = 1)	
Specific gravity	0.978		
Water solubility	0.36 %		
Solubility in other solvents	Not determined		
Partition coefficient	3.03		
Autoignition temperature	Not established		
Decomposition temperature	Not determined		
Kinematic viscosity	Not determined		
Dynamic viscosity	Not determined		
Explosive properties	Not determined		
Oxidizing properties	Not determined		

Other information

# **10. STABILITY AND REACTIVITY**

Reactivity Not reactive under normal conditions

**Chemical stability** Stable under recommended storage conditions.

#### Possibility of hazardous reactions

None under normal processing

Hazardous polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent or flame arresters, resulting in blockage of vents. Conditions to avoid for hazard polymerization: excessive heat, storage in absence of inhibitor, inadvertent addition of catalyst

#### Conditions to avoid

Avoid all possible sources of ignition, contamination.

#### Incompatible materials

Oxidizers. Reducing agent. Material has strong solvent properties and can soften paint and rubber.

Hazardous decomposition products If h

If heated to decomposition, CO and CO<sub>2</sub> may be produced.

# **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposures

#### Product information

Inhalation	Harmful if inhaled.
Eye contact	Causes severe eye irritation.
Skin contact	Causes skin irritation. May be harmful in contact with skin.
Ingestion	May be harmful if swallowed.

#### **Component information**

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
Citric plasticizer	6300 mg/kg (rat)	>2000 mg/kg (rabbit)	>15.68 mg/L (rat) 4 h
N-Butyl Methacrylate 97-88-1	16 µg/kg (rat)	10181 mg/kg (rabbit)	4910 ppm (rat) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	=5660 /kg (rat)	= 16 mL/kg (rabbit)	-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	-	1400 mg/m³ (rat) 4 h

#### Information on physical, chemical and toxicological effects

**Symptoms** May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. Irritating to mouth, throat, and stomach if ingested.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization	May cause allergic skin reaction.		
Carcinogenicity	This product does not contain any carcinogens or potential carcinogens as listed by OSHA, IARC or NTP.		
Reproductive toxicity	May damage fertility or the unborn child.		
STOT – single exposure	May cause respiratory irritation. May cause drowsiness or dizziness		
STOT – repeated exposure	May cause damage to organs through prolonged or repeated exposure.		
Numerical measures of toxici	ty – Product Not determined		

#### The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	4697	mg/kg
ATEmix (dermal)	2098	mg/kg
ATEmix (inhalation-dust/mist)	4998	mg/l

#### **Ecotoxicity**

Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Citric Plasticizer	0.4: 96 h Pseudokirchneriella subcapitata mg/L EC50 static 1.2: 72 h Pseudokirchneriella subcapitata mg/L EC50	0.31 – 5.45: 96 h Pimephales promelas mg/L LC50 static 0.42 – 1.28: 96 h Lepomis macrochirus mg/L LC50 static 0.71 – 1.2: 96 h Pimephales promelas mg/L LC50 flow-through 1.24 – 5.3: 96 h Oncorhynchus mykiss mg/L LC50 static 1.38 – 1.74: 96 h Lepomis macrochirus mg/L LC50 static 1.24: 96 h Oncorhynchus mykiss mg/L LC50 flow-through	EC50 = 10.9 mg/L 30 min EC50 = 10.9 mg/L 5 min EC50 =11.1 mg/L 15 min EC50 = 2.2 mg/L 24 h	2.99 48 h Daphnia magna mg/L EC50 Static 3.4: 48 h Daphnia magna mg/L EC50
N-Butyl Methacrylate 97-88-1	57: 96 h Pseudokirchneriella subcapitata mg/L EC50	11:96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 37 mg/L 5 min EC50 = 49 mg/L 15 min EC50 = 55 mg/L 5 min EC50 > 253.6 mg/L 18 h	32:48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	144: 96 h Oncorhynchus mykiss LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-	-
N,N-Dimethyl-p- Toluidine 99-97-8	-	42-50.5: 96 h Pimephales promelas mg/L LC50 flow-through	-	-

Persistence and degradability Material is readily biodegradable. 88% in 28 days

**Bioaccumulation** 

This product has moderate potential for bioaccumulation.

This product is predicted to have moderate mobility in soil. <u>Mobility</u>

Chemical Name	Partition coefficient
Citric Plasticizer	5.38
N-Butyl Methacrylate	2.26

Other adverse effects

This product is substantially removed in biological treatment process BOD 28 day / DOC = 32.8%.

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Disposal of wastes	Follow all local and national government regulations in disposing material or contaminated packaging.	
	For U.S Dispose of in accordance with federal, state and local regulations. Do not flush to surface or sanitary sewer system Dispose of by incineration or in accordance with local regulations. Do not incinerate closed containers.	
Contaminated Packaging	Dispose of all empty containers in accordance with local and national government regulations.	

Chemical Name	RCRA	RCRA – Basis for Listing	RCRA – D Series Wastes	RCRA – U Series Wastes
Citric Plasticizer	U069	Included in waste stream;	-	U069
		F039		

# **14. TRANSPORTATION INFORMATION**

DOT

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	

#### <u>IATA</u>

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	

#### IMDG

UN / ID No	UN1993
Proper shipping name	Flammable liquid, n.o.s. (n-Butyl Methacrylate, stabilized / Plasticizer solution)
Hazard Class	3
Packing Group	

# 15. REGULATORY INFORMATION

#### International Inventories

DSL	Listed	Canadian Domestic Substances List
EINECS	Listed	European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging Medical Devices Directive 93/42/EEC - Class I Medical Devices

#### **US Federal Regulations**

Chemical Name	CAS	Weight %	SARA 313 Threshold Values %
Citric Plasticizer	Proprietary	<50	1.0

#### SARA 311 / 312 Hazard Categories

Chemical Name	CWA – Reportable	CWA – Toxic	CWA – Priority	CWA – Hazardous
	Quantities	Pollutants	Pollutants	Substances
Citric Plasticizer	10 lb.	Х	Х	Х

Chemical Name	Hazardous Substances	CERCLA /	Reportable Quantity (RQ)
	RQs	SARA RQ	Final
Citric Plasticizer	10 lb.	-	10 lb. / 4.54 kg

#### US State Regulations

Chemical Name	California Proposition 65
Citric Plasticizer	Developmental Female Reproductive Male Reproductive

#### US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Citric Plasticizer	Х	Х	Х
N-Butyl Methacrylate	Х	Х	Х

# **16. OTHER INFORMATION**

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Issue Date Revision Date Revision Note 26-Sept-2014 14-July-2015

Section 2 – Revise classification categories, revise some Hazard Statements and Precautionary Statements, remove pictogram

Information to be updated in due course

Hazard pictograms listed in this SDS to be added to product label

#### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet



# SAFETY DATA SHEET

Version 1

**Revision Date Issue Date** 26-Sept-2014 **IDENTIFICATION** 1. **Product Identifier Product Name** FLEXACRYL POWDER Other means of identification SDS# 001 Product Code 0920, 0923, 0930, 0934, 0950, 0956, 0970, 0980, 1123, 1134, 1156 Recommended use of the chemical and restrictions on use **Recommended Use** Fabrication of denture relines Details of the supplier of the safety data sheet Supplier Address Lang Dental Mfg. Co., Inc. 175 Messner Dr. Wheeling, IL 60090 USA Emergency telephone number **Company Phone Number** 847-215-6622 **Emergency Telephone (INFOTRAC)** 352-323-3500 (International) 800-535-5053 (North America)

# 2. HAZARDS IDENTIFICATION

#### Classification

Skin sensitization

Category 1

Signal word

Warning

Hazard statements May cause an allergic skin reaction



Appearance

Fine, white or pink

Odor Faint odor in bulk

Precautionary Statements – Prevention

Avoid breathing dust, fumes, gas, mist, vapors or spray.

Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves.

#### **Precautionary Statements – Response**

If on skin, wash with plenty of soap and water. If skin irritation or rash occurs, get medical advice / attention. Wash contaminated clothing before reuse.

#### Precautionary Statements – Disposal

Dispose of contents / container to an approved waste disposal plant.

#### Hazards not otherwise classified (HNOC)

Not applicable

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
Polymer	9003-42-3	< 99	*
Benzoyl peroxide	94-36-0	<2	*

\*Specific chemical weight has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### First aid measures

Inhalation	Remove to fresh air. Keep at rest in a position comfortable for breathing, Get medical attention if discomfort persists.	
Eye contact	Rinse immediately with plenty of water, including under the eyelids, for at least 15 minutes. If irritation persists, get medical advice / attention.	
Ingestion	Do NOT induce vomiting. Drink plenty of water or milk immediately. If vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately and provide an estimate of when and how much material was ingested.	
Skin Contact	Wash with soap and water. If irritation persists, call a physician. Take off contaminated clothing and wash before reuse.	
Most important symptoms	and effects, both acute and delayed	
Symptoms	Eyes, skin and respiratory tract may be irritated by gross overexposure to particulates. Eyes may be red, itchy, irritated or watering from overexposure. Ingestion of large amounts may be irritating if product is swallowed. May cause nausea, headache, vomiting or diarrhea.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Treat symptomatically.	
5. FIRE-FIGHTING MEASURES		

#### **Extinguishing Media**

Suitable: Unsuitable: Water, carbon dioxide (CO<sub>2</sub>), dry chemical Avoid extinguishing methods which may generate dust clouds. Water stream can disperse dust in air producing a fire hazard and possible explosion hazard if exposed to ignition source.

#### Specific hazards arising from the chemical

Flexacryl Powder 001

For bulk size: Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust.

#### Protective equipment and precautions for firefighters

Self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

	6. ACCIDENTAL RELEASE MEASURES		
Personal proceptions, protective	equipment and emergency procedures		
Personal precautions	Use personal protective equipment as required. Remove any contaminated clothing and wash		
reisonal precautions	thoroughly before reuse.		
Environmental precautions	See Section 12 for additional ecological information.		
Methods and material for contain	ment and clean-up		
Method for containment	Prevent further leakage or spillage if safe to do so.		
Method for clean-up	Sweep up to avoid slipping hazard. Keep airborne particulates at a minimum when cleaning up		
	spills. Clean up in accordance with all applicable regulations. Wash all affected areas with plenty of		
	warm water and soap.		
	7. HANDLING AND STORAGE		
Precautions for safe handling			
Advice on safe handling	Use only in well-ventilated areas. Avoid contact with skin, eyes or clothing. Avoid breathing dust or		
5	fume. Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly		
	after handling. Do not eat, drink or smoke when using this product.		
Conditions for safe storage, inclu	iding any incompatibilities		
Storage Conditions	Keep containers tightly closed to prevent water absorption and contamination. Store in a dry, cool		
	and well-ventilated place away from direct sunlight or other sources of light or intense heat.		
	Preferable storage temperature not to exceed 35°C.		
Packaging materials	Keep in original container.		
Incompatible materials	Strong oxidizing agents		

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### Exposure guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Benzoyl peroxide	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	IDLH: 1500 mg/m <sup>3</sup>
94-36-0		TWA: 5 mg/m <sup>3</sup> (vacated)	TWA: 5 mg/m <sup>3</sup>

Appropriate engineering controls

Apply technical measures to comply with the occupational exposure limits. When working with large quantities of product, provide adequate ventilation (e.g. local exhaust ventilation, fans). Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes. Use good local exhaust at processing equipment, including buffers, sanders, grinders and polishers.

#### Individual protection measures, such as personal protective equipment

Eye / face protection	Depending on the use of this product, safety glasses or goggles may be worn. If necessary, refer to US OSHA 29 CFR SS1910.133, Canadian standards or the European Standard EN 166. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.
Skin and body protection	If anticipated that prolonged and repeated skin contact will occur during use of this product, wear gloves for routine industrial use. If necessary, refer to US OSHA 29 CFR SS1910.138 or the appropriate standards of Canada or the EC member states.
Respiratory protection	No special respiratory protection is required under typical circumstances of use or handling. If necessary, use only respiratory protection authorized per US OSHA requirement in 29 CFR SS 1910.134, or applicable US state regulations, or the appropriate standards of Canada, its provinces, EC member states or Australia. VENTILATION: Local exhaust at processing equipment.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	Powder Fine White or pink	Odor Odor threshold	Faint odor in bulk Not determined
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas) Flammability limits in air Upper flammability limit Lower flammability limit Vapor pressure Vapor density Specific gravity Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Explosive properties Oxidizing properties	Values Not determined Not applicable 304°C / 580°F Not applicable Non-flammable Not applicable Not applicable Not applicable Not applicable Not applicable Not applicable Not determined Insoluble in water Not determined Not determined	<u>Remarks / Method</u>	

# **10. STABILITY AND REACTIVITY**

<u>Reactivity</u>	Not reactive under normal conditions
Chemical stability	Stable under recommended storage conditions
Possibility of hazardous reactions	None under normal processing
Hazardous polymerization	Does not occur.
Conditions to avoid	Heating above 240°C / 464°F

#### Incompatible materials

Strong oxidizing agents

Hazardous decomposition products

Methacrylate monomer, oxides of carbon when burned

### **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposures

Product information	This product has not been tested on animals to obtain toxicology data.
Inhalation	Persons with impaired lung function or asthma-like conditions may experience additional breathing difficulties.
Eye contact	Avoid contact with eyes.
Skin contact	May be irritating to skin in some sensitive individuals, especially after prolonged or repeated contact.
Ingestion	Large amounts may cause nausea, headache, vomiting or diarrhea.

**Component information** 

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
Benzoyl peroxide 94-36-0	6400 mg/kg (rat)	-	-

#### Information on physical, chemical and toxicological effects

Symptoms See Section 4.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Not classifiable as a human carcinogen (IARC group 3)

Not determined

The following values are calculated based on chapter 3.1 of the GHS document. ATEmix (oral) 6250 mg/kg

# **12. ECOLOGICAL INFORMATION**

**Ecotoxicity** There is no specific data available for this product; however, very large releases may be harmful or fatal to overexposed aquatic life.

Persistence and degradability	Not determined

Bioaccumulation Not determined

Mobility Not determined

Other adverse effects Not determined

### **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

**Disposal of wastes** 

Disposal should be in accordance with applicable regional, national and local laws and regulations.

	Chemical Name	California Hazardous Waste Status
Ī	Benzoyl peroxide	6400 mg/kg (rat)
	94-36-0	

Contaminated Packaging

For bulk only: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards due to residual material associated with empty containers. Dispose of all empty containers properly in accordance with federal, state and local regulations.

Chemical Name	California Hazardous Waste Status
Benzoyl peroxide	Toxic, Ignitable, Reactive
94-36-0	

# 14. TRANSPORTATION INFORMATION

DOT Not regulated

IATA Not regulated

IMDG

Not regulated

#### International Inventories

TSCA For use in FDA regulated products only DSL Listed United States Toxic Substances Control Act, Section 8(b) Inventory Canadian Domestic Substances

#### US Federal Regulations

Chemical Name	CAS	Weight %	SARA 313 - Threshold Values %
Benzoyl peroxide	94-36-0	1	1.0

**15. REGULATORY INFORMATION** 

# US State Regulations

#### US State Right-to-know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Benzoyl peroxide	Х	Х	Х
94-36-0			

# **16. OTHER INFORMATION**

HMIS	Health Hazards	Flammability	Physical Hazards
	1	1	0

Issue Date Revision Date Revision Note 26-Sept-2014

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet

Flexacryl Powder 001

LANG

# SAFETY DATA SHEET

Issue Date 26-Sept-2014

Revision Date

Version 3

### 1. IDENTIFICATION

14-July-2015

Product Identifier	
Product Name	FLEXACRYL HARD LIQUID

Other means of identification

 SDS#
 037

 UN/ID No
 UN1993

 Product Code
 0903, 0904, 0906, 0907, 0908, 0923, 0934, 0956

#### Recommended use of the chemical and restrictions on use

Recommended Use Fabrication of denture relines

#### Details of the supplier of the safety data sheet

Supplier Address Lang Dental Mfg. Co., Inc. 175 Messner Dr. Wheeling, IL 60090 USA

Emergency telephone number	
Company Phone Number	847-215-6622
Emergency Telephone (INFOTRAC)	352-323-3500 (International)
	800-535-5053 (North America)

Authorized European Representative MediMark® Europe SARL 11, rue Emile Zola – BP 2332 38033 Grenoble Cedex 2 France Tel: +33 476 86 43 22 Fax: +33 476 17 19 82

# 2. HAZARDS IDENTIFICATION

Email: info@medimark-europe.com

#### **Classification**

Flammable liquids	Category 3
Skin corrosion/irritation	Category 2
Skin sensitization	Category 1
Serious eye damage / eye irritation	Category 2A
STOT Single exposure	Category 3
Hazardous to the aquatic environment- Acute hazard	Category 2

Signal word Warning

Hazard statements H226 Flammable liquid and vapor.

- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H335 May cause respiratory irritation.



Colorless to slightly yellow

Physical state Liquid

Odor Acrid

#### **Precautionary Statements – Prevention**

- P271 Use only outdoors or in a well-ventilated area.
- P264 Wash face, hands and any exposed skin thoroughly after handling.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P261 Avoid breathing dust.
- P210 Keep away from heat/sparks/open flames/hot surface. No smoking.
- P233 Keep container tightly closed.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P273 Avoid release to the environment.

#### **Precautionary Statements – Response**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P312 Call a POISON CENTER or doctor/physician if you feel unwell. P322 P322 If a POISON CENTER or doctor/physician if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P303+P361+P353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.

P362 Take off contaminated clothing and wash it before reuse.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378 In case of fire: Use CO<sub>2</sub>, dry chemical or foam for extinction.

 Precautionary Statements – Storage
 P403+P233
 Store in a well-ventilated place. Keep container tightly closed.

 P403+P235
 Store in a well-ventilated place. Keep cool.

Precautionary Statements – Disposal P501 Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified (HNOC) May be harmful if swallowed.

Other Information Harmful to aquatic life.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight - %	Trade Secret
N-Butyl Methacrylate	97-88-1	<94	*
Trimethylolpropane	3290-92-4	<10	*
Trimethacrylate			
N, N-Dimethyl-p-Toluidine	99-97-8	<2	*

\*Specific chemical weight has been withheld as a trade secret.

Flexacryl Hard Liquid 037 v.3

# 4. FIRST AID MEASURES

#### First aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Keep patient warm and at rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.		
Eye contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a physician immediately.		
Ingestion	Do NOT induce vomiting. Wash out mouth with water and give 200-300 mL (half pint) of water to drink. Get medical attention. Never give anything by mouth to an unconscious person.		
Skin Contact	Wash off immediately with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation or rash occurs, get medical advice/attention.		
Most important symptoms and effects, both acute and delayed			
Symptoms	May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. Irritating to mouth, throat and stomach if ingested.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

#### Extinguishing Media

**Suitable:** Chemical foam, carbon dioxide (CO<sub>2</sub>), dry chemical **Unsuitable:** Not determined.

#### Specific hazards arising from the chemical

Vapors may travel to source of ignition and flash back. Fine mist or sprays may be flammable at temperatures below the flash point. Sealed containers may rupture explosively if hot. Cool containers exposed to flames with water until well after the fire is out.

Hazardous Combustion Products:	Carbon oxides
Sensitivity to Static Discharge:	Yes

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Fight fire from a safe location.

# 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures			
Personal precautions	Refer to protective measures listed in Sections 7 and 8. Review Fire Fighting Measure Handling (Personnel) sections before proceeding with clean-up. Ventilate affected area contained breathing apparatus (SCBA). Evacuate personnel to safe area.		
Environmental precautions	Do not allow into any sewer, on the ground or any body of water.		
Methods and material for containment	and clean-up		
Method for containment	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate are Dike far ahead of liquid spill for later disposal.	a).	
Flexacryl Hard Liquid 037 v.3		Page 3 of 8	

Take up with sand, earth or other non-combustible absorbent material. Clean-up material as a RCRA Hazardous Waste. Use non-sparking hand tools and explosion-proof electrical equipment.

# 7. HANDLING AND STORAGE

#### Precautions for safe handling

Advice on safe handling	Do not breathe dust, fume, gas, mist, vapor or spray. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Keep containers closed when not in use. Ground container and transfer equipment to eliminate static electric sparks. Keep away from heat, spark, open flame and hot surfaces. NO SMOKING. Use only in well-ventilated areas. Use personal protection recommended in Section 8. Contaminated work clothing should not be allowed out of the workplace. Use non-sparking hand tools and explosion-proof electrical equipment. Take precautionary measures against static discharge.
Conditions for safe storage, including a	any incompatibilities
Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Protect from direct sunlight. Store in accordance with National Fire Protection Association recommendations. Maintain air space inside storage containers. Inhibitor requires air (oxygen) contact to function.

Incompatible materials	Oxidizers, reducing agent
	Material has strong solvent properties and can soften paint and rubber.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines	The following information is given as general guidance.	
Appropriate engineering controls		
Engineering controls	Apply technical measures to comply with the occupational exposure limits.	
Individual protection measures, such a	s personal protective equipment	
Eye / face protection	Wear approved safety goggles.	
Skin and body protection	Wear impervious protective clothing, including: booths, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Nitrile rubber is better than PVC.	
Respiratory protection	Use NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure is not known or any other circumstances where air purifying respirators may not provide adequate protections.	
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.	

# 9. PHYSICAL AND CHEMICAL PROPERTIES

threshold

#### Information on basic physical and chemical properties

Physical state	Liquid	Odor
Appearance	Liquid	Odor
Color	Clear to slightly yellow	

Flexacryl Hard Liquid 037 v.3

Acrid

Not determined

<u>Property</u> pH	<u>Values</u> Not determined	Remarks / Method
Melting point / freezing point	Not determined	
Boiling point / boiling range	163-164°C / 325-327°	F
Flash point	51°C / 124°F	
Evaporation rate	Not determined	
Flammability (solid, gas)	n/a (liquid)	
Flammability limits in air		
Upper flammability limit	8.0%	
Lower flammability limit	2.0%	
Vapor pressure	28mm Hg	@ 20°C
Vapor density	4.9	@15.5°C (Air = 1)
Specific gravity	0.910	
Water solubility	0.36%	
Solubility in other solvents	Not determined	
Partition coefficient	Not determined	
Autoignition temperature	296°C / 564.8°F	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic viscosity	Not determined	
Explosive properties	Not determined	
Oxidizing properties	Not determined	

#### Other information

# **10. STABILITY AND REACTIVITY**

Reactivity Not reactive under normal conditions		
Chemical stability	Stable under recommended storage conditions	
Possibility of hazar	dous reactions None under normal processing	
Hazardo	us polymerization Hazardous polymerization may occur. Monomer vapors are uninhibited and may form polymers in vent or flame arresters, resulting in blockage of vents. Conditions to avoid for hazardous polymerization: excessive heat, storage in absence of inhibitor, inadvertent addition of catalyst.	
Conditions to avoid	<ul> <li>Heat</li> <li>All possible sources of ignition</li> <li>Contamination</li> </ul>	
Incompatible mater	<u>ials</u> Oxidizers Reducing agent Material has strong solvent properties and can soften paint and rubber.	

Hazardous decomposition products Carbon oxides

# **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposures

#### **Product information**

Inhalation	Harmful if inhaled.
Eye contact	Causes severe eye irritation.
Skin contact	Causes skin irritation.
Ingestion	May be harmful if swallowed.

#### **Component information**

Chemical Name	ORAL LD50	DERMAL LD50	INHALATION LC50
N-Butyl Methacrylate 97-88-1	16 g/kg (rat)	10181 mg/kg (rabbit)	4910 ppm (rat) 4 h
Trimethylolpropane Trimethacrylate 3290-92-4	=5660 /kg (rat)	= 16 mL/kg (rabbit)	-
N, N-Dimethyl-p-Toluidine 99-97-8	1650 mg/kg (rat)	-	1400 mg/m³ (rat) 4 h

#### Information on physical, chemical and toxicological effects

Symptoms May cause skin and eye irritation. May cause irritation to the mucous membranes and upper respiratory tract. Irritating to mouth, throat and stomach if ingested.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

- Carcinogenicity Not classifiable as a human carcinogen
- **STOT single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.
- **STOT repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- Numerical measures of toxicity Product Not determined

#### The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	3864	mg/kg
ATEmix (dermal)	10834	mg/kg
ATEmix (inhalation-dust/mist)	5225	mg/l

# 12. ECOLOGICAL INFORMATION

#### **Ecotoxicity**

#### Harmful to aquatic life.

Chemical Name	Algae / aquatic plants	Fish	Toxicity to microorganisms	Crustacea
N-Butyl Methacrylate 97-88-1	57: 96 h Psuedokirchneriella subcapitata mg/L EC50	11: 96 h Pimephales promelas mg/L LC50 flow-through;	EC50 = 37 mg/L 5 min EC50 = 49 mg/L 15 min EC50 = 55 mg/L 30 min EC50 > 253.6 mg/L 18 h	32: 48 h Daphnia magna mg/L EC50
Trimethylolpropane Trimethacrylate 3290-92-4	-	144: 96 h Oncorhynchus mykiss LC50 160: 96 h Pimephales promelas mg/L LC50 112: 96 h Lepomis macrochirus mg/L LC50	-	-
N,N-Dimethyl-p- Toluidine 99-97-8	-	42-50.5: 96 h Pimphales promelas mg/L LC50 flow-through	-	-

Flexacryl Hard Liquid 037 v.3

#### Persistence and degradability Material is readily biodegradable. 88% in 28 days

**Bioaccumulation** This product has moderate potential for bioaccumulation.

Mobility The product is predicted to have moderate mobility in soil.

Chemical Name	Partition coefficient
N-Butyl Methacrylate	2.26

<u>Other adverse effects</u> This product is substantially removed in biological treatment processes BOD 28 day/DOC=32.8%

# **13. DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Disposal of wastes	Follow all local and national government regulations in disposing material or contaminated packaging.	
	For U.S Dispose of in accordance with federal, state and local regulations. Do not flush to surface or sanitary sewer system Dispose of by incineration or in accordance with local regulations. Do not incinerate closed containers.	
Contaminated Packaging	Dispose of all empty containers in accordance with local and national government regulations.	

# **14. TRANSPORTATION INFORMATION**

Note Based on package size, product may be eligible for limited quantity exception

#### DOT

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	

#### IATA

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	

#### IMDG

UN / ID No	UN1993
Proper shipping name	N-Butyl Methacrylate, stabilized / Trimethylolpropane Trimethacrylate solution
Hazard Class	3
Packing Group	

# **15. REGULATORY INFORMATION**

#### International Inventories

 DSL
 Listed
 Canadian Domestic Substances List

 EINECS
 Listed
 European Inventory of Existing Chemical Substances

EU Regulations EC No. 1272/2008 (CLP) Classification, Labeling, Packaging Medical Devices Directive 93/42/EEC - Class I Medical Devices

#### US Federal Regulations SARA 311 / 312 Hazard Categories US State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Butyl methacrylate	Х	Х	Х
97-88-1			

# **16. OTHER INFORMATION**

NFPA	Health Hazards	Flammability	Instability
	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical Hazards
	2	2	2

Issue Date	26-Sept-2014
Revision Date	14-July-2015
Revision Note	Section 2 – revise classification categories, revise some Hazard Statements and Precautionary Statements,
	remove pictogram

Information to be updated in due course

Hazard pictograms listed in this SDS to be added to product label.

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet