

## SAFETY DATA SHEETS

**This SDS packet was issued with item:**

073239167

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

071691005 072557858 072557890 072557908 072557916 072557924 072557932 072557940 072557965 072557973  
072558021 072558039 073239100 073239118 073239126 073239134 073239142 073239159 073239217 073239225  
073239233 073239456 073239464 073239472 073239480 073239498 073239506 073239555 073239563 073239571  
073239589 073241304 073241338 073241346 073241353 073241361 073241379 073241387 073241411 073241429  
073241437 073242443 073242476 073242682 078634810 078634813 078634822 078634955

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 1 of 5

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Luxatemp Ultra

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

#### 1.3. Details of the supplier of the safety data sheet

**Company Name:** DMG AMERICA LLC  
**Address:** 242 South Dean Street  
**City, State, Zip Code:** Englewood, NJ. 07631  
**Telephone:** (800) 662-6383  
**email address:** [Info@dmg-america.com](mailto:Info@dmg-america.com)  
**Website:** [www.dmg-america.com](http://www.dmg-america.com)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Indications of danger: Xi - Irritant  
R phrases:  
Irritating to eyes, respiratory system and skin.  
May cause sensitisation by skin contact.

#### **GHS classification**

Hazard Statements:  
May cause respiratory irritation.  
Causes serious eye irritation.  
Causes skin irritation.  
May cause an allergic skin reaction.

#### 2.2. Label elements

Signal word: Warning  
Pictograms: GHS07



#### **Hazard statements**

H335 May cause respiratory irritation.  
H319 Causes serious eye irritation.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.

#### **Precautionary statements**

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P302+P352 IF ON SKIN: Wash with plenty of soap and water.

#### 2.3. Other hazards

No risks worthy of mention. Please observe the information on the safety data sheet at all times.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 2 of 5

### Chemical characterization

chemical characterization (preparation): Acrylate.-resin.

### Hazardous components

EC No	Chemical name	Quantity
CAS No	Classification	
Index No	GHS classification	
REACH No		
	Dimethacrylate Resin	35-45 %
41637-38-1	Xi - Irritant R36/37/38-43	

Full text of R and H phrases: see Section 16.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### After inhalation

Exposition vermeiden. Provide fresh air. Move victim to fresh air. Put victim at rest and keep warm.

#### After contact with skin

After contact with skin, wash immediately with: Water and soap.

#### After contact with eyes

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

#### After ingestion

Consult physician.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

#### Suitable extinguishing media

Water fog. Extinguishing powder. Sand. Foam. Carbon dioxide (CO<sub>2</sub>).

#### Extinguishing media which must not be used for safety reasons

High power water jet.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation.

### 6.2. Environmental precautions

Do not empty into drains or the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

Collect mechanically. Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advice on safe handling

Keep container tightly closed. Wear suitable protective clothing and gloves. Avoid contact with eyes.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place.

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 3 of 5

Store only in original container.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

#### 8.2. Exposure controls



#### Protective and hygiene measures

When using do not eat or drink.

#### Respiratory protection

The following must be prevented: inhalation.

#### Hand protection

Tested protective gloves are to be worn: Suitable material: NBR (Nitrile rubber).

#### Eye protection

Tightly sealed safety glasses.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state:	Paste
Colour:	characteristic
Odour:	ester

	Test method
pH-Value (at 20 °C):	ca. 7

#### Changes in the physical state

Boiling point:	>250 °C
point of decomposition:	200 °C
Flash point:	>150 °C
Ignition temperature:	>380 °C
Vapour pressure: (at 20 °C)	1 hPa
Density:	1,5 g/cm <sup>3</sup>
Water solubility:	10 g/L
Vapour density:	1

### SECTION 10: Stability and reactivity

#### 10.4. Conditions to avoid

heat. Light.  
Decomposition takes place from temperatures above: 200 °C  
Decomposition under formation of: Acrylate.

#### 10.5. Incompatible materials

radical former. Keep away from strong acids, leachates, heavy metal salts and reducing materials.

#### 10.6. Hazardous decomposition products

Can be released in case of fire: Gas / vapours, irritant. (Acrylate., pungent). nitrogen oxides (NO<sub>x</sub>).

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 4 of 5

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

##### Acute toxicity

LD50: Rat. 5000 mg/kg

##### Irritation and corrosivity

Frequently or prolonged contact with skin may cause dermal irritation.

Irritant effect on the eye:

##### Additional information on tests

Contains Methacrylic esters.: May produce an allergic reaction.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Acute fish toxicity LC50: >360 mg/l/48h

#### 12.2. Persistence and degradability

Preparation not tested.

#### Further information

Do not empty into drains or the aquatic environment.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

##### Advice on disposal

Can be burnt together with household waste in compliance with official regulations in contact with approved waste disposal companies and with authorities in charge.

Paste: Carry out a burning of hazardous waste according to official regulations.

##### Waste disposal number of waste from residues/unused products

180106 WASTES FROM HUMAN OR ANIMAL HEALTH CARE AND/OR RELATED RESEARCH (except kitchen and restaurant wastes not arising from immediate health care); wastes from natal care, diagnosis, treatment or prevention of disease in humans; chemicals consisting of or containing dangerous substances  
Classified as hazardous waste.

### SECTION 14: Transport information

#### Other applicable information

Not a hazardous material with respect to these transportation regulations.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

##### National regulatory information

### SECTION 16: Other information

#### Full text of R phrases referred to under Sections 2 and 3

36/37/38 Irritating to eyes, respiratory system and skin.

43 May cause sensitisation by skin contact.

#### Full text of H statements referred to under Sections 2 and 3

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

# Safety Data Sheet

## Luxatemp Ultra

Product code: 110901, 110904-110911 (1300\_GHS)

Page 5 of 5

H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.

---

*The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.*