

SAFETY DATA SHEETS

This SDS packet was issued with item:

071058163

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071028125 71028125

SAFETY DATA SHEET

TOKUYAMA UNIVERSAL BOND BOND B

1. Identification

Product identifier

Product name TOKUYAMA UNIVERSAL BOND BOND B

Recommended use of the chemical and restrictions on use

Application Dental adhesive. For dental professionals only.

Details of the supplier of the safety data sheet

Supplier Tokuyama Dental America, Inc.
740 Garden View Ct., Suite 200 Encinitas,
CA 92024 U.S.A.
Tel: (877) 378 3548 (Toll-Free)
Tel: (760)942-7211
Fax: (760)942-7212

Contact Person <http://www.tokuyama-dental.com/tdc/contact.html>

Manufacturer Tokuyama Dental Corporation
38-9, Taitou 1-chome, Taitou-ku, Tokyo
110-0016, Japan
TEL: +81-3-3835-2261
FAX: +81-3-3835-2265

Emergency telephone number

Emergency telephone California Poison Control System - San Francisco Division
San Francisco General Hospital
Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco
Emergency telephone number: +1 800 222 1222
E-mail address: coadmin@calpoison.org
<http://www.calpoison.org>

National Capital Poison Center
3201 New Mexico Ave, Ste 310, Washington DC
Emergency telephone number: +1 800 222 1222
Telephone number: +1 202 362 3867
Facsimile number: +1 202 362 8377
E-mail address: pc@poison.org
<http://www.poison.org>

2. Hazard(s) identification

Classification of the substance or mixture


OSHA Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

Physical hazards Flam. Liq. 2 - H225

Health hazards Skin Irrit 2 - H315: Eye Irrit 2A - H319: STOT SE 3 - H336

Environmental hazards Not Classified

Label elements

TOKUYAMA UNIVERSAL BOND BOND B**Pictogram****Signal word**

Danger

Hazard statements

H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.
 P240 Ground/ bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P261 Avoid breathing vapor/ spray.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 If on skin: Wash with plenty of water.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P312 Call a poison center/ doctor if you feel unwell.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.
 P501 Dispose of contents/ container in accordance with local regulations.

Contains

ACETONE, PROPAN-2-OL

Other hazards**Hazards not otherwise classified (HNOC)**

Not applicable.

3. Composition/information on ingredients**Mixtures**

ACETONE	60-100%
CAS number: 67-64-1	
PROPAN-2-OL	10-30%
CAS number: 67-63-0	

TOKUYAMA UNIVERSAL BOND BOND B

3-(TRIETHOXYSILYL)PROPYL METHACRYLATE CAS number: 21142-29-0	1-5%
1,1,3,3-TETRAMETHYLBUTYL HYDROPEROXIDE CAS number: 5809-08-5	1-5%
2,6-DI-tert-BUTYL-p-CRESOL CAS number: 128-37-0 M factor (Chronic) = 1	<1%

4. First-aid measures

Description of first aid measures

General information	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
Inhalation	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
Ingestion	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Keep affected person under observation. Get medical attention.
Skin Contact	Wash skin thoroughly with soap and water. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue.

Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	May cause drowsiness or dizziness.
Skin contact	Irritating to skin. Prolonged contact may cause dryness of the skin.
Eye contact	Irritating to eyes.

Indication of immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media	Highly flammable liquid and vapour. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

Special hazards arising from the substance or mixture

TOKUYAMA UNIVERSAL BOND BOND B

Specific hazards	Highly flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO ₂).
<u>Advice for firefighters</u>	
Protective actions during firefighting	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapors. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.
-----------------------------	--

Environmental precautions

Environmental precautions	Avoid discharge into drains or watercourses or onto the ground.
----------------------------------	---

Methods and material for containment and cleaning up

Methods for cleaning up	Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Do not allow material to enter confined spaces, due to the risk of explosion. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
--------------------------------	--

Reference to other sections	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

7. Handling and storage

Precautions for safe handling

TOKUYAMA UNIVERSAL BOND BOND B

Usage precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Avoid breathing gas, fume, vapours or spray. Handle all packages and containers carefully to minimize spills. Avoid the formation of mists. Keep container tightly sealed when not in use. Do not handle broken packages without protective equipment. Keep away from food, drink and animal feeding stuffs.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed, in a cool, well ventilated place. Store locked up. Keep only in the original container. Protect containers from damage. Store away from the following materials: Oxidizing materials. Organic peroxides/hydroperoxides.
----------------------------	---

Specific end uses(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

8. Exposure Controls/personal protection

Control parameters

Occupational exposure limits

ACETONE

Long-term exposure limit (8-hour TWA): ACGIH 250 ppm 594 mg/m³

Short-term exposure limit (15-minute): ACGIH 500 ppm 1187 mg/m³

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m³

PROPAN-2-OL

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m³

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m³

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m³

A4

2,6-DI-tert-BUTYL-p-CRESOL

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m³ inhalable fraction and vapor

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A4 = Not Classifiable as a Human Carcinogen.

Exposure controls

Appropriate engineering controls	Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Observe any occupational exposure limits for the product or ingredients.
Eye/face protection	Wear tight-fitting, chemical splash goggles or face shield.

TOKUYAMA UNIVERSAL BOND BOND B

Hand protection	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing and wash it before reuse.
Respiratory protection	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

9. Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance	Liquid
Color	Blue
Odor	Characteristic
Odor threshold	Not available.
pH	Not available.
Melting point	Not available.
Initial boiling point and range	>35°C
Flash point	-14.6°C
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor pressure	Not available.
Vapor density	Not available.
Relative density	0.834
Solubility(ies)	No information available.
Partition coefficient	Not available.
Auto-ignition temperature	Not available.
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.

TOKUYAMA UNIVERSAL BOND BOND B

Oxidizing properties Not available.

Other information Not available.

10. Stability and reactivity

Reactivity	The following materials may react violently with the product: Oxidizing materials. Organic peroxides/hydroperoxides. See the other subsections of this section for further details.
Stability	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
Possibility of hazardous reactions	The following materials may react strongly with the product: Oxidizing materials. Organic peroxides/hydroperoxides.
Conditions to avoid	Vapors may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
Materials to avoid	Oxidizing materials. Organic peroxides/hydroperoxides.
Hazardous decomposition products	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO ₂).

11. Toxicological information

Information on toxicological effects

Routes of exposure Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.

Notes (oral LD₅₀) Not available.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not available.

Skin corrosion/irritation

Skin corrosion/irritation Skin Irrit. 2 - H315, Irritating to skin.

Animal data Not available.

Serious eye damage/irritation

Serious eye damage/irritation Eye Irrit. 2 - H319 Causes serious eye irritation.

Respiratory sensitization

Respiratory sensitization Not available.

Skin sensitization

Skin sensitization Not available.

Germ cell mutagenicity

Genotoxicity - in vitro Not available.

Carcinogenicity

Carcinogenicity Not available.

TOKUYAMA UNIVERSAL BOND BOND B

IARC carcinogenicity	Some of the ingredients are listed or exempt. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
NTP carcinogenicity	Some of the ingredients are listed or exempt.
OSHA Carcinogenicity	None of the ingredients are listed.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	Not available.
Reproductive toxicity - development	Not available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	STOT SE 3 - H336 May cause drowsiness or dizziness.
Target organs	Central nervous system
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
<u>Aspiration hazard</u>	
Aspiration hazard	Not available.
<u>Toxicological information on ingredients.</u>	

PROPAN-2-OL

Carcinogenicity

IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
NTP carcinogenicity	Reasonably anticipated to be a human carcinogen.
OSHA Carcinogenicity	Not listed.

POLY(METHYL METHACRYLATE)

Carcinogenicity

IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
-----------------------------	--

2,6-DI-tert-BUTYL-p-CRESOL

Carcinogenicity

IARC carcinogenicity	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
NTP carcinogenicity	Reasonably anticipated to be a human carcinogen.
OSHA Carcinogenicity	Not listed.

12. Ecological Information

Toxicity

Toxicity	No information available.
Acute toxicity - fish	Not available.
Acute toxicity - aquatic invertebrates	Not available.
Acute toxicity - aquatic plants	Not available.

Persistence and degradability

TOKUYAMA UNIVERSAL BOND BOND B

Persistence and degradability The degradability of the product is not known.

Bioaccumulative potential

Bio-Accumulative Potential No data available on bioaccumulation.

Partition coefficient Not available.

Mobility in soil

Mobility Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Other adverse effects

Other adverse effects None known.

13. Disposal considerations

Waste treatment methods

General information The generation of waste should be minimized or avoided wherever possible. Reuse or recycle products wherever possible. This material and its container must be disposed of in a safe way. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. Empty containers or liners may retain some product residues and hence be potentially hazardous.

Disposal methods Dispose of surplus products and those that cannot be recycled via a licensed waste disposal contractor. Waste, residues, empty containers, discarded work clothes and contaminated cleaning materials should be collected in designated containers, labeled with their contents. Incineration or landfill should only be considered when recycling is not feasible.

14. Transport information

General For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

UN Number

UN No. (IMDG) 1133

UN No. (ICAO) 1133

UN No. (DOT) UN1133

UN proper shipping name

Proper shipping name (IMDG) ADHESIVES

Proper shipping name (ICAO) ADHESIVES

Proper shipping name (DOT) ADHESIVES

Transport hazard class(es)

DOT hazard class 3

DOT hazard label 3

IMDG Class 3

TOKUYAMA UNIVERSAL BOND BOND B

ICAO class/division 3

Transport labels



DOT transport labels



Packing group

IMDG packing group II

ICAO packing group II

DOT packing group II

Environmental hazards

Environmentally Hazardous Substance

No.

Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-D

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

Regulatory Status This Product is Hazardous under the OSHA Hazard Communication Standard.

International Regulations

US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities

None of the ingredients are listed or exempt.

CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

ACETONE

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

SARA 313 Emission Reporting

None of the ingredients are listed or exempt.

CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

TOKUYAMA UNIVERSAL BOND BOND B

FDA - Essential Chemical

None of the ingredients are listed or exempt.

FDA - Precursor Chemical

None of the ingredients are listed or exempt.

SARA (311/312) Hazard Categories

Fire
Acute
Chronic

OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

US State Regulations

California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

PROPAN-2-OL

California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

PROPAN-2-OL

Present.

Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

PROPAN-2-OL

Present.

Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

PROPAN-2-OL

Present.

TOKUYAMA UNIVERSAL BOND BOND B

Minnesota "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

ACETONE

PROPAN-2-OL

New Jersey "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

PROPAN-2-OL

Present.

Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

2,6-DI-tert-BUTYL-p-CRESOL

Present.

ACETONE

Present.

PROPAN-2-OL

Present.

16. Other information

Revision comments	This is first issue.
Revision date	11/20/2016
Revision	1
Hazard statements in full	H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.