

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

075022959

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

075022603 075022744

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

0750020750 075014907 075022611 075022629 075022637 075022645 075022652 075022660 075022678 075022686  
075022694 075022702 075022710 075022728 075022736 075022751 075022769 075022777 075022785 075022918  
075022926 075022934 075022942 075022967 075022975 075022991 075023007 075023015 075023031 075023049  
075023056 075023064 075023072 075023213 075023239 075023262 075023288 075023296 075023304 075023312  
075023320 075023346 075023353 075023361 075023379 075023395 075023403 075023411 075023429 075023437  
075023510 075023528



## Material Safety Data Sheet

Copyright, 2013, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 6028/ 6029/ 5916 3M™ ESPE™ FILTEK™ SUPREME ULTRA UNIVERSAL RESTORATIVE  
**MANUFACTURER:** 3M  
**DIVISION:** 3M ESPE Dental Products  
**ADDRESS:** 3M Center, St. Paul, MN 55144-1000

**EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)**

**Issue Date:** 05/20/13  
**Supercedes Date:** 12/30/10

**Document Group:** 26-5783-1

#### Product Use:

**Intended Use:** Dental Product  
**Limitations on Use:** For use only by dental professionals  
**Specific Use:** Dental Restorative

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
SILANE TREATED CERAMIC	444758-98-9	60 - 80
SILANE TREATED SILICA	248596-91-0	1 - 10
DIURETHANE DIMETHACRYLATE (UDMA)	72869-86-4	1 - 10
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	41637-38-1	1 - 10
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	1565-94-2	1 - 10
SILANE TREATED ZIRCONIA	Unknown	1 - 10
POLYETHYLENE GLYCOL DIMETHACRYLATE	25852-47-5	< 5
TRIETHYLENE GLYCOL DIMETHACRYLATE (TEGDMA)	109-16-0	< 5
2,6-DI-TERT-BUTYL-P-CRESOL	128-37-0	< 0.5

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Paste

**Odor, Color, Grade:** Slight acrylate odor, Tooth colored

**General Physical Form:** Solid

**Immediate health, physical, and environmental hazards:** May cause allergic skin reaction. This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

### 3.2 POTENTIAL HEALTH EFFECTS

**Eye Contact:**

Mild Eye Irritation: Signs/symptoms may include redness, pain, and tearing.

**Skin Contact:**

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, and itching.

**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

**Autoignition temperature**

*No Data Available*

**Flash Point**

*No flash point*

**Flammable Limits(LEL)**

*Not Applicable*

**Flammable Limits(UEL)**

*Not Applicable*

### 5.2 EXTINGUISHING MEDIA

Ordinary combustible material. Use fire extinguishers with class A extinguishing agents (e.g., water, foam).

### 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

**Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.**

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode.

### 6.2. Environmental precautions

Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

### Clean-up methods

Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Collect as much of the spilled material as possible. Clean up residue.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Avoid eye contact. Avoid skin contact. Avoid breathing of dust created by cutting, sanding, grinding or machining. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Wash hands after handling and before eating.

### 7.2 STORAGE

Store in a cool, dry place.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Not applicable. Provide appropriate local exhaust for cutting, grinding, sanding or machining. Do not use in a confined area or areas with little or no air movement.

### 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

#### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields

### 8.2.2 Skin Protection

Avoid skin contact. Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials. See Section 7.1 for additional information on skin protection.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection. Avoid breathing of dust created by cutting, sanding, grinding or machining.

### 8.2.4 Prevention of Swallowing

Do not ingest. Wash hands after handling and before eating.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
2,6-DI-TERT-BUTYL-P-CRESOL	ACGIH	TWA, inhalable fraction and vapor	2 mg/m <sup>3</sup>	

#### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Slight acrylate odor, Tooth colored
<b>General Physical Form:</b>	Solid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	No flash point
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Density</b>	1.9 g/cm <sup>3</sup>
<b>Vapor Density</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Specific Gravity</b>	1.9 [Ref Std: WATER=1]
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Volatile Organic Compounds</b>	<i>Not Applicable</i>
<b>Kow - Oct/Water partition coef</b>	<i>Not Applicable</i>
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	<i>Not Applicable</i>
<b>Viscosity</b>	<i>No Data Available</i>

## SECTION 10: STABILITY AND REACTIVITY

**Stability:** Stable.

### Materials and Conditions to Avoid:

#### 10.1 Conditions to avoid

Heat

#### 10.2 Materials to avoid

Strong oxidizing agents

**Hazardous Polymerization:** Hazardous polymerization will not occur.

## Hazardous Decomposition or By-Products

### Substance

Carbon monoxide  
Carbon dioxide

### Condition

During Combustion  
During Combustion

## SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

## SECTION 12: ECOLOGICAL INFORMATION

### ECOTOXICOLOGICAL INFORMATION

Not determined.

### CHEMICAL FATE INFORMATION

Not determined.

## SECTION 13: DISPOSAL CONSIDERATIONS

**Waste Disposal Method:** Dispose of completely cured (or polymerized) wastes in a sanitary landfill.

As a disposal alternative, incinerate uncured product in an industrial or commercial incinerator in the presence of a combustible material.

**EPA Hazardous Waste Number (RCRA):** Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**

LE-F100-0683-6, 70-2010-5780-2, 70-2010-5781-0, 70-2010-5791-9, 70-2010-5792-7, 70-2010-5793-5, 70-2010-5794-3, 70-2010-5795-0, 70-2010-5796-8, 70-2010-5797-6, 70-2010-5798-4, 70-2010-5799-2, 70-2010-5800-8, 70-2010-5801-6, 70-2010-5802-4, 70-2010-5803-2, 70-2010-5804-0, 70-2010-5805-7, 70-2010-5806-5, 70-2010-5807-3, 70-2010-5808-1, 70-2010-5809-9, 70-2010-5810-7, 70-2010-5811-5, 70-2010-5812-3, 70-2010-5813-1, 70-2010-5814-9, 70-2010-5815-6, 70-2010-5816-4, 70-2010-5817-2, 70-2010-5818-0, 70-2010-5819-8, 70-2010-5820-6, 70-2010-5821-4, 70-2010-5822-2, 70-2010-5823-0, 70-2010-5824-8, 70-2010-5825-5, 70-2010-5828-9, 70-2010-5829-7, 70-2010-5830-5, 70-2010-5831-3, 70-2010-5832-1, 70-2010-5833-9, 70-2010-5834-7, 70-2010-5835-4, 70-2010-5836-2, 70-2010-5837-0, 70-2010-5838-8, 70-2010-5839-6, 70-2010-5840-4, 70-2010-5841-2, 70-2010-5842-0, 70-2010-5843-8, 70-2010-5844-6, 70-2010-5845-3, 70-2010-5846-1, 70-2010-5847-9, 70-2010-5848-7, 70-2010-5849-5, 70-2010-5850-3, 70-2010-5851-1, 70-2010-5852-9, 70-2010-5853-7, 70-2010-5854-5, 70-2010-5855-2, 70-2010-5856-0, 70-2010-5857-8, 70-2010-5858-6, 70-2010-5859-4, 70-2010-5860-2, 70-2010-5861-0, 70-2010-5862-8, 70-2010-5863-6, 70-2010-7731-3, 70-2010-7732-1, 70-2010-7733-9, 70-2010-7734-7, 70-2010-7735-4, 70-2010-7736-2, 70-2010-7737-0, 70-2010-7738-8, 70-2010-7741-2, 70-2010-7742-0, 70-2010-8997-9, 70-2010-8998-7, 70-2010-8999-5, 70-2010-9400-3

**For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.**

**SECTION 15: REGULATORY INFORMATION**

**US FEDERAL REGULATIONS**

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

**STATE REGULATIONS**

Contact 3M for more information.

**CHEMICAL INVENTORIES**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

**INTERNATIONAL REGULATIONS**

Contact 3M for more information.

**This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.**

**SECTION 16: OTHER INFORMATION**

**NFPA Hazard Classification**

**Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

**Revision Changes:**

Section 1: Product use information was modified.

Section 16: Disclaimer (second paragraph) was modified.

Section 3: Potential effects from skin contact information was modified.  
Section 7: Handling information was modified.  
Section 8: Engineering controls information was modified.  
Section 8: Respiratory protection information was modified.  
Section 10: Hazardous decomposition or by-products table was modified.  
Section 9: Density information was modified.  
Section 9: Vapor density value was modified.  
Section 9: Vapor pressure value was modified.  
Section 9: Boiling point information was modified.  
Section 5: Flammable limits (UE) information was modified.  
Section 5: Flammable limits (LEL) information was modified.  
Section 5: Autoignition temperature information was modified.  
Section 5: Flash point information was modified.  
Section 9: Property description for optional properties was modified.  
Section 9: Specific gravity information was modified.  
Section 9: pH information was modified.  
Section 9: Melting point information was modified.  
Section 9: Solubility in water value was modified.  
Section 9: Flash point information was modified.  
Section 9: Flammable limits (LEL) information was modified.  
Section 9: Flammable limits (UEL) information was modified.  
Section 9: Autoignition temperature information was modified.  
Section 14: ID Number(s) Template 1 was modified.  
Section 2: Ingredient table was modified.  
Section 8: Exposure guidelines ingredient information was modified.  
Section 16: Web address was added.  
Section 8: Hand protection information was added.  
Section 1: Address was added.  
Copyright was added.  
Company logo was added.  
Telephone header was added.  
Company Telephone was added.  
Section 1: Emergency phone information was added.  
Section 1: Emergency phone information was deleted.  
Company Logo was deleted.  
Copyright was deleted.  
Section 16: Web address heading was deleted.  
Section 1: Address line 1 was deleted.  
Section 1: Address line 2 was deleted.

**DISCLAIMER:** The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M

**3M USA MSDSs are available at [www.3M.com](http://www.3M.com)**







## Safety Data Sheet

Copyright, 2017, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document Group:</b>	26-5783-1	<b>Version Number:</b>	6.01
<b>Issue Date:</b>	12/29/17	<b>Supersedes Date:</b>	08/14/17

### SECTION 1: Identification

#### 1.1. Product identifier

6028/ 6029/ 5916 3M™ ESPE™ FILTEK™ SUPREME ULTRA UNIVERSAL RESTORATIVE

#### 1.2. Recommended use and restrictions on use

##### Recommended use

Dental Product, Restorative

##### Restrictions on use

For use only by dental professionals

#### 1.3. Supplier's details

<b>MANUFACTURER:</b>	3M
<b>DIVISION:</b>	Oral Care Solutions Division
<b>ADDRESS:</b>	3M Center, St. Paul, MN 55144-1000, USA
<b>Telephone:</b>	1-888-3M HELPS (1-888-364-3577)

#### 1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

### SECTION 2: Hazard identification

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

#### 2.1. Hazard classification

Skin Sensitizer: Category 1.

#### 2.2. Label elements

##### Signal word

Warning

##### Symbols

Exclamation mark |

##### Pictograms

**Hazard Statements**

May cause an allergic skin reaction.

**Precautionary Statements****Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.

Wear protective gloves.

Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
SILANE TREATED CERAMIC	444758-98-9	60 - 80 Trade Secret *
SILANE TREATED SILICA	248596-91-0	1 - 10 Trade Secret *
DIURETHANE DIMETHACRYLATE (UDMA)	72869-86-4	1 - 10 Trade Secret *
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	41637-38-1	1 - 10 Trade Secret *
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	1565-94-2	1 - 10 Trade Secret *
SILANE TREATED ZIRCONIA	None	1 - 5 Trade Secret *
POLYETHYLENE GLYCOL DIMETHACRYLATE	25852-47-5	< 5 Trade Secret *
Triethylene glycol dimethacrylate	109-16-0	< 1 Trade Secret *

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

**Eye Contact:**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get

medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide

Carbon dioxide

**Condition**

During Combustion

During Combustion

**5.3. Special protective actions for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

**6.3. Methods and material for containment and cleaning up**

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Avoid breathing of dust created by cutting, sanding, grinding or machining. A no-touch technique is recommended. If skin contact occurs, wash skin with soap and water. Acrylates may penetrate commonly-used gloves. If product contacts glove, remove and discard glove, wash hands immediately with soap and water and then re-glove. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) Do not get in eyes.

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from oxidizing agents.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational exposure limits**

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

**8.2. Exposure controls****8.2.1. Engineering controls**

Use in a well-ventilated area.

**8.2.2. Personal protective equipment (PPE)****Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Safety Glasses with side shields

**Skin/hand protection**

See Section 7.1 for additional information on skin protection.

**Respiratory protection**

None required.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>General Physical Form:</b>	Solid
<b>Specific Physical Form:</b>	Paste
<b>Odor, Color, Grade:</b>	Slight acrylate odor, Tooth colored
<b>Odor threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point</b>	<i>No Data Available</i>
<b>Boiling Point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	No flash point
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Classified
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapor Pressure</b>	<i>Not Applicable</i>
<b>Vapor Density</b>	<i>Not Applicable</i>
<b>Density</b>	1.9 g/cm <sup>3</sup>
<b>Specific Gravity</b>	1.9 [Ref Std:WATER=1]
<b>Solubility In Water</b>	<i>No Data Available</i>
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>Not Applicable</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>

Viscosity	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<i>Not Applicable</i>
VOC Less H2O & Exempt Solvents	<i>Not Applicable</i>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### 10.5. Incompatible materials

Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
None known.	

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

This document has been prepared in accordance with the U.S. OSHA Hazard Communication Standard, which requires the inclusion of all known hazards of the product or ingredients regardless of the potential risk. The risks of the hazards communicated in this document may vary depending on the potential for exposure.

The information below represents toxicological information associated with the individual components of the uncured product. Once properly mixed and/or cured, the product is safe for its intended use.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

**Skin Contact:**

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

**Eye Contact:**

Contact with the eyes during product use is not expected to result in significant irritation.

**Ingestion:**

May be harmful if swallowed.

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
SILANE TREATED CERAMIC	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED CERAMIC	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
SILANE TREATED SILICA	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED SILICA	Ingestion		LD50 estimated to be > 5,000 mg/kg
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
DIURETHANE DIMETHACRYLATE (UDMA)	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	Ingestion	Rat	LD50 > 2,000 mg/kg
DIURETHANE DIMETHACRYLATE (UDMA)	Ingestion	Rat	LD50 > 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Dermal	Professional judgment	LD50 estimated to be 2,000 - 5,000 mg/kg
SILANE TREATED ZIRCONIA	Dermal		LD50 estimated to be > 5,000 mg/kg
SILANE TREATED ZIRCONIA	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
POLYETHYLENE GLYCOL DIMETHACRYLATE	Dermal		LD50 estimated to be > 5,000 mg/kg
POLYETHYLENE GLYCOL DIMETHACRYLATE	Ingestion	Rat	LD50 > 5,000 mg/kg
Triethylene glycol dimethacrylate	Dermal	Professional judgment	LD50 estimated to be > 5,000 mg/kg
Triethylene glycol dimethacrylate	Ingestion	Rat	LD50 10,837 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
SILANE TREATED CERAMIC	similar compounds	No significant irritation
SILANE TREATED SILICA	Professional judgment	No significant irritation

	nt	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not available	Minimal irritation
SILANE TREATED ZIRCONIA	Rabbit	No significant irritation
Triethylene glycol dimethacrylate	Guinea pig	Mild irritant

### Serious Eye Damage/Irritation

Name	Species	Value
SILANE TREATED CERAMIC	similar compounds	Mild irritant
SILANE TREATED SILICA	Professional judgement	No significant irritation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Not available	Moderate irritant
SILANE TREATED ZIRCONIA	Rabbit	Mild irritant
Triethylene glycol dimethacrylate	Professional judgement	Moderate irritant

### Skin Sensitization

Name	Species	Value
SILANE TREATED CERAMIC	similar compounds	Not classified
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	Guinea pig	Not classified
DIURETHANE DIMETHACRYLATE (UDMA)	Guinea pig	Sensitizing
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Guinea pig	Sensitizing
Triethylene glycol dimethacrylate	Human and animal	Sensitizing

### Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
BISPHENOL A POLYETHYLENE GLYCOL DIETHER DIMETHACRYLATE	In Vitro	Not mutagenic
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	In Vitro	Some positive data exist, but the data are not sufficient for classification
SILANE TREATED ZIRCONIA	In Vitro	Some positive data exist, but the data are not sufficient for classification
Triethylene glycol dimethacrylate	In Vitro	Some positive data exist, but the data are not sufficient for classification

### Carcinogenicity

Name	Route	Species	Value
SILANE TREATED CERAMIC	Inhalation	similar compounds	Some positive data exist, but the data are not sufficient for classification
SILANE TREATED ZIRCONIA	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Triethylene glycol dimethacrylate	Dermal	Mouse	Not carcinogenic



**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for female reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for male reproduction	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	Not classified for development	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
Triethylene glycol dimethacrylate	Ingestion	Not classified for female reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for male reproduction	Mouse	NOAEL 1 mg/kg/day	1 generation
Triethylene glycol dimethacrylate	Ingestion	Not classified for development	Mouse	NOAEL 1 mg/kg/day	1 generation

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
SILANE TREATED CERAMIC	Inhalation	pulmonary fibrosis	Not classified	similar compounds	NOAEL Not available	
BISPHENOL A DIGLYCIDYL ETHER DIMETHACRYLATE (BISGMA)	Ingestion	endocrine system   liver   nervous system   kidney and/or bladder	Not classified	Mouse	NOAEL 0.8 mg/kg/day	prematuring & during gestation
SILANE TREATED ZIRCONIA	Inhalation	pulmonary fibrosis	Not classified	Multiple animal species	NOAEL Not available	
SILANE TREATED ZIRCONIA	Inhalation	respiratory system	Not classified	Human	NOAEL Not available	occupational exposure
Triethylene glycol dimethacrylate	Dermal	kidney and/or bladder   blood	Not classified	Mouse	NOAEL 833 mg/kg/day	78 weeks

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information****Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

**Chemical fate information**

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

**SECTION 13: Disposal considerations****13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. If no other disposal options are available, waste product that has been completely cured or polymerized may be placed in a landfill properly designed for industrial waste.

**EPA Hazardous Waste Number (RCRA):** Not regulated

**SECTION 14: Transport Information**

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

**SECTION 15: Regulatory information****15.1. US Federal Regulations**

Contact 3M for more information.

**EPCRA 311/312 Hazard Classifications:****Physical Hazards**

Not applicable

**Health Hazards**

Respiratory or Skin Sensitization

**Additional TSCA Information**

<u>Components</u>	<u>CAS No</u>	<u>Consent Order/SNUR</u>
SILANE TREATED SILICA	248596-91-0	Allowed use(s): Coating additive.

**15.2. State Regulations**

Contact 3M for more information.

**California Proposition 65****Ingredient**

Toluene

**C.A.S. No.**

108-88-3

**Classification**

Developmental Toxin

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

**15.3. Chemical Inventories**

This material contains one or more substances not listed on the TSCA Inventory. Commercial use of this material is regulated by the FDA.

Contact 3M for more information.

**15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: Other information

### NFPA Hazard Classification

Health: 2 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document Group:</b>	26-5783-1	<b>Version Number:</b>	6.01
<b>Issue Date:</b>	12/29/17	<b>Supersedes Date:</b>	08/14/17

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at [www.3M.com](http://www.3M.com)