

SAFETY DATA SHEETS

This SDS packet was issued with item:

070391045

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071399450 071402973 076202956



Lithium-ion battery in equipment - Radii Plus and Radii Cal

SDI Limited

Version No: 4.1.1.1
Safety Data Sheet according to WHMIS 2015 requirements

Issue Date: 01/11/2019
Print Date: 07/10/2020
L.GHS.CAN.EN

SECTION 1 Identification

Product Identifier

Product name	Lithium-ion battery in equipment - Radii Plus and Radii Cal
Synonyms	Lithium-ion (Li-ion) battery pack. Nominal voltage: 7.4V, Rated Capacity: 1550mAh, Wh rating: 11.47 Wh
Proper shipping name	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT (including lithium ion polymer batteries); or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)
Other means of identification	Not Available

Recommended use of the chemical and restrictions on use

Relevant identified uses	Battery in Radii Plus and Radii Cal, to be used as dental curing lights. Potentially hazardous materials are sealed and contained in equipment. Equipment is packed in strong outer packaging to withstand normal handling and use. Exposure could occur if the equipment has been exposed to high temperatures (>125°C), battery or cells have been opened, crushed, disassembled or burned.
---------------------------------	---

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	SDI Limited	SDI (North America) Inc.	SDI
Address	3-15 Brunsdon Street Bayswater VIC 3153 Australia	1279 Hamilton Parkway Itasca IL 60143 United States	Rua Dr. Virgílio de Carvalho Pinto, 612 Pinheiros, Sao Paulo 05415-020 Brazil
Telephone	+61 3 8727 7111 (Business Hours)	+1 630 361 9200 (Business hours) 1 800 228 5166	+55 11 3092 7100 (Business Hours)
Fax	+61 3 8727 7222	+1 630 361 9222	+55 11 3092 7101
Website	www.sdi.com.au	http://www.sdi.com.au	http://www.sdi.com.au/
Email	info@sdi.com.au	USA.Canada@sdi.com.au	Brasil@sdi.com.au

Registered company name	SDI Dental Limited
Address	Block 8, St Johns Court Santry Dublin 9 Ireland
Telephone	+353 1 886 9577 (Business Hours) 800 0225 5734
Fax	Not Available
Website	http://www.sdi.com.au/
Email	Ireland@sdi.com.au


Emergency phone number

Association / Organisation	SDI Limited	SDI	SDI Dental Limited
Emergency telephone numbers	+61 3 8727 7111	+61 3 8727 7111	+61 3 8727 7111
Other emergency telephone numbers	ray.cahill@sdi.com.au	Not Available	Not Available

SECTION 2 Hazard(s) identification

Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Not Applicable
-----------------------	----------------

Label elements

Hazard pictogram(s)	Not Applicable
----------------------------	----------------

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

Signal word **Not Applicable****Hazard statement(s)**

Not Applicable

Physical and Health hazard(s) not otherwise classified

Not Applicable

Precautionary statement(s) Prevention

Not Applicable

Precautionary statement(s) Response

Not Applicable

Precautionary statement(s) Storage

Not Applicable

Precautionary statement(s) Disposal

Not Applicable

SECTION 3 Composition / information on ingredients**Substances**

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
Not Available		Battery Cell contains
12190-79-3	<38	<u>lithium cobaltate</u>
21324-40-3	<3	<u>lithium fluorophosphate</u>
96-49-1	<6	<u>ethylene carbonate</u>
Not Available	<8	chain carbonate
7782-42-5	<20	<u>graphite</u>
7439-92-1	<0.1	<u>lead</u>
7439-97-6	<0.0005	<u>mercury (elemental)</u>
Not Available		Note: other 25% includes the below materials:
Not Available		Al (Positive Base Film, Cap, Can, Tab)
Not Available		Cu (Negative film base)
Not Available		Ni (Tab, Terminal)
Not Available		Fe (Terminal)
Not Available		Resin (PP, PE, PET) (Separator, Plastic, Parts, Insulator)
Not Available		Circuit Module contains
7439-92-1	<0.1	<u>lead</u>
7439-97-6	0	<u>mercury (elemental)</u>
7440-47-3	0	<u>chromium</u>
7440-43-9	0	<u>cadmium</u>
Not Available	0	plastic case and Si2O
Not Available		Plastic Parts and Paints contains
25971-63-5	>81	<u>bisphenol A/ phosgene polymer</u>
Not Available	<12	flame retardant
Not Available	<7	elastomer

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SECTION 4 First-aid measures**Description of first aid measures**

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation.

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Seek medical attention.
Ingestion	<ul style="list-style-type: none"> ▶ Not considered a normal route of entry. ▶ For advice, contact a Poisons Information Centre or a doctor at once. ▶ Urgent hospital treatment is likely to be needed. ▶ If swallowed do NOT induce vomiting. ▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. ▶ Observe the patient carefully. ▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. ▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. ▶ Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Fire-fighting measures**Extinguishing media**

Use dry chemical powder, alcohol-resistant foam, carbon dioxide, or water as a fine spray.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
-----------------------------	-------------

Special protective equipment and precautions for fire-fighters

Fire Fighting	<p>Slight hazard when exposed to heat, flame and oxidisers.</p> <ul style="list-style-type: none"> ▶ Use fire fighting procedures suitable for surrounding area. ▶ DO NOT approach containers suspected to be hot. ▶ Cool fire exposed containers with water spray from a protected location. ▶ If safe to do so, remove containers from path of fire. ▶ Equipment should be thoroughly decontaminated after use.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ The material is not readily combustible under normal conditions. ▶ However, it will break down under fire conditions and the organic component may burn. ▶ Not considered to be a significant fire risk. ▶ Heat may cause expansion or decomposition with violent rupture of containers. ▶ Decomposes on heating and may produce toxic fumes of carbon monoxide (CO). ▶ May emit acrid smoke.

SECTION 6 Accidental release measures**Personal precautions, protective equipment and emergency procedures**

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	<p>Clean up all spills immediately. Avoid contact with skin and eyes. Place in suitable containers for disposal.</p>
Major Spills	<ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Wear protective clothing, safety glasses, dust mask, gloves. ▶ Secure load if safe to do so. Bundle/collect recoverable product. ▶ Use dry clean up procedures and avoid generating dust. ▶ Vacuum up (consider explosion-proof machines designed to be grounded during storage and use). ▶ Water may be used to prevent dusting. ▶ Collect remaining material in containers with covers for disposal. ▶ Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage**Precautions for safe handling**

Safe handling	<p>Use good occupational work practice. Observe manufacturer's storage and handling recommendations contained within this SDS. Avoid physical damage to containers.</p>
Other information	<ul style="list-style-type: none"> ▶ Store away from incompatible materials. ▶ Keep dry. ▶ Store under cover. ▶ Protect containers against physical damage. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. <p>Store out of direct sunlight Keep away from heat and naked flames.</p>

Lithium-ion battery in equipment - Radii Plus and Radii Cal

Conditions for safe storage, including any incompatibilities

Suitable container	▶ DO NOT repack. Use containers supplied by manufacturer only.
Storage incompatibility	▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	lithium cobaltate	Cobalt metal, dust and fume (as Co)	0.05 mg/m ³	0.15 mg/m ³	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	lithium cobaltate	Cobalt - Inorganic compounds (as Co)	0.02 mg/m ³	Not Available	Not Available	TLV Basis: asthma; pulmonary function; myocardial effects. BEI
Canada - Alberta Occupational Exposure Limits	lithium cobaltate	Cobalt, elemental inorganic compounds, as Co	0.02 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	lithium cobaltate	Cobalt and inorganic compounds, (as Co)	0.02 mg/m ³	0.06 mg/m ³	Not Available	T20
Canada - Manitoba Occupational Exposure Limits	lithium cobaltate	Not Available	0.02 mg/m ³	Not Available	Not Available	TLV@ Basis: Asthma; pulm tunc; myocardial eff; BEI
Canada - British Columbia Occupational Exposure Limits	lithium cobaltate	Cobalt and inorganic compounds, as Co	0.02 mg/m ³	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	lithium cobaltate	Cobalt and inorganic compounds, as Co	0.02 mg/m ³	Not Available	Not Available	TLV@ Basis: Asthma; pulm tunc; myocardial eff; BEI
Canada - Northwest Territories Occupational Exposure Limits	lithium cobaltate	Cobalt and inorganic compounds, (as Co)	0.02 mg/m ³	0.06 mg/m ³	Not Available	Schedule R
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	lithium cobaltate	Cobalt elemental, and inorganic compounds (as Co)	0.02 mg/m ³	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	graphite	Graphite - All forms except graphite fibers	2 mg/m ³	Not Available	Not Available	TLV Basis: pneumoconiosis
Canada - Alberta Occupational Exposure Limits	graphite	Graphite, respirable (all forms except graphite fibres)	2 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	graphite	Graphite, natural-all forms except graphite fibres (respirable fraction++)	2 mg/m ³	4 mg/m ³	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	graphite	Not Available	2 mg/m ³	Not Available	Not Available	TLV@ Basis: Pneumoconiosis
Canada - British Columbia Occupational Exposure Limits	graphite	Graphite - All forms except graphite fibres, Respirable	2 mg/m ³	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	graphite	Graphite (all forms except graphite fibers)	2 mg/m ³	Not Available	Not Available	TLV@ Basis: Pneumoconiosis
Canada - Northwest Territories Occupational Exposure Limits	graphite	Graphite, natural-all forms except graphite fibres (respirable fraction)	2 mg/m ³	4 mg/m ³	Not Available	Not Available
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	graphite	Graphite (all forms except fibers)	2 mg/m ³	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	lead	Lead, inorganic, fumes and dusts (as Pb)	0.15 mg/m ³	0.45 mg/m ³	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	lead	Lead - elemental and inorganic compounds (as Pb)	0.05 mg/m ³	Not Available	Not Available	TLV Basis: central nervous system impairment; peripheral nervous system impairment; hematologic effects. BEI
Canada - Alberta Occupational Exposure Limits	lead	Lead elemental & inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	lead	Lead and inorganic compounds, (as Pb)	0.05 mg/m ³	0.15 mg/m ³	Not Available	T20
Canada - Manitoba Occupational Exposure Limits	lead	Not Available	0.05 mg/m ³	Not Available	Not Available	TLV@ Basis: CNS & PNS impair; hematologic eff; BEI
Canada - British Columbia Occupational Exposure Limits	lead	Lead - elemental and inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	lead	Lead and inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	TLV@ Basis: CNS & PNS impair; hematologic eff; BEI

Lithium-ion battery in equipment - Radii Plus and Radii Cal

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Ontario Occupational Exposure Limits	lead	Lead chromate - as Pb (see listing for lead)	0.05 mg/m ³	Not Available	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Ontario Occupational Exposure Limits	lead	Lead - Tetraethyl lead, as Pb	0.10 mg/m ³	0.30 mg/m ³	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Northwest Territories Occupational Exposure Limits	lead	Lead and inorganic compounds, (as Pb)	0.05 mg/m ³	0.15 mg/m ³	Not Available	Schedule R
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	lead	Lead, and inorganic compounds, (as Pb)	0.05 mg/m ³	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mercury (elemental)	Mercury (all forms except Alkyl) (as Hg)	0.05 mg/m ³	0.15 mg/m ³	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mercury (elemental)	Mercury (Alkyl compounds) - Skin (as Hg)	0.001 ppm / 0.01 mg/m ³	0.03 mg/m ³ / 0.003 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	mercury (elemental)	Mercury - Elemental (as Hg)	0.025 mg/m ³	Not Available	Not Available	TLV Basis: central nervous system impairment; kidney damage
Canada - Alberta Occupational Exposure Limits	mercury (elemental)	Mercury, as Hg in Inorganic compounds, including metallic mercury	0.025 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	mercury (elemental)	Mercury, (as Hg): Alkyl compounds	0.01 mg/m ³	0.03 mg/m ³	Not Available	Skin
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	mercury (elemental)	Mercury, (as Hg): Inorganic forms, including metallic mercury	0.025 mg/m ³	0.075 mg/m ³	Not Available	Skin
Canada - Manitoba Occupational Exposure Limits	mercury (elemental)	Not Available	0.025 mg/m ³	Not Available	Not Available	TLV® Basis: CNS impair; kidney dam; BEI
Canada - British Columbia Occupational Exposure Limits	mercury (elemental)	Mercury - Elemental, as Hg	0.025 mg/m ³	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	mercury (elemental)	Mercury, all forms except alkyl, as Hg - Elemental and inorganic forms	0.025 mg/m ³	Not Available	Not Available	TLV® Basis: CNS impair; kidney dam; BEI
Canada - Ontario Occupational Exposure Limits	mercury (elemental)	Mercury, elemental mercury, inorganic and organic compounds of mercury, as Hg - All forms of except alkyl, as Hg	0.025 mg/m ³	Not Available	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Northwest Territories Occupational Exposure Limits	mercury (elemental)	Mercury, (as Hg): Inorganic forms, including metallic mercury	0.025 mg/m ³	0.075 mg/m ³	Not Available	Skin
Canada - Northwest Territories Occupational Exposure Limits	mercury (elemental)	Mercury, (as Hg): Alkyl compounds	0.01 mg/m ³	0.03 mg/m ³	Not Available	Skin
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	mercury (elemental)	Mercury, mercury vapor (as Hg)	0.025 mg/m ³	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	lead	Lead, inorganic, fumes and dusts (as Pb)	0.15 mg/m ³	0.45 mg/m ³	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	lead	Lead - elemental and inorganic compounds (as Pb)	0.05 mg/m ³	Not Available	Not Available	TLV Basis: central nervous system impairment; peripheral nervous system impairment; hematologic effects. BEI
Canada - Alberta Occupational Exposure Limits	lead	Lead elemental & inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	lead	Lead and inorganic compounds, (as Pb)	0.05 mg/m ³	0.15 mg/m ³	Not Available	T20
Canada - Manitoba Occupational Exposure Limits	lead	Not Available	0.05 mg/m ³	Not Available	Not Available	TLV® Basis: CNS & PNS impair; hematologic eff; BEI
Canada - British Columbia Occupational Exposure Limits	lead	Lead - elemental and inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	lead	Lead and inorganic compounds, as Pb	0.05 mg/m ³	Not Available	Not Available	TLV® Basis: CNS & PNS impair; hematologic eff; BEI

Lithium-ion battery in equipment - Radii Plus and Radii Cal

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Ontario Occupational Exposure Limits	lead	Lead chromate - as Pb (see listing for lead)	0.05 mg/m3	Not Available	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Ontario Occupational Exposure Limits	lead	Lead - Tetraethyl lead, as Pb	0.10 mg/m3	0.30 mg/m3	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Northwest Territories Occupational Exposure Limits	lead	Lead and inorganic compounds, (as Pb)	0.05 mg/m3	0.15 mg/m3	Not Available	Schedule R
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	lead	Lead, and inorganic compounds, (as Pb)	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mercury (elemental)	Mercury (all forms except Alkyl) (as Hg)	0.05 mg/m3	0.15 mg/m3	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	mercury (elemental)	Mercury (Alkyl compounds) - Skin (as Hg)	0.001 ppm / 0.01 mg/m3	0.03 mg/m3 / 0.003 ppm	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	mercury (elemental)	Mercury - Elemental (as Hg)	0.025 mg/m3	Not Available	Not Available	TLV Basis: central nervous system impairment; kidney damage
Canada - Alberta Occupational Exposure Limits	mercury (elemental)	Mercury, as Hg in Inorganic compounds, including metallic mercury	0.025 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	mercury (elemental)	Mercury, (as Hg): Alkyl compounds	0.01 mg/m3	0.03 mg/m3	Not Available	Skin
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	mercury (elemental)	Mercury, (as Hg): Inorganic forms, including metallic mercury	0.025 mg/m3	0.075 mg/m3	Not Available	Skin
Canada - Manitoba Occupational Exposure Limits	mercury (elemental)	Not Available	0.025 mg/m3	Not Available	Not Available	TLV® Basis: CNS impair; kidney dam; BEI
Canada - British Columbia Occupational Exposure Limits	mercury (elemental)	Mercury - Elemental, as Hg	0.025 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	mercury (elemental)	Mercury, all forms except alkyl, as Hg - Elemental and inorganic forms	0.025 mg/m3	Not Available	Not Available	TLV® Basis: CNS impair; kidney dam; BEI
Canada - Ontario Occupational Exposure Limits	mercury (elemental)	Mercury, elemental mercury, inorganic and organic compounds of mercury, as Hg - All forms of except alkyl, as Hg	0.025 mg/m3	Not Available	Not Available	* Denotes a chemical agent listed in Table 1 of Ontario Regulation 490/09 (Designated Substances) made under the Act. See clause 2 (2) (a) of this Regulation.
Canada - Northwest Territories Occupational Exposure Limits	mercury (elemental)	Mercury, (as Hg): Inorganic forms, including metallic mercury	0.025 mg/m3	0.075 mg/m3	Not Available	Skin
Canada - Northwest Territories Occupational Exposure Limits	mercury (elemental)	Mercury, (as Hg): Alkyl compounds	0.01 mg/m3	0.03 mg/m3	Not Available	Skin
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	mercury (elemental)	Mercury, mercury vapor (as Hg)	0.025 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	chromium	Chromium - Metal and insoluble salts	0.1 mg/m3	3.0 mg/m3	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	chromium	Chromium - Metal	0.5 mg/m3	Not Available	Not Available	TLV Basis: upper respiratory tract & skin irritation
Canada - Alberta Occupational Exposure Limits	chromium	Chromium, metal and inorganic compounds, as Cr: Water-soluble Cr VI compounds	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	chromium	Chromium, metal and inorganic compounds, as Cr: Insoluble Cr VI compounds	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - Alberta Occupational Exposure Limits	chromium	Chromium, metal and inorganic compounds, as Cr: Metal and Cr III compounds	0.5 mg/m3	Not Available	Not Available	Not Available
Canada - Manitoba Occupational Exposure Limits	chromium	Not Available	0.5 mg/m3	Not Available	Not Available	TLV® Basis: URT & skin irr
Canada - British Columbia Occupational Exposure Limits	chromium	Chromium - Metal	0.5 mg/m3	Not Available	Not Available	Not Available

Lithium-ion battery in equipment - Radii Plus and Radii Cal

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Canada - Prince Edward Island Occupational Exposure Limits	chromium	Chromium, and inorganic compounds, as Cr - Metal and Cr III compounds	0.5 mg/m3	Not Available	Not Available	TLV® Basis: URT & skin irr
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	chromium	Chromium (metal)	0.5 mg/m3	Not Available	Not Available	Not Available
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	cadmium	K Cadmium oxide production (as Cd)	Not Available	Not Available	Not Available	(See Table 14)
Canada - Yukon Permissible Concentrations for Airborne Contaminant Substances	cadmium	Cadmium oxide fume (as Cd)	0.05 mg/m3	Not Available	Not Available	Not Available
Canada - Nova Scotia Occupational Exposure Limits	cadmium	Cadmium - Metal & compounds (as Cd)	0.002 mg/m3	Not Available	Not Available	TLV Basis: kidney damage
Canada - Nova Scotia Occupational Exposure Limits	cadmium	Cadmium - Metal & compounds (as Cd)	0.01 mg/m3	Not Available	Not Available	TLV Basis: kidney damage
Canada - Alberta Occupational Exposure Limits	cadmium	Cadmium, elemental	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	cadmium	Cadmium, and compounds, (as Cd): (total fraction)	0.01 mg/m3	0.03 mg/m3	Not Available	T20
Canada - Saskatchewan Occupational Health and Safety Regulations - Contamination Limits	cadmium	Cadmium, and compounds, (as Cd): (respirable fraction++)	0.002 mg/m3	0.006 mg/m3	Not Available	T20
Canada - Manitoba Occupational Exposure Limits	cadmium	Not Available	0.01 mg/m3	Not Available	Not Available	TLV® Basis: Kidney dam; BEI
Canada - British Columbia Occupational Exposure Limits	cadmium	Cadmium and compounds, as Cd	0.01 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	cadmium	Cadmium and compounds, Respirable, as Cd	0.002 mg/m3	Not Available	Not Available	Not Available
Canada - Prince Edward Island Occupational Exposure Limits	cadmium	Cadmium	0.01 mg/m3	Not Available	Not Available	TLV® Basis: Kidney dam; BEI
Canada - Northwest Territories Occupational Exposure Limits	cadmium	Cadmium, and compounds, (as Cd): (total fraction)	0.01 mg/m3	0.03 mg/m3	Not Available	Schedule R
Canada - Northwest Territories Occupational Exposure Limits	cadmium	Cadmium, and compounds, (as Cd): (respirable fraction)	0.002 mg/m3	0.006 mg/m3	Not Available	Schedule R
Canada - Quebec Permissible Exposure Values for Airborne Contaminants	cadmium	Cadmium elemental and compounds (as Cd)	0.025 mg/m3	Not Available	Not Available	Not Available
Canada - British Columbia Occupational Exposure Limits	bisphenol A/ phosgene polymer	Particles (Insoluble or Poorly Soluble) Not Otherwise Classified (PNOC)	10 mg/m3	Not Available	Not Available	(N) - the 8-hour TWA listed in the Table is for the total dust. The substance also has an 8-hour TWA of 3 mg/m ³ for the respirable fraction.

Emergency Limits

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
lithium fluorophosphate	Lithium hexafluorophosphate	7.5 mg/m3	83 mg/m3	500 mg/m3
ethylene carbonate	Glycol carbonate; (Ethylene carbonate)	30 mg/m3	330 mg/m3	2,000 mg/m3
graphite	Carbon; (Graphite, 7782-42-5)	6 mg/m3	330 mg/m3	2,000 mg/m3
lead	Lead	0.15 mg/m3	120 mg/m3	700 mg/m3
mercury (elemental)	Mercury vapor	0.15 mg/m3	Not Available	Not Available
lead	Lead	0.15 mg/m3	120 mg/m3	700 mg/m3
mercury (elemental)	Mercury vapor	0.15 mg/m3	Not Available	Not Available
chromium	Chromium	1.5 mg/m3	17 mg/m3	99 mg/m3
cadmium	Cadmium	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
lithium cobaltate	Not Available	Not Available
lithium fluorophosphate	Not Available	Not Available
ethylene carbonate	Not Available	Not Available
graphite	1,250 mg/m3	Not Available
lead	Not Available	Not Available
mercury (elemental)	10 mg/m3	Not Available
lead	Not Available	Not Available
mercury (elemental)	10 mg/m3	Not Available
chromium	250 mg/m3	Not Available

Continued...

Lithium-ion battery in equipment - Radii Plus and Radii Cal

Ingredient	Original IDLH	Revised IDLH
cadmium	9 mg/m ³	Not Available
bisphenol A/ phosgene polymer	Not Available	Not Available

Occupational Exposure Banding


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
lithium fluorophosphate	E	≤ 0.01 mg/m ³
ethylene carbonate	E	≤ 0.01 mg/m ³

Notes:

Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.

MATERIAL DATA

Exposure controls

Appropriate engineering controls	None under normal operating conditions. Provide adequate ventilation in warehouse or closed storage areas.
Personal protection	
Eye and face protection	None under normal operating conditions. OTHERWISE: ▶ Safety glasses.
Skin protection	See Hand protection below
Hands/feet protection	None under normal operating conditions. OTHERWISE: ▶ Rubber Gloves
Body protection	See Other protection below
Other protection	None under normal operating conditions. OTHERWISE: ▶ Overalls. ▶ PVC Apron. ▶ PVC protective suit may be required if exposure severe. ▶ Eyewash unit. ▶ Ensure there is ready access to a safety shower.

Respiratory protection

Type AHG-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AHG-AUS P2	-	AHG-PAPR-AUS / Class 1 P2
up to 50 x ES	-	AHG-AUS / Class 1 P2	-
up to 100 x ES	-	AHG-2 P2	AHG-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- ▶ The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- ▶ Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- ▶ Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection program.
- ▶ Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

Appearance	Solid articles, insoluble in water.		
Physical state	Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available

Continued...

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	Product is considered stable and hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	Not normally a hazard due to physical form of product.
Ingestion	Considered an unlikely route of entry in commercial/industrial environments Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion may result in nausea, abdominal irritation, pain and vomiting
Skin Contact	Not normally a hazard due to physical form of product.
Eye	Not normally a hazard due to physical form of product.
Chronic	Not normally a hazard due to physical form of product.

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal	TOXICITY	IRRITATION
	Not Available	Not Available
lithium cobaltate	TOXICITY	IRRITATION
	Not Available	Not Available
lithium fluorophosphate	TOXICITY	IRRITATION
	Oral (rat) LD50: 50-300 mg/kg ^[1]	Not Available
ethylene carbonate	TOXICITY	IRRITATION
	Not Available	Eye (rabbit): 20 mg - mild
		Eye: adverse effect observed (irritating) ^[1]
		Skin (rabbit): 660 mg - moderate
		Skin: no adverse effect observed (not irritating) ^[1]
graphite	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[2]	Not Available
lead	TOXICITY	IRRITATION
	0.01 mg/kg ^[2]	Not Available
	450 mg/kg ^[2]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
mercury (elemental)	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

lead	TOXICITY	IRRITATION
	0.01 mg/kg ^[2]	Not Available
	450 mg/kg ^[2]	
	Oral (rat) LD50: >2000 mg/kg ^[1]	
mercury (elemental)	TOXICITY	IRRITATION
	Oral (rat) LD50: >2000 mg/kg ^[1]	Not Available
chromium	TOXICITY	IRRITATION
	Not Available	Not Available
cadmium	TOXICITY	IRRITATION
	39 mg/kg ^[2]	Not Available
	70 mg/kg ^[2]	
	88 mg/kg ^[2]	
	Inhalation (rat) LC50: 0.003125 mg/l/30m ^[2]	
	Oral (rat) LD50: 225 mg/kg ^[2]	
bisphenol A/ phosgene polymer	TOXICITY	IRRITATION
	Not Available	Not Available
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

LITHIUM COBALTATE	<p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens).</p> <p>Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis.</p> <p>Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.</p> <p>Goitrogenic:</p> <p>Goitrogens are substances that suppress the function of the thyroid gland by interfering with iodine uptake, which can, as a result, cause an enlargement of the thyroid, i.e., a goitre</p> <p>Goitrogens include:</p> <ul style="list-style-type: none"> ▶ Vitexin, a flavanoid, which inhibits thyroid peroxidase thus contributing to goiter. ▶ Ions such as thiocyanate and perchlorate which decrease iodide uptake by competitive inhibition; as a consequence of reduced thyroxine and triiodothyronine secretion by the gland, at low doses, this causes an increased release of thyrotropin (by reduced negative feedback), which then stimulates the gland. ▶ Lithium which inhibits thyroid hormone release. ▶ Certain foods, such as soy and millet (containing vitexins) and vegetables in the genus Brassica (e.g. broccoli, brussels sprouts, cabbage, horseradish). ▶ Caffeine (in coffee, tea, cola, chocolate) which acts on thyroid function as a suppressant.
	ETHYLENE CARBONATE

Lithium-ion battery in equipment - Radii Plus and Radii Cal

(hydrocephalus, umbilical herniation, gastroschisis, cleft palate, misshapen and compressed stomach) and skeletal malformations at 3000 mg/kg/day, but not at 1500 mg/kg/day.

For ethylene glycol:

Ethylene glycol is quickly and extensively absorbed through the gastrointestinal tract. Limited information suggests that it is also absorbed through the respiratory tract; dermal absorption is apparently slow. Following absorption, ethylene glycol is distributed throughout the body according to total body water. In most mammalian species, including humans, ethylene glycol is initially metabolised by alcohol dehydrogenase to form glycolaldehyde, which is rapidly converted to glycolic acid and glyoxal by aldehyde oxidase and aldehyde dehydrogenase. These metabolites are oxidised to glyoxylate; glyoxylate may be further metabolised to formic acid, oxalic acid, and glycine. Breakdown of both glycine and formic acid can generate CO₂, which is one of the major elimination products of ethylene glycol. In addition to exhaled CO₂, ethylene glycol is eliminated in the urine as both the parent compound and glycolic acid. Elimination of ethylene glycol from the plasma in both humans and laboratory animals is rapid after oral exposure; elimination half-lives are in the range of 1-4 hours in most species tested.

Respiratory Effects. Respiratory system involvement occurs 12-24 hours after ingestion of sufficient amounts of ethylene glycol and is considered to be part of a second stage in ethylene glycol poisoning. The symptoms include hyperventilation, shallow rapid breathing, and generalized pulmonary edema with calcium oxalate crystals occasionally present in the lung parenchyma. Respiratory system involvement appears to be dose-dependent and occurs concomitantly with cardiovascular changes. Pulmonary infiltrates and other changes compatible with adult respiratory distress syndrome (ARDS) may characterise the second stage of ethylene glycol poisoning. Pulmonary oedema can be secondary to cardiac failure, ARDS, or aspiration of gastric contents. Symptoms related to acidosis such as hyperpnea and tachypnea are frequently observed; however, major respiratory morbidities such as pulmonary edema and bronchopneumonia are relatively rare and usually only observed with extreme poisoning (e.g., in only 5 of 36 severely poisoned cases).

Cardiovascular Effects. Cardiovascular system involvement in humans occurs at the same time as respiratory system involvement, during the second phase of oral ethylene glycol poisoning, which is 12-24 hours after acute exposure. The symptoms of cardiac involvement include tachycardia, ventricular gallop and cardiac enlargement. Ingestion of ethylene glycol may also cause hypertension or hypotension, which may progress to cardiogenic shock. Myocarditis has been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol. As in the case of respiratory effects, cardiovascular involvement occurs with ingestion of relatively high doses of ethylene glycol. Nevertheless, circulatory disturbances are a rare occurrence, having been reported in only 8 of 36 severely poisoned cases. Therefore, it appears that acute exposure to high levels of ethylene glycol can cause serious cardiovascular effects in humans. The effects of a long-term, low-dose exposure are unknown.

Gastrointestinal Effects. Nausea, vomiting with or without blood, pyrosis, and abdominal cramping and pain are common early effects of acute ethylene glycol ingestion. Acute effects of ethylene glycol ingestion in one patient included intermittent diarrhea and abdominal pain, which were attributed to mild colonic ischaemia; severe abdominal pain secondary to colonic stricture and perforation developed 3 months after ingestion, and histology of the resected colon showed birefringent crystals highly suggestive of oxalate deposition.

Musculoskeletal Effects. Reported musculoskeletal effects in cases of acute ethylene glycol poisoning have included diffuse muscle tenderness and myalgias associated with elevated serum creatinine phosphokinase levels, and myoclonic jerks and tetanic contractions associated with hypocalcaemia.

Hepatic Effects. Central hydropic or fatty degeneration, parenchymal necrosis, and calcium oxalate crystals in the liver have been observed at autopsy in cases of people who died following acute ingestion of ethylene glycol.

Renal Effects. Adverse renal effects after ethylene glycol ingestion in humans can be observed during the third stage of ethylene glycol toxicity 24-72 hours after acute exposure. The hallmark of renal toxicity is the presence of birefringent calcium oxalate monohydrate crystals deposited in renal tubules and their presence in urine after ingestion of relatively high amounts of ethylene glycol. Other signs of nephrotoxicity can include tubular cell degeneration and necrosis and tubular interstitial inflammation. If untreated, the degree of renal damage caused by high doses of ethylene glycol progresses and leads to haematuria, proteinuria, decreased renal function, oliguria, anuria, and ultimately renal failure. These changes in the kidney are linked to acute tubular necrosis but normal or near normal renal function can return with adequate supportive therapy.

Metabolic Effects. One of the major adverse effects following acute oral exposure of humans to ethylene glycol involves metabolic changes. These changes occur as early as 12 hours after ethylene glycol exposure. Ethylene glycol intoxication is accompanied by metabolic acidosis which is manifested by decreased pH and bicarbonate content of serum and other bodily fluids caused by accumulation of excess glycolic acid. Other characteristic metabolic effects of ethylene glycol poisoning are increased serum anion gap, increased osmolal gap, and hypocalcaemia. Serum anion gap is calculated from concentrations of sodium, chloride, and bicarbonate, is normally 12-16 mM, and is typically elevated after ethylene glycol ingestion due to increases in unmeasured metabolite anions (mainly glycolate).

Neurological Effects: Adverse neurological reactions are among the first symptoms to appear in humans after ethylene glycol ingestion. These early neurotoxic effects are also the only symptoms attributed to unmetabolised ethylene glycol. Together with metabolic changes, they occur during the period of 30 minutes to 12 hours after exposure and are considered to be part of the first stage in ethylene glycol intoxication. In cases of acute intoxication, in which a large amount of ethylene glycol is ingested over a very short time period, there is a progression of neurological manifestations which, if not treated, may lead to generalized seizures and coma. Ataxia, slurred speech, confusion, and somnolence are common during the initial phase of ethylene glycol intoxication as are irritation, restlessness, and disorientation. Cerebral edema and crystalline deposits of calcium oxalate in the walls of small blood vessels in the brain were found at autopsy in people who died after acute ethylene glycol ingestion. Effects on cranial nerves appear late (generally 5-20 days post-ingestion), are relatively rare, and according to some investigators constitute a fourth, late cerebral phase in ethylene glycol intoxication. Clinical manifestations of the cranial neuropathy commonly involve lower motor neurons of the facial and bulbar nerves and are reversible over many months.

Reproductive Effects: Reproductive function after intermediate-duration oral exposure to ethylene glycol has been tested in three multi-generation studies (one in rats and two in mice) and several shorter studies (15-20 days in rats and mice). In these studies, effects on fertility, foetal viability, and male reproductive organs were observed in mice, while the only effect in rats was an increase in gestational duration.

Developmental Effects: The developmental toxicity of ethylene glycol has been assessed in several acute-duration studies using mice, rats, and rabbits. Available studies indicate that malformations, especially skeletal malformations occur in both mice and rats exposed during gestation; mice are apparently more sensitive to the developmental effects of ethylene glycol. Other evidence of embryotoxicity in laboratory animals exposed to ethylene glycol exposure includes reduction in foetal body weight.

Cancer: No studies were located regarding cancer effects in humans or animals after dermal exposure to ethylene glycol.

Genotoxic Effects: Studies in humans have not addressed the genotoxic effects of ethylene glycol. However, available *in vivo* and *in vitro* laboratory studies provide consistently negative genotoxicity results for ethylene glycol.

CHROMIUM

Gastrointestinal tumours, lymphoma, musculoskeletal tumours and tumours at site of application recorded.

For chrome(III) and other valence states (except hexavalent):

For inhalation exposure, all trivalent and other chromium compounds are treated as particulates, not gases.

The mechanisms of chromium toxicity are very complex, and although many studies on chromium are available, there is a great deal of uncertainty about how chromium exerts its toxic influence. Much more is known about the mechanisms of hexavalent chromium toxicity than trivalent chromium toxicity. There is an abundance of information available on the carcinogenic potential of chromium compounds and on the genotoxicity and mutagenicity of chromium compounds in experimental systems. The consensus from various reviews and agencies is that evidence of carcinogenicity of elemental, divalent, or trivalent chromium compounds is lacking. Epidemiological studies of workers in a number of industries (chromate production, chromate pigment production and use, and chrome plating) conclude that while occupational exposure to hexavalent chromium compounds is associated with an increased risk of respiratory system cancers (primarily bronchogenic and nasal), results from occupational exposure studies to mixtures that were mainly elemental and trivalent (ferrochromium alloy worker) were inconclusive. Studies in leather tanners, who were exposed to trivalent chromium were consistently negative. In addition to the lack of direct evidence of carcinogenicity of trivalent or elemental chromium and its compounds, the genotoxic evidence is overwhelmingly negative.

The lesser potency of trivalent chromium relative to hexavalent chromium is likely related to the higher redox potential of hexavalent chromium and its greater ability to enter cells.

The general inability of trivalent chromium to traverse membranes and thus be absorbed or reach peripheral tissue in significant amounts is generally accepted as a probable explanation for the overall absence of systemic trivalent chromium toxicity. Elemental and divalent forms of chromium are not able to traverse membranes readily either. This is not to say that elemental, divalent, or trivalent chromium compounds cannot traverse membranes and reach peripheral tissue, the mechanism of absorption is simply less efficient in comparison to absorption of hexavalent

Lithium-ion battery in equipment - Radii Plus and Radii Cal

	<p>chromium compounds. Hexavalent chromium compounds exist as tetrahedral chromate anions, resembling the forms of other natural anions like sulfate and phosphate which are permeable across nonselective membranes. Trivalent chromium forms octahedral complexes which cannot easily enter through these channels, instead being absorbed via passive diffusion and phagocytosis. Although trivalent chromium is less well absorbed than hexavalent chromium, workers exposed to trivalent compounds have had detectable levels of chromium in the urine at the end of a workday. Absorbed chromium is widely distributed throughout the body via the bloodstream, and can reach the foetus. Although there is ample in vivo evidence that hexavalent chromium is efficiently reduced to trivalent chromium in the gastrointestinal tract and can be reduced to the trivalent form by ascorbate and glutathione in the lungs, there is no evidence that trivalent chromium is converted to hexavalent chromium in biological systems. In general, trivalent chromium compounds are cleared rapidly from the blood and more slowly from the tissues. Although not fully characterized, the biologically active trivalent chromium molecule appears to be chromodulin, also referred to as (GTF). Chromodulin is an oligopeptide complex containing four chromic ions. Chromodulin may facilitate interactions of insulin with its receptor site, influencing protein, glucose, and lipid metabolism. Inorganic trivalent chromium compounds, which do not appear to have insulin-potentiating properties, are capable of being converted into biologically active forms by humans and animals</p> <p>Chromium can be a potent sensitiser in a small minority of humans, both from dermal and inhalation exposures.</p> <p>The most sensitive endpoint identified in animal studies of acute exposure to trivalent chromium appears to involve the respiratory system. Specifically, acute exposure to trivalent chromium is associated with impaired lung function and lung damage.</p> <p>Based on what is known about absorption of chromium in the human body, its potential mechanism of action in cells, and occupational data indicating that valence states other than hexavalent exhibit a relative lack of toxicity the toxicity of elemental and divalent chromium compounds is expected to be similar to or less than common trivalent forms.</p> <p>The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing. Tenth Annual Report on Carcinogens: Substance known to be Carcinogenic <i>[National Toxicology Program: U.S. Dep. of Health and Human Services 2002]</i></p>		
BISPHENOL A/ PHOSGENE POLYMER	<p>The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics</p> <p>Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity. Results suggest that the 4-hydroxyl group of the A-phenyl ring and the B-phenyl ring of BPA derivatives are required for these hormonal activities, and substituents at the 3,5-positions of the phenyl rings and the bridging alkyl moiety markedly influence the activities.</p> <p>Bisphenols promoted cell proliferation and increased the synthesis and secretion of cell type-specific proteins. When ranked by proliferative potency, the longer the alkyl substituent at the bridging carbon, the lower the concentration needed for maximal cell yield; the most active compound contained two propyl chains at the bridging carbon. Bisphenols with two hydroxyl groups in the para position and an angular configuration are suitable for appropriate hydrogen bonding to the acceptor site of the oestrogen receptor.</p>		
LITHIUM COBALTATE & LITHIUM FLUOROPHOSPHATE & GRAPHITE & CHROMIUM & BISPHENOL A/ PHOSGENE POLYMER	No significant acute toxicological data identified in literature search.		
LITHIUM FLUOROPHOSPHATE & ETHYLENE CARBONATE & GRAPHITE & MERCURY (ELEMENTAL)	<p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p>		
LEAD	WARNING: Lead is a cumulative poison and has the potential to cause abortion and intellectual impairment to unborn children of pregnant workers.		
MERCURY (ELEMENTAL)	Animal studies have shown that mercury may be a reproductive effector.		
Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✗
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

Legend: ✗ – Data either not available or does not fill the criteria for classification
✓ – Data available to make classification

SECTION 12 Ecological information

Toxicity

Lithium-ion battery in equipment - Radii Plus and Radii Cal	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
lithium cobaltate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.406mg/L	2
	EC50	48	Crustacea	0.002-0.618mg/L	2
	EC50	96	Algae or other aquatic plants	0.071-0.314mg/L	2
	NOEC	96	Crustacea	0.001-0.2819mg/L	2

Continued...

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

lithium fluorophosphate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	42mg/L	2
	EC50	48	Crustacea	98mg/L	2
	EC50	96	Algae or other aquatic plants	43mg/L	2
	NOEC	528	Fish	0.2mg/L	2
ethylene carbonate	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>100mg/L	2
	EC50	48	Crustacea	>100mg/L	2
	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	72	Algae or other aquatic plants	100mg/L	2
graphite	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>100mg/L	2
	EC50	48	Crustacea	>100mg/L	2
	EC50	72	Algae or other aquatic plants	>100mg/L	2
	NOEC	72	Algae or other aquatic plants	>=100mg/L	2
lead	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.3558mg/L	2
	EC50	48	Crustacea	0.029mg/L	2
	EC50	72	Algae or other aquatic plants	0.0205mg/L	2
	NOEC	240	Algae or other aquatic plants	0.001-mg/L	2
mercury (elemental)	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.15mg/L	2
	EC50	48	Crustacea	0.0003mg/L	2
	EC50	96	Algae or other aquatic plants	0.009mg/L	2
	NOEC	2688	Crustacea	0.00025mg/L	2
lead	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.3558mg/L	2
	EC50	48	Crustacea	0.029mg/L	2
	EC50	72	Algae or other aquatic plants	0.0205mg/L	2
	NOEC	240	Algae or other aquatic plants	0.001-mg/L	2
mercury (elemental)	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.15mg/L	2
	EC50	48	Crustacea	0.0003mg/L	2
	EC50	96	Algae or other aquatic plants	0.009mg/L	2
	NOEC	2688	Crustacea	0.00025mg/L	2
chromium	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
cadmium	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	0.001-0.5mg/L	2
	EC50	48	Crustacea	2.1mg/L	5
	EC50	72	Algae or other aquatic plants	0.018mg/L	2
	NOEC	504	Crustacea	0.00016mg/L	2
bisphenol A/ phosgene polymer	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data				

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
------------	-------------------------	------------------

Continued...

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

Ingredient	Persistence: Water/Soil	Persistence: Air
ethylene carbonate	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
ethylene carbonate	LOW (LogKOW = -0.3388)

Mobility in soil

Ingredient	Mobility
ethylene carbonate	LOW (KOC = 9.168)


SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal	
	Consult State Land Waste Management Authority for disposal. Bury residue in an authorised landfill.

SECTION 14 Transport information

Labels Required

	
Marine Pollutant	NO

Land transport (TDG)

UN number	3481	
UN proper shipping name	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT (including lithium ion polymer batteries); or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)	
Transport hazard class(es)	Class	9
	Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	34, 123, 137, 138, 159
	Explosive Limit and Limited Quantity Index	0
	ERAP Index	Not Applicable

Air transport (ICAO-IATA / DGR)

UN number	3481	
UN proper shipping name	Lithium ion batteries packed with equipment (including lithium ion polymer batteries); Lithium ion batteries contained in equipment (including lithium ion polymer batteries)	
Transport hazard class(es)	ICAO/IATA Class	9
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	12FZ
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	A48 A88 A99 A154 A164 A181 A185 A206 A213; A88 A99 A154 A164 A181 A185 A206 A213
	Cargo Only Packing Instructions	967; 966
	Cargo Only Maximum Qty / Pack	35 kg
	Passenger and Cargo Packing Instructions	967; 966
	Passenger and Cargo Maximum Qty / Pack	5 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Forbidden
	Passenger and Cargo Limited Maximum Qty / Pack	Forbidden

Sea transport (IMDG-Code / GGVSee)

UN number	3481
-----------	------

Lithium-ion battery in equipment - Ralii Plus and Ralii Cal

UN proper shipping name	LITHIUM ION BATTERIES CONTAINED IN EQUIPMENT or LITHIUM ION BATTERIES PACKED WITH EQUIPMENT (including lithium ion polymer batteries)	
Transport hazard class(es)	IMDG Class	9
	IMDG Subrisk	Not Applicable
Packing group	Not Applicable	
Environmental hazard	Not Applicable	
Special precautions for user	EMS Number	F-A , S-I
	Special provisions	188 230 310 348 360 376 377 384 387
	Limited Quantities	0

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 Regulatory information**Safety, health and environmental regulations / legislation specific for the substance or mixture**

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

lithium cobaltate is found on the following regulatory lists

Canada Domestic Substances List (DSL)

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

lithium fluorophosphate is found on the following regulatory lists

Canada Non-Domestic Substances List (NDSL)

ethylene carbonate is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

graphite is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

lead is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1 : Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

mercury (elemental) is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

lead is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1 : Carcinogenic to humans

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B : Possibly carcinogenic to humans

mercury (elemental) is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

chromium is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

cadmium is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

Canada Toxicological Index Service - Workplace Hazardous Materials Information System - WHMIS GHS

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 1 : Carcinogenic to humans

Continued...

Lithium-ion battery in equipment - Radii Plus and Radii Cal

bisphenol A/ phosgene polymer is found on the following regulatory lists

Canada Categorization decisions for all DSL substances

Canada Domestic Substances List (DSL)

National Inventory Status

National Inventory	Status
Australia - AIIC	Yes
Australia - Non-Industrial Use	No (lithium cobaltate; lithium fluorophosphate; ethylene carbonate; graphite; lead; mercury (elemental); lead; mercury (elemental); chromium; cadmium; bisphenol A/ phosgene polymer)
Canada - DSL	No (lithium fluorophosphate)
Canada - NDSL	No (lithium cobaltate; ethylene carbonate; graphite; lead; mercury (elemental); lead; mercury (elemental); chromium; cadmium; bisphenol A/ phosgene polymer)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (bisphenol A/ phosgene polymer)
Japan - ENCS	No (lithium fluorophosphate; graphite; lead; mercury (elemental); lead; mercury (elemental); chromium; cadmium; bisphenol A/ phosgene polymer)
Korea - KECI	Yes
New Zealand - NZIoC	No (lithium fluorophosphate)
Philippines - PICCS	No (lithium cobaltate)
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	No (lithium cobaltate; lithium fluorophosphate; ethylene carbonate; bisphenol A/ phosgene polymer)
Vietnam - NCI	No (lithium cobaltate)
Russia - ARIPS	No (lithium cobaltate; lithium fluorophosphate; bisphenol A/ phosgene polymer)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing (see specific ingredients in brackets)

SECTION 16 Other information

Revision Date	01/11/2019
Initial Date	15/12/2015

SDS Version Summary

Version	Issue Date	Sections Updated
3.1.1.1	12/01/2016	Disposal, Fire Fighter (fire/explosion hazard), First Aid (inhaled), Storage (suitable container)
4.1.1.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average
 PC – STEL: Permissible Concentration-Short Term Exposure Limit
 IARC: International Agency for Research on Cancer
 ACGIH: American Conference of Governmental Industrial Hygienists
 STEL: Short Term Exposure Limit
 TEEL: Temporary Emergency Exposure Limit.
 IDLH: Immediately Dangerous to Life or Health Concentrations
 OSF: Odour Safety Factor
 NOAEL :No Observed Adverse Effect Level
 LOAEL: Lowest Observed Adverse Effect Level
 TLV: Threshold Limit Value
 LOD: Limit Of Detection
 OTV: Odour Threshold Value
 BCF: BioConcentration Factors
 BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited
 3-15 Brunson Street, Bayswater Victoria, 3153, Australia
 Phone Number: +61 3 8727 7111
 Department issuing SDS: Research and Development
 Contact: Technical Director