

## **SAFETY DATA SHEETS**

**This SDS packet was issued with item:**

071028125

**The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).**

071058155 071058163

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

71028125

# SAFETY DATA SHEET

## TOKUYAMA UNIVERSAL BOND BOND A

### 1. Identification

#### Product identifier

**Product name** TOKUYAMA UNIVERSAL BOND BOND A

#### Recommended use of the chemical and restrictions on use

**Application** Dental adhesive. For dental professionals only.

#### Details of the supplier of the safety data sheet

**Supplier** Tokuyama Dental America, Inc.  
740 Garden View Ct., Suite 200 Encinitas,  
CA 92024 U.S.A.  
Tel: (877) 378 3548 (Toll-Free)  
Tel: (760)942-7211  
Fax: (760)942-7212

**Contact Person** <http://www.tokuyama-dental.com/tdc/contact.html>

**Manufacturer** Tokuyama Dental Corporation  
38-9, Taitou 1-chome, Taitou-ku, Tokyo  
110-0016, Japan  
TEL: +81-3-3835-2261  
FAX: +81-3-3835-2265

#### Emergency telephone number

**Emergency telephone** California Poison Control System - San Francisco Division  
San Francisco General Hospital  
Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco  
Emergency telephone number: +1 800 222 1222  
E-mail address: [coadmin@calpoison.org](mailto:coadmin@calpoison.org)  
<http://www.calpoison.org>

National Capital Poison Center  
3201 New Mexico Ave, Ste 310, Washington DC  
Emergency telephone number: +1 800 222 1222  
Telephone number: +1 202 362 3867  
Facsimile number: +1 202 362 8377  
E-mail address: [pc@poison.org](mailto:pc@poison.org)  
<http://www.poison.org>

### 2. Hazard(s) identification

#### Classification of the substance or mixture

**OSHA Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Skin Irrit. 2 - H315: Eye Irrit. 2A - H319: Skin Sens. 1 - H317: STOT SE 3 - H336

**Environmental hazards** Not Classified

#### Label elements

# TOKUYAMA UNIVERSAL BOND BOND A

## Pictogram



## Signal word

Danger

## Hazard statements

H225 Highly flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H317 May cause an allergic skin reaction.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

## Precautionary statements

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
 P240 Ground/ bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing vapor/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P302+P352 If on skin: Wash with plenty of water.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a poison center/ doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.  
 P501 Dispose of contents/ container in accordance with local regulations.

## Contains

ACETONE, 2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER, 2-HYDROXYETHYL METHACRYLATE, TRIETHYLENE GLYCOL DIMETHACRYLATE

## Other hazards

### Hazards not otherwise classified (HNOC)

Not applicable.

## 3. Composition/information on ingredients

### Mixtures

ACETONE

30-60%

CAS number: 67-64-1

## TOKUYAMA UNIVERSAL BOND BOND A

<b>2-PROPENOIC ACID, 2-METHYL-, (1-METHYLETHYLIDENE)BIS[4,1-PHENYLENEOXY(2-HYDROXY-3,1-PROPANEDIYL)] ESTER</b> CAS number: 1565-94-2	<b>10-30%</b>
<b>2-HYDROXYETHYL METHACRYLATE</b> CAS number: 868-77-9	<b>10-30%</b>
<b>TRIETHYLENE GLYCOL DIMETHACRYLATE</b> CAS number: 109-16-0	<b>5-10%</b>
<b>METHACRYLOXYALKYL ACID PHOSPHATE (PHOSPHORIC ACID MONOMER)</b> CAS number: 52628-03-2	<b>1-5%</b>
<b>2,6-DI-tert-BUTYL-p-CRESOL</b> CAS number: 128-37-0 M factor (Chronic) = 1	<b>&lt;1%</b>

#### 4. First-aid measures

##### Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Keep affected person under observation. Get medical attention.
<b>Skin Contact</b>	Wash skin thoroughly with soap and water. In the event of any sensitization symptoms developing, ensure further exposure is avoided. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

##### Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Skin contact</b>	Irritating to skin. May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	Irritating to eyes.

##### Indication of immediate medical attention and special treatment needed

## TOKUYAMA UNIVERSAL BOND BOND A

**Notes for the doctor**                      Treat symptomatically.

### 5. Fire-fighting measures

#### Extinguishing media

**Suitable extinguishing media**      Highly flammable gases or vapors. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media**      Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture

**Specific hazards**                      Highly flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.

**Hazardous combustion products**      Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

#### Advice for firefighters

**Protective actions during firefighting**      Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters**      Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

**Personal precautions**                      Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapors. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.

#### Environmental precautions

**Environmental precautions**              Avoid discharge into drains or watercourses or onto the ground.

#### Methods and material for containment and cleaning up

**Methods for cleaning up**                      Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Do not allow material to enter confined spaces, due to the risk of explosion. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.

**Reference to other sections**              For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## TOKUYAMA UNIVERSAL BOND BOND A

### 7. Handling and storage

#### Precautions for safe handling

##### **Usage precautions**

Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Avoid breathing gas, fume, vapours or spray. Handle all packages and containers carefully to minimize spills. Avoid the formation of mists. Keep container tightly sealed when not in use. Do not handle broken packages without protective equipment. Keep away from food, drink and animal feeding stuffs.

##### **Advice on general occupational hygiene**

Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

#### Conditions for safe storage, including any incompatibilities

##### **Storage precautions**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed, in a cool, well ventilated place. Store locked up. Keep only in the original container. Protect containers from damage. Store away from the following materials: Oxidizing materials. Organic peroxides/hydroperoxides.

#### Specific end uses(s)

##### **Specific end use(s)**

The identified uses for this product are detailed in Section 1.2.

### 8. Exposure Controls/personal protection

#### Control parameters

#### Occupational exposure limits

##### **ACETONE**

Long-term exposure limit (8-hour TWA): ACGIH 250 ppm 594 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 500 ppm 1187 mg/m<sup>3</sup>

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m<sup>3</sup>

##### **2,6-DI-tert-BUTYL-p-CRESOL**

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m<sup>3</sup> inhalable fraction and vapor

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

A4 = Not Classifiable as a Human Carcinogen.

OSHA = Occupational Safety and Health Administration.

#### Exposure controls

##### **Appropriate engineering controls**

Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Observe any occupational exposure limits for the product or ingredients.

##### **Eye/face protection**

Wear tight-fitting, chemical splash goggles or face shield.

##### **Hand protection**

Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.

## TOKUYAMA UNIVERSAL BOND BOND A

<b>Other skin and body protection</b>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<b>Hygiene measures</b>	Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing and wash it before reuse.
<b>Respiratory protection</b>	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Liquid
<b>Color</b>	Colorless ~ Yellow
<b>Odor</b>	Characteristic
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	>35°C
<b>Flash point</b>	-17.6°C
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.968
<b>Solubility(ies)</b>	No information available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not available.
<b>Oxidizing properties</b>	Not available.

### 10. Stability and reactivity

<b>Reactivity</b>	The following materials may react violently with the product: Oxidizing materials. Organic peroxides/hydroperoxides. See the other subsections of this section for further details.
-------------------	---

## TOKUYAMA UNIVERSAL BOND BOND A

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidizing materials. Organic peroxides/hydroperoxides.
<b>Conditions to avoid</b>	Vapors may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
<b>Materials to avoid</b>	Oxidizing materials. Organic peroxides/hydroperoxides.
<b>Hazardous decomposition products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).

### 11. Toxicological information

#### Information on toxicological effects

<b>Routes of exposure</b>	Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.
<b><u>Acute toxicity - oral</u></b>	
<b>Notes (oral LD<sub>50</sub>)</b>	Not available.
<b><u>Acute toxicity - dermal</u></b>	
<b>Notes (dermal LD<sub>50</sub>)</b>	Not available.
<b><u>Acute toxicity - inhalation</u></b>	
<b>Notes (inhalation LC<sub>50</sub>)</b>	Not available.
<b><u>Skin corrosion/irritation</u></b>	
<b>Skin corrosion/irritation</b>	Skin Irrit. 2 - H315, Irritating to skin.
<b>Animal data</b>	Not available.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Eye Irrit. 2 - H319 Causes serious eye irritation.
<b><u>Respiratory sensitization</u></b>	
<b>Respiratory sensitization</b>	Not available.
<b><u>Skin sensitization</u></b>	
<b>Skin sensitization</b>	Skin Sens. 1 - H317 May cause an allergic skin reaction.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	Not available.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Not available.
<b>IARC carcinogenicity</b>	Some of the ingredients are listed or exempt. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b>NTP carcinogenicity</b>	Some of the ingredients are listed or exempt.
<b>OSHA Carcinogenicity</b>	None of the ingredients are listed.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Not available.



## TOKUYAMA UNIVERSAL BOND BOND A

**Reproductive toxicity - development** Not available.

**Specific target organ toxicity - single exposure**

**STOT - single exposure** STOT SE 3 - H336 May cause drowsiness or dizziness.

**Target organs** Central nervous system

**Specific target organ toxicity - repeated exposure**

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

**Aspiration hazard**

**Aspiration hazard** Not available.

**Toxicological information on ingredients.**

### SILICON DIOXIDE

**Carcinogenicity**

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**NTP carcinogenicity** Reasonably anticipated to be a human carcinogen.

**OSHA Carcinogenicity** Not listed.

### 2,6-DI-tert-BUTYL-p-CRESOL

**Carcinogenicity**

**IARC carcinogenicity** IARC Group 3 Not classifiable as to its carcinogenicity to humans.

**NTP carcinogenicity** Reasonably anticipated to be a human carcinogen.

**OSHA Carcinogenicity** Not listed.

## 12. Ecological Information

**Toxicity**

**Toxicity** No information available.

**Acute toxicity - fish** Not available.

**Acute toxicity - aquatic invertebrates** Not available.

**Acute toxicity - aquatic plants** Not available.

**Persistence and degradability**

**Persistence and degradability** The degradability of the product is not known.

**Bioaccumulative potential**

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

**Mobility in soil**

**Mobility** Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

**Results of PBT and vPvB assessment**

## TOKUYAMA UNIVERSAL BOND BOND A

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### Other adverse effects

**Other adverse effects** None known.

## 13. Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/ regional/ national/ international regulations.

Must not be disposed of together with household garbage. Dispose at suitable refuse site. Do not allow to enter drains, sewers or watercourses. Empty containers may retain some product residues and hence be potentially hazardous.

### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

## 14. Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

### UN Number

**UN No. (IMDG)** 1133

**UN No. (ICAO)** 1133

**UN No. (DOT)** UN1133

### UN proper shipping name

**Proper shipping name (IMDG)** ADHESIVES

**Proper shipping name (ICAO)** ADHESIVES

**Proper shipping name (DOT)** ADHESIVES

### Transport hazard class(es)

**DOT hazard class** 3

**DOT hazard label** 3

**IMDG Class** 3

**ICAO class/division** 3

### Transport labels



### DOT transport labels



## TOKUYAMA UNIVERSAL BOND BOND A

### Packing group

IMDG packing group	II
ICAO packing group	II
DOT packing group	II

### Environmental hazards

#### Environmentally Hazardous Substance

No.

### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-D

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory information

**Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.

### International Regulations

#### US Federal Regulations

##### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

##### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*ACETONE*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

##### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

##### **SARA 313 Emission Reporting**

None of the ingredients are listed or exempt.

##### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

##### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

##### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

##### **SARA (311/312) Hazard Categories**

Fire  
Acute  
Chronic

##### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

## TOKUYAMA UNIVERSAL BOND BOND A

### US State Regulations

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are listed or exempt.

#### **California Air Toxics "Hot Spots" (A-I)**

The following ingredients are listed or exempt:

*SILICON DIOXIDE*

Present.

#### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

#### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*SILICON DIOXIDE*

Present.

*ACETONE*

Present.

#### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*SILICON DIOXIDE*

Present.

*ACETONE*

Present.

#### **Rhode Island "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

#### **Minnesota "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*SILICON DIOXIDE*

Present.

*ACETONE*

Present.

#### **New Jersey "Right To Know" List**

The following ingredients are listed or exempt:

**TOKUYAMA UNIVERSAL BOND BOND A**

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

**Pennsylvania "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*SILICON DIOXIDE*

Present.

*ACETONE*

Present.

**16. Other information****Revision comments**

<b>Revision date</b>	10/15/2022
<b>Revision</b>	2
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.

# SAFETY DATA SHEET

## TOKUYAMA UNIVERSAL BOND BOND B

### 1. Identification

#### Product identifier

**Product name** TOKUYAMA UNIVERSAL BOND BOND B

#### Recommended use of the chemical and restrictions on use

**Application** Dental adhesive. For dental professionals only.

#### Details of the supplier of the safety data sheet

**Supplier** Tokuyama Dental America, Inc.  
740 Garden View Ct., Suite 200 Encinitas,  
CA 92024 U.S.A.  
Tel: (877) 378 3548 (Toll-Free)  
Tel: (760)942-7211  
Fax: (760)942-7212

**Contact Person** <http://www.tokuyama-dental.com/tdc/contact.html>

**Manufacturer** Tokuyama Dental Corporation  
38-9, Taitou 1-chome, Taitou-ku, Tokyo  
110-0016, Japan  
TEL: +81-3-3835-2261  
FAX: +81-3-3835-2265

#### Emergency telephone number

**Emergency telephone** California Poison Control System - San Francisco Division  
San Francisco General Hospital  
Bldg 5 Rm 2A21, 1001 Potrero Ave, San Francisco  
Emergency telephone number: +1 800 222 1222  
E-mail address: [coadmin@calpoison.org](mailto:coadmin@calpoison.org)  
<http://www.calpoison.org>

National Capital Poison Center  
3201 New Mexico Ave, Ste 310, Washington DC  
Emergency telephone number: +1 800 222 1222  
Telephone number: +1 202 362 3867  
Facsimile number: +1 202 362 8377  
E-mail address: [pc@poison.org](mailto:pc@poison.org)  
<http://www.poison.org>

### 2. Hazard(s) identification

#### Classification of the substance or mixture

**OSHA Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.

**Physical hazards** Flam. Liq. 2 - H225

**Health hazards** Skin Irrit 2 - H315: Eye Irrit 2A - H319: STOT SE 3 - H336

**Environmental hazards** Not Classified

#### Label elements

**TOKUYAMA UNIVERSAL BOND BOND B****Pictogram****Signal word**

Danger

**Hazard statements**

H225 Highly flammable liquid and vapor.  
 H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
 P240 Ground/ bond container and receiving equipment.  
 P241 Use explosion-proof electrical equipment.  
 P242 Use only non-sparking tools.  
 P243 Take precautionary measures against static discharge.  
 P261 Avoid breathing vapor/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P302+P352 If on skin: Wash with plenty of water.  
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a poison center/ doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P370+P378 In case of fire: Use alcohol resistant foam, carbon dioxide or dry powder to extinguish.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with local regulations.

**Contains**

ACETONE, PROPAN-2-OL

**Other hazards****Hazards not otherwise classified (HNOC)**

Not applicable.

**3. Composition/information on ingredients****Mixtures**

<b>ACETONE</b> CAS number: 67-64-1	<b>60-100%</b>
<b>PROPAN-2-OL</b> CAS number: 67-63-0	<b>10-30%</b>

## TOKUYAMA UNIVERSAL BOND BOND B

<b>3-(TRIETHOXYSILYL)PROPYL METHACRYLATE</b> CAS number: 21142-29-0	<b>1-5%</b>
<b>1,1,3,3-TETRAMETHYLBUTYL HYDROPEROXIDE</b> CAS number: 5809-08-5	<b>1-5%</b>
<b>2,6-DI-tert-BUTYL-p-CRESOL</b> CAS number: 128-37-0 M factor (Chronic) = 1	<b>&lt;1%</b>

### 4. First-aid measures

#### Description of first aid measures

<b>General information</b>	Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical personnel.
<b>Inhalation</b>	Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Give a few small glasses of water or milk to drink. Never give anything by mouth to an unconscious person. Keep affected person under observation. Get medical attention.
<b>Skin Contact</b>	Wash skin thoroughly with soap and water. Get medical attention if symptoms are severe or persist after washing.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if any discomfort continues.
<b>Protection of first aiders</b>	First aid personnel should wear appropriate protective equipment during any rescue.

#### Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
<b>Inhalation</b>	May cause drowsiness or dizziness.
<b>Skin contact</b>	Irritating to skin. Prolonged contact may cause dryness of the skin.
<b>Eye contact</b>	Irritating to eyes.

#### Indication of immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	Treat symptomatically.
-----------------------------	------------------------

### 5. Fire-fighting measures

#### Extinguishing media

<b>Suitable extinguishing media</b>	Highly flammable liquid and vapour. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.

#### Special hazards arising from the substance or mixture



## TOKUYAMA UNIVERSAL BOND BOND B

<b>Specific hazards</b>	Highly flammable liquid and vapour. Containers can burst violently or explode when heated, due to excessive pressure build-up. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Fire-water run-off in sewers may create fire or explosion hazard.
<b>Hazardous combustion products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).
<b><u>Advice for firefighters</u></b>	
<b>Protective actions during firefighting</b>	Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. If a leak or spill has not ignited, use water spray to disperse vapors and protect men stopping the leak. Control run-off water by containing and keeping it out of sewers and watercourses.
<b>Special protective equipment for firefighters</b>	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

### 6. Accidental release measures

#### **Personal precautions, protective equipment and emergency procedures**

<b>Personal precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet. No action shall be taken without appropriate training or involving any personal risk. Evacuate area. Provide adequate ventilation. No smoking, sparks, flames or other sources of ignition near spillage. Promptly remove any clothing that becomes contaminated. Avoid inhalation of dust and vapors. Use suitable respiratory protection if ventilation is inadequate. Avoid contact with skin and eyes.
-----------------------------	--

#### **Environmental precautions**

<b>Environmental precautions</b>	Avoid discharge into drains or watercourses or onto the ground.
----------------------------------	---

#### **Methods and material for containment and cleaning up**

<b>Methods for cleaning up</b>	Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Use only non-sparking tools. Contain and absorb spillage with sand, earth or other non-combustible material. Collect and place in suitable waste disposal containers and seal securely. Do not allow material to enter confined spaces, due to the risk of explosion. Wash thoroughly after dealing with a spillage. For waste disposal, see Section 13.
--------------------------------	--

<b>Reference to other sections</b>	For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.
------------------------------------	---

### 7. Handling and storage

#### **Precautions for safe handling**

## TOKUYAMA UNIVERSAL BOND BOND B

<b>Usage precautions</b>	Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Avoid breathing gas, fume, vapours or spray. Handle all packages and containers carefully to minimize spills. Avoid the formation of mists. Keep container tightly sealed when not in use. Do not handle broken packages without protective equipment. Keep away from food, drink and animal feeding stuffs.
<b>Advice on general occupational hygiene</b>	Do not eat, drink or smoke when using this product. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Wash contaminated clothing before reuse.

### Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed, in a cool, well ventilated place. Store locked up. Keep only in the original container. Protect containers from damage. Store away from the following materials: Oxidizing materials. Organic peroxides/hydroperoxides.
----------------------------	---

### Specific end uses(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

## 8. Exposure Controls/personal protection

### Control parameters

#### Occupational exposure limits

##### **ACETONE**

Long-term exposure limit (8-hour TWA): ACGIH 250 ppm 594 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 500 ppm 1187 mg/m<sup>3</sup>

A4

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 2400 mg/m<sup>3</sup>

##### **PROPAN-2-OL**

Long-term exposure limit (8-hour TWA): OSHA 400 ppm 980 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 492 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 400 ppm 984 mg/m<sup>3</sup>

A4

##### **2,6-DI-tert-BUTYL-p-CRESOL**

Long-term exposure limit (8-hour TWA): ACGIH 2 mg/m<sup>3</sup> inhalable fraction and vapor

A4

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A4 = Not Classifiable as a Human Carcinogen.

### Exposure controls

<b>Appropriate engineering controls</b>	Provide adequate ventilation. Use explosion-proof electrical, ventilating and lighting equipment. Observe any occupational exposure limits for the product or ingredients.
<b>Eye/face protection</b>	Wear tight-fitting, chemical splash goggles or face shield.

## TOKUYAMA UNIVERSAL BOND BOND B

<b>Hand protection</b>	Wear protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected. Frequent changes are recommended.
<b>Other skin and body protection</b>	Wear appropriate clothing to prevent repeated or prolonged skin contact.
<b>Hygiene measures</b>	Wash hands thoroughly after handling. Wash at the end of each work shift and before eating, smoking and using the toilet. Do not eat, drink or smoke when using this product. Take off immediately all contaminated clothing and wash it before reuse.
<b>Respiratory protection</b>	Ensure all respiratory protective equipment is suitable for its intended use and is NIOSH approved. Check that the respirator fits tightly and the filter is changed regularly. Gas and combination filter cartridges should comply with OSHA 1910.134. Full face mask respirators with replaceable filter cartridges should comply with OSHA 1910.134. Half mask and quarter mask respirators with replaceable filter cartridges should comply with OSHA 1910.134.

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

<b>Appearance</b>	Liquid
<b>Color</b>	Blue
<b>Odor</b>	Characteristic
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not available.
<b>Initial boiling point and range</b>	>35°C
<b>Flash point</b>	-14.6°C
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Relative density</b>	0.834
<b>Solubility(ies)</b>	No information available.
<b>Partition coefficient</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not available.

## TOKUYAMA UNIVERSAL BOND BOND B

**Oxidizing properties** Not available.

**Other information** Not available.

### 10. Stability and reactivity

<b>Reactivity</b>	The following materials may react violently with the product: Oxidizing materials. Organic peroxides/hydroperoxides. See the other subsections of this section for further details.
<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.
<b>Possibility of hazardous reactions</b>	The following materials may react strongly with the product: Oxidizing materials. Organic peroxides/hydroperoxides.
<b>Conditions to avoid</b>	Vapors may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented.
<b>Materials to avoid</b>	Oxidizing materials. Organic peroxides/hydroperoxides.
<b>Hazardous decomposition products</b>	Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Irritating gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO <sub>2</sub> ).

### 11. Toxicological information

#### Information on toxicological effects

**Routes of exposure** Skin , Eyes , Ingestion , Inhalation , Health effects: See section 4.

**Notes (oral LD<sub>50</sub>)** Not available.

#### Acute toxicity - dermal

**Notes (dermal LD<sub>50</sub>)** Not available.

#### Acute toxicity - inhalation

**Notes (inhalation LC<sub>50</sub>)** Not available.

#### Skin corrosion/irritation

**Skin corrosion/irritation** Skin Irrit. 2 - H315, Irritating to skin.

**Animal data** Not available.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Eye Irrit. 2 - H319 Causes serious eye irritation.

#### Respiratory sensitization

**Respiratory sensitization** Not available.

#### Skin sensitization

**Skin sensitization** Not available.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Not available.

#### Carcinogenicity

**Carcinogenicity** Not available.

## TOKUYAMA UNIVERSAL BOND BOND B

<b>IARC carcinogenicity</b>	Some of the ingredients are listed or exempt. IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b>NTP carcinogenicity</b>	Some of the ingredients are listed or exempt.
<b>OSHA Carcinogenicity</b>	None of the ingredients are listed.
<b><u>Reproductive toxicity</u></b>	
<b>Reproductive toxicity - fertility</b>	Not available.
<b>Reproductive toxicity - development</b>	Not available.
<b><u>Specific target organ toxicity - single exposure</u></b>	
<b>STOT - single exposure</b>	STOT SE 3 - H336 May cause drowsiness or dizziness.
<b>Target organs</b>	Central nervous system
<b><u>Specific target organ toxicity - repeated exposure</u></b>	
<b>STOT - repeated exposure</b>	Not classified as a specific target organ toxicant after repeated exposure.
<b><u>Aspiration hazard</u></b>	
<b>Aspiration hazard</b>	Not available.
<b><u>Toxicological information on ingredients.</u></b>	

### PROPAN-2-OL

#### Carcinogenicity

<b>IARC carcinogenicity</b>	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b>NTP carcinogenicity</b>	Reasonably anticipated to be a human carcinogen.
<b>OSHA Carcinogenicity</b>	Not listed.

### POLY(METHYL METHACRYLATE)

#### Carcinogenicity

<b>IARC carcinogenicity</b>	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
-----------------------------	--

### 2,6-DI-tert-BUTYL-p-CRESOL

#### Carcinogenicity

<b>IARC carcinogenicity</b>	IARC Group 3 Not classifiable as to its carcinogenicity to humans.
<b>NTP carcinogenicity</b>	Reasonably anticipated to be a human carcinogen.
<b>OSHA Carcinogenicity</b>	Not listed.

## 12. Ecological Information

### Toxicity

<b>Toxicity</b>	No information available.
<b>Acute toxicity - fish</b>	Not available.
<b>Acute toxicity - aquatic invertebrates</b>	Not available.
<b>Acute toxicity - aquatic plants</b>	Not available.

### Persistence and degradability

## TOKUYAMA UNIVERSAL BOND BOND B

**Persistence and degradability** The degradability of the product is not known.

### Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** Not available.

### Mobility in soil

**Mobility** Volatile liquid. The product contains organic solvents which will evaporate easily from all surfaces.

### Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### Other adverse effects

**Other adverse effects** None known.

## 13. Disposal considerations

### 13.1 Waste treatment methods

Dispose of contents/ container in accordance with the local/ regional/ national/ international regulations. Must not be disposed of together with household garbage. Dispose at suitable refuse site. Do not allow to enter drains, sewers or watercourses. Empty containers may retain some product residues and hence be potentially hazardous.

### 13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

## 14. Transport information

**General** For limited quantity packaging/limited load information, consult the relevant modal documentation using the data shown in this section.

### UN Number

**UN No. (IMDG)** 1133

**UN No. (ICAO)** 1133

**UN No. (DOT)** UN1133

### UN proper shipping name

**Proper shipping name (IMDG)** ADHESIVES

**Proper shipping name (ICAO)** ADHESIVES

**Proper shipping name (DOT)** ADHESIVES

### Transport hazard class(es)

**DOT hazard class** 3

**DOT hazard label** 3

**IMDG Class** 3

## TOKUYAMA UNIVERSAL BOND BOND B

ICAO class/division 3

### Transport labels



### DOT transport labels



### Packing group

IMDG packing group II

ICAO packing group II

DOT packing group II

### Environmental hazards

#### Environmentally Hazardous Substance

No.

### Special precautions for user

Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

EmS F-E, S-D

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

## 15. Regulatory information

**Regulatory Status** This Product is Hazardous under the OSHA Hazard Communication Standard.

### International Regulations

#### US Federal Regulations

##### **SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities**

None of the ingredients are listed or exempt.

##### **CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)**

The following ingredients are listed or exempt:

*ACETONE*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

##### **SARA Extremely Hazardous Substances EPCRA Reportable Quantities**

None of the ingredients are listed or exempt.

##### **SARA 313 Emission Reporting**

None of the ingredients are listed or exempt.

##### **CAA Accidental Release Prevention**

None of the ingredients are listed or exempt.

## TOKUYAMA UNIVERSAL BOND BOND B

### **FDA - Essential Chemical**

None of the ingredients are listed or exempt.

### **FDA - Precursor Chemical**

None of the ingredients are listed or exempt.

### **SARA (311/312) Hazard Categories**

Fire  
Acute  
Chronic

### **OSHA Highly Hazardous Chemicals**

None of the ingredients are listed or exempt.

### **US State Regulations**

#### **California Proposition 65 Carcinogens and Reproductive Toxins**

None of the ingredients are listed or exempt.

#### **California Air Toxics "Hot Spots" (A-I)**

The following ingredients are listed or exempt:

*PROPAN-2-OL*

#### **California Air Toxics "Hot Spots" (A-II)**

None of the ingredients are listed or exempt.

#### **California Directors List of Hazardous Substances**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

*PROPAN-2-OL*

Present.

#### **Massachusetts "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

*PROPAN-2-OL*

Present.

#### **Rhode Island "Right To Know" List**

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

*PROPAN-2-OL*

Present.



## TOKUYAMA UNIVERSAL BOND BOND B

### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

*ACETONE*

*PROPAN-2-OL*

### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

*PROPAN-2-OL*

Present.

### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

*2,6-DI-tert-BUTYL-p-CRESOL*

Present.

*ACETONE*

Present.

*PROPAN-2-OL*

Present.

## 16. Other information

### Revision comments

<b>Revision date</b>	10/15/2022
<b>Revision</b>	2
<b>Hazard statements in full</b>	H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

The information which is contained in this document is based on available data. However, as such has been obtained from various sources, including independent laboratories, it is given without warranty or representation that is complete, accurate and can be relied upon. Tokuyama Dental Corp. has not attempted to conceal in any way the deleterious aspects of the product listed herein, but makes no warranty as to such information.