

SAFETY DATA SHEETS

This SDS packet was issued with item:

072358174

N/A



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

1 Identification

· **Product identifier**

· **Trade name: Universal Adhesive**

· **Application of the substance / the mixture**

Tray adhesive for use with silicone impression materials

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Tel.: +49 (0)800 4372522

· **Information department:**

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545

e-mail: customer.servicehkna@kulzer-dental.com

· **Emergency telephone number:**

Emergency CONTACT (24-Hour-Number)

GBK/Infotrac ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard(s) identification

· **Classification of the substance or mixture**

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

· **Label elements**

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

titanium tetrabutanolate

ethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye damage.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

(Contd. on page 2)

USA



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 1)

Immediately call a poison center/doctor.
Store locked up.

· **Classification system**

· **NFPA ratings for USA (scale 0-4)**



· **HMIS-Ratings (Scale 0-4)**



· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** -

· **Dangerous components:**

141-78-6	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336	10-25%
1330-20-7	xylene, mixed isomers, pure Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-10%
5593-70-4	titanium tetrabutanolate Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315	0-5%
100-41-4	ethylbenzene Flam. Liq. 2, H225; Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	0-5%
556-67-2	octamethylcyclotetrasiloxane Flam. Liq. 3, H226; Repr. 2, H361	<1%

· **Additional information** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**

- **After inhalation** Supply fresh air; consult doctor in case of complaints.
- **After skin contact**
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact**
Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing**
Rinse out mouth and then drink plenty of water.
If symptoms persist consult doctor.
- **Information for doctor**
 - **Most important symptoms and effects, both acute and delayed**
No further relevant information available.

(Contd. on page 3)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents**
CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.
 - **For safety reasons unsuitable extinguishing agents** Water with full jet.
- **Special hazards arising from the substance or mixture**
Can form explosive gas-air mixtures.
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
 - **Protective equipment:** No special measures required.
- **Additional information** -

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
No dangerous substances are released.
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

· **Protective Action Criteria for Chemicals**

· PAC-1:		
141-78-6	ethyl acetate	1,200 ppm
5593-70-4	titanium tetrabutanolate	0.67 ppm
100-41-4	ethylbenzene	33 ppm
556-67-2	octamethylcyclotetrasiloxane	30 ppm
· PAC-2:		
141-78-6	ethyl acetate	1,700 ppm
5593-70-4	titanium tetrabutanolate	7.4 ppm
100-41-4	ethylbenzene	1100* ppm
556-67-2	octamethylcyclotetrasiloxane	68 ppm
· PAC-3:		
141-78-6	ethyl acetate	10000** ppm
5593-70-4	titanium tetrabutanolate	44 ppm
100-41-4	ethylbenzene	1800* ppm
556-67-2	octamethylcyclotetrasiloxane	130 ppm

USA

(Contd. on page 4)



**Safety Data Sheet
acc. to OSHA HCS**

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 3)

7 Handling and storage

- **Handling**
 - **Precautions for safe handling**
Keep receptacles tightly sealed.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage**
 - **Requirements to be met by storerooms and receptacles:** Store in a cool location.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

141-78-6 ethyl acetate	
PEL	Long-term value: 1400 mg/m ³ , 400 ppm
REL	Long-term value: 1400 mg/m ³ , 400 ppm
TLV	Long-term value: 1440 mg/m ³ , 400 ppm
1330-20-7 xylene, mixed isomers, pure	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI
100-41-4 ethylbenzene	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI
556-67-2 octamethylcyclotetrasiloxane	
WEEL	Long-term value: 10* ppm *OARS WEEL

(Contd. on page 5)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 4)

· Ingredients with biological limit values:

1330-20-7 xylene, mixed isomers, pure

BEI 1.5 g/g creatinine
Medium: urine
Time: end of shift
Parameter: Methylhippuric acids

100-41-4 ethylbenzene

BEI 0.7 g/g creatinine
Medium: urine
Time: end of shift at end of workweek
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-
Medium: end-exhaled air
Time: not critical
Parameter: Ethyl benzene (semi-quantitative)

· Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment

· General protective and hygienic measures

- Avoid contact with the eyes.
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

· Protection of hands:

Check protective gloves prior to each use for their proper condition.
recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

- Butyl rubber, BR
- Nitrile rubber, NBR

· Eye protection: Not absolutely necessary.

· Body protection: Light weight protective clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

· Form: Fluid

(Contd. on page 6)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 5)

· Color:	Blue
· Odor:	Ester-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
· Melting point/Melting range:	undetermined
· Boiling point/Boiling range:	77 °C (170.6 °F)
· Flash point:	3 °C (37.4 °F)
· Flammability (solid, gaseous)	Not applicable.
· Ignition temperature:	460 °C (860 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
· Lower:	2,1 Vol %
· Upper:	11,5 Vol %
· Vapor pressure at 20 °C (68 °F):	102 hPa (76.5 mm Hg)
· Density at 20 °C (68 °F):	1,20169 g/cm ³ (10.0281 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
· Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
· dynamic:	Not determined.
· kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Possibility of hazardous reactions** No dangerous reactions known
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** none
- **Additional information:** -

USA

(Contd. on page 7)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 6)

11 Toxicological information

· **Information on toxicological effects**

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	5600 mg/kg (rat)
Dermal	LD50	18000 mg/kg (rabbit)
Sensitization	Sensib.	nicht sensib. (guinea pig) (OECD-Prüfrichtlinie 406)

1330-20-7 xylene, mixed isomers, pure

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	6350 mg/l (rat)

100-41-4 ethylbenzene

Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene, mixed isomers, pure	3
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity:**

141-78-6 ethyl acetate

EC50/48h	3300 mg/l (algae)
	717 mg/l (daphnia) (DIN 38412)
LC50/96h	230 mg/l (fish)

· **Persistence and degradability** No further relevant information available.

· **Behavior in environmental systems:**

· **Bioaccumulative potential** No further relevant information available.

· **Mobility in soil** No further relevant information available.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

USA

(Contd. on page 8)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017




Trade name: **Universal Adhesive**

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	UN1866
· UN proper shipping name · DOT · ADR · IMDG, IATA	Resin solution 1866 Resin solution, special provision 640D RESIN SOLUTION
· Transport hazard class(es) · DOT	
	
· Class · Label	3 Flammable liquids 3
· ADR	
	
· Class · Label	3 (F1) Flammable liquids 3
· IMDG, IATA	
	
· Class · Label	3 Flammable liquids 3
· Packing group · DOT, ADR, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids 33 F-E, S-E

(Contd. on page 9)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 8)

· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	-
· ADR	
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· SARA Section 355 (extremely hazardous substances)	None of the ingredients is listed.
· TSCA (Toxic Substances Control Act)	None of the ingredients is listed.
· TSCA new (21st Century Act) (Substances not listed)	1330-20-7 xylene, mixed isomers, pure

· **Carcinogenicity categories**

· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene, mixed isomers, pure	A4
100-41-4	ethylbenzene	A3

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS05 GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

titanium tetrabutanolate
ethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.

(Contd. on page 10)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

(Contd. of page 9)

Causes skin irritation.
Causes serious eye damage.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Use explosion-proof electrical/ventilating/lighting/equipment.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Immediately call a poison center/doctor.
Store locked up.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapor.
H226 Flammable liquid and vapor.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.
H351 Suspected of causing cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

· **Date of preparation / last revision** 11/28/2017 / 2

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
OSHA: Occupational Safety & Health
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1

(Contd. on page 11)



Safety Data Sheet
acc. to OSHA HCS

Printing date 11/28/2017

Reviewed on 11/28/2017

Trade name: Universal Adhesive

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 2: Carcinogenicity – Category 2
Carc. 2: Carcinogenicity – Category 2
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. of page 10)

USA