## **SAFETY DATA SHEETS**

# This SDS packet was issued with item:

073263662

The safety data sheets (SDS) in this packet apply to the individual products listed below. Please refer to invoice for specific item number(s).

071101740 073263688

The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).

071101765 073263654



Page 1/11

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

- **1** Identification
- · Product identifier
- · Trade name: PATTERN RESIN LS (Liquid)
- · Application of the substance / the mixture Manufacture of dental prothesis
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: GC America Inc. 3737 W. 127th Street Alsip, IL 60803 USA

sds@gcamerica.com

- · Information department: Regulatory Affairs
- Emergency telephone number: During normal opening times (Mon.-Fri. 8:00 AM-5:00 PM CST): +1 (708) 597-0900 Transportation (CHEMTREC®) Emergency Telephone No. +1 (800) 424-9300

#### **2 Hazard identification**

#### · Classification of the substance or mixture

Flammable Liquids - Category 2

Skin Irritation - Category 2

Skin Sensitizer - Category 1

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure - Category 3

H335 May cause respiratory irritation.

#### · Additional information:

The information provided is in regards to the toxicity and hazard rating(s) of the individual component(s) in the formulation. The associated risk(s) depends on the route(s) of exposure. The hazard rating system is based entirely on the existence of the risk(s) and does not take into account the likelihood of reduced risk(s) through proper usage and handling.

#### · Label elements

#### · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: methyl methacrylate (MMA) ethyl methacrylate UV-light absorber\*\* dimethacrylate\*\*
- Hazard statements Highly flammable liquid and vapour.

(Contd. on page 2)

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

## Trade name: PATTERN RESIN LS (Liquid)

(Contd. of page 1) Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation. · Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Additional information: 20.6 % of the mixture consists of an ingredient or ingredients of unknown acute toxicity. · Classification system: • NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 2 · HMIS-ratings (scale 0 - 4) HEALTH \*2 Health = \*23 Fire = 3FIRE Reactivity = 2 **REACTIVITY** 2

## 3 Composition/Information on ingredients

#### · Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

<ul> <li>Dangerous co</li> </ul>	omponents:	
CAS: 80-62-6	methyl methacrylate (MMA)	40 - 70% w/w
CAS: 97-63-2	ethyl methacrylate	5 - 10% w/w
	accelerant**	1 - 5% w/w
	UV-light absorber**	≤ 1% w/w
	dimethacrylate**	≤ 1% w/w

#### · Additional information:

If a substance is marked with \*\*, then substance is a trade secret. This is allowed under OSHA's Hazard Communication Standard (HCS) as a trade secret and under GHS as Confidential Business Information (CBI).

## 4 First aid measures

#### · Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product. If symptoms persist consult doctor.

#### After inhalation:

Supply fresh air; consult doctor in case of complaints.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

CA

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

## Trade name: PATTERN RESIN LS (Liquid)

(Contd. of page 2)

• After skin contact: Immediately wash with water and soap and rinse thoroughly. Seek medical treatment.

#### After eye contact: Protect unharmed eye.

Rinse opened eye for several minutes under running water. If symptoms persist consult doctor.

After swallowing:
 Rinse out mouth and then drink plenty of water.
 If symptoms persist consult doctor.

Information for doctor:

· Most important symptoms and effects, both acute and delayed Allergic reactions

- Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Firefighting measures

- Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture Formation of toxic gases is possible during heating or in case of fire.
- · Advice for firefighters
- Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

### 6 Accidental release measures

 Personal precautions, protective equipment and emergency procedures Remove persons from danger area. Keep away from ignition sources Avoid contact with the eyes and skin. Wear protective clothing. · Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to penetrate the ground/soil. In case of seepage into the ground inform responsible authorities. · Methods and material for containment and cleaning up: Ensure adequate ventilation. Absorb liquid components with liquid-binding material. Dispose of the collected material according to regulations. Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

(Contd. of page 3)

#### 7 Handling and storage

#### · Handling:

- Precautions for safe handling Observe instructions for use.
  Ensure good ventilation/exhaustion at the workplace.
  Prevent formation of aerosols.
  Avoid contact with the eyes and skin.
  Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
  Protect from heat.
  Protect against electrostatic charges.
  Do not spray on a naked flame or any incandescent material.
  Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions:
- Observe instructions for use / storage. Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. Store in a cool place. • **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/ Personal protection

#### · Additional information about design of technical systems: No further data; see item 7.

- Control parameters
- · Components with limit values that require monitoring at the workplace:

#### CAS: 80-62-6 methyl methacrylate (MMA)

- EL Short-term value: 100 ppm Long-term value: 50 ppm S(D)
- EV Short-term value: 100 ppm Long-term value: 50 ppm

#### CAS: 97-63-2 ethyl methacrylate

- EL Long-term value: 50 ppm
- EV Short-term value: 100 ppm Long-term value: 50 ppm

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed. Avoid contact with the eyes and skin.

(Contd. on page 5)

CA

(Contd. of page 4)

## Safety Data Sheet according to HPR, Schedule 1

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

Wash hands before breaks and at the end of work. Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. • Breathing equipment:



Suitable respiratory protective device recommended.

#### · Protection of hands:



Protective gloves

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### · Eye protection:

Manufacturing sites:

Wear safety glasses with side shields (or goggles). Distribution, Workplace, and Household Settings: No special protective equipment required

## 9 Physical and chemical properties

General Information		
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 ℃	
Flash point:	10 ℃	
Flammability (solid, gaseous):	Not applicable.	
Ignition temperature:	Undetermined.	
Decomposition temperature:	Not determined.	

CA

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

	(Contd. of page 5)
· Auto igniting:	Product is not self-igniting.
· Danger of explosion:	Heating may cause an explosion. Product is not explosive. However, formation of explosive air/ vapor mixtures are possible.
<ul> <li>Explosion limits: Lower: Upper:</li> </ul>	2.1 Vol % 12.5 Vol %
· Vapor pressure:	Not determined.
<ul> <li>Density at 20 °C:</li> <li>Relative density</li> <li>Vapor density</li> <li>Evaporation rate</li> </ul>	0.95 g/cm <sup>3</sup> Not determined. Not determined. Not determined.
<ul> <li>Solubility in / Miscibility with Water:</li> </ul>	Insoluble.
· Partition coefficient (n-octanol/wate	er): Not determined.
<ul> <li>· Viscosity:</li> <li>Dynamic:</li> <li>Kinematic:</li> <li>· Other information</li> </ul>	Not determined. Not determined. No further relevant information available.

## 10 Stability and reactivity

- · Reactivity Danger of polymerization.
- Chemical stability Stable at ambient temperature.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** Spontaneous polymerization can be caused in unstabilized product e.g. by ambient heat. Danger of receptacles bursting because of high vapor pressure if heated. Exothermic polymerization.
- Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Incompatible materials: Reacts with peroxides and other radical forming substances. Reacts with amines. Reacts with heavy metals.
- Hazardous decomposition products: No dangerous decomposition products known.

<b>11 Toxicological information</b>	

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:
- accelerant\*\*

Oral LD50 1,650 mg/kg (rat (f+m))

(Contd. on page 7)

CA

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

## Trade name: PATTERN RESIN LS (Liquid)

	(Contd. of page 6)
Dermal LD50 > 2,000 mg/kg (rat (f+m))	
Inhalative LC50/4 h 254 mg/l (rat (f+m))	
· Primary irritant effect:	
• on the skin: Irritant to skin and mucous membranes.	
on the eye: No irritating effect.	
<ul> <li>Sensitization: Sensitization possible through skin contact.</li> </ul>	
Additional toxicological information:	
The product shows the following dangers according to internally approved calculation	on methods for
preparations: Irritant	
· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
methyl methacrylate (MMA)	3
butylated hydroxytoluene (BHT)	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· Carcinogenic categories' legend:	
IARC Group 1: The agent is carcinogenic to humans.	
IARC Group 2A: The agent is probably carcinogenic to humans.	
IARC Group 2B: The agent is possibly carcinogenic to humans. IARC Group 3: The agent is not classifiable as to its carcinogenicity to humans.	
IARC Group 4: The agent is probably not carcinogenic to humans.	
NTP K: Known to be human carcinogen.	
NTP R: Reasonably anticipated to be human carcinogen.	
· Repeated dose toxicity. No further relevant information available.	
CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)	
No further relevant information available. No further relevant information available.	

#### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

CA

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

(Contd. of page 7)

## **13 Disposal considerations**

· Waste treatment methods

- **Recommendation:** Dispose of contents / container in accordance with local / regional / national / international regulations.
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

Transport information	
· UN-Number · DOT, TDG, IMDG, IATA	UN1247
· UN proper shipping name · DOT · TDG · IMDG, IATA	Methyl methacrylate monomer, stabilized solution 1247 Methyl methacrylate monomer, stabilized solution METHYL METHACRYLATE MONOMER, STABILIZE solution
· Transport hazard class(es)	
<sup>.</sup> Class <sup>.</sup> Label <sup>.</sup> TDG (Transport dangerous goods):	3 Flammable liquids 3
· Class · Label	3 (F1) Flammable liquids 3
· Class	3 Flammable liquids
· Label	3
<ul> <li>Packing group</li> <li>DOT, TDG, IMDG, IATA</li> </ul>	II
· Environmental hazards: · Marine pollutant:	No
<ul> <li>Special precautions for user</li> <li>Danger code (Kemler):</li> </ul>	Warning: Flammable liquids 339
	(Contd. on page

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

	(Contd. of page 8)
<ul> <li>EMS Number:</li> <li>Stowage Category</li> <li>Stowage Code</li> </ul>	F-E,S-D B SW2 Clear of living quarters.
<ul> <li>Transport in bulk according to Annex MARPOL73/78 and the IBC Code</li> </ul>	Il of Not applicable.
· Transport/Additional information:	
<ul> <li>TDG</li> <li>Excepted quantities (EQ)</li> </ul>	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

## **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture • SARA (Superfund Amendments and Reauthorization Act)

- Section 355 (extremely hazardous substances):
- None of the ingredients is listed.
- · Section 313 (Specific toxic chemical listings):

methyl methacrylate (MMA)

- TSCA (Toxic Substances Control Act):
- methyl methacrylate (MMA)
- methoxyethyl methacrylate
- ethyl methacrylate
- accelerant\*\*
- UV-light absorber\*\*
- dimethacrylate\*\*
- · Canadian substance listings:
- · Canadian Domestic Substances List (DSL)
- methyl methacrylate (MMA)
- ethyl methacrylate
- accelerant\*\*
- UV-light absorber\*\*
- dimethacrylate\*\*
- butylated hydroxytoluene (BHT)

(Contd. on page 10)

CA

(Contd. of page 9)

## Safety Data Sheet according to HPR, Schedule 1

Printing date 03/13/2018

ethyl methacrylate

Version CA-EN-Rev 1

Reviewed on 01/09/2018

Trade name: PATTERN RESIN LS (Liquid)

· Canadian Ingredient Disclosure list (limit 0.1%)

· Canadian Ingredient Disclosure list (limit 1%)

methyl methacrylate (MMA)	
<ul> <li>GHS label elements</li> <li>The product is classified and labeled according to the Globally Harmonized System - Hazard pictograms</li> </ul>	stem (GHS).
GHS02 GHS07	
· Signal word Danger	
<ul> <li>Hazard-determining components of labeling: methyl methacrylate (MMA) ethyl methacrylate UV-light absorber** dimethacrylate**</li> <li>Hazard statements Highly flammable liquid and vapour. Causes skin irritation. May cause an allergic skin reaction. May cause an allergic skin reaction. May cause respiratory irritation.</li> <li>Precautionary statements Keep away from heat, hot surfaces, sparks, open flames and other ignition sou Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse ski Store locked up. Dispose of contents/container in accordance with local/regional/national/international/international</li> </ul>	in with water [or shower]. ational regulations.
16 Other information	
<ul> <li>Department issuing SDS: Regulatory Affairs</li> <li>Contact: Regulatory Affairs Telephone No. +1 (708) 597-0900 sds@gcamerica.com</li> <li>Date of preparation / last revision 03/13/2018 / -</li> <li>Abbreviations and acronyms: GHS: Globally Harmonized System of Classification and Labelling of Chemicals HCS: Hazard Communication Standard (USA) MSDS: Material Safety Data Sheet SDS: Safety Data Sheet ECHA: European Chemicals Agency OSHA: Occupational Safety and Health Administration (USA) LEL: Lower Explosive Limit UEL: Upper Explosive Limit IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transport Association</li> </ul>	
In In. International All Transport Association	(Contd. on page 11)

ĊA

Printing date 03/13/2018

Version CA-EN-Rev 1

Reviewed on 01/09/2018

## Trade name: PATTERN RESIN LS (Liquid)

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPVB: very Persistent and very Bioaccumulative • <b>Sources</b> • Manufacturers' MSDSs/SDSs • OSHA (https://www.osha.gov/dts/chemicalsampling/toc/chmcas.html) • TOXNET (http://toxnet.nlm.nih.gov/) • ECHA (http://echa.europa.eu/) • EnviChem (www.echemportal.org) • <b>Notes:</b> CAS Registry Number is a Registered Trademark of the American Chemical Society. CHEMTREC® is a registered service mark of the American Chemistry Council, Inc.	(Contd. of page 10)
• * Data compared to the previous version altered. This version replaces all previous	versions.
• <b>Disclaimer:</b> The information contained herein is believed to be true and accurate. However, recommendations or suggestions are made without any guarantee, representation or or implied, on our part. Therefore, no warranty is made or to be implied that the info this document is accurate or complete, and we accordingly exclude all liability in conner of this information or the products referred to herein. All such risks are assumed by the The information contained herein is also subject to change without notice. For the ave however, nothing in this document excludes or limits our liability for death or personal provide the product of the product of the personal provide the product of the personal provide the personal provides on the personal provides of the per	warranty, express rmation set out in ection with the use e purchaser/user. roidance of doubt,

our negligence or for fraudulent misrepresentation.