

## SAFETY DATA SHEETS

**This SDS packet was issued with item:**

076319776

**The safety data sheets (SDS) in this packet apply to one or more components included in the items listed below. Items listed below may require one or more SDS. Please refer to invoice for specific item number(s).**

070351809 070351817 070351825 070351833 070356261 070826834 070826842 070826867 070826875 070826883  
070826891 070826933 070826941 070826958 070826966 070869073 076203004 076203012 076203020 076203038  
076203046 076203053 076203061 076203079 076203087 076203095 076203103 076203111 076203129 076203137  
076203145 076203152 076203160 076203178 076203244 076203251 076203269 076203277 076203285 076203293  
076203301 076203319 076203327 076203335 076203343 076203350 076203368 076203376 076203384 076203392  
076203400 076203418 076207997 076208003 076208011 076208029 076208037 076208045 076208052 076208060  
076208169 076208177 076208185 076208193 076208201 076319503 076319545 076319552 076319560 076319578  
076319586 076319594 076319602 076319610 076319628 076319636 076319644 076319651 076319669 076319677  
076319719 076319727 076319735 076319743 076319750 076319768 076319784 076319792 076319842 076319859  
076320105 076320154 076320162 076320196 076320212 076320220 076320238 076320246 076341002 076341010  
076341028 076341036 076341044 076341051 076341069 076341077 076341085 076341093 076341101 076341119  
076341127 076341135 076341143 076341150 076341168 076341176 076341184 076341192 076341200 076341218  
076341226 076341390 076341408 076341416 076341424 076341432 076341440 076341457 076341473 076341507  
076341531 076341549 076341556 076341564 076341572 076341580 076341598 076341614 076341648 076341671  
076372502 076372510 076372528 076372536 076372650 076372668 076372676 076372684 076372692 076372718  
076372726 076372734 076372742 076372767 076372775 076372932 076372940 076372957 076373401 076373468  
076373476 076373484 076373492 076373500 076373518 076373526 076373534 076373559 076373567  
076373575 076373583 076373617 076373625 076373633 076373641 076373658 076373666 076373682



### 1. Substance / Preparation and Company name

Product Name: Glacier; Wave; Wave MV; Wave HV; ROK, ICE and LC Opaquer

Recommended use: For filling of cavitated teeth by dental professionals.

#### **Manufacturer / Supplier**

SDI Limited  
3-13 Brunsdon Street, Bayswater  
Victoria, 3153, Australia

#### **Telephone:**

+61 3 8727 7111 (Business hours)

Southern Dental Industries Ltd  
Block 8, St Johns Court  
Swords Road  
Santry, Dublin 9, Ireland

#### **Telephone:**

+353 1 886 9577 (Business Hours)

SDI Inc.  
729 N.Route 83, Suite 315  
Bensenville 60106 IL, USA

#### **Telephone:**

630 238 8300 (Business hours)

SDI Brasil Indústria e Comércio Ltda  
Rua Dr. Virgílio de Carvalho Pinto, 612  
Pinheiros, São Paulo, 05415-020  
Brasil

#### **Telephone:**

+55 11 3092 7100 (Business Hours)

**Emergency contact number:** +61 3 8727 7111

### 2. Composition / Information on ingredients

| <u>Composition:</u>                | <u>CAS No.</u> | <u>Wt. %</u> |
|------------------------------------|----------------|--------------|
| Acrylic monomer                    | -              | 18.0 – 40.0  |
| Balance ingredient (non-hazardous) |                | 60.0 – 82.0  |

### 3. Hazard Identification

Products may cause irritation to the skin, eye and mucous membrane. Ingestion of unpolymerised material may cause gastric irritation. In isolated cases, contact allergies have been reported with acrylic resins. Anyone with known history of resin allergies are advised to seek the advice of a specialist before use.

Risk phrases - **36/37/38:** Irritating to eyes, respiratory system and skin.

Safety phrases - **26/28:** In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin, wash immediately with soap and water.

- **3/15/16:** Keep in a cool place, away from heat and sources of ignition.

- **2:** Keep out of reach of children.



---

#### 4. First Aid Measures

|                 |  |
|-----------------|--|
| Eye (contact):  | Flush opened eye with running water for at least 5 minutes. Seek medical attention.                                |
| Skin (contact): | Remove contaminated clothing. Wash skin with soap and water. In case of allergic reaction, seek medical attention. |
| Ingestion:      | Seek medical attention.  |
| Inhalation:     | None expected.   |

---

#### 5. Fire Fighting Measures

|                                     |  |
|-------------------------------------|--|
| Suitable extinguishing media:       | Sand, chemical foam, carbon dioxide, dry chemicals.  |
| Unusual Fire and Explosion Hazards: | Heat can cause polymerization with rapid release of energy which may melt the container.   |
| Special protective equipment:       | No special measures required for small quantity (less than 1 kg). For large quantity, wear approved respirator and protective gear. Use water spray to cool container. |

---

#### 6. Accidental Release Measures

|                            |  |
|----------------------------|--|
| Personal precautions:      | Not required.  |
| Environmental precautions: | Prevent any spillage from entering waterways, drains or sewage system. |
| Methods for cleaning up:   | Scoop up bulk material and transfer to containers for disposal.        |

---

#### 7. Handling and storage

##### Handling

Replace caps immediately after use.

##### Storage

Storage by the end user (Dental Clinic) is recommended to be at temperatures between 10° - 25°C (50° - 77°F) and should be kept away from direct sunlight.

##### Distribution

During distribution, to our customers, this product can be transported in non-refrigerated conditions between 15° to 25° C. This product can also withstand temperatures up to 40° C for short periods (2 to 3 days) and intermittent peaks up to 50°C.



---

## 8. Exposure controls and personal protection

|                                      |   |
|--------------------------------------|---|
| Respiratory protection:              | None required under normal conditions of use  |
| Hand protection:                     | Rubber, latex or PVC gloves.  |
| Eye protection:                      | Not absolutely necessary  |
| General safety and hygiene measures: | Follow good housekeeping practices and good industrial hygiene in handling this material. Remove any naked lights or strong heat sources. |

---

## 9. Physical and chemical properties

|                           |  |
|---------------------------|--|
| Appearance:               | Tooth coloured viscous / flowable paste. |
| Odour:                    | Ester like.                              |
| Boiling point:            | Gel before boiling.                      |
| Melting point:            | Not established.                         |
| Specific gravity:         | 1.5 - 2.0                                |
| Flash point:              | Not established.                         |
| Flammable:                | Not established.                         |
| Autoflammability:         | Do not self ignite.                      |
| Explosive properties:     | Do not present an explosion hazard.      |
| Oxidizing properties:     | Not established.                         |
| Vapour pressure (@ 20°C): | 0 mbar                                   |
| Relative density:         | Not established.                         |
| Solubility:               | Insoluble in water.                      |

---



---

#### 10. Stability and Reactivity

|  |  |
|--|--|
| Stability:                             | Stable under normal conditions.  |
| Conditions to avoid:                   | Avoid heat, ignition sources, aging, contamination and intense visible light.  |
| Materials to avoid:                    | Free radical formers, e.g. peroxides, reducing substances and / or heavy metals ions.  |
| Hazardous decomposition products:      | None under normal conditions. Oxides of carbon when burned.  |
| Hazardous reactivity (polymerization): | Heat and intense light can cause polymerization. Spontaneous polymerization may occur in the presence of radical formers. May polymerize under these conditions with heat evolution. |

---

#### 11. Toxicological information

|                 |  |
|-----------------|--|
| Acute toxicity: | May be irritating to skin, eye and mucous membrane.                                  |
| Sensitization:  | No sensitizing effect known. In isolated cases contact allergies have been reported. |
| Inhalation:     | None expected.   |

---

#### 12. Ecological information

|                  |   |
|------------------|---|
| Self assessment: | Slightly hazardous for water. Do not allow large quantities to reach sewage system and waterways. |
|------------------|---|

---

#### 13. Disposal considerations

Dispose of in accordance with local official regulations.

---

#### 14. Transport information

Glacier, Wave, Wave MV, Wave HV, Rok, Ice and LC Opaquer are not classified as Dangerous Goods for air, sea, rail or road transport.

---



---

**15. Regulatory information**

These products are regulated by:

TGA  
Medical Devices 93/42/EEC  
FDA  
National regulations

---

**16. Other information**

The information provided herein is given in good faith, but no warranty expressed or implied is made.

**Prepared by:** SDI Limited  
3-13 Brunsdon Street, Bayswater  
Victoria, 3153, Australia

**Phone Number:**  
+61 3 8727 7111

**Department issuing MSDS:** Research and Development  
**Contact:** Operations Director

---



## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

### SDI Limited

Version No: 6.1.1.1

Safety Data Sheet according to WHS and ADG requirements

Issue Date: 18/03/2016

Print Date: 22/03/2016

Initial Date: Not Available

L.GHS.AUS.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

|                               |  |
|-------------------------------|--|
| Product name                  | Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer |
| Synonyms                      | Not Available  |
| Other means of identification | Not Available  |

### Relevant identified uses of the substance or mixture and uses advised against

|                          |   |
|--------------------------|---|
| Relevant identified uses | For filling of cavitated teeth by dental professionals. |
|--------------------------|---|

### Details of the supplier of the safety data sheet

|                         |   |  |   |
|-------------------------|---|--|---|
| Registered company name | SDI Limited   | SDI Brazil Industria E Comercio Ltda                                   | SDI Germany GmbH                        |
| Address                 | 3-15 Brunsdon Street VIC Bayswater 3153 Australia   | Rua Dr. Virgilio de Carvalho Pinto, 612 São Paulo CEP 05415-020 Brazil | Hansestrasse 85 Cologne D-51149 Germany |
| Telephone               | +61 3 8727 7111 (Business Hours)                    | +55 11 3092 7100   | +49 0 2203 9255 0                       |
| Fax                     | +61 3 8727 7222                                     | +55 11 3092 7101   | +49 0 2203 9255 200                     |
| Website                 | www.sdi.com.au                                      | www.sdi.com.au   | www.sdi.com.au                          |
| Email                   | info@sdi.com.au                                     | brasil@sdi.com.au  | germany@sdi.com.au                      |
| Registered company name | SDI (North America) Inc.                            |  |   |
| Address                 | 1279 Hamilton Parkway IL Itasca 60143 United States |  |   |
| Telephone               | +1 630 361 9200 (Business hours)                    |  |   |
| Fax                     | Not Available                                       |  |   |
| Website                 | Not Available                                       |  |   |
| Email                   | USA.Canada@sdi.com.au                               |  |   |

### Emergency telephone number

|                                   |                       |               |               |
|-----------------------------------|-----------------------|---------------|---------------|
| Association / Organisation        | SDI Limited           | Not Available | Not Available |
| Emergency telephone numbers       | +61 3 8727 7111       | Not Available | Not Available |
| Other emergency telephone numbers | ray.cahill@sdi.com.au | Not Available | Not Available |
| Association / Organisation        | Not Available         |               |               |
| Emergency telephone numbers       | +61 3 8727 7111       |               |               |
| Other emergency telephone numbers | Not Available         |               |               |

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture


**HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

|                               |   |
|-------------------------------|---|
| Poisons Schedule              | Not Applicable  |
| Classification <sup>[1]</sup> | Skin Sensitizer Category 1  |
| Legend:                       | 1. Classification by vendor; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI |

### Label elements

Continued...

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

|                    |   |
|--------------------|---|
| GHS label elements |  |
|--------------------|---|

|             |                |
|-------------|----------------|
| SIGNAL WORD | <b>WARNING</b> |
|-------------|----------------|

**Hazard statement(s)**

|      |                                      |
|------|--------------------------------------|
| H317 | May cause an allergic skin reaction. |
|------|--------------------------------------|

**Precautionary statement(s) Prevention**

|      |  |
|------|--|
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P261 | Avoid breathing dust/fume/gas/mist/vapours/spray.                          |
| P272 | Contaminated work clothing should not be allowed out of the workplace.     |

**Precautionary statement(s) Response**

|           |  |
|-----------|--|
| P363      | Wash contaminated clothing before reuse.                         |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water.                  |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention. |

**Precautionary statement(s) Storage**

Not Applicable

**Precautionary statement(s) Disposal**

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS****Substances**

See section below for composition of Mixtures

**Mixtures**

| CAS No        | %[weight] | Name   |
|---------------|-----------|--|
| Not Available | 6-46      | acrylic monomers as                                    |
| 72869-86-4    |           | <u>diurethane dimethacrylate</u>                       |
| 109-16-0      |           | <u>triethylene glycol dimethacrylate</u>               |
| 24448-20-2    |           | <u>2,2-bis[4-(2-methacryloxy)ethoxy]phenyl]propane</u> |

**SECTION 4 FIRST AID MEASURES****Description of first aid measures**

|                     |   |
|---------------------|---|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Wash out immediately with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul> |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Seek medical attention in event of irritation.</li> </ul>   |
| <b>Inhalation</b>   | <ul style="list-style-type: none"> <li>▶ If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>▶ Other measures are usually unnecessary.</li> </ul> <p>If irritation continues, seek medical attention.</p>   |
| <b>Ingestion</b>    | Seek medical attention.   |

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

**SECTION 5 FIREFIGHTING MEASURES****Extinguishing media**

- ▶ Foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.
- ▶ Water spray or fog - Large fires only.

**Special hazards arising from the substrate or mixture**

|                             |             |
|-----------------------------|-------------|
| <b>Fire Incompatibility</b> | None known. |
|-----------------------------|-------------|

Continued...



## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         | <ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Fight fire from a safe distance, with adequate cover.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control the fire and cool adjacent area.</li> <li>▶ Avoid spraying water onto liquid pools.</li> <li>▶ <b>Do not</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> </ul> |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"> <li>▶ Non combustible.</li> <li>▶ Not considered a significant fire risk, however containers may burn.</li> </ul> <p>May emit corrosive fumes. Decomposes on heating and produces; carbon dioxide (CO<sub>2</sub>) carbon monoxide (CO)</p>   |

## SECTION 6 ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

|                     |  |
|---------------------|--|
| <b>Minor Spills</b> | <ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid contact with skin and eyes.</li> <li>▶ Wear impervious gloves and safety goggles.</li> <li>▶ Trowel up/scrape up.</li> <li>▶ Place spilled material in clean, dry, sealed container.</li> <li>▶ Flush spill area with water.</li> </ul>   |
| <b>Major Spills</b> | <p>Minor hazard.</p> <ul style="list-style-type: none"> <li>▶ Clear area of personnel.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Control personal contact with the substance, by using protective equipment as required.</li> <li>▶ Prevent spillage from entering drains or water ways.</li> <li>▶ Contain spill with sand, earth or vermiculite.</li> <li>▶ Collect recoverable product into labelled containers for recycling.</li> <li>▶ Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.</li> <li>▶ Wash area and prevent runoff into drains or waterways.</li> <li>▶ If contamination of drains or waterways occurs, advise emergency services.</li> </ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ <b>DO NOT allow material to contact humans, exposed food or food utensils.</b></li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ Keep containers securely sealed when not in use.</li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately. Launder contaminated clothing before re-use.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul> |
| <b>Other information</b> | <p>Store between 10 and 25 deg. C.<br/><b>Do not</b> store in direct sunlight.</p>   |

### Conditions for safe storage, including any incompatibilities

|                                |   |
|--------------------------------|---|
| <b>Suitable container</b>      | <ul style="list-style-type: none"> <li>▶ <b>DO NOT repack.</b> Use containers supplied by manufacturer only.</li> <li>▶ Check that containers are clearly labelled and free from leaks</li> </ul> |
| <b>Storage incompatibility</b> | <ul style="list-style-type: none"> <li>▶ Avoid storage with reducing agents.</li> </ul>   |

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### Control parameters

#### OCCUPATIONAL EXPOSURE LIMITS (OEL)

#### INGREDIENT DATA

Not Available

#### EMERGENCY LIMITS

| Ingredient                        | Material name   | TEEL-1               | TEEL-2                | TEEL-3                 |
|-----------------------------------|---|----------------------|-----------------------|------------------------|
| diurethane dimethacrylate         | Diurethane dimethacrylate   | 60 mg/m <sup>3</sup> | 660 mg/m <sup>3</sup> | 4000 mg/m <sup>3</sup> |
| triethylene glycol dimethacrylate | Methacrylic acid, diester with triethylene glycol; (Polyester TGM3) | 33 mg/m <sup>3</sup> | 360 mg/m <sup>3</sup> | 2100 mg/m <sup>3</sup> |

Continued...

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

| Ingredient                                      | Original IDLH | Revised IDLH  |
|---|---------------|---------------|
| acrylic monomers as                             | Not Available | Not Available |
| diurethane dimethacrylate                       | Not Available | Not Available |
| triethylene glycol dimethacrylate               | Not Available | Not Available |
| 2,2-bis[4-(2-methacryloxy)ethoxy]phenyl]propane | Not Available | Not Available |

## MATERIAL DATA

## Exposure controls

| Appropriate engineering controls  | <p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p> <p>Employers may need to use multiple types of controls to prevent employee overexposure.</p> <p>General exhaust is adequate under normal operating conditions. Local exhaust ventilation may be required in special circumstances. If risk of overexposure exists, wear approved respirator. Supplied-air type respirator may be required in special circumstances. Correct fit is essential to ensure adequate protection. Provide adequate ventilation in warehouses and enclosed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.</p> <table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Air Speed:</th> </tr> </thead> <tbody> <tr> <td>solvent, vapours, degreasing etc., evaporating from tank (in still air).</td> <td>0.25-0.5 m/s (50-100 f/min)</td> </tr> <tr> <td>aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s (100-200 f/min.)</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> <tr> <td>grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)</td> <td>2.5-10 m/s (500-2000 f/min.)</td> </tr> </tbody> </table> <p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> <tr> <td>4: Large hood or large air mass in motion</td> <td>4: Small hood-local control only</td> </tr> </tbody> </table> <p>Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.</p> | Type of Contaminant: | Air Speed: | solvent, vapours, degreasing etc., evaporating from tank (in still air). | 0.25-0.5 m/s (50-100 f/min) | aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.) | direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion) | 1-2.5 m/s (200-500 f/min.) | grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion) | 2.5-10 m/s (500-2000 f/min.) | Lower end of the range | Upper end of the range | 1: Room air currents minimal or favourable to capture | 1: Disturbing room air currents | 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity | 3: Intermittent, low production. | 3: High production, heavy use | 4: Large hood or large air mass in motion | 4: Small hood-local control only |
|---|--|----------------------|------------|--|-----------------------------|---|----------------------------|--|----------------------------|---|------------------------------|------------------------|------------------------|---|---------------------------------|--|----------------------------------|----------------------------------|-------------------------------|---|----------------------------------|
|   | Type of Contaminant:   | Air Speed:           |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min)  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| grinding, abrasive blasting, tumbling, high speed wheel generated dusts (released at high initial velocity into zone of very high rapid air motion)   | 2.5-10 m/s (500-2000 f/min.)   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Lower end of the range  | Upper end of the range   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 1: Room air currents minimal or favourable to capture   | 1: Disturbing room air currents  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 2: Contaminants of low toxicity or of nuisance value only.  | 2: Contaminants of high toxicity   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 3: Intermittent, low production.  | 3: High production, heavy use  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| 4: Large hood or large air mass in motion   | 4: Small hood-local control only   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Personal protection   |   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Eye and face protection   | <p>No special equipment for minor exposure i.e. when handling small quantities.</p> <p>OTHERWISE:</p> <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent]</li> </ul>   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Skin protection   | See Hand protection below  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Hands/feet protection   | <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>▶ Rubber Gloves</li> </ul>  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Body protection   | See Other protection below   |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Other protection  | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ P.V.C. apron.</li> <li>▶ Barrier cream.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eye wash unit.</li> </ul>  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |
| Thermal hazards   | Not Available  |                      |            |  |                             |   |                            |  |                            |   |                              |                        |                        |   |                                 |  |                                  |                                  |                               |   |                                  |

## Respiratory protection

Type A Filter of sufficient capacity, (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | A-AUS                | -                    | A-PAPR-AUS / Class 1   |
| up to 50 x ES                      | -                    | A-AUS / Class 1      | -                      |
| up to 100 x ES                     | -                    | A-2                  | A-PAPR-2 ^             |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

|   |   |  |                |
|---|---|--|----------------|
| <b>Appearance</b>                                   | Tooth coloured viscous/ flowable paste with ester-like odour, insoluble in water. |  |                |
| <b>Physical state</b>                               | Free-flowing Paste  | <b>Relative density (Water = 1)</b>            | 1.5-2.0        |
| <b>Odour</b>  | Not Available   | <b>Partition coefficient n-octanol / water</b> | Not Available  |
| <b>Odour threshold</b>                              | Not Available   | <b>Auto-ignition temperature (°C)</b>          | Not Available  |
| <b>pH (as supplied)</b>                             | Not Available   | <b>Decomposition temperature</b>               | Not Available  |
| <b>Melting point / freezing point (°C)</b>          | Not Available   | <b>Viscosity (cSt)</b>                         | Not Available  |
| <b>Initial boiling point and boiling range (°C)</b> | Gel before boiling  | <b>Molecular weight (g/mol)</b>                | Not Applicable |
| <b>Flash point (°C)</b>                             | Not Available   | <b>Taste</b>                                   | Not Available  |
| <b>Evaporation rate</b>                             | Not Available   | <b>Explosive properties</b>                    | Not Available  |
| <b>Flammability</b>                                 | Not Available   | <b>Oxidising properties</b>                    | Not Available  |
| <b>Upper Explosive Limit (%)</b>                    | Not Available   | <b>Surface Tension (dyn/cm or mN/m)</b>        | Not Available  |
| <b>Lower Explosive Limit (%)</b>                    | Not Available   | <b>Volatile Component (%vol)</b>               | Not Available  |
| <b>Vapour pressure (kPa)</b>                        | Not Available   | <b>Gas group</b>                               | Not Available  |
| <b>Solubility in water (g/L)</b>                    | Immiscible  | <b>pH as a solution (1%)</b>                   | Not Available  |
| <b>Vapour density (Air = 1)</b>                     | Not Available   | <b>VOC g/L</b>                                 | Not Available  |

### SECTION 10 STABILITY AND REACTIVITY

|   |   |
|---|---|
| <b>Reactivity</b>                         | See section 7   |
| <b>Chemical stability</b>                 | Product is considered stable and hazardous polymerisation will not occur. |
| <b>Possibility of hazardous reactions</b> | See section 7   |
| <b>Conditions to avoid</b>                | See section 7   |
| <b>Incompatible materials</b>             | See section 7   |
| <b>Hazardous decomposition products</b>   | See section 5   |

### SECTION 11 TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.  |
| <b>Ingestion</b>    | The material has <b>NOT</b> been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. The material may still be damaging to the health of the individual, following ingestion, especially where pre-existing organ (e.g liver, kidney) damage is evident. Present definitions of harmful or toxic substances are generally based on doses producing mortality rather than those producing morbidity (disease, ill-health). Gastrointestinal tract discomfort may produce nausea and vomiting. In an occupational setting however, ingestion of insignificant quantities is not thought to be cause for concern.   |
| <b>Skin Contact</b> | Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. |

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

|         |   |
|---------|---|
| Eye     | Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. |
| Chronic | Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.  |

| Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer | TOXICITY                                    | IRRITATION    |
|--|---|---------------|
|  |   | Not Available |
| diurethane dimethacrylate  | TOXICITY                                    | IRRITATION    |
|  | Oral (rat) LD50: >5000 mg/kg <sup>[1]</sup> | Not Available |
| triethylene glycol dimethacrylate                                    | TOXICITY                                    | IRRITATION    |
|  | Oral (rat) LD50: 10837 mg/kg <sup>[2]</sup> | Nil reported  |
| 2,2-bis[4-(2-methacryloxy)ethoxy]phenyl]propane                      | TOXICITY                                    | IRRITATION    |
|  | Not Available                               | Not Available |

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|   |   |
|---|---|
| DIURETHANE DIMETHACRYLATE                       | <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p> <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p> <p>UV (ultraviolet)/ EB (electron beam) acrylates are generally of low toxicity<br/>UV/EB acrylates are divided into two groups; "stenomeric" and "eurymeric" acrylates.<br/>The first group consists of well-defined acrylates which can be described by a simple idealised chemical; they are low molecular weight species with a very narrow weight distribution profile.<br/>The eurymeric acrylates cannot be described by an idealised structure and may differ fundamentally between various suppliers; they are of relatively high molecular weight and possess a wide weight distribution.<br/>Stenomeric acrylates are usually more hazardous than the eurymeric substances. Stenomeric acrylates are also well defined which allows comparison and exchange of toxicity data - this allows more accurate classification.<br/>The stenomerics cannot be classified as a group; they exhibit substantial variation.<br/>Where no "official" classification for acrylates and methacrylates exists, there has been cautious attempts to create classifications in the absence of contrary evidence. For example<br/>Monoalkyl or monoarylestere of acrylic acids should be classified as R36/37/38 and R51/53<br/>Monoalkyl or monoaryl estere of methacrylic acid should be classified as R36/37/38<br/>* Possible carcinogen; possible sensitizer; possible irreversible effects * Polysylms MSDS</p> |
| TRIETHYLENE GLYCOL DIMETHACRYLATE               | <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p> <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p>   |
| 2,2-BIS[4-(2-METHACRYLOXY)ETHOXY]PHENYL]PROPANE | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of</p>  |

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

UV (ultraviolet)/ EB (electron beam) acrylates are generally of low toxicity

UV/EB acrylates are divided into two groups; "stenomeric" and "eurymeric" acrylates.

The first group consists of well-defined acrylates which can be described by a simple idealised chemical; they are low molecular weight species with a very narrow weight distribution profile.

The eurymeric acrylates cannot be described by an idealised structure and may differ fundamentally between various suppliers; they are of relatively high molecular weight and possess a wide weight distribution.

Stenomeric acrylates are usually more hazardous than the eurymeric substances. Stenomeric acrylates are also well defined which allows comparison and exchange of toxicity data - this allows more accurate classification.

The stenomerics cannot be classified as a group; they exhibit substantial variation.

No significant acute toxicological data identified in literature search.

The chemical structure of hydroxylated diphenylalkanes or bisphenols consists of two phenolic rings joined together through a bridging carbon. This class of endocrine disruptors that mimic oestrogens is widely used in industry, particularly in plastics

Bisphenol A (BPA) and some related compounds exhibit oestrogenic activity in human breast cancer cell line MCF-7, but there were remarkable differences in activity. Several derivatives of BPA exhibited significant thyroid hormonal activity towards rat pituitary cell line GH3, which releases growth hormone in a thyroid hormone-dependent manner. However, BPA and several other derivatives did not show such activity. Results suggest that the 4-hydroxyl group of the A-phenyl ring and the B-phenyl ring of BPA derivatives are required for these hormonal activities, and substituents at the 3,5-positions of the phenyl rings and the bridging alkyl moiety markedly influence the activities.

Bisphenols promoted cell proliferation and increased the synthesis and secretion of cell type-specific proteins. When ranked by proliferative potency, the longer the alkyl substituent at the bridging carbon, the lower the concentration needed for maximal cell yield; the most active compound contained two propyl chains at the bridging carbon. Bisphenols with two hydroxyl groups in the para position and an angular configuration are suitable for appropriate hydrogen bonding to the acceptor site of the oestrogen receptor.

Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental Review Division (HERD), Office of Toxic Substances (OTS), of the US EPA previously concluded that all chemicals that contain the acrylate or methacrylate moiety (CH<sub>2</sub>=CHCOO or CH<sub>2</sub>=C(CH<sub>3</sub>)COO) should be considered to be a carcinogenic hazard unless shown otherwise by adequate testing.

This position has now been revised and acrylates and methacrylates are no longer *de facto* carcinogens.

Where no "official" classification for acrylates and methacrylates exists, there has been cautious attempts to create classifications in the absence of contrary evidence. For example

Monalkyl or monoarylestere of acrylic acids should be classified as R36/37/38 and R51/53

Monoalkyl or monoaryl estere of methacrylic acid should be classified as R36/37/38

|                                   |   |                          |   |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity                    | ⊖ | Carcinogenicity          | ⊖ |
| Skin Irritation/Corrosion         | ⊖ | Reproductivity           | ⊖ |
| Serious Eye Damage/Irritation     | ⊖ | STOT - Single Exposure   | ⊖ |
| Respiratory or Skin sensitisation | ✓ | STOT - Repeated Exposure | ⊖ |
| Mutagenicity                      | ⊖ | Aspiration Hazard        | ⊖ |

Legend: ✗ - Data available but does not fill the criteria for classification  
✓ - Data required to make classification available  
⊖ - Data Not Available to make classification

## SECTION 12 ECOLOGICAL INFORMATION

## Toxicity

| Ingredient                        | Endpoint | Test Duration (hr) | Species                       | Value     | Source |
|-----------------------------------|----------|--------------------|-------------------------------|-----------|--------|
| diurethane dimethacrylate         | EC50     | 48                 | Crustacea                     | >1.2mg/L  | 2      |
| diurethane dimethacrylate         | EC50     | 72                 | Algae or other aquatic plants | >0.68mg/L | 2      |
| diurethane dimethacrylate         | NOEC     | 72                 | Algae or other aquatic plants | >0.21mg/L | 2      |
| triethylene glycol dimethacrylate | LC50     | 96                 | Fish                          | 16.4mg/L  | 2      |
| triethylene glycol dimethacrylate | EC50     | 504                | Crustacea                     | 51.9mg/L  | 2      |
| triethylene glycol dimethacrylate | EC50     | 72                 | Algae or other aquatic plants | 72.8mg/L  | 2      |
| triethylene glycol dimethacrylate | NOEC     | 72                 | Algae or other aquatic plants | 18.6mg/L  | 2      |

## Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

**DO NOT** discharge into sewer or waterways.

## Persistence and degradability

| Ingredient                        | Persistence: Water/Soil | Persistence: Air |
|-----------------------------------|-------------------------|------------------|
| triethylene glycol dimethacrylate | LOW                     | LOW              |

## Bioaccumulative potential

| Ingredient | Bioaccumulation |
|------------|-----------------|
|            |                 |

Continued...

## Glacier, Wave, Wave MV, Wave HV, ROK, ICE, Luna, Aura and LC Opaquer

|                                   |                     |
|-----------------------------------|---------------------|
| triethylene glycol dimethacrylate | LOW (LogKOW = 1.88) |
|-----------------------------------|---------------------|

### Mobility in soil

| Ingredient                        | Mobility       |
|-----------------------------------|----------------|
| triethylene glycol dimethacrylate | LOW (KOC = 10) |

## SECTION 13 DISPOSAL CONSIDERATIONS

### Waste treatment methods

| Product / Packaging disposal |  |
|------------------------------|--|
|                              | Consult State Land Waste Management Authority for disposal.<br>Bury residue in an authorised landfill. |

## SECTION 14 TRANSPORT INFORMATION

### Labels Required

|                  |                |
|------------------|----------------|
| Marine Pollutant | NO             |
| HAZCHEM          | Not Applicable |

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

## SECTION 15 REGULATORY INFORMATION

### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### DIURETHANE DIMETHACRYLATE(72869-86-4) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

#### TRIETHYLENE GLYCOL DIMETHACRYLATE(109-16-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

#### 2,2-BIS[4-(2-METHACRYLOXY)ETHOXY]PHENYL]PROPANE(24448-20-2) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

| National Inventory            | Status   |
|-------------------------------|--|
| Australia - AICS              | Y  |
| Canada - DSL                  | N (diurethane dimethacrylate)  |
| Canada - NDSL                 | N (2,2-bis[4-(2-methacryloxy)ethoxy]phenyl]propane; triethylene glycol dimethacrylate)   |
| China - IECSC                 | Y  |
| Europe - EINEC / ELINCS / NLP | Y  |
| Japan - ENCS                  | N (diurethane dimethacrylate)  |
| Korea - KECI                  | Y  |
| New Zealand - NZIoC           | Y  |
| Philippines - PICCS           | Y  |
| USA - TSCA                    | Y  |
| <b>Legend:</b>                | Y = All ingredients are on the inventory<br>N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

| Name                      | CAS No                 |
|---------------------------|------------------------|
| diurethane dimethacrylate | 41137-60-4, 72869-86-4 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by SDI Limited using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Continued...

**Definitions and abbreviations**

PC – TWA: Permissible Concentration-Time Weighted Average  
PC – STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit,  
IDLH: Immediately Dangerous to Life or Health Concentrations  
OSF: Odour Safety Factor  
NOAEL: No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index

The information contained in the Safety Data Sheet is based on data considered to be accurate, however, no warranty is expressed or implied regarding the accuracy of the data or the results to be obtained from the use thereof.

Other information:

Prepared by: SDI Limited  
3-15 Brunson Street, Bayswater Victoria, 3153, Australia

Phone Number: +61 3 8727 7111

Date of preparation/revision: 23rd September 2015

Department issuing SDS: Research and Development

Contact: Technical Director